

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
8 July 2004 (08.07.2004)


PCT

(10) International Publication Number
WO 2004/057439 A2

- (51) International Patent Classification⁷: **G06F** Anne [US/US]; 2215 Penman Lane, Bountiful, UT 84010 (US). LAUMAN, Jason, R. [US/US]; 765 East Ninth Avenue, Salt Lake City, UT 84103 (US). COCHELLA, Christopher [US/US]; 864 South Diestel Road, Salt Lake City, UT 84105 (US).
- (21) International Application Number: PCT/US2003/017138
- (22) International Filing Date: 31 May 2003 (31.05.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 60/384,703 31 May 2002 (31.05.2002) US
- (71) Applicant (for all designated States except US): **UNIVERSITY OF UTAH RESEARCH FOUNDATION** [US/US]; 210 Park Building, Salt Lake City, UT 84112 (US).
- (72) Inventors; and
- (73) Inventors/Applicants (for US only): **GOEDE, Patricia,**
- (74) Agent: **CLAYTON, Grant, R.**; Clayton, Howarth & Cannon, P.C., P.O. Box 1909, Sandy, UT 84091 (US).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,

[Continued on next page]

(54) Title: SYSTEM AND METHOD FOR VISUAL ANNOTATION AND KNOWLEDGE REPRESENTATION



(57) Abstract: A method and system for visually annotating an image. Annotations and notes to images, such as digital medical and healthcare images, may be stored in a structured vector representation alongside image information in a single, non-volatile and portable file or in a separate file from the image. The annotations may be composed of point, line and polygon drawings and text symbols, labels or definitions and captions or descriptions. The annotations may be structured in a manner that facilitates grouping and manipulation as user defined groups. The annotations may be related to an image but not inextricably bound such that the original image is completely preserved. Annotations may further be selectively displayed on the image for context appropriate viewing. The annotations may be retrieved for purposes such as editing, printing, display, indexing and reporting for example, and may be displayed on an image for interactive use with an embedded self-contained user interface.

WO 2004/057439 A2



ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *without international search report and to be republished
upon receipt of that report*

51. The Field of the Invention.

The present invention relates generally to a method and system for annotating an image, and more particularly, but not necessarily entirely, to a computerized method and system for creating, storing, displaying and associating structured, vector based, interactive visual annotations and interactive visual notes (also referred as "IVN") with a digital image.

10 2. Description of Background Art.

Annotation of visual material is a necessary activity, one that represents an important part of teaching, publishing and communicating visual information. Since the widespread adoption of computers and especially the Internet, the use of digital images in computer-assisted presentations has grown tremendously. Doctors, educators, geologists, architects, engineers, scientists are 15 examples of professions where the use of digital images is becoming more widespread.

Image annotating, in a broad sense, includes any technique which allows an author to label, point to or otherwise indicate some feature of the image that is the focus of attention, including textual commentary. Providing an individual with the ability to add symbols, labels and captions to describe the contents of an image or to convey a concept and direct the viewer to important 20 features of an image has been established for decades. It has been long accepted that assigning captions or a definition and providing an option to write a legend that further describes a region of interest that is unique to an image allows an author to convey intellectual information regarding the structures in the image itself. Traditional methods for annotating images have allowed authors to place pointers, textual information and labels to indicate structures contained 25 in an image but that information remains static. Moreover, to change annotated features on an image often requires that the author scrape off the rub-on labels and start over or to reprint the image and start over with annotating the features of the image.

Today, digital image data is generated from a vast array of electronic devices and with the wide acceptance of the use of computers to accomplish the tasks of annotation gives rise to that 30 fact that many applications have been designed to give authors the ability to annotate electronic image data. The same traditional sets of tools that have allowed authors to prepare image data for publication have essentially been reproduced in an electronic environment and can be used in addition to, or completely replace, traditional tools for annotating images.

Digital images are typically stored as raster images, also referred to as bitmap images. 35 Examples of formats that are raster based include JPEG, GIF, BMP, PNM, TIFF, PPM, PNG and many others. Raster images are generally defined to be a rectangular array of regularly sampled values, known as pixels. Each pixel (picture element) has one or more numbers associated with it, generally specifying a color which the pixel should be displayed in. Most formats for raster images, including those mentioned above, compress the pixel information to shrink the size of the 40 data needed to encode the image.

Authors of digital material are finding that creating, presenting, and cataloging digital images is a difficult task despite the technologic improvements. Visually annotating or illustrating digital images with symbols and text is a fundamental task many users of images must perform when preparing material for illustration. For example, clinicians and biomedical 45 investigators must make visual annotations when preparing material for illustration.

Annotating visual media has evolved from scratch-on LETRASET® dry transfer labeling to using expensive, sophisticated and complicated image manipulation computer software like ADOBE® PHOTOSHOP® or MACROMEDIA® FREEHAND® software. At the same time, the need to illustrate images with annotations requires very little (symbols, labels, shapes and arrows) and remains a simple task. 50 While rub-on labels certainly have large drawbacks, i.e., they cannot be used for annotating digital images, they embody the simplicity of annotating an image quickly with the necessary information. Sophisticated software, while capable of generating simple annotations, requires a high degree of skill and knowledge to navigate the complexity of options and functions to achieve what is, in the end, a simple task. Moreover, the previously available systems and methods do not 55 promote interactivity with a user, neither in their output nor in their presentation. Thus, simplicity, interactivity and low cost continue as unsatisfied objectives for the process of effectively annotating visual digital material despite technologic improvements.

Not only is most image manipulation software functional overkill for creating simple annotations, this software flattens images where the annotations are "fixed" to the image much like 60 rub-on labels. The flattening of image annotations causes several problems that also existed with rub-on labels: editing difficulties, poor image quality, lack of interactivity and information loss. These problems are further illustrated below.

Annotations are not easily edited in a flattened image. The process of editing a flattened image requires using the original image—often in a proprietary format—in the native environment of 65 the authoring software. This process requires locating the original (not the presentation image currently in use) image or images—typically on a local hard drive—making the changes and then redistributing that image to the various publishing targets: Internet/WWW, paper-based copies, and so on. If the original image is lost then the annotations must be completed again from scratch. Those that have used this process—locating an image, making changes, then redistributing the 70 image—can attest to the time and frustration involved.

In the previously available systems and methods, annotations when flattened become part of the raster-based (drawn with pixels) image as opposed to being stored as vector (drawn in true physical space) information. As the raster annotations are re-scaled (zoom in or out) their appearance often become incomprehensible.

75 Flattening of annotations to an image means not only that the annotations cannot be scaled accordingly, it means that the annotations cannot be manipulated in other ways, such as, creating interactive presentations for the purpose of communicating a visual relationship or integrating the annotations into a learning assessment tool. Since the Internet has emerged as a viable medium to deliver educational materials, presentors are more often using the Internet to provide computer- 80 assisted presentations of educational material. Moreover, providing computer-assisted presentations has become easier than ever with the advancements in technology, computer hardware, software and improvements in the Internet and World Wide Web as delivery mechanism. For example, in an illustration of brain anatomy it may be necessary to illustrate the neurology and gross anatomy side-by-side. But it may also be useful to hide or turn off the gross anatomy in order to 85 illustrate the neurology then turn the gross anatomy back on to illustrate the relationship(s) between the two groupings. This scenario could be solved with raster images, however, it would require three images—one with neurology, one with gross anatomy, and one with both. Thus, there is four times the effort to produce this basic level of interactivity. Additionally, if these images are being viewed on the Internet it would mean three times longer wait in addition to the

labor and disk space utilized in producing three images. As the interactivity of an educational presentation increases the effort involved with raster images will grow exponentially.

The fourth and possibly the most significant problem arising from flattened annotations is the loss of information. For example, in the situation of medical research and instruction, 5 scientists, teachers, physicians, residents and students go to a network, such as the Internet, expecting to find resources on a particular topic by entering a keyword or phrase representing the subject or title of their objective. In order for a resource to be found, information about that resource must be indexed or cataloged like the age-old library card catalog.

10 Annotated images are one example of the valuable resources that need to be integrated into a catalog or index in order to be found and to realize their value. Annotated images offer more value than the base image in that there is intellectual or authored content assigned to the features of the image providing instructive value beyond the image itself. The annotations are part of the content. In order to index the annotated image this and other information-metadata-about the image (subject, keyword, format, date created, copyright, etc.) must 15 be cataloged. However, annotations that are flattened to the image are not available for cataloging. Either the content of the annotations is lost or the annotations must be entered again into another system and associated with the image. This de-coupling of content from the image and re-entry of the annotations into a separate storage system which is required when using the previously available systems and methods results in a more labor intensive, complex and disjoint 20 procedure.

Another disadvantage to using a flattened image is the inability to allow multispecialty authoring. Multispecialty authoring is the ability to add visual annotations, stored as groups, according to authorship. Often it is necessary that several different individuals annotate the same image. For example, several different specialties in the medical field may need to annotate 25 an x-ray image. Using a flattened image, this would be extremely difficult.

Another drawback to flattened images is that it is difficult to modify annotated images to make them context appropriate. Annotated images often contain annotations that are not appropriate for the persons viewing the image for a variety of reasons. For example, this might include information that is prohibited from being disseminated by privacy laws or simply information that 30 is irrelevant given the audience. Removing or hiding from view the annotations from a flattened image is not efficient due to the fact that the annotations are embedded in the image.

Still another drawback to the use of flattened images is the difficulty in reusing the annotated image. Reusing images in a variety of different mediums is an attractive option for authors. Authors will often decide to publish annotated image data to a variety of media. Some 35 will publish in traditional peer reviewed journals and textbooks and others will want to publish annotated material to the World Wide Web. Moreover, the context in which an image will appear may require that the content, both image and annotations, be presented differently. When working from a flattened image, a great deal of work must be duplicated to provide suitable flattened images for each context. Thus, it is in the best interest of the system architect and the author to create 40 an archive image with associated annotations and store annotations as vector information or text data.

Reuse (linking or referencing) enables authors to easily and accurately link information, and then maintain links across document revisions and system changes. Adhering to a reuse policy could potentially reduce storage costs, and reuse rather than duplication promotes sharing of 45 existing authored material rather than recreating it. The traditional known forms of output-based reuse include print publication, color plates, 35 mm slides, and the many forms of digital publication (e.g., PDF, HTML, etc.). Another form of reuse is in-system digital reuse of existing information. For example, a user might add multiple sets of annotations to an image and then desire to activate or inactivate the various sets of annotations to customize the image for use in 50 different contexts, such as on a world wide web page, in a print document, or in the portable document format (PDF).

As discussed above, the previously available methods and systems are thus characterized by several disadvantages that are addressed by the present invention. The present invention minimizes, and in some aspects eliminates, the above-mentioned failures, and other problems, by 55 utilizing the methods and structural features described herein.

BRIEF DESCRIPTION OF THE DRAWINGS

The features and advantages of the invention will become apparent from a consideration of the subsequent detailed description presented in connection with the accompanying drawings in which:

60 FIG. 1 is a flow chart showing the steps carried out in accordance with one illustrative embodiment of the present invention.

FIG. 2 is a reproduction of a computer display showing the various features of one illustrative embodiment of the present invention.

65 FIG. 3A illustrates an example of an annotated image in accordance with one aspect of the present invention.

FIG. 3B illustrates the non-embedded nature of the annotations in FIG. 3A in accordance with one aspect of the present invention.

FIG. 4 is a flow chart showing the steps carried out in accordance with one illustrative embodiment of the present invention.

70 FIG. 5A and 5B illustrate the interactive nature of the annotations in accordance with one aspect of the present invention.

FIG. 6 is a diagram showing the steps carried out in accordance with one illustrative embodiment of the present invention.

75 FIG. 7 is a flow diagram illustrating the multispecialty annotation features provided by one illustrative embodiment of the present invention.

DETAILED DESCRIPTION OF THE ILLUSTRATIVE EMBODIMENTS

For the purposes of promoting an understanding of the principles in accordance with the invention, reference will now be made to the illustrative embodiments described herein. It will nevertheless be understood that no limitation of the scope of the invention is thereby intended. 80 Any alterations and further modifications of the inventive features illustrated herein, and any additional applications of the principles of the invention as illustrated herein, which would normally occur to one skilled in the relevant art and having possession of this disclosure, are to be considered within the scope of the invention described and claimed.

The publications and other reference materials referred to herein to describe the background 85 of the invention and to provide additional detail regarding its practice are hereby incorporated by reference herein. The references discussed herein are provided solely for their disclosure

prior to the filing date of the present application. Nothing herein is to be construed as a suggestion or admission that the inventors are not entitled to antedate such disclosure by virtue of prior invention. Further, it must be noted that, as used in this specification and the appended claims, the singular forms "a," "an," and "the" include plural referents unless the context clearly dictates otherwise.

In describing and claiming the present invention, the following terminology will be used in accordance with the definitions set out below.

As used herein, "comprising," "including," "containing," "characterized by," and grammatical equivalents thereof are inclusive or open-ended terms that do not exclude additional, unrecited elements or method steps.

As discussed above, the main drawbacks which accompany the previously available flattening image annotations results in a variety of undesirable side effects: repetition of work, increase in authoring effort, increased organization requirements, increased complexity, difficulties to automate image cataloging, reduced instructional capability. All of the problems associated with the use of raster based images can either be eliminated or reduced substantially by not flattening the annotations to the image by the use of storing the annotations as vector based graphics.

With these objectives in focus, the illustrative embodiments of the present invention will define the requirements of a digital non raster-based annotation architecture and annotating methodology for digital images that will serve as a basis for use in a number of exemplary areas: authoring tools, presentation programs, and cataloging systems. The solution which is desirably provided in accordance with one aspect of the present invention is to separate the annotation information from the image information and at the same time attach or store the annotation information with the image file as vector-based text information. This method makes the annotations and metadata accessible, for example accessible to a user performing text searching for pertinent information, while still keeping the image and annotation information linked together.

The features and advantages of the invention will be set forth in the description which follows, and in part will be apparent from the description, or may be learned by the practice of the invention without undue experimentation. The features and advantages of the invention may be realized and obtained by means of the instruments and combinations particularly pointed out in the appended claims.

The present invention contemplates a system and method that allows annotations to be captured in a non-raster format. Because the annotations are stored in a vector file that is linked to the image file, the annotation will travel with the image information and the process of editing image annotations becomes much easier. As used herein, a "vector image" or "vector information" means a graphic comprising shapes, curves, lines, and text which together make the image. These shapes, curves, lines, and text can be constructed using mathematical formulas or other instructions as is known in the art to describe them instead of defining a grid of pixels as is the case with raster or bitmap images. A vector image can be in a two or three dimensional format.

With vector based image annotations it is not necessary to manage multiple original versions in a proprietary format or distribute multiple copies of the same image. The annotations remain accessible-at any time-for editing in the published image (the one most easily retrieved) without reverting to prior versions or copies. Thus, image annotation workflow is streamlined while at the same time reducing disk space usage.

Separation of the annotations in accordance with the present invention in this way makes it possible for a computer to catalog the resource automatically by "looking into" the resource itself for the annotations and metadata rather than requiring a person to enter this information into a separate system. Thus, the present invention's exemplary separation of annotations of an image simplifies and facilitates the automated cataloging of image resources improving the retrieval and increasing the value of image resources.

Referring now to FIG. 1, a process and methodology for annotating digital images with vector annotations is shown in accordance with the principles of the present invention. The first illustrative step is to open an image file (110) to annotate. Typically, the image file is a raster based image, for example a bitmap image and can be an image stored in one of many available formats such as, without limitation, JPEG, BMP, PNM, PNG, TIFF, and PPM. PNG as an image format is useful because it is supported by most image manipulation programs and, more importantly, because the PNG file itself can be used as a storage container for other types of information in addition to image information.

The image typically resides in a permanent storage medium such as on a hard drive, CD, DVD, flash memory or other similar storage device. The image can stem from any number of sources including, without limitation, a scanned image, a digital photograph, a work created on a computer, such as an architectural drawing, computed tomography, magnetic resonance image or any other valid source for a digital image. The image can be in a two dimensional or three dimensional format.

Once the image has been selected and opened (110), the next step is for the author to annotate the image (112). Typically, the step of annotating an image (112) can include several different substeps depending upon the needs of the author. Generally, an annotation will include one or more of the following: a region of interest, a pointer, and textual information such as a symbol, a label and/or a caption. The visible portion of the annotation on the image may include the region of interest, the pointer and the symbol. The region of interest, pointer and symbol may allow a medical educator, for example, to identify anatomical structures that convey relevant information about that image. Each of these will be defined in more detail below.

The region of interest is the visible portion of the annotation that is of interest. For example, in the medical field, a region of interest could be a feature or structure on an image (e.g., pathology, tumor, nerve) that conveys a clinical or research finding. While any manner to mark the region of interest will suffice, an author generally draws a point, line, or polygon to indicate a region of interest. The region of interest may be described by a set of points that may define a polygon, polyline or set of points, for example. A polygon may be used when the region of interest is a well-defined area, the polyline (or edge) may be used when the separation of regions is of interest and the points may be used when the interesting features are too small to practically enclose with a polygon.

The pointer for the annotation is partially defined by the author and partially computed based on where the author initially places it. For example, the author selects where the tail of the pointer should appear, and an algorithm calculates the closest point on the region of interest to place the pointer tip. This dual mechanism for anchoring the pointer allows the author to make choices about the layout of visual information on the image, without relying on a totally automated, and potentially unpredictable, layout algorithm. It is also within the scope of the present invention to utilize free from placement of pointers.

The textual information that is defined by the annotation methodology and includes the symbol, label and caption. Providing the ability to add textual information about the annotation enables the author to comment or add their expert knowledge on contents of an image in the form of a symbol, label and caption. The comments may refer to a detail of the image or the annotated image as a whole. The symbol, label and caption are a set of information commonly used across many fields, but may have specialty-specific terminology.

The symbol that is customarily associated with a visual piece of the annotation is taken from the textual information that is derived from a lexicon or free text entry. In the one illustrative embodiment of the present invention, the symbol is an abbreviation, typically derived from the label. The character length of the symbol allows it to be drawn on the image with numerous sets of other annotations, without obscuring visual information or interfering with the other annotations. When the symbol is used in this manner, it may be used as a key to link the visual annotation to the textual information. As mentioned, the symbol may be derived from a lexicon relating to the field in which the author is working. The symbol may be a lexicon specific piece of textual information that allows the annotation to be linked to a larger body of information outside the image. For authors who do not use predefined lexicons during the authoring process, the symbol may be enough to match the annotation with external information.

The label is the word or phrase that defines the visual annotation. For medical purposes, this label may also be taken from a lexicon or vocabulary, which enables dictionary-style lookup in the software implementation. The lexicon-specific piece of textual information allows the annotation to be linked to a larger body of information outside the image. For authors who do not use lexicons during the authoring process, the symbol may be enough to match the annotation with external information. The illustrative embodiments of present invention does not restrict or define lexicons because use of lexicons is the author's preference or institution's policy. If the label is drawn from a defined lexicon, it should at least be consistent across the author's work. The caption is defined as a sentence or paragraph that describes the annotation. The description may include references to other pieces of information that may be part of an index or hypertext system. The caption should not contain information about the image as a whole, which is handled through a constant non-visual annotation.

Throughout the annotation process, the author should also be able to determine the presentation attributes. The presentation attributes define how the annotations should be drawn when rendered. The visible parts of the presentation attributes may also be interpreted differently depending on the medium (e.g. laser printer, journal article or web browser). The presentation attributes may include size, color, pointer type and tip location.

Illustrative of the embodiments of the present invention, each of the attributes may have only three or four options presented to the user to provide better control over presentation and annotation reuse. All presentation attributes in the present invention may be guidelines for the rendering and reuse of visual characteristics including fonts, sizes and colors. The Hypertext Markup Language (HTML) has used this approach with success.

The options for the annotation size attribute may be, without limitation, small, default and large, for example. This option controls the size of the pointer and associated text rendered with the visual annotation. The options for annotation color may be, without limitation, "light," "default" and "dark," for example. This option may control the color of the region of interest (polygon), the pointer and any text that is rendered as part of the annotation. The color that each of the three-color attributes map to may be defined in a style sheet.

The pointer type options may be, without limitation, "spot," "line," "pin," "arrow" and "arrowhead," for example. Other pointer types may be added, but these four options form the illustrative foundation for the kinds of pointers that may appear with the region of interest. The style sheet and rendering software may control the details (appearance) of these pointers.

In accordance with one illustrative embodiment of the present invention, the pointer tip option may control where the tip of the pointer appears relative to the region of interest. The options may include "center" and "edge," for example. Using this attribute, the embodiment of the present invention may determine the actual pixel location of the pointer tip. The illustrative embodiments of the present invention may alternatively utilize free form placement.

Once the image has been annotated, the next step is to save the annotations and metadata, if present, as vector information linked to the image (114). The term linking, in addition to its normal meaning, also means, for the purposes of this application to save the vector information inside the image file itself or as a separate file. Some image formats, such as PNG, allow the vector information to be saved inside of the image file itself.

It will be appreciated that one advantage to saving the annotations and metadata as vector information is that vector based annotations improve the quality of image presentation because the annotations can be re-drawn or scaled dynamically based on their "equation" within the geographic space of the image. Therefore, image annotations can be shown clearly at all scales as the viewer re-scales the presentation (zooms in or out). In the same way that annotations can be scaled they can also be dynamically manipulated to create instructive and exciting interactive presentations, integrated into a learning assessment program, or other goal oriented task.

In accordance with the illustrative embodiments of the present invention, it is possible to store text information such as vector-based image annotations and metadata inside the image file along side the actual image information. The metadata includes any additional information about the image or annotations that may be useful. For example, the metadata may include the names of persons adding annotations to the image, including the date and time that the annotations were performed. The metadata may also include patient information in the case of medical images. The metadata may also include the names of persons who have viewed the image or annotations and the date and time of the viewing.

If storing text information inside the image file along side the actual image information is not possible, the annotation can also be stored in a separate file from the image with a relational mechanism, all in accordance with the illustrative embodiments of the present invention. This text information is not automatically displayed as a default by most image viewers and remains visually hidden. However, this information is accessible to many programming languages for interactive display, annotation drawing, publishing to multiple targets and cataloging. In this manner, storing metadata and vector-based annotations as text inside the image file, this information can more easily "travel" with the image information.

While the vector information can be stored in any format, one preferred method is to store the vector information in the Extensible Markup Language ("XML") format. This methodology ensures that annotations remain accessible as vector data, not embedded in the image, as well as maintain the links between the image and annotation information. It will be appreciated that storing the vector information in the XML format allows the annotations and images to become re-usable.

Moreover, with vector-based image annotations, management of multiple original versions in a proprietary format or distribution of multiple copies of the same image is not necessary.

Further, in accordance with the illustrative embodiments of the present invention, the output is not platform specific. Rather, the output format may utilize the Scalable Vector Graphics ("SVG") format, which is an extension of the eXtensible Markup Language (XML) specification. Metadata that includes visual annotations, author information, lexicons and information related to the authoring sessions are stored within the file. SVG facilitates extensibility, interactive web viewing, and reuse. SVG also allows the annotations and visual expert knowledge (i.e., labels and captions) to remain linked to the image, as opposed to embedding the annotations to the image. To facilitate the interactivity of the annotated images, the illustrative embodiments of the present invention utilize Adobe's SVG plug-in (Adobe Systems, San Jose, California) for viewing annotated images over the Internet.

It will be appreciated that this form of output facilitates cross-media distribution. Cross-media publishing is a term that defines a set of methods that allow source material to be collected at a single source in a manner allowing reuse and redistribution across multiple delivery channels such as the Internet, electronic books, textbooks and presentations. For example, the medical content market development continues to be a thriving industry that ranges from standard textbooks and references to digital subscription services and web portals. In other words, an image annotated using the present invention is easily transported from one form of media to another form of media.

The present invention has been developed for the cross media publishing and digital content authoring markets is designed to integrate into existing systems for visually annotating images that are to be used for publishing in textbooks, on the Internet as a subscription Continuing Education module or on CD-ROM.

FIG. 2 illustrates an exemplary image that might be displayed on a computer screen that has been annotated pursuant to the an illustrative embodiment of the present invention as explained above. This example is useful for understanding the different features of the illustrative embodiment of the present invention and should not be construed as limiting in anyway. As can be observed, several regions of interest have been marked on the image. One region of interest, indicated by reference numeral 118, is noted by the label 122 "Cyst" which is connected to the region of interest 118 by a pointer 120. Also, a caption 124 and symbol 126 for the region of interest 118 can be observed. In this manner, it will be appreciated that the annotations are useful in conveying information to the observer. FIG. 2 also exemplifies the advantageous use of groups and views in accordance with the present invention.

FIGS. 3A and 3B respectively show an annotated image and the annotations without the image. The annotations shown in FIG. 3A show marked regions of interest with their respective pointers and labels. As can be seen, the annotations are "overlaid" over the original image as shown in FIG. 3A. FIG. 3B demonstrates that the annotations are not embedded in the original but are in fact stored in a separate file that is preferably linked to the image file. The annotations are stored in an image independent vector format for high-resolution display at all scales. Note that the original image remains unedited and more importantly, no pixels of the original raster image were changed or edited.

In accordance with the illustrative embodiment of the present invention, the separate annotation file may contain a digital signature of the image file in case the two files are separated. As will be explained in greater detail below, reuse of the image is facilitated since the original image remains unchanged and the annotations remain linked to the image.

It will be appreciated that because the annotations are not embedded into the image, they can be referenced, grouped (as shown in FIG. 2) and indexed for a variety of purposes. In addition, while multiple annotations can be added to an image, not all of the annotations need be displayed at the option of the presenter, to create a context appropriate annotated image. These multiple annotations can be interactive as will be explained below.

FIG. 4 is an illustrative example of the methodology of how the present invention facilitates a plurality annotations and groupings. The first step is to select and open an image (128) that has been stored electronically. The author then is free to define a region of interest (130) and add the appropriate symbols, labels and pointers (132) as desired. The author is then free to chose to add additional annotations (136). It should be noted that the author may be adding annotations to an image already annotated by another person (referred to herein as "multiuser authoring"). This is particularly true in a medical setting where several doctors may be adding annotations to the same image.

Once the image has been annotated, the next step is to group or order the annotations hierarchically (136). The order is a character sequence that allows the annotations of the image to be organized in an outline format, allows the annotations to be grouped (or nested) logically, and may impart priority (like the first annotation in the outline is the most important). The order is treated as an annotation but is used to identify and set up the hierarchy that the visual annotations fall into. This piece of textual information is an invisible annotation that links the pieces of textual information consisting of the symbol, label or caption to the image.

In accordance with the illustrative embodiments of the present invention, the textual information that is the order or grouping, is linked and stored with the image, much like the chunks of data that are embedded within Portable Networks Graphics (PNG) format. This feature is similar to the concept of a table of contents. The textual information that defines the order or grouping of the visual annotations is a constant, non-visual annotation always exists at the first position in the outline, and is a part of the information used to create the image's metadata.

In accordance with another desirable feature of the illustrative embodiments of the present invention, the region of interests can optionally be organized into context-appropriate views (138). Context-appropriate viewing of an image and related annotations is a feature that allows the annotations on an image to be turned on or off for a particular audience or presentation. The annotation view attribute controls the visibility of an annotation because the annotations are separate from the image and are separate from each other. Thus, the view attribute can turn annotations on/off in a context-appropriate manner. Depending on the context, portions of annotations may be viewed in a presentation while other portions remain hidden. As represented at step 140, saving the file with annotations as vector information linked to the image is carried out in accordance with the illustrative embodiments of the present invention.

FIGS. 5A and 5B are exemplary of context appropriate viewing in accordance with the illustrative embodiments of the present invention described herein. In FIG. 5A, as can be seen in the box 142, all of the annotations for this image have been selected and are being displayed. As seen in FIG. 5B, the box 144 shows that only the first two annotations have been selected and displayed. It is important to note that the underlying image is the same for both of the annotated

images. That is, both of the FIGS. 5A and 5B use the same file for the underlying image. Because the annotations are saved in a separately from the image (not embedded in the image), the annotations can be selectively displayed on the image.

Desirably, in the illustrative embodiments of the present invention, an annotation and related textual information (i.e., label or caption) consist of discrete pieces of information that, when viewed, are interactive. Interactivity in this sense is defined as giving the viewer the ability to turn on/off annotated groups on the image. Annotations and associated textual information are viewed and controlled independently from the image.

Likewise, reuse of the image is facilitated by providing an open "hook" to link the image and related annotations to larger cataloging systems. The ability to reuse underlying annotated images for different purposes (i.e., publication, web viewing or professional conferences) is an important improvement of the present invention over the previously available systems and methods. The present invention gives the author the ability to annotate an image once and reuse the annotations or the image with or without the previous annotations. Authors can store the archived image with the linked annotations. Importantly, the images remain unaltered because the annotations are not embedded into the image. Therefore, the image remains in an archival format and can be reused for other purposes or applications.

As explained previously, in accordance with the present invention, by adopting open standards such as XML and SVG in the illustrative embodiments of the present invention, authors have the ability to save images with the annotations linked to the images, in a structured format of XML (SVG). The open and extensible features of SVG promote indexing of the image with associated annotations and textual information, thus allowing images and annotations to be catalogued in a database or asset management system.

In the previously available systems and methods, the complexity of most graphical programs and the problems caused by flattening image annotations, there is often no way to relate or group annotations as can be done with the present invention. Most of these previously available graphical programs will allow the user to create any visual appearance desired. However, these programs are only interested in the appearance of things and do not keep track of the inherent structure, relationships or intellectual groupings of the annotations as does the present invention.

For example, in gross anatomy there are many anatomical groupings. These groupings represent an intellectual categorization that can be visually illustrated. Thus, there are two valuable aspects to such groupings: visual and inherent intellectual structure. An author may group annotations by using color to create the visual relationships. With the previously available pertinent software programs this is the end result. Other than the appearance of the image there is no way of knowing that (or working with) an annotation is part of one group or another. The structure of these groupings—which annotated feature belongs to which group—is lost when using the previously available systems and methods. In other words, it is not possible to interactively illustrate such relationships without retaining the intellectual structure of the annotations. Using the simple example provided above, using the previously available systems and methods it is not be possible to visually hide the gross anatomy so as to illustrate the relationship to neurology without retaining the information structure. Moreover, using the previously available systems and methods it is not be possible to dynamically integrate these relationships in a learning assessment tool by asking questions such as, "What group does the visible feature below to: gross anatomy or neurology?"

In addition, in accordance with the illustrative embodiments of the present invention the retained structure of annotations could be used to automatically generate an image caption or a hierarchical legend of the annotated features. Without access to these relationships via a separation from the base image, as is done with the present invention, the dynamic and interactive features are not possible.

FIG. 6 is a diagram showing the data flow carried out in accordance with an illustrative embodiment of the present invention. The first step is to extract the image data. The extractor (146) is an illustrative process that reads the digital information and assembles the auxiliary information for use by a human or computer (or any other data processing device) for annotation in accordance with the illustrative embodiments of the present invention. Digital information can also consist of color settings, grayscale levels, image pixel dimensions, or the type of image the user is requesting, i.e., TIF, JPEG, DICOM, etc. A human user or a wide variety of machine processes may initiate the process of extraction during the open image dialog.

The next step is to organize the data. The organizer (148) acts upon the extracted information, and arranges the digital information to reflect the human user's conceptual organization in the illustrative embodiments of the present invention. The organization of the digital information reflects its origin or intended use by permitting the user to decide what the intended use will be. Organization includes, but is not limited to, a hierarchy, set, slices, channels, sequence and a single source of digital information (e.g., a single image). For example, micro thin slices of tissue that contain the same cells, but are stained differently to identify different cell types in each slice. In this example, the organization is a single cross section of cells with each slice showing unique cell types.

The next step is to construct the annotations. The constructor (150) is a machine aided human user process that allows visual annotation elements to be created manually by the user in the illustrative embodiments of the present invention. The constructor (150) represents a class of visual elements that includes, but is not limited to, a point, a line, a polygon, a plane and a cube. The constructor (150) annotation elements available to the human user are selected by a computer process based on applicability to the dimensions of the original digital information.

The next step is to segment the data. In the illustrative embodiment, the segmentor (152) is a computer process that automatically (with no human intervention) identifies and detects visual features (i.e. edges, areas, planes, cubes, etc.) within the digital information, and automatically creates visual and non-visual annotations for those features. The segmentor (152) falls within the common definition of segmentation within the computer graphics industry.

The indicator (154) is a machine aided human user process that allows visual indication elements to be created manually by the user in the illustrative embodiments of the present invention. The indicator (154) represents a class of visual elements that includes, but is not limited to, a spot, a string, an arrowhead, an arrow and a pin. Each indicator (154) has a core set of properties that include the anchor point (e.g., the tip of an arrow) and the properties that govern its shape for visual presentation. The indicator (154) allows the author in the process of annotation to focus the attention of a human user (viewer), and visually ties feature relevant information to the annotation when it is not appropriate to display the information directly on the

annotation itself. The indicator (154) maintains the relationships between visual and non-visual annotation elements and image data (including image data which is 1D, 2D, 3D, or 4D).

The connector (156) is a visual or non-visual machine aided human user process that allows connection elements to be created manually by the user in the illustrative embodiments of the present invention. A connection element enables the human user to define the relationship of two or more annotations. The definition of the connector (156) relationship determines how machine, such as a computer, presents the connection, and how the human user may interact with the connection and connected annotation elements. Connectors (156) include, but are not exclusive to, groups, views, rules and structural hierarchy of annotated features. For example in the case of a medical image, the carotid sheath contains the carotid artery, internal jugular vein and the vagus nerve. The connector (156) defines the structural relationship between the carotid sheath and the elements contained in the carotid sheath. The connector (156) provides the ability to define or select a context-appropriate view based on the groups of annotation.

The descriptor (158) is a machine aided human user process that allows description elements to be created manually by the user in the illustrative embodiments of the present invention. A description element may be attached to any other annotation element, and appear visually with the annotation or as a dynamic visual element like an Interactive Visual Note. A description element may be free-form text, or may follow a coding convention or lexicon to constrain the description entry of the human user. For example, in the case of a medical image the descriptor (158) may contain a clinical note entered by an attending physician, a pathology report entered by a pathologist, or a caption that defines an aspect of the annotated region of interest.

The illustrative embodiments of the present invention provide particular advantages in view of the provision of features related to Interactive Visual Notes. Some users will find that IVN is the most desirable feature of the present invention. IVN is supported by many illustrative embodiments of the present invention and provides, inter alia, interactive on/off functions. In addition to using the symbol for on/off presentation and the combination of symbol-label-caption for generation of legends, in accordance with some illustrative embodiments of the present invention the symbol-label-caption may also be used for extensive note taking on an annotation-by-annotation basis without obscuring the visual presentation or requiring a separate "reporting" interface. The embodiments of the present invention providing such advantageous features provide that reports or extensive notes may be contextually presented on demand by the user while viewing the image and associated annotations. This feature provides the advantage that the user does not have to interrupt his "visual" workflow to obtain text-based information. Particular illustrative embodiments of the present invention provided a handle or "hot-spot" at the end of the pointer or arrow (which could be located anywhere) which triggers the dynamic display of a reporting window that may have text, tables, charts and possibly other secondary information or even contain an image that is used as a reference. This feature advantageously makes the given visual presentation much more rich while improving the user's efficiency and workflow.

The deductor (160) is machine process that may or may not be aided by human user input to analyze and deduce new visual and non-visual information from the pre-existing annotated information using a set of defined rules in the illustrative embodiments of the present invention. The deductor (160) is a mechanism for automating information manipulation within the annotation process that may require a mix of human input and computer algorithms. For example, in a medical image a deductor (160) may count the number of each type of cell and the mean distance between the cells in a slice of stained tissue. In the case of a medical image, the deductor (160) may create output that could be read and be integrated into an existing system for cell analysis. The deductor (160) could also create output that is read and applied to a template in a publishing process.

The presenter (162) is the machine process that creates the interactive visual interface based on the visual and non-visual annotated information for consumption and manipulation by a human user in the illustrative embodiments of the present invention. The manner in which the presenter (162) creates the visual interface may be determined by viewing goals, role or privilege level of the human user. Also, the presenter (162) may be constrained by technical limitation of a computer system upon which it resides, which requires the presenter (162) to generate a visual interface appropriate computer system. For example, a user might be a student who receives a simplified presentation for study purposes, which may be different than the same information presented for reference purposes to an expert user.

FIG. 7 illustrates an example of one application of the present invention utilizing multispecialty authoring. It is to be understood that the example illustrated in FIG. 7 is merely illustrative of the many different beneficial applications of the present invention. The example of FIG. 7 shows how multiple authors may contribute annotations incrementally to the same image without variation to the original image, i.e., embedding the annotations in the original image. The primary care physician 164 is presented with a patient with a headache. The primary care physician 164 orders that an image 166 be taken of the affected area. A pediatrician 168 receives the image 166 along with the initial clinical assessment made by the primary care physician 164. After reviewing the image 166, the pediatrician 168 annotates the pathology and adds clinical notes thereby creating an annotated image 166A.

Still referring to FIG. 7, a pediatric neurologist 170 then receives the annotated image 166A and adds additional annotations thereby creating annotated image 166B. Annotated image 166B is then sent back to the primary care physician 164 with the annotations of both the pediatrician 168 and the pediatric neurologist 170. The primary care physician can then view the annotations interactively, that is, either separately or jointly.

An example of the structured output of vector information in the XML format is shown in Appendix 1. It should be understood that the structured output contained in Appendix 1 is provided for exemplary purposes only and should not be construed as limiting the present invention in anyway.

The following examples illustrate the various applications of the present invention. The examples are for illustrative purposes only and should not be construed as limiting in anyway but instead should be taken as representative of the wide applicability of the present invention to many different fields and professions.

Example 1

A neurosurgeon reviews a volume rendered set of MRI data that indicates the patient has an aneurysm. The neurosurgeon visually annotates a region of interest and adds a clinical note that is linked to the region of interest. The neurosurgeon identifies a previously undetected aneurysm and marks that region for consult with the neuroradiologist. The annotated image set may be sent to, or checked back into radiology imaging system with the annotations and added expert content linked to the three-dimensional model. The surgeon calls the radiologist for a consult on the

second aneurysm prior to sending the patient to surgery. The radiologist adds a clinical note that confirms the additional diseased region of interest without destroying the original information that was added by the surgeon. The neurosurgeon consults with the patient, outlining the second aneurysm prior to the surgery. Other neurosurgeons and radiologists, with the appropriate permissions, may check out the visually annotated image data set for review as reference or further multi-user annotation

Example 2

An investigator proceeds with an experiment which involves staining serial sections of a primate retina with three neurotransmitters to determine what cells interact with the neurotransmitters and the levels of interaction. The scientist discovers that one neurotransmitter affects all cell types and proceeds to cut serial sections of the tissue and combine them into a three dimensional surface rendering that maps the neurotransmitters and cells that are affected. The scientist visually annotates one of the synaptic ribbons that is formed within the secondary neuron framework and adds an expert interpretation of the synaptic interaction. The scientist sends the image to a colleague for an additional expert opinion of the structures. The colleague makes visual notes on the image set (without destroying or altering the underlying image set). The visual note is comprised of lines, polygons and points with associated text-based symbols and descriptions that outline an area on the image set. The visually annotated image set is maintained and examined by a molecular biologist for additional expert opinion of the interactions between neurotransmitters and cell types. The additional visual annotations and expert visual notes are stored with the originating scientist's notes.

Example 3

A plant biologist receives digital electron photographs/images (EM) of a stained tissue sample from a diseased plant. The plant biologist draws shapes (polygons, lines or edges, and points), pointers and textual symbols and descriptions with the visual annotation technology to indicate a region of interest and communicate expert understanding/interpretation of the EM images. This annotated image may be sent to, or checked back into a cataloging system at an agricultural center to be viewed by other individuals. Other plant biologists, with the appropriate permissions, may check out the image and visual annotation set for review as reference or further multi-user annotation. The annotated image may also be used for print output for a publication or sent electronically (email, Internet) to other experts for consultation. Such visual assets may later be used for time-based comparisons of the same area or as supporting material in a legal proceeding.

Example 4

A chemist determines the chemical structure of a compound that reduces the fat absorption in the large intestine. The chemist runs an electrophoretic gel to determine the weight of the chemical structures that make up the compound and discovers that one structure has different properties than the others. The chemist generates a digital image and visually annotates the questionable structure on the digital image. The chemist sends the image to another chemist for an additional expert opinion of the structure. The receiving chemist makes visual notes on the image (without destroying or altering the underlying image). The visual note is comprised of lines, polygons and points with associated text-based symbols and descriptions that outline an area on the image. These notes are then stored with the originating chemist's notes and are reviewed for any problems or questions. Likewise, both chemists can make additional visual notes about the work performed or problems encountered which are subsequently stored for review by other chemists and colleagues. The visual notes can be linked to additional images as they are generated as part of the investigation.

Example 5

A geologist receives digital aerial photographs/images of an earthquake fault area. The geologist may check-in the image(s) into a cataloging system. The geologist draws shapes (polygons, lines or edges, and points), pointers and textual symbols and descriptions with a digital annotation tool to communicate expert understanding of the aerial images. This annotated image may be checked back into the cataloging system. Other geologists with the appropriate permissions may check-out the image and visual annotation set for review as reference or further multi-user annotation. The annotated image may also be used for print output for a publication or sent electronically (email, Internet) to other experts for consultation. Such visual assets may later be used for time-based comparisons of the same area or as supporting material in a legal proceeding.

Example 6

A contracting electrician receives a digital blueprint for wiring a residential building. While reviewing the digital blueprint (image) the electrician makes visual notes on the blueprint (without destroying or altering the underlying blueprint). The visual note is comprised of lines, polygons and points with associated text-based symbols and descriptions. These notes are then stored with the general contractor and are reviewed for any problems or questions. Likewise the on-site electrician doing the wiring may review the visual notes to facilitate on-site work. While performing the on-site work the on-site electrician makes additional visual notes about the work performed or problems encountered which are subsequently stored for review by the general contractor and contracting electrician.

Example 7

A homeowner receives a digital blueprint from architect. While reviewing on-site progress the homeowner applies visual notes to blueprint for later communication to architect and general contractor. The general contractor can use the annotated regions of the blueprints to convey information to subcontractors. The notes are stored and reviewed by architect, general contractor and subcontractor. The architect, general contractor and subcontractor in turn, make additional annotation and notes. All notes and adjustments to the original blueprint are logged for review by all parties.

Example 8

The manager of a road construction project opens a map of the worksite and visually outlines the areas to be excavated and the areas of concern like telecommunications or sewer lines that should be avoided. This underlying map of the worksite with the applied expert knowledge of the project manager is given to the excavation crew for spatial guidance on where to and where not to excavate. Annotations and visual notes can be created and applied to layers in a system where one layer is telecommunications, another layer outlines water and sewer lines or electrical power lines. The annotations and visual notes are not embedded in the layers of images but remain in their original positions as the underlying images are changing.

Example 9

A mineralogist opens a digital microscopic image of a mineral sample as part of a mineral (oil, mining) exploration project. The expert mineralogist visually annotates the image with shapes (polygons, lines, points) and associated text-based symbols and descriptions. The image and associated visual annotations are logged and stored in the enterprise system. This analysis resides as reference material for later investigation and subsequent review and annotation by senior investigators for directing the exploration investigation. In addition, the analysis may be archived and retrieved at a later time for exploration reconsideration. The visual annotations are designed to be linked to the image data set and can be linked to additional images as they are generated as part of the investigation.

Example 10

An individual author can open an image in the visual annotation software. The author can then identify a region of interest and outline the region of interest, place an arrow and label indicating some feature in or on the region of interest and assign a group to the collective (e.g., abnormal structures versus normal structures) and write a caption for the annotated region of interest. The annotated groups can be organized in a hierarchical fashion according to the author's outline (e.g., a table of contents). The author can continue to visually annotate features on the same image or a set of images without destroying the underlying image(s), or having the visually annotated structures collide with one another. At the time of publishing the author may select from the hierarchy of annotated regions of interest by turning off and on individual or groups of regions of interest and associated captions for output to a digital press or other publication media (e.g., WWW or CD-ROM).

Example 11

A physician viewing an image of a cyst that has been heavily annotated over time by multiple specialist's can obtain particular advantage from the Interactive Visual Note (IVN) feature of selected illustrative embodiments of the present invention. In embodiments of the present invention incorporating IVN, the physician can select a single region of interest that contains additional information regarding the region of interest. For example, of immediate interest may be a cyst for which two annotations are selectively displayed. Each annotation outlines the cyst at a later date). At the end of each pointer for each annotation is a "hotspot." By moving the mouse pointer to that hotspot the user is dynamically presented a microscopic image of the pathology as well as a table reporting the microbiological/molecular findings. These results may be extensive and would, if not hidden as a default, take up the entire screen. But, these reports can be called up on demand while viewing the image, which is the main (in the case of this user) analytic medium. In contrast, previously available systems typically show the user the image and then the user must read the interpretation (in some of the illustrative embodiments of the present invention replaced by interactive visual annotations and brief notes, such as symbols-labels-captions) and view reports at separate locations. In accordance with selected illustrative embodiment of the present invention, the reporting or display of any related information can now be displayed or provided at the same location as the image, which improves the workflow of the user.

Example 12

The interactive visual note (IVN) feature of selected embodiments of the present invention provides physicians and healthcare support personnel with solutions to effectively and efficiently access and use the medical knowledge base across practice environments; facilities decision support and medical training. For example, healthcare specialists in the field administering small pox vaccines require the ability to collect visual image data of vaccinated individuals and add clinical findings that allow them to track the efficacy of the vaccination. The healthcare specialist in the field may annotate the affected region of interest (inoculation site) using a pointer, label or caption on the image and add a note to the annotations that supports the clinical findings. Additional annotations can be placed at the margins on the inoculation site indicating a change in scar formation over time (an outline at a later date). The medical specialist in the hospital setting receives the annotated images as a visual reference to develop a medical plan and reviews the field specialists' findings to determine if the inoculation was successful and adds an expert opinion of the findings to the annotated image data. Expanding on the above example, the field specialist reviews the medical specialist's expert findings and adds additional findings to the annotated region of interest such as adverse drug interactions observed in the field or changes observed in the inoculation site. The information remains linked to the visually annotated regions of interest and can be dynamically presented to the user as an IVN when the mouse cursor is in the "hot-spot". This collection of information, residing in a consistent user interface, can be reviewed by the appropriate governing body (for example, Centers for Disease Control) for additional indications or used to identify populations at risk. Field and medical specialists and officials who track small pox inoculations review medically relevant information in a consistent interface.

Example 13

Visually annotating a region of interest and adding a clinical note to indicate a clinical finding and linking that information to the patient record is also advantageously included in selected embodiments of the present invention, which can also function as a tool for decision support by the user. For example, a primary care physician located in a rural clinic treats a patient for a neck mass. The patient does not respond to antibiotics so the primary care physician requests a clinical and radiology consult and at a tertiary care facility. The radiologist visually annotates a region of interest (neck mass) and also visually annotates the abnormal or affected anatomy surrounding the neck mass. The radiologist calls for a surgical consult. The surgeon identifies and visually annotates an additional region of interest but also adds a clinical note to clarify the findings. The surgeon consults with the radiologist prior to surgery on the additional findings that grouped according to the surgical grouping. The radiologist's findings are grouped according to the radiology group and do not collide with the surgeons findings. Continuing this example, the surgeon removes the neck mass and sends it to pathology for testing. The pathologist visually annotates the histopathology and indicates the regions of interest that correspond to the CT regions of interest verifying the findings of the

radiologist and the surgeon. The pathologist's findings can also be contained in the interactive visual note along with the clinical findings of the radiologist and surgeon. The visual annotations, clinical notes and pathology report is contained in one record that can be viewed by the primary care physician in the rural clinic. The clinical case becomes a clinical reference for future congenital neck mass diagnosis.

Example 14

The visual annotation and knowledge representation features of the illustrative embodiments of the present invention can improve the delivery and quality of healthcare in the field environment. By leveraging the capability to transmit data using low bandwidths, vital medical information and essential medical expertise can be shared regardless of location and made available as far forward in a military theater of operations as necessary, without increasing the logistical footprint. This feature is particularly advantageous for deployed forces operating in an austere environment and a geographically distant theater supporting combat or humanitarian assistance operations where certain medical specialties may not be available. For example, a medic can capture visual information and annotate affected regions of interest in the field and send it to a central surgical hospital for immediate consult and triage. The medical specialist in a surgical facility can make a decision to transport the patient and at the same time, add a clinical note indicating initial findings for the patient that can be reviewed by the intake physicians. The ability to collect clinical notes among healthcare providers at all levels, ensures consistency in presentation of complex medical information. Providing an interface that medical professionals can use across skill levels and practice environments simplifies the medical decision making process between hospital and clinics to deployed forces and improve diagnosis, treatment, and evacuation decisions. Improved medical decision support can be critical on-board deployed ships, for example. By offering improved diagnosis, the illustrative embodiments of the present invention can prevent the unnecessary evacuation of personnel to medical facilities when they otherwise could be treated on-board ship.

From an understanding of the foregoing, it will be appreciated that the present invention advantageously allows: (1) A region of interest to be specified within an image using a raster independent notation, and promote the capture of associated textual information; (2) For each annotation to be easily manipulated (moved, sized, deleted) independently from other annotations (non-embedded annotations); (3) Annotations to be grouped using user defined group names (hierarchical groupings); (4) Annotations to be presented using user defined preferences (context appropriate viewing); (5) Multiple images to be viewed and annotated concurrently (multispecialty authoring); (6) Annotations to be saved in a simple format, for example XML, that may be permanently associated with the image; and (7) Image and annotations can be exported as a "flat" rasterized image for use in HTML pages, digital slide presentations and publications (providing cross-media capability).

Appendix 2, set forth below, contains an illustrative example of one embodiment of programming code that can be executed on a computer in accordance with the features of the present invention. It should be understood that the code in Table 2 should not be construed as limiting of the present invention in anyway.

It is to be understood that the above-described arrangements are only illustrative of the application of the principles of the present invention. Numerous modifications and alternative arrangements may be devised by those skilled in the art without departing from the spirit and scope of the present invention and the appended claims are intended to cover such modifications and arrangements. Thus, while the present invention has been shown in the drawings and described above with particularity and detail, it will be apparent to those of ordinary skill in the art that numerous modifications, including, but not limited to, variations in size, materials, shape, form, function and manner of operation, assembly and use may be made without departing from the principles and concepts set forth herein.

```
<IAT>
<canvas>
  <border color="black" > 0.02 0.02 0.02 0.02 </border>
</canvas>
5  <annotations>
    <roi type="area" order="2" >
      <views> NEW </views>
      <authors last="John Doe" revision="0"> </authors>
      <code> </code>
10    <symbol> MCF </symbol>
      <label> Middle Cranial Fossae </label>
      <caption> </caption>
      <cs_class> </cs_class>
      <cs_tumor> </cs_tumor>
15    <cs_node> </cs_node>
      <cs_metastasis> </cs_metastasis>
      <cs_note> </cs_note>
      <vertexs> 0.08056,0.66667 0.05833,0.58125 0.06944,0.50208 0.14444,0.38333 0.20278,0.36875
0.26389,0.36458 0.32222,0.37500 0.38056,0.40000 0.43333,0.43958 0.43889,0.42500 0.45833,0.41458
20 0.48889,0.40417 0.51667,0.40833 0.54167,0.40625 0.56944,0.42292 0.59444,0.44375 0.61944,0.43542
0.65556,0.40208 0.69722,0.37917 0.75278,0.36875 0.81389,0.37500 0.89167,0.39792 0.91944,0.43750
0.95278,0.53958 0.95278,0.59792 0.93889,0.65417 0.92222,0.68750 0.89722,0.72083 0.86944,0.71250
0.83056,0.68542 0.73333,0.62292 0.64444,0.56458 0.56389,0.54583 0.49444,0.53958 0.41944,0.54583
0.34722,0.56875 0.29722,0.59792 0.17778,0.67292 0.14444,0.71250 0.11667,0.71458 </vertexs>
25  <pointer head="1" point="1" tail="0.08611,0.61042" shape="none" text="symbol" > </pointer>
      <color> black </color>
    </roi>
    <roi type="area" order="2.5" >
      <views> NEW </views>
30    <authors last="John Doe" revision="0"> </authors>
      <code> </code>
      <symbol> SOF </symbol>
      <label> Superior Oribal Fissure </label>
      <caption> </caption>
35    <cs_class> </cs_class>
      <cs_tumor> </cs_tumor>
      <cs_node> </cs_node>
      <cs_metastasis> </cs_metastasis>
      <cs_note> </cs_note>
40    <vertexs> 0.43333,0.43958 0.44444,0.42708 0.45556,0.42292 0.46389,0.43125 0.45833,0.44583
0.45556,0.45625 0.44444,0.46667 0.43611,0.46667 0.43056,0.45000 </vertexs>
      <pointer head="5" point="5" tail="0.49722,0.46667" shape="line" text="symbol" > </pointer>
      <color> black </color>
    </roi>
45    <roi type="area" order="2.4" >
      <views> NEW </views>
      <authors last="Jane Doe" revision="0"> </authors>
      <code> </code>
      <symbol> FS </symbol>
50    <label> Foramen Spinosum </label>
      <caption> </caption>
      <cs_class> </cs_class>
      <cs_tumor> </cs_tumor>
      <cs_node> </cs_node>
55    <cs_metastasis> </cs_metastasis>
      <cs_note> </cs_note>
      <vertexs> 0.31389,0.52708 0.32222,0.51667 0.33611,0.51667 0.33889,0.52708 0.33056,0.53542
0.31667,0.53542 </vertexs>
      <pointer head="auto" point="0" tail="0.26944,0.52500" shape="line" text="symbol" > </pointer>
60    <color> black </color>
    </roi>
    <roi type="area" order="2.1" >
      <views> NEW </views>
      <authors last="John Doe" revision="0"> </authors>
65    <code> </code>
      <symbol> FL </symbol>
      <label> Foramen Lacerum </label>
      <caption> The foramen lacerum is an artifact of a dried skull. In life, nothing is transmitted
70 through it vertically and it is closed by a plate of cartilage. </caption>
      <cs_class> </cs_class>
      <cs_tumor> </cs_tumor>
      <cs_node> </cs_node>
      <cs_metastasis> </cs_metastasis>
      <cs_note> </cs_note>
75    <vertexs> 0.40278,0.52917 0.41111,0.51875 0.42500,0.50833 0.44444,0.50417 0.46111,0.50625
0.46111,0.51875 0.45000,0.52708 0.42778,0.53333 0.40833,0.53542 </vertexs>
      <pointer head="auto" point="5" tail="0.49444,0.51667" shape="line" text="symbol" > </pointer>
      <color> black </color>
    </roi>
80    <roi type="area" order="3.1" >
      <views> NEW </views>
```

```

5  <authors last="Jane Doe" revision="3">
    <author name="Jack Doe" revision="1">
        <label> Cribriform Plate </label>
        <color> red </color>
    </author>
    <author name="John Doe" revision="0">
        <label> Cranial Plate </label>
        <color> white </color>
    </author>
10 </authors>
    <code> </code>
    <symbol> CP </symbol>
    <label> Cribriform Plate </label>
    <caption> </caption>
15 <cs_class> </cs_class>
    <cs_tumor> </cs_tumor>
    <cs_node> </cs_node>
    <cs_metastasis> </cs_metastasis>
    <cs_note> </cs_note>
20 <vertexs> 0.47778,0.27083 0.49444,0.23542 0.51111,0.24792 0.51667,0.26667 0.52778,0.24583
    0.54167,0.23958 0.56111,0.27708 0.55556,0.30417 0.54722,0.32708 0.53333,0.34583 0.50278,0.34167
    0.48889,0.32083 0.48611,0.29583 </vertexs>
    <pointer head="auto" point="6" tail="0.59167,0.27500" shape="line" text="symbol" > </pointer>
    <color> black </color>
25 </roi>
    <roi type="area" order="2.2" >
        <views> NEW </views>
        <authors last="Jane Doe" revision="0"> </authors>
        <code> </code>
        <symbol> FO </symbol>
        <label> Foramen Ovale </label>
        <caption> </caption>
        <cs_class> </cs_class>
        <cs_tumor> </cs_tumor>
        <cs_node> </cs_node>
        <cs_metastasis> </cs_metastasis>
        <cs_note> </cs_note>
        <vertexs> 0.34444,0.50417 0.36389,0.49375 0.37500,0.48958 0.38889,0.48750 0.39444,0.49167
        0.39444,0.49583 0.39444,0.50417 0.39167,0.51250 0.38056,0.52083 0.36944,0.52500 0.35556,0.52500
40 0.34444,0.52083 0.33889,0.51250 </vertexs>
        <pointer head="auto" point="0" tail="0.30278,0.47083" shape="line" text="symbol" > </pointer>
        <color> black </color>
    </roi>
    <roi type="area" order="2.3" >
45 <views> NEW </views>
        <authors last="Jane Doe" revision="0"> </authors>
        <code> </code>
        <symbol> FR </symbol>
        <label> Foramen Rotundum </label>
50 <caption> </caption>
        <cs_class> </cs_class>
        <cs_tumor> </cs_tumor>
        <cs_node> </cs_node>
        <cs_metastasis> </cs_metastasis>
        <cs_note> </cs_note>
55 <vertexs> 0.39444,0.43958 0.40556,0.43958 0.41389,0.44167 0.42778,0.44792 0.43056,0.46042
        0.41667,0.45833 0.40278,0.45417 0.39444,0.44792 </vertexs>
        <pointer head="0" point="0" tail="0.34722,0.42292" shape="line" text="symbol" > </pointer>
        <color> black </color>
60 </roi>
    <roi type="area" order="1" >
        <views> NEW </views>
        <authors last="John Doe" revision="0"> </authors>
        <code> </code>
        <symbol> PCF </symbol>
        <label> Posterior Cranial Fossae </label>
        <caption> </caption>
        <cs_class> </cs_class>
        <cs_tumor> </cs_tumor>
        <cs_node> </cs_node>
70 <cs_metastasis> </cs_metastasis>
        <cs_note> </cs_note>
        <vertexs> 0.50000,0.88125 0.65833,0.87292 0.75278,0.83125 0.85000,0.76875 0.88333,0.74167
        0.76944,0.65417 0.72222,0.63333 0.69167,0.60208 0.60556,0.55208 0.51111,0.54792 0.41389,0.54792
75 0.34722,0.57708 0.26944,0.62708 0.18056,0.68542 0.14722,0.74167 0.18889,0.78542 0.23611,0.82083
        0.34444,0.86042 </vertexs>
        <pointer head="14" point="14" tail="0.17500,0.73542" shape="none" text="symbol" > </pointer>
        <color> black </color>
    </roi>
80 <roi type="area" order="1.1" >
    <views> NEW </views>
```


Appendix 1

```

    <authors last="John Doe" revision="0"> </authors>
    <code> </code>
    <symbol> FM </symbol>
    <label> Foramen Magnum </label>
5    <caption> </caption>
    <cs_class> </cs_class>
    <cs_tumor> </cs_tumor>
    <cs_node> </cs_node>
    <cs_metastasis> </cs_metastasis>
10   <cs_note> </cs_note>
    <vertexs> 0.50556,0.61667 0.52500,0.62083 0.54444,0.63333 0.56944,0.65208 0.58333,0.65833
0.58889,0.67917 0.60556,0.68958 0.60278,0.72917 0.58611,0.74792 0.55556,0.76667 0.53056,0.77708
0.50000,0.78542 0.47222,0.78125 0.44722,0.76458 0.42222,0.75208 0.41389,0.73750 0.41111,0.71875
0.41111,0.69583 0.41389,0.68333 0.42222,0.67083 0.45278,0.64167 0.47778,0.62500 </vertexs>
15   <pointer head="17" point="17" tail="0.43056,0.71458" shape="none" text="symbol" > </pointer>
    <color> #ffffff </color>
    </roi>
    <roi type="area" order="3" >
    <views> NEW </views>
20   <authors last="John Doe" revision="0"> </authors>
    <code> </code>
    <symbol> ACF </symbol>
    <label> Anterior Cranial Fossae </label>
    <caption> </caption>
25   <cs_class> </cs_class>
    <cs_tumor> </cs_tumor>
    <cs_node> </cs_node>
    <cs_metastasis> </cs_metastasis>
    <cs_note> </cs_note>
30   <vertexs> 0.35278,0.12917 0.46111,0.11042 0.50278,0.12083 0.53889,0.11458 0.63056,0.12083
0.70000,0.13958 0.82222,0.25417 0.85556,0.31667 0.87778,0.35833 0.87222,0.37708 0.75833,0.35625
0.68333,0.37083 0.63889,0.39583 0.62222,0.41458 0.60000,0.42083 0.56944,0.40208 0.51389,0.39375
0.45278,0.40208 0.43333,0.41042 0.41944,0.41458 0.36944,0.38125 0.31111,0.35833 0.23611,0.34792
0.18611,0.36042 0.15556,0.35417 0.20278,0.25000 0.26667,0.17917 </vertexs>
35   <pointer head="25" point="25" tail="0.20556,0.28333" shape="none" text="symbol" > </pointer>
    <color> black </color>
    </roi>
    </annotations>
</IAT>
```

```

iat.ant.txt
# Copyright (c) 2001, University of Utah
# All rights reserved.
#
5 # iat.ant.tcl

source iat.antptr.tcl
source iat.antio.tcl
source iat.antsvg.tcl
10 namespace eval iat::ant {

    variable TRACE 0
    variable next_nsid 1
    variable rawkey 1
    variable rawsave 0
    # this assumes roi pts < 1000
    # see ant_create_pointer...
    variable autoptr 1000
    variable thisptr 1000

    variable precmd ""
    variable ord2key
    variable leaf_id 0
    25 # all annotations
    variable view "ALL"

    # active annotation
    30 variable antkey ""
    variable order
    variable point
    variable points [list]
    variable head
    35 variable heads
    variable verts
    variable tails
    variable dSYMs
    variable dPTRs
    40 variable kind "none"
    variable color "default"
    variable code ""
    variable symbol ""
    variable label ""
    45 variable caption ""
    variable cs_class ""
    variable cs_tumor ""
    variable cs_node ""
    variable cs_metastasis ""
    50 array set heads [list]
    array set verts [list]
    array set tails [list]
    array set dSYMs [list]
    55 variable fillColor
    variable linecolor

    variable styleColorLight #FFF
    60 variable styleColorDefault yellow
    variable styleColorDark #000

    variable styleFontName helvetica
    variable styleFontSmall 28
    65 variable styleFontDefault 38
    variable styleFontLarge 48

}

70 namespace eval iat::antOLD {

    # flags
    variable channels ""
    # annotations
    75 variable polygons
    variable canvas
    variable offsetX 0
    variable offsetY 0
    variable imageX 0
    80 variable imageY 0
    variable roiKey

```

```

variable pointsDirty 0
variable symbolDirty 0
variable points
variable sectors
5 variable point
variable rawID
variable select

variable orders
10 variable kinds
variable symbols
variable labels
variable captions
variable centers
15 variable pointers
variable sizes
variable colors
# not part of methodology - only presentation ???
variable views
20 variable sorls
variable pointerPoints
variable symbolPoints

variable order
25 variable kind
variable symbol
variable label
variable caption
variable center
30 variable pointer
variable size
variable color
variable symbolPoint
variable view
35 variable sorl

# calculated...
variable fillColor
variable linecolor
40 variable pointerPoint
variable angle

variable orderToKey

45 variable callbackSelect
set callbackSelect "noop"

variable callbackDeselect
set callbackDeselect "noop"
50

set roiKey ""
set rawID 1000
set points [list]
set select "NONE"
55 set imageX 100
set imageY 100

variable styleColorLight #FFF
variable styleColorDefault yellow
60 variable styleColorDark #000

variable styleFontName helvetica
variable styleFontSmall 28
variable styleFontDefault 38
65 variable styleFontLarge 48

#font create LABEL -family arial -size 32
)

70 #package require iat.roi.svg

proc iat::ant::next_nsid {} {
    variable next_nsid
    return [incr next_nsid]
75 }

proc iat::ant::proc ( ns cmd args ) {
    variable TRACE
    if ($TRACE) { puts "iat::ant::proc: $ns $cmd $args" }
80
    variable antkey

```

```

variable color
variable inview
variable code
  variable symbol
5  variable label
  variable caption
  variable cs_class
  variable cs_tumor
  variable cs_node
10 variable cs_metastasis
  variable cs_note

  switch $cmd {
    "configure" {
15      #puts " cmd = configure: $args"
      foreach (key value) $args {
        #puts " key = $key & value = $value"
        switch -- $key {
          "-canvas" { set_canvas $ns $value }
20          "-cmdcanvas" { set_cmdcanvas $ns $value }
            "-size" { set_image_size $ns $value }
            "-offset" { set_image_offset $ns $value }
            "-select" { set_select_mode $ns $value }
        }
      }
    }
    "cget" {
      #puts " cmd = cget: $args"
      switch -- [lindex $args 0] {
30        "-offset" { return [get_image_offset $ns] }
        "-size" { return [get_image_size $ns] }
      }
    }
    "begin" {
35      switch -- [lindex $args 0] {
        "canvas" { precmd $ns canvas }
        "annotations" { precmd $ns annotations }
      }
    }
    "end" {
40      }
    "close" {
      return [ant_close $ns]
    }
    "create" {
45      #puts " cmd = create: $args"
      #ant_create [lindex $args 0]
      switch -- [lindex $args 0] {
        "roi" { return [ant_create $ns [lindex $args 1]] }
        "vertex" { return [ant_vertex_add $ns [lindex $args 1]] }
50        "vertexs" { return [ant_vertexs_add $ns [lindex $args 1]] }
        "pointer" { return [ant_create_pointer $ns [lindex $args 1] [lindex $args 2] [lindex $args
31] )
      }
    }
    "delete" {
55      #puts " cmd = delete: $args"
      switch -- [lindex $args 0] {
        "ptrvert" { return [ant_delete_ptrvert $ns [lindex $args 1] [lindex $args 2]] }
        "pointer" { return [ant_delete_pointer $ns [lindex $args 1]] }
60        "vertex" { return [ant_delete_vertex $ns [lindex $args 1]] }
        "active" { return [ant_delete $ns active] }
        "annotation" { return [ant_delete $ns [lindex $args 1]] }
        default { return [ant_delete $ns [lindex $args 1]] }
65      }
      #ant_delete $ns [lindex $args 0]
    }
    "deselect" {
      ant_deselect $ns
70      }
    "draw" {
      #puts " cmd = draw: $args"
      switch -- [lindex $args 0] {
        "segments" { return [ant_draw_segments $ns] }
        "vertexs" { return [ant_draw_vertexs $ns] }
75        "active" { return [ant_draw $ns active] }
        "all" { return [ant_draw_all $ns] }
        default { return [ant_draw $ns [lindex $args 0]] }
      }
    }
    "dump" {
80      }

```

```

        ant_dump $ns 0
    }
    "dump_keys" {
        ant_dump_keys $ns
    }
    "dump_svg" {
        ant_dump_svg $ns 0
    }
    "erase" {
        #puts " cmd = draw: $args"
        switch -- [lindex $args 0] {
            "all" { return [ant_erase_all $ns]}
            default { ant_erase $ns [lindex $args 0] }
        }
    }
    "insert" {
        #puts " cmd = insert: $args"
        switch -- [lindex $args 0] {
            "vertex" { return [ant_insert_vertex $ns [lindex $args 1] [lindex $args 2]] }
            "ptrvert" { return [ant_insert_ptrvert $ns [lindex $args 1] [lindex $args 2]
[lindex $args 3]] }
        }
    }
    "kind" {
        ant_kind $ns
    }
    "load" {
        ant_load $ns [lindex $args 0]
    }
    "make" {
        switch -- [lindex $args 0] {
            "active" { return [ant_make $ns active [lindex $args 1]] }
            "all" { return [ant_make_all $ns [lindex $args 1]] }
            "svg" { return [ant_make_svg_all $ns [lindex $args 1]] }
        }
    }
    "move" {
        #puts " cmd = move: $args"
        switch -- [lindex $args 0] {
            "delta" { return [ant_move_ant_delta $ns [lindex $args 1]] }
            "vertex" { return [ant_move_vertex $ns [lindex $args 1] [lindex $args 2]] }
            "head" { return [ant_move_ptr_head $ns [lindex $args 1] [lindex $args 2]] }
            "ptrvert" { return [ant_move_ptr_vert $ns [lindex $args 1] [lindex $args 2]
[lindex $args 3]] }
            "tail" { return [ant_move_ptr_tail $ns [lindex $args 1] [lindex $args 2]] }
        }
    }
    "read_cmds" {
        return [ants_read_cmds $ns [lindex $args 0]]
    }
    "parse" {
        return [ants_parse $ns [lindex $args 0]]
    }
    "point" {
        ant_point $ns [lindex $args 0]
    }
    "points" {
        ant_points $ns
    }
    "pointer" {
        #puts " cmd = move: $args"
        switch -- [lindex $args 0] {
            "style" { return [ant_ptr_style $ns [lindex $args 1] [lindex $args 2]] }
            "pin" { return [ant_ptr_pin $ns [lindex $args 1] [lindex $args 2]] }
            "symbol" { return [ant_ptr_symbol $ns [lindex $args 1] [lindex $args 2]] }
        }
    }
    "save" {
        ant_save $ns
    }
    "select" {
        return [ant_select $ns [lindex $args 0]]
    }
    "get" {
        #puts " cmd = get: $args"
        switch -- [lindex $args 0] {
            "key" { return $antkey }
            "color" { return $color }
            "code" { return $code }
            "inview" { return $inview }
            "symbol" { return $symbol }
        }
    }

```

```

    "label" { return $label }
    "caption" { return $caption }
    "cs_class" { return $cs_class }
    "cs_tumor" { return $cs_tumor }
5    "cs_node" { return $cs_node }
    "cs_metastasis" { return $cs_metastasis }
    "cs_note" { return $cs_note }
    default { return $antkey }
    }
10  }
    "set" {
        #puts " cmd = set: $args"
        switch -- [lindex $args 0] {
            #head" { return [ant_set_pointer $ns [lindex $args 1]] }
            "color" { return [ant_set_color $ns [lindex $args 1]] }
15    "order" { return [ant_set_order $ns [lindex $args 1]] }
            "view" { return [ant_set_view $ns [lindex $args 1]] }
            "inview" { return [ant_set_inview $ns [lindex $args 1]] }
            "code" { return [ant_set_code $ns [lindex $args 1]] }
20    "symbol" { return [ant_set_symbol $ns [lindex $args 1]] }
            "label" { return [ant_set_label $ns [lindex $args 1]] }
            "caption" { return [ant_set_caption $ns [lindex $args 1]] }
            "cs_class" { return [ant_set_cs_class $ns [lindex $args 1]] }
            "cs_tumor" { return [ant_set_cs_tumor $ns [lindex $args 1]] }
25    "cs_node" { return [ant_set_cs_node $ns [lindex $args 1]] }
            "cs_metastasis" { return [ant_set_cs_metastasis $ns [lindex $args 1]] }
            "cs_note" { return [ant_set_cs_note $ns [lindex $args 1]] }
        }
    }
30  "update" {
        #puts " cmd = set: $args"
        switch -- [lindex $args 0] {
            "view" { return [ant_update_view $ns] }
35    }
        default {
            puts "ERROR unknown command = $cmd"
        }
    }
40  return {}
}

proc iat::ant::precmd { ns pre } {
45  variable precmd

  upvar #0 [join [list [namespace current] $ns cmdcanvas] ::] cmdcanvas

50  switch $pre {
    "canvas" { set precmd $cmdcanvas }
    "annotations" { set precmd [join [list [namespace current] $ns ] ::] }
    default {
        puts "ERROR unknown precmd = $pre"
55    }
  }
}

proc iat::ant::create { args } {
60  variable TRACE
  if ($TRACE) { puts "iat::ant::create: $args" }

  set nsid [next_nsid]

65  set ns [namespace current]::ants$nsid

  namespace eval $ns {
    variable select_mode annotation
    variable cmdcanvas
    variable canvas
    variable offsetX 0
    variable offsetY 0
    variable imageX 0
    variable imageY 0
75  variable orders
    variable polys
    variable aheads
    variable averts
    variable atails
    variable adSYMs
80  variable adPTRs

```



```

        variable kinds
        variable colors
        variable invIEWS
        variable codes
5       variable symbols
        variable labels
        variable captions
        variable cs_classss
        variable cs_tumors
10      variable cs_nodes
        variable cs_metastasiss
        variable cs_notes

        array set aheads [list]
15      array set averts [list]
        array set atails [list]
        array set sdSYMs [list]
    )

20      set cmd "proc [namespace current]::ants$nsid { cmd args } {eval [namespace current]::proc ants$nsid
\ $cmd \ $args}"
        namespace eval :: $cmd
        eval "[namespace current]::ants$nsid configure $args"

25      ant_create_defaults

        return [namespace current]::ants$nsid
    )

30 proc iat::ant::ant_close { ns } {
    variable TRACE
    if {$TRACE} { puts "iat::ant::close: $ns" }

        ant_delete_all $ns
35      ant_create_defaults
    }

    proc iat::ant::destroy { args } {
40      variable TRACE
        if {$TRACE} { puts "iat::ant::destroy: $args" }
    }

45 proc iat::ant::set_canvas { ns args } {
    variable TRACE
        if {$TRACE} { puts "iat::ant::set_canvas: $ns $args" }

        upvar #0 [join [list [namespace current] $ns canvas] ::] canvas
50      set canvas [lindex $args 0]
    }

55 proc iat::ant::set_cmdcanvas { ns args } {
    variable TRACE
        if {$TRACE} { puts "iat::ant::set_cmdcanvas: $ns $args" }

        variable precmd
60      upvar #0 [join [list [namespace current] $ns cmdcanvas] ::] cmdcanvas

        set cmdcanvas [lindex $args 0]
        set precmd $cmdcanvas
65    }

    proc iat::ant::set_image_size { ns args } {
        variable TRACE
70      if {$TRACE} { puts "iat::ant::set_image_size: $ns $args" }

        upvar #0 [join [list [namespace current] $ns imageX] ::] imageX
        upvar #0 [join [list [namespace current] $ns imageY] ::] imageY

75      set imageX [lindex [lindex $args 0] 0]
        set imageY [lindex [lindex $args 0] 1]

        font_update $ns

80    }

```

```

proc iat::ant::set_image_offset { ns args } {
    variable TRACE
    if {$TRACE} { puts "iat::ant::set_image_offset: $ns $args" }

5      upvar #0 [join [list [namespace current] $ns offsetX] ::] offsetX
      upvar #0 [join [list [namespace current] $ns offsetY] ::] offsetY

      set offsetX [lindex [lindex $args 0] 0]
      set offsetY [lindex [lindex $args 0] 1]
10    }

    proc iat::ant::set_select_mode { ns mode } {
        variable TRACE
15      if {$TRACE} { puts "iat::ant::set_select_mode: $ns $mode" }

        upvar #0 [join [list [namespace current] $ns select_mode] ::] select_mode

        if {$mode == "edit"} {
20          set select_mode edit
        } else {
            set select_mode annotation
        }
    }
25 }

    proc iat::ant::ant_set_color { ns clr } {
        variable TRACE
30      if {$TRACE} { puts "iat::ant::ant_set_color: $ns $clr" }

        variable rawsave
        variable color
        variable styleColorDefault

35      if {$clr == ""} {
            set color $styleColorDefault
        } else {
            set color $clr
        }
40      if {!$rawsave} {
            ant_save $ns
            #ant_draw $ns active
        }
45 }

    proc iat::ant::ant_set_order { ns txt } {
        variable TRACE
50      if {$TRACE} { puts "iat::ant::ant_set_order: $ns $txt" }

        variable rawsave
        variable order

        set order $txt

55      if {!$rawsave} {
            #ant_save $ns
            #ant_draw $ns active
        }
60 }

    proc iat::ant::ant_set_view { ns txt } {
        variable TRACE
65      if {$TRACE} { puts "iat::ant::ant_set_view: $ns $txt" }

        variable rawsave
        variable view

        set view $txt

70      if {!$rawsave} {
            ant_save $ns
            ant_draw_all $ns
        }
75 }

    proc iat::ant::ant_update_view { ns } {
        variable TRACE
80      if {$TRACE} { puts "iat::ant::ant_update_view: $ns" }

```

Appendix 2

```

upvar #0 [join [list [namespace current] $ns inviews] ::] inviews

set allvals [list]
foreach (key value) [array get inviews] {
5   #puts "  inview: $key = $value"
    set vals [split $value]
    foreach (val) $vals {
        if {[lsearch $allvals $val] < 0} {
10         set allvals [concat $allvals $val]
        }
    }
}

#return [list A B C]
15 return [lsort -dictionary $allvals]
}

proc iat::ant::ant_set_inview { ns txt } {
    variable TRACE
20   if ($TRACE) { puts "iat::ant::ant_set_inview: $ns $txt" }

    variable rawsave
    variable inview

25   set inview $txt

    if (!$rawsave) {
        #ant_save $ns
        #ant_draw $ns active
30   }
}

proc iat::ant::ant_set_code { ns txt } {
    variable TRACE
35   if ($TRACE) { puts "iat::ant::ant_set_code: $ns $txt" }

    variable rawsave
    variable code

40   set code $txt

    if (!$rawsave) {
        #ant_save $ns
        #ant_draw $ns active
45   }
}

proc iat::ant::ant_set_symbol { ns txt } {
    variable TRACE
50   if ($TRACE) { puts "iat::ant::ant_set_symbol: $ns $txt" }

    variable rawsave
    variable symbol

55   set symbol $txt

    if (!$rawsave) {
        #ant_save $ns
        #ant_draw $ns active
60   }
}

proc iat::ant::ant_set_label { ns txt } {
    variable TRACE
65   if ($TRACE) { puts "iat::ant::ant_set_label: $ns $txt" }

    variable rawsave
    variable label

70   set label $txt

    if (!$rawsave) {
        #ant_save $ns
        #ant_draw $ns active
75   }
}

proc iat::ant::ant_set_cs_class { ns txt } {
    variable TRACE
80   if ($TRACE) { puts "iat::ant::ant_set_cs_class: $ns $txt" }
}

```

```

    variable rawsave
    variable cs_class

    set cs_class $txt
5
)

proc iat::ant::ant_set_cs_tumor { ns txt } {
    variable TRACE
10    if {$TRACE} { puts "iat::ant::ant_set_cs_tumor: $ns $txt" }

    variable rawsave
    variable cs_tumor

15    set cs_tumor $txt

}

proc iat::ant::ant_set_cs_node { ns txt } {
20    variable TRACE
    if {$TRACE} { puts "iat::ant::ant_set_cs_node: $ns $txt" }

    variable rawsave
    variable cs_node

25    set cs_node $txt

}

30 proc iat::ant::ant_set_cs_metastasis { ns txt } {
    variable TRACE
    if {$TRACE} { puts "iat::ant::ant_set_cs_metastasis: $ns $txt" }

    variable rawsave
35    variable cs_metastasis

    set cs_metastasis $txt

}

40 proc iat::ant::ant_set_cs_note { ns txt } {
    variable TRACE
    if {$TRACE} { puts "iat::ant::ant_set_cs_note: $ns $txt" }

45    variable rawsave
    variable cs_note

    set cs_note $txt

50 }

proc iat::ant::ant_set_caption { ns txt } {
    variable TRACE
55    if {$TRACE} { puts "iat::ant::ant_set_caption: $ns $txt" }

    variable rawsave
    variable caption

    set caption $txt

60    if (!$rawsave) {
        #ant_save $ns
        #ant_draw $ns active
    }

65 }

# must be called as part of imageUpdate
proc iat::ant::font_update { ns } {
    variable styleFontName
70    variable styleFontSmall
    variable styleFontDefault
    variable styleFontLarge

    upvar #0 [join [list [namespace current] $ns imageX] ::] imageX
75    upvar #0 [join [list [namespace current] $ns imageY] ::] imageY

    set flist [list]
    lappend flist styleFontSmall fontSmall
    lappend flist styleFontDefault fontDefault
    lappend flist styleFontLarge fontLarge
80    foreach {size font} $flist {

```

Appendix 2

```

#upvar #0 styleSize $size
set calcSize [expr round(ceil((($imageX + $imageY)/2) * 0.001 * (set $size)))]
font configure $font -family $styleFontName -size $calcSize
}
5 )

proc iat::ant::ant_next_key () {
    variable rawkey
    set key $rawkey
10    incr rawkey
    return $key
}

proc iat::ant::orderChange (old new) {
15    variable kind
    variable order
    variable orders
    variable orderToKey

20    if {[info exists orderToKey($old)]} {
        set orderToKey($new) $orderToKey($old)
        unset orderToKey($old)
        set order $new
        set orders($orderToKey($new)) $new
25    } else {
        # something is wrong... orderToKey is not in sync with annotations...
        error "orderToKey does not contain $old"
    }

    # if current annotation is a group then change sub-annotations orders
    # that match the old order pattern...
30    if {$kind == "group"} {
        foreach (key ord) [array get orders] {
            if {[regexp "^$old" $ord]} {
                set tmpord ""
35                regsub "^$old" $ord $new tmpord
                #puts "iat::ant::orderChange group $ord -> $tmpord"
                set orders($key) $tmpord
            }
        }
40    }
}

proc iat::ant::orderToKey ( ord ) {
45    variable orders
    variable orderToKey

    set key ""
    if {[info exists orderToKey($ord)]} {
50        set key $orderToKey($ord)
    }

    return $key
}

55 proc iat::ant::imageUpdate { ox oy ix iy } {
    variable canvas
    variable offsetX
    variable offsetY
    variable imageX
60    variable imageY
    variable polygons
    variable points

    # breaking api and not loading/saving annotation...

65    set offsetX $ox
    set offsetY $oy
    set imageX $ix
    set imageY $iy

70    # pointer needs this into too...
    iat::pointer::imageUpdate

    styleFontUpdate

75 )

proc iat::ant::isPointInPoints { pt pts } {
    set n 0
    set x [lindex $pt 0]
80    set y [lindex $pt 1]
    foreach pt $pts {

```

```

    set vx [lindex $pt 0]
    set vy [lindex $pt 1]
    if {[expr abs($vx - $x)] < 4} {
        if {[expr abs($vy - $y)] < 4} {
5         return $n
        }
    }
    incr n
10    return -1
}

proc iat::ant::isPointInBox { x y box } {
    set x1 [lindex $box 0]
15    set y1 [lindex $box 1]
    set x2 [lindex $box 2]
    set y2 [lindex $box 3]
    if {[expr $x > $x1 && $x < $x2]} {
        if {[expr $y > $y1 && $y < $y2]} {
20         return 1
        }
    }
    return 0
}

25 proc iat::ant::pointsTranslateOLD { dx dy pts } {
    #puts "iat::ant::points_translate: $dx $dy"
    #puts " points = $pts"
    set newpts [list]
    foreach pt $pts {
30         set x [expr [lindex $pt 0] + $dx]
        set y [expr [lindex $pt 1] + $dy]
        lappend newpts [list $x $y]
    }
35    return $newpts
}

proc iat::ant::pointsFrom10K_OLD { maxX maxY pts } {
    #puts "iat::ant::pointsFrom10K: $pts"
40    set newpts [list]
    foreach pt $pts {
        set x [expr round([lindex $pt 0]*$maxX)/10000)+1]
        set y [expr round([lindex $pt 1]*$maxY)/10000)+1]
        # also add offset!
45        #set x [expr $x + $offsetX]
        #set y [expr $y + $offsetY]
        lappend newpts [list $x $y]
    }
    return $newpts
50 }

proc iat::ant::pointsTo10K_OLD { maxX maxY pts } {
    #puts "iat::ant::pointsTo10K: $maxX $maxY $pts"
    set newpts [list]
55    foreach pt $pts {
        set x [expr round([lindex $pt 0]*10000)/$maxX]
        set y [expr round([lindex $pt 1]*10000)/$maxY]
        lappend newpts [list $x $y]
    }
    #puts "before: $pts"
    #puts "after: $newpts"
    return $newpts
}

65 proc iat::ant::pointsTo10K { maxX maxY pts } {
    #puts "iat::ant::pointsTo10K: $maxX $maxY $pts"
    set newpts [list]
    foreach pt $pts {
        set x [format "%1.5f" [expr double([lindex $pt 0])/($maxX)]]
70        set y [format "%1.5f" [expr double([lindex $pt 1])/($maxY)]]
        lappend newpts [list $x $y]
    }
    #puts "before: $pts"
    #puts "after: $newpts"
75    return $newpts
}

proc iat::ant::pointsFrom10K { maxX maxY pts } {
    #puts "iat::ant::pointsFrom10K: $pts"
80    set newpts [list]
    foreach pt $pts {

```


Appendix 1

```

    set x [expr round([lindex $pt 0]*$maxX)]
    set y [expr round([lindex $pt 1]*$maxY)]
    lappend newpts [list $x $y]
}
5  #puts "before: $pts"
   #puts "after: $newpts"
   return $newpts
}

10 # calculate "centroid" of one, two and three+ point rois
   proc iat::ant::roiCentroid () {
       #puts "polygonCentroid"
       variable points
       set ttlpts [llength $points]
15  set xs [list]
       set ys [list]
       foreach pt $points {
           lappend xs [lindex $pt 0]
           lappend ys [lindex $pt 1]
20  }
       if {$ttlpts <= 0} {
           return 0
       } elseif {$ttlpts == 1} {
           return [list [lindex $xs 0] [lindex $ys 0]]
25  } elseif {$ttlpts == 2} {
           set midx [expr ([lindex $xs 0]+[lindex $xs 1])/2]
           set midy [expr ([lindex $ys 0]+[lindex $ys 1])/2]
           return [list $midx $midy]
       }
30  #puts "xs = $xs"
       #puts "ys = $ys"
       set n [llength $xs]
       if {$n < 3} { return 3 }
       set ai 0 ; set atmp 0 ; set xtmp 0 ; set ytmp 0
35  set j 0
       for {set i [expr $n -1]} {$j < $n} {incr j} {
           set ai [expr [lindex $xs $i] * [lindex $ys $j] - [lindex $xs $j] * [lindex $ys $i]]
           incr atmp $ai
           incr xtmp [expr ([lindex $xs $j] + [lindex $xs $i]) * $ai]
40  incr ytmp [expr ([lindex $ys $j] + [lindex $ys $i]) * $ai]
           set i $j
       }
       set area [expr $atmp / 2]
       if {$atmp != 0} {
45  set xc [expr $xtmp / (3 * $atmp)]
           set yc [expr $ytmp / (3 * $atmp)]
           return [list $xc $yc]
       }
       return 2
50  }

   proc iat::ant::ant_create_defaults () {
       #puts "iat::ant::ant_create_defaults"

55  variable antkey
       variable order
       variable points
       variable heads
       variable verts
60  variable tails
       variable dSYMs
       variable dPTRs
       variable kind
       variable color
75  variable inview
       variable code
       variable symbol
       variable label
       variable caption
       variable cs_class
70  variable cs_tumor
       variable cs_node
       variable cs_metastasis
       variable cs_note
75  variable styleColorDefault

       set antkey ""
       set order "0"
80  set points [list]
       array unset heads

```

```

    array set heads [list]
    array unset verts
    array set verts [list]
    array unset tails
5   array set tails [list]
    array unset dSYMs
    array set dSYMs [list]
    array unset dPTRs
    array set dPTRs [list]
10
    set kind "none"
    set color $styleColorDefault
    set inview ""
    set code ""
15    set symbol ""
    set label ""
    set caption ""
    set cs_class ""
    set cs_tumor ""
20    set cs_node ""
    set cs_metastasis ""
    set cs_note ""

    return
25 )

proc iat::ant::ant_create ( ns (inkind (none)) ) {
    variable TRACE
    if ($TRACE) { puts "iat::ant::ant_create: $ns $inkind" }
30    upvar #0 [join [list [namespace current] $ns orders] ::] orders

    variable antkey
    variable order
35    variable kind

    ant_create_defaults

    # find max existing order...
40    set max 0
    foreach (key value) [array get orders] {
        if ([expr ceil($value)] > $max) {
            set max [expr int(ceil($value))]
        }
    }
45    incr max

    set antkey [ant_next_key]
    set order $max
50    set kind $inkind
}

proc iat::ant::ant_create_pointer ( ns head tailpt (vertpts {}) ) {
55    variable TRACE
    if ($TRACE) { puts "iat::ant::ant_create_pointer: $ns $head $tailpt $vertpts" }

    variable rawsave
    variable autoptr
60    variable thisptr
        variable antkey
        variable points
        variable heads
        variable verts
65    variable tails
    variable dSYMs
    variable dPTRs

    set idx $head
70    if ($rawsave) {
        if ($idx == "auto") {
            # this assumes roi has < 1000 pts
            set idx [incr autoptr]
        }
    }
75    } else {
        if ($idx == "auto") {
            set idx [nearest_point $tailpt $points]
        }
    }
80    }

    #puts " idx = $idx"

```

```

    set thisptr $idx
    set heads($idx) $head
    set verts($idx) $vertpts
    set tails($idx) $tailpt
5    set dSYMs($idx) "none"
    set dPTRs($idx) "arrow"

    if (!$rawsave) { ant_save $ns }
}
10 proc iat::ant::ant_ptr_symbol { ns ptnum (style "none") } {
    variable TRACE
    if ($TRACE) { puts "iat::ant::ant_ptr_symbol: $ns $ptnum $style" }

15    variable rawsave
    variable thisptr
    variable dSYMs

    if ($ptnum == "active") { set ptnum $thisptr }
20    #puts " ptnum = $ptnum"
    if ($style == "toggle") {
        set old $dSYMs($ptnum)
        switch $old {
25            "none" { set style "symbol" }
            "symbol" { set style "label" }
            "label" { set style "code" }
            "code" { set style "none" }
            default { set style "symbol" }
        }
        set dSYMs($ptnum) $style
    } else {
        set dSYMs($ptnum) $style
    }

35    if (!$rawsave) { ant_save $ns }
}

proc iat::ant::ant_ptr_style { ns ptnum (style "arrow") } {
    variable TRACE
40    if ($TRACE) { puts "iat::ant::ant_pointer_style: $ns $ptnum $style" }

    variable rawsave
    variable thisptr
    variable dPTRs

45    if ($ptnum == "active") { set ptnum $thisptr }
    #puts " ptnum = $ptnum"
    if ($style == "toggle") {
        set old $dPTRs($ptnum)
50        switch $old {
            "none" { set style "line" }
            "line" { set style "arrow" }
            "arrow" { set style "diamond" }
            "diamond" { set style "none" }
65        }
        set dPTRs($ptnum) $style
    } else {
        set dPTRs($ptnum) $style
    }

60    if (!$rawsave) { ant_save $ns }
}

proc iat::ant::ant_ptr_pin { ns ptnum (pin "auto") } {
75    variable TRACE
    if ($TRACE) { puts "iat::ant::ant_pointer_style: $ns $ptnum $pin" }

    variable rawsave
    variable heads

70    #puts " ptnum = $ptnum"
    if ($pin == "toggle") {
        set old $heads($ptnum)
        switch $old {
75            "auto" { set pin $ptnum }
            default { set pin "auto" }
        }
        set heads($ptnum) $pin
    } else {
80        set heads($ptnum) $pin
    }
}

```

```

    if (!$rawsave) { ant_save $ns }
}

5 proc iat::ant::ant_delete { ns key } {
    variable TRACE
    if ($TRACE) { puts "iat::ant::ant_delete: $ns $key" }

    variable antkey

10    upvar #0 [join [list [namespace current] $ns polys] ::] polys
    upvar #0 [join [list [namespace current] $ns kinds] ::] kinds
    upvar #0 [join [list [namespace current] $ns aheads] ::] aheads
    upvar #0 [join [list [namespace current] $ns averts] ::] averts
15    upvar #0 [join [list [namespace current] $ns atails] ::] atails
    upvar #0 [join [list [namespace current] $ns colors] ::] colors
    upvar #0 [join [list [namespace current] $ns inviews] ::] inviews
    upvar #0 [join [list [namespace current] $ns symbols] ::] symbols
    upvar #0 [join [list [namespace current] $ns labels] ::] labels

20    if ($key == "") { set key $antkey }
    if ($key == "active") { set key $antkey }
    #puts " DELETING ANT: $key"

25    if ([info exists polys($key)]) {
        set polys($key) [array get [list]]
        set kinds($key) [array get [list]]
        set aheads($key) [array get [list]]
        set averts($key) [array get [list]]
30        set atails($key) [array get [list]]
        set colors($key) [array get [list]]
        set inviews($key) [array get [list]]
        set symbols($key) [array get [list]]
        set labels($key) [array get [list]]

35        unset polys($key)
        unset kinds($key)
        unset aheads($key)
        unset averts($key)
40        unset atails($key)
        unset colors($key)
        unset inviews($key)
        unset symbols($key)
        unset labels($key)

45    }

    ant_create_defaults
}

50 proc iat::ant::ant_delete_all { ns } {
    variable TRACE
    if ($TRACE) { puts "iat::ant::ant_delete_all: $ns" }

55    variable rawkey

    upvar #0 [join [list [namespace current] $ns polys] ::] polys

    foreach (key value) [array get polys] {
60        puts " key = $key, value = $value"
        ant_delete $ns $key
    }
    set rawkey 1

65 }

proc iat::ant::roiDelete { (key {}) } {
    #puts "roi::roiDelete: $key"
    variable canvas
    variable polygons
70    variable roiKey
    variable points
    variable sectors
    variable point
75    variable select

    variable orders
    variable symbols
    variable labels
80    variable captions
    variable centers

```

```

#variable gravitys
variable pointers
variable sizes
#variable lengths
5 variable colors
#variable views

variable order
variable symbol
10 variable label
variable caption
variable center
#variable gravity
variable pointer
15 variable size
#variable length
variable color
#variable view

20 variable orderToKey

if {$key == ""} { set key $roiKey }

if {[info exists polygons($key)]} {
25   roiLoad $key
   unset polygons($roiKey)
   unset orders($roiKey)
   unset symbols($roiKey)
   unset labels($roiKey)
30   unset captions($roiKey)
   unset centers($roiKey)
   #unset gravitys($roiKey)
   unset pointers($roiKey)
   unset sizes($roiKey)
35   #unset lengths($roiKey)
   unset colors($roiKey)
   #unset views($roiKey)
}

40 if {[info exists orderToKey($order)]} {
   unset orderToKey($order)
}

set roiKey ""
set points [list]
45 set order ""
set symbol ""
set label ""
set caption ""
set center ""
50 #set gravity ""
set pointer ""
set size ""
#set length ""
set color ""
55 #set view ""

set select READY
)

60 proc iat::ant::roiDeleteAll {} {
   #puts "roi::roiDeleteAll"
   variable rawID
   variable roiKey
   variable orders
65   variable select

   roiEraseAll

   set keys [lsort -dictionary [array names orders]]
70   foreach key $keys {
       roiDelete $key
   }
   set rawID 1000

75   set select READY
}

proc iat::ant::ant_load { ns key } {
   variable TRACE
80   if ($TRACE) { puts "iat::ant::ant_load: $ns $key" }

```

```

variable antkey
variable order
    variable points
    variable heads
5    variable verts
variable tails
variable dSYMs
variable dPTRs
    variable kind
10    variable color
variable invview
variable code
    variable symbol
variable label
15    variable caption
variable cs_class
variable cs_tumor
variable cs_node
variable cs_metastasis
20    variable cs_note

    upvar #0 [join [list [namespace current] $ns offsetX] ::] offsetX
    upvar #0 [join [list [namespace current] $ns offsetY] ::] offsetY
    upvar #0 [join [list [namespace current] $ns imageX] ::] imageX
25    upvar #0 [join [list [namespace current] $ns imageY] ::] imageY
upvar #0 [join [list [namespace current] $ns orders] ::] orders
upvar #0 [join [list [namespace current] $ns polys] ::] polys
    upvar #0 [join [list [namespace current] $ns aheads] ::] aheads
    upvar #0 [join [list [namespace current] $ns averts] ::] averts
30    upvar #0 [join [list [namespace current] $ns atails] ::] atails
upvar #0 [join [list [namespace current] $ns adSYMs] ::] adSYMs
upvar #0 [join [list [namespace current] $ns adPTRs] ::] adPTRs
upvar #0 [join [list [namespace current] $ns kinds] ::] kinds
    upvar #0 [join [list [namespace current] $ns colors] ::] colors
35    upvar #0 [join [list [namespace current] $ns invviews] ::] invviews
upvar #0 [join [list [namespace current] $ns codes] ::] codes
upvar #0 [join [list [namespace current] $ns symbols] ::] symbols
    upvar #0 [join [list [namespace current] $ns labels] ::] labels
upvar #0 [join [list [namespace current] $ns captions] ::] captions
40    upvar #0 [join [list [namespace current] $ns cs_classes] ::] cs_classes
upvar #0 [join [list [namespace current] $ns cs_tumors] ::] cs_tumors
upvar #0 [join [list [namespace current] $ns cs_nodes] ::] cs_nodes
upvar #0 [join [list [namespace current] $ns cs_metastasis] ::] cs_metastasis
upvar #0 [join [list [namespace current] $ns cs_notes] ::] cs_notes
45

if {$key == "default"} {
    ant_create_defaults
    return
}
50 if {$key == ""} { return }

set antkey $key
set tmps $polys($antkey)
set tmps [pointsFrom10K $imageX $imageY $tmps]
55 set tmps [points_translate $offsetX $offsetY $tmps]
set points $tmps
#puts " points($antkey) = $points"

60 #puts " before heads = [array get heads]"
array unset heads
array set heads $aheads($antkey)
#puts " heads($antkey) = [array get heads]"

65 set tmps [list]
foreach {key value} $atails($antkey) {
    set pts [pointsFrom10K $imageX $imageY [list $value]]
    set pts [points_translate $offsetX $offsetY $pts]
70     lappend tmps $key [lindex $pts 0]
}
#puts " before tails = [array get tails]"
array unset tails
array set tails $tmps
#puts " tails($antkey) = [array get tails]"
75

array unset dSYMs
array set dSYMs $adSYMs($antkey)

array unset dPTRs
80 array set dPTRs $adPTRs($antkey)

```


Appendix 2

```
set tmps [list]
foreach {key value} $averts($santkey) {
    set pts [pointsFrom10K $imageX $imageY $value]
    set pts [points_translate $offsetX $offsetY $pts]
5     lappend tmps $key $pts
}
#puts " before verts = [array get verts]"
array unset verts
array set verts $tmps
10 #puts " verts($santkey) = [array get verts]"

set order $orders($santkey)
set kind $kinds($santkey)
set color $colors($santkey)
15 set inview $inviews($santkey)
set code $codes($santkey)
set symbol $symbols($santkey)
set label $labels($santkey)
20 set caption $captions($santkey)

set cs_class $cs_classss($santkey)
set cs_tumor $cs_tumors($santkey)
set cs_node $cs_nodes($santkey)
set cs_metastasis $cs_metastasisss($santkey)
25 set cs_note $cs_notes($santkey)

return

30 #puts "roiLoad"
variable canvas
variable polygons
variable roiKey
variable imageX
35 variable imageY
variable offsetX
variable offsetY
variable points
variable pointsDirty
40 variable symbolDirty
variable point
variable select

variable orders
45 variable kinds
variable symbols
variable labels
variable captions
variable centers
50 variable pointers
variable sizes
variable colors
variable views
variable sorls
55 variable pointerPoints
variable symbolPoints

variable order
variable kind
60 variable symbol
variable label
variable caption
variable center
variable pointer
65 variable size
variable color
variable view
variable sorl
variable pointerPoint
70 variable symbolPoint
variable angle

if {$key == ""} { return }

75 set roiKey $key
set points $polygons($roiKey)
set points [pointsFrom10K $imageX $imageY $points]
set points [points_translate $offsetX $offsetY $points]

80 #puts "pre load lblpt = $symbolPoints($roiKey)"
set symbolPoint $symbolPoints($roiKey)
```

Appendix 2

```

set symbolPoint [pointsFrom10K $imageX $imageY [list $symbolPoint]]
set symbolPoint [lindex [points_translate $offsetX $offsetY $symbolPoint] 0]
#puts "post load lblpt = $symbolPoint"

5   set order $orders($roiKey)
    set kind $kinds($roiKey)
    set symbol $symbols($roiKey)
    set label $labels($roiKey)
    set caption $captions($roiKey)
10  set center $centers($roiKey)
    set pointer $pointers($roiKey)
    set size $sizes($roiKey)
    set color $colors($roiKey)
    set view $views($roiKey)
15  set sorl $sorls($roiKey)
    #set pointerPoint $pointerPoints($roiKey)

    set pointsDirty 0
    set symbolDirty 0

20  roiPreDrawCalc

    #puts "order = $order"
    #puts "symbol = $symbol"
25  #puts "label = $label"
    #puts "caption = $caption"
    #puts "center = $center"
    #puts "gravity = $gravity"
    #puts "pointer = $pointer"
30 }

proc iat::ant::ant_save { ns } {
    variable TRACE
    if {$TRACE} { puts "iat::ant::ant_save: $ns" }

35    variable rawsave
    variable antkey
    variable order
    variable points
    variable heads
40    variable verts
    variable tails
    variable dSYMs
    variable dPTRs
    variable kind
45    variable color
    variable inview
    variable code
    variable symbol
50    variable label
    variable caption
    variable cs_class
    variable cs_tumor
    variable cs_node
55    variable cs_metastasis
    variable cs_note
    variable view

    if {$antkey == ""} { return }
    if {$points == {}} {
        ant_create_defaults
        return
    }

60    upvar #0 [join [list [namespace current] $ns offsetX] ::] offsetX
    upvar #0 [join [list [namespace current] $ns offsetY] ::] offsetY
    upvar #0 [join [list [namespace current] $ns imageX] ::] imageX
    upvar #0 [join [list [namespace current] $ns imageY] ::] imageY
    upvar #0 [join [list [namespace current] $ns orders] ::] orders
70    upvar #0 [join [list [namespace current] $ns polys] ::] polys
    upvar #0 [join [list [namespace current] $ns aheads] ::] aheads
    upvar #0 [join [list [namespace current] $ns averts] ::] averts
    upvar #0 [join [list [namespace current] $ns atails] ::] atails
    upvar #0 [join [list [namespace current] $ns adSYMs] ::] adSYMs
75    upvar #0 [join [list [namespace current] $ns adPTRs] ::] adPTRs
    upvar #0 [join [list [namespace current] $ns kinds] ::] kinds
    upvar #0 [join [list [namespace current] $ns colors] ::] colors
    upvar #0 [join [list [namespace current] $ns inviews] ::] inviews
    upvar #0 [join [list [namespace current] $ns codes] ::] codes
80    upvar #0 [join [list [namespace current] $ns symbols] ::] symbols
    upvar #0 [join [list [namespace current] $ns labels] ::] labels

```

Appendix 2

```

upvar #0 [join [list [namespace current] $ns captions] ::] captions
upvar #0 [join [list [namespace current] $ns cs_classss] ::] cs_classss
upvar #0 [join [list [namespace current] $ns cs_tumors] ::] cs_tumors
upvar #0 [join [list [namespace current] $ns cs_nodes] ::] cs_nodes
5 upvar #0 [join [list [namespace current] $ns cs_metastasisss] ::] cs_metastasisss
upvar #0 [join [list [namespace current] $ns cs_notes] ::] cs_notes

# if ($rawsave) { puts " RAW SAVE!" }

10 if ($rawsave) {
} else {
    if ( $inview == "" && $view != "ALL" && $view != "NONE" ) {
        set inview $view
    } elseif ( $inview == "" && $view == "ALL" ) {
15         set inview "NEW"
    } elseif ( $inview == "" && $view == "NONE" ) {
        set inview "NEW"
    }
}

20 if ($rawsave) {
    set tmps $points
} else {
    set tmps $points
    set tmps [points_translate -$offsetX -$offsetY $tmps]
25     set tmps [pointsTo10K $imageX $imageY $tmps]
}

set polys($antkey) $tmps
#puts " points($antkey) = $polys($antkey)"

30 # pointer heads
set aheads($antkey) [array get heads]
set adSYMs($antkey) [array get dSYMs]
set adPTRs($antkey) [array get dPTRs]
35 #puts " aheads($antkey) = $aheads($antkey)"

# pointer tails
set tmps [list]
foreach {key value} [array get tails] {
40     if ($rawsave) {
        set pts [list $value]
    } else {
        set pts [points_translate -$offsetX -$offsetY [list $value]]
        set pts [pointsTo10K $imageX $imageY $pts]
45     }
    lappend tmps $key [lindex $pts 0]
}

set atails($antkey) $tmps
#puts " atails($antkey) = $atails($antkey)"

50 # pointer verticies
set tmps [list]
foreach {key value} [array get verts] {
    if ($rawsave) {
55         set pts $value
    } else {
        set pts [points_translate -$offsetX -$offsetY $value]
        set pts [pointsTo10K $imageX $imageY $pts]
    }
60     lappend tmps $key $pts
}

set averts($antkey) $tmps
#puts " averts($antkey) = $averts($antkey)"

65 set orders($antkey) $order
set kinds($antkey) $kind
set colors($antkey) $color
set inviews($antkey) $inview
set codes($antkey) $code
70 set symbols($antkey) $symbol
set labels($antkey) $label
set captions($antkey) $caption

set cs_classss($antkey) $cs_class
75 set cs_tumors($antkey) $cs_tumor
set cs_nodes($antkey) $cs_node
set cs_metastasisss($antkey) $cs_metastasis
set cs_notes($antkey) $cs_note

80 # This must be done carefully...
# Calculate dynamic data for annotation. Currently: heads

```

Appendix 2

```

# raw data must not be left in loaded data...
if ($rawsave) {
  set rawsave 0

5   ant_load $ns $antkey

  foreach (key value) [array get heads] {
    if ($value == "") { continue }
    if ($value == "auto") {
10      set idx [nearest_point $tails($key) $points]
      if ($idx != $key) {
        # update head and tail
        #puts " RAWSAVE PTR UPDATE: $key -> $idx"
        set heads($idx) auto
        set verts($idx) $verts($key)
15      set tails($idx) $tails($key)
        set dSYMs($idx) $dSYMs($key)
        set dPTRs($idx) $dPTRs($key)
        set heads($key) ""
        set verts($key) ""
20      set tails($key) ""
        set dSYMs($key) ""
        set dPTRs($key) ""
      }
    }
25  }

  ant_save $ns
  ant_create_defaults
  set rawsave 1
30 }

  return

35 #puts "order = $orders($roiKey)"
  #puts "symbol = $symbols($roiKey)"
  #puts "label = $labels($roiKey)"
  #puts "caption = $captions($roiKey)"
  #puts "length = $lengths($roiKey)"
40 #puts "size = $sizes($roiKey)"
  #puts "color = $colors($roiKey)"
  #puts "pointer = $pointers($roiKey)"
  #puts "gravity = $gravities($roiKey)"
  #puts "center = $centers($roiKey)"
45 }

proc iat::ant::ant_kind { ns } {
  variable TRACE
50  if ($TRACE) { puts "iat::ant::ant_kind: $ns" }

  variable kind

  return $kind
55 }

proc iat::ant::ant_point { ns idx } {
  variable TRACE
60  if ($TRACE) { puts "iat::ant::ant_point: $ns $idx" }

  variable points

  return [lindex $points $idx]
}

65 proc iat::ant::ant_points { ns } {
  variable TRACE
  if ($TRACE) { puts "iat::ant::ant_points: $ns" }

70  variable points

  return $points
}

75 proc iat::ant::roiMoveRelative { dpt } {
  variable canvas
  variable points

80  set dx [lindex $dpt 0]
  set dy [lindex $dpt 1]

```

Appendix 2

```

    set points [pointsTranslate $dx $dy $points]

    return 0
}
5
proc iat::ant::roiCopy () {
    #puts "roiCopy"
    variable canvas
    variable points

10    set newpts $points
    roiCreate
    set points $newpts

15    return 0
}

proc iat::ant::ant_erase { ns key } {
    variable TRACE
20    if ($TRACE) { puts "iat::ant::ant_erase: $ns $key" }

    variable antkey

    upvar #0 [join [list [namespace current] $ns canvas] ::] canvas

25    set key [string tolower $key]
    if {$key == ""} { set key $antkey }
    if {$key == "active"} { set key $antkey }

30    $canvas delete handle
    $canvas delete segment
    $canvas delete ptrvert
    $canvas delete ptrsect

35    $canvas delete key$key
}

proc iat::ant::ant_erase_all { ns } {
40    variable TRACE
    if ($TRACE) { puts "iat::ant::ant_erase_all: $ns" }

    upvar #0 [join [list [namespace current] $ns polys] ::] polys

45    foreach {key value} [array get polys] {
        ant_erase $ns $key
    }
}

50
proc iat::ant::ant_draw_precalc { ns } {
    #puts "iat::ant::ant_draw_precalc: $ns"

    variable points
    variable kind
    variable color
    #variable center
    #variable pointer
    #variable angle
60    #variable pointerPoint
    #variable symbolPoint

    variable fillColor
    variable linecolor
    variable styleColorLight
65    variable styleColorDefault
    variable styleColorDark
    variable symbolFont

70    if ($color == "default") {
        set fillColor $styleColorDefault
        set linecolor $styleColorDefault
    } else {
        switch $color {
75            "light" { set fillColor $styleColorLight ; set linecolor $styleColorDark }
            "dark" { set fillColor $styleColorDark ; set linecolor $styleColorLight }
            default {
                set fillColor $color
                set linecolor $color
80            }
        }
    }
}

```

```

    }
}

# group doesn't have visual annotation piece
5 if {$kind == "group"} { return }

#set angle [x2pts_angle $pointerPoint $symbolPoint]

set size default
10 set symbolFont fontDefault
switch $size {
    "small" { set symbolFont fontSmall }
    "default" { set symbolFont fontDefault }
    "large" { set symbolFont fontLarge }
15 }

return

# This is one case where symbolPoint is not user specified (also default)
20 if {"$center$pointer" == "centernone"} {
    set symbolPoint [roiCentroid]
}

# draw from center or gravitate to edge...
25 if {$center == "center"} {
    set pt [roiCentroid]
    # This needs to be really repaired... one and two point rois
    # dont have a center, so choose the first point...
    if {$pt == 3} { set pt [lindex $points 0] }
30 } else {
    #set tmp [iat::pointer::gravityPoint $gravity [join $points]]
    set tmp [iat::pointer::nearestPoint $symbolPoint $points]
    set pt [lindex $points $tmp]
}
35 #puts "pointer index: $tmp"
set pointerPoint $pt
set angle [iat::pointer::2ptsAngle $pointerPoint $symbolPoint]
#set angle [iat::pointer::gravityAngle $gravity]
40 }

proc iat::ant::ant_draw { ns key } {
    variable TRACE
    if {$TRACE} { puts "iat::ant::ant_draw: $ns $key" }
45 upvar #0 [join [list [namespace current] $ns polys] ::] polys

    variable view
    variable invview

50 variable antkey
    variable points
    variable kind
    #variable order
    variable color
    variable fillColor
55 variable linecolor
    #variable view
    #variable pointerPoint

60 upvar #0 [join [list [namespace current] $ns canvas] ::] canvas
    upvar #0 [join [list [namespace current] $ns offsetX] ::] offsetX
    upvar #0 [join [list [namespace current] $ns offsetY] ::] offsetY

    set order "orderX"

65 set key [string tolower $key]
    if {$key == ""} { set key $antkey }
    if {$key == "active"} { set key $antkey }
    if {$key == ""} { return 0 }
70 # Must do this every draw in case of scale...
    ant_erase $ns $key
    ant_load $ns $key

75 # return based on view
    if {$view == "ALL"} {
        # do nothing...
    } else {
        if {$view == "NONE"} { return 0 }
80 if {[lsearch [split $invview] $view] < 0} { return 0 }
    }
}

```

```

ant_draw_precalc $ns

if {$kind == "none"} { return 2 }
5 if {$kind == "group"} { return 0 }

#puts " antkey = $antkey"
#puts " kind = $kind"

10 set parts "all"
switch $parts {
    "none" {}
    "region" {}
    # all or pointer
15 default {
        ant_draw_pointers $ns
    }
}

20 switch $parts {
    "none" {}
    "pointer" {}
    # all or region
    default {
25 set tmps [join $points]
        switch $kind {
            "edge" {
                $canvas create line $tmps -smooth true -width 2 -fill $fillcolor -tags [list ant roi
30 key$antkey $order]
            }
            "area" {
                $canvas create poly $tmps -smooth true -outline $fillcolor -width 2 -fill "" -tags [list
ant roi key$antkey $order]
                $canvas create poly $tmps -outline black -width 2 -fill "" -tags [list ant roi
35 key$antkey $order]
            }
            # point is default!
            default {
                foreach {x y} $tmps {
40 $canvas create oval [expr $x-6] [expr $y-6] [expr $x+6] [expr $y+6] -outline
$fillcolor -width 3 -fill "" -tags [list ant roi key$antkey $order]
                }
            }
        }
45 }
    }

$canvas raise head

50 return 0
}

proc iat::ant::ant_draw_all { ns } {
    variable TRACE
55 if {$TRACE} { puts "iat::ant::ant_draw_all: $ns" }

    upvar #0 [join [list [namespace current] $ns polys] ::] polys

    foreach {key value} [array get polys] {
60 ant_draw $ns $key
    }
}

65 proc iat::ant::ant_draw_pointers { ns (style normal) } {
    variable TRACE
    if {$TRACE} { puts "iat::ant::ant_draw_pointers: $ns" }

    variable heads

70 set rv -1
    set go 1
    while {$go >= 0} {
        set go -1
75 foreach {key value} [array get heads] {
            if {$value == ""} { continue }
            set go [ant_draw_pointer $ns $key $style]
            if {$go >= 0} { set rv $go; break }
            if {$style == "edit"} {
80 ant_draw_ptr_vertexes $ns $key
                ant_draw_ptr_sectors $ns $key
            }
        }
    }
}

```

Appendix 2

```

    }
  }
}

5   return $rv
}

proc iat::ant::ant_draw_pointerSAVE { ns ptnum {style normal}} {
  #puts "iat::ant::ant_draw_pointer: $ns $ptnum"

10   variable antkey
      variable points
      variable heads
      variable verts
15   variable tails

      variable color
      variable fillcolor
      variable linecolor

20   upvar #0 [join [list [namespace current] $ns canvas] ::] canvas

  puts " heads($ptnum) = $heads($ptnum)"
  puts " tails($ptnum) = $tails($ptnum)"

25   set value $heads($ptnum)
      if {$value == ""} { return }
      if {$value == "auto"} {
        set idx [nearest_point $tails($ptnum) $points]
30         if {$idx != $ptnum} {
          # update head and tail
          set heads($idx) auto
          set verts($idx) $verts($ptnum)
          set tails($idx) $tails($ptnum)
35         set heads($ptnum) ""
          set verts($ptnum) ""
          set tails($ptnum) ""
          set ptnum $idx
          return $idx
40       }
      }
      set headpt [lindex $points $ptnum]
      set tailpt $tails($ptnum)
      if {$tailpt == ""} { return }

45   puts " head = $headpt"
      puts " verts = $verts($ptnum)"
      puts " tail = $tailpt"

50   set ptrlen [lindex [x2pts_length $headpt $tailpt] 0]
      set angle [x2pts_angle $headpt $tailpt]

      set x [lindex $headpt 0]
      set y [lindex $headpt 1]
      set pinfo [create_pointer $ns arrow $ptrlen]
      if {$pinfo == -1} { return }
      if {[llength $pinfo] > 1} {
        set ppts [lindex $pinfo 1]
60 set sub 0
        if {$sub == 1} {
          set tmpa [x2pts_angle $headpt $tailpt]
          #puts "tmp angle = $tmpa"
          set ppts [points_rotate $tmpa $ppts]
65         set ppts [points_translate_1st $x $y $ppts]
          #canvas create line "$pointerPoint $symbolPoint" -width 2 -fill blue -tags [list adorer
key$roiKey]
        } else {
          set ppts [points_rotate $angle $ppts]
70         set ppts [points_translate_1st $x $y $ppts]
        }
      }
      if {$style == "edit"} {
        set tmps [join [concat $headpt $verts($ptnum) $tailpt]]
        $canvas create line $tmps -width 2 -fill yellow -tags [list segment]
75      } elseif {$style == "annotation"} {
        $canvas create poly $ppts -outline yellow -width 2 -fill "" -tags [list segment num$ptnum]
        # head handle
        set x [lindex $headpt 0]
        set y [lindex $headpt 1]
80        set x1 [expr $x -3]
        set x2 [expr $x +3]

```



```

        set y1 [expr $y -3]
        set y2 [expr $y +3]
        $canvas create oval $x1 $y1 $x2 $y2 -fill yellow -outline black -width 1 -tags [list handle
5 head num$ptnum]
        # tail handle
        set x [lindex $tailpt 0]
        set y [lindex $tailpt 1]
        set x1 [expr $x -3]
        set x2 [expr $x +3]
10        set y1 [expr $y -3]
        set y2 [expr $y +3]
        $canvas create oval $x1 $y1 $x2 $y2 -fill yellow -outline black -width 1 -tags [list handle
tail num$ptnum]
    ) else {
15        $canvas create poly $ppts -outline $linecolor -width 1 -fill $fillcolor -tags [list ant
pointer key$antkey]
    }
}

20 return -1
}

proc iat::ant::ant_draw_pointer { ns ptnum {style normal}} {
    variable TRACE
25    if {$TRACE} { puts "iat::ant::ant_draw_pointer: $ns $ptnum" }

    variable antkey
    variable points
    variable heads
30    variable verts
    variable tails
    variable dSYMs
    variable dPTRs
    variable kind
35    variable code
    variable symbol
    variable label

    variable color
    variable fillcolor
    variable linecolor
    variable symbolFont
    variable pxi

40    upvar #0 [join [list [namespace current] $ns canvas] ::] canvas

    set value $heads($ptnum)
    if {$value == ""} { return }
    if {$value == "auto"} {
50        set idx [nearest_point $tails($ptnum) $points]
        if {$idx != $ptnum} {
            # update head and tail
            set heads($idx) auto
            set verts($idx) $verts($ptnum)
55            set tails($idx) $tails($ptnum)
            set dSYMs($idx) $dSYMs($ptnum)
            set dPTRs($idx) $dPTRs($ptnum)
            set heads($ptnum) ""
            set verts($ptnum) ""
60            set tails($ptnum) ""
            set dSYMs($ptnum) ""
            set dPTRs($ptnum) ""
            set ptnum $idx
            return $idx
65        }
    }

    #puts " ptnum = $ptnum"
    set headpt [lindex $points $ptnum]
70    set tailpt $tails($ptnum)
    if ($tailpt == "") { return }
    set draw_symbol $dSYMs($ptnum)
    set draw_style $dPTRs($ptnum)

75    #puts " head = $headpt"
    #puts " verts = $verts($ptnum)"
    #puts " tail = $tailpt"

    set ptrlen [lindex [x2pts_length $headpt $tailpt] 0]
80    if ([llength $verts($ptnum)] > 0) {
        set angle [x2pts_angle $headpt [lindex $verts($ptnum) 0]]
    }
}

```

```

    } else {
        set angle [x2pts_angle $headpt $tailpt]
    }

5   set sub 0

    set x [lindex $headpt 0]
    set y [lindex $headpt 1]
    set pinfo [create_pointer $ns $draw_style $ptrlen]
10  if {$pinfo == -1} { return }
    if {[llength $pinfo] > 1} {
        set hppts $pinfo
        if {$sub == 1} {
            set tmpa [x2pts_angle $headpt $tailpt]
            #puts "tmp angle = $tmpa"
            set ppts [points_rotate $tmpa $ppts]
            set ppts [points_translate_list $x $y $ppts]
            #canvas create line "$pointerPoint $symbolPoint" -width 2 -fill blue -tags [list adorning
key$roiKey]
20        } else {
            set hppts [points_rotate $angle $hppts]
            set hppts [points_translate_list $x $y $hppts]
        }
        set tmps [list]
25        lappend tmps $headpt
        set tmps [concat $tmps $verts($ptnum)]
        lappend tmps $tailpt
        set ppts [makeList $ns $ptnum $tmps]
        if {$style == "edit"} {
30            set tmps [join [concat $headpt $verts($ptnum) $tailpt]]
            #canvas create line $tmps -width 2 -fill yellow -tags [list segment]
            if {$draw_style != "none"} {
                #canvas create poly $ppts -smooth true -outline red -width 2 -fill white -tags [list ant
pointer key$antkey]
35            #canvas create poly $hppts -outline red -width 2 -fill white -tags [list ant pointer key$antkey]
            }
            elseif {$style == "annotation"} {
                #canvas create poly $ppts -outline yellow -width 2 -fill "" -tags [list segment num$ptnum]
                if {$draw_style != "none"} {
40                    #canvas create poly $ppts -smooth true -outline red -width 2 -fill white -tags [list ant pointer
key$antkey]
                    #canvas create poly $hppts -outline red -width 2 -fill white -tags [list ant pointer key$antkey]
                }
                # head handle
45                #set x [lindex $headpt 0]
                #set y [lindex $headpt 1]
                #set x1 [expr $x -3]
                #set x2 [expr $x +3]
                #set y1 [expr $y -3]
50                #set y2 [expr $y +3]
                #canvas create oval $x1 $y1 $x2 $y2 -fill yellow -outline black -width 1 -tags [list handle head
num$ptnum]
                # tail handle
                set x [lindex $tailpt 0]
                set y [lindex $tailpt 1]
                set x1 [expr $x -3]
                set x2 [expr $x +3]
                set y1 [expr $y -3]
                set y2 [expr $y +3]
60                #canvas create oval $x1 $y1 $x2 $y2 -fill yellow -outline black -width 1 -tags [list handle tail
num$ptnum]
            } else {
                if {$draw_style != "none"} {
                    #canvas create poly $ppts -smooth true -outline $linecolor -width 1 -fill $fillcolor
65 -tags [list ant pointer key$antkey]
                    #canvas create poly $hppts -outline $linecolor -width 1 -fill $fillcolor -tags [list ant pointer
key$antkey]
                }
            }
70        }

        set xt [lindex $tailpt 0]
        set yt [lindex $tailpt 1]

75        if {[llength $verts($ptnum)] > 0} {
            set angle [x2pts_angle [lindex $verts($ptnum) end] $tailpt]
        } else {
            set angle [x2pts_angle $headpt $tailpt]
        }
80        set anchor [iat::ant::gravity_label $angle]

```

```

set dx 0
switch $anchor {
    "e" { set dx -$px1 }
    "w" { set dx $px1 }
5    "default" { set dx 0 }
}
set symbolfill $fillcolor
if ($style != "normal") {
    set symbolfill red
10 }
#puts " draw_symbol = $draw_symbol"
if ($draw_symbol != "none") {
    set ptrtxt ""
    switch $draw_symbol {
15     "symbol" { set ptrtxt $symbol }
        "label" { set ptrtxt $label }
        default { set ptrtxt "" }
    }
    if ($ptrtxt == "") { set ptrtxt $draw_symbol }
20 $canvas create text [expr $xt+$dx] $yt -text $ptrtxt \
    -font $symbolFont \
    -anchor "$anchor" \
        -fill $symbolfill \
    -tags [list adorne key$antkey]
25 }
    $canvas create line [list [expr $xt-4] [expr $yt+4] [expr $xt+4] [expr $yt-4]] -fill red -width 2
    -tags [list adorne key$roiKey]
    $canvas create line [list [expr $xt+4] [expr $yt+4] [expr $xt-4] [expr $yt-4]] -fill red -width 2
    -tags [list adorne key$roiKey]
30 $canvas raise tail
    return -1
}
35

proc iat::ant::makeIt { ns ptnum pts } {
    variable TRACE
    if ($TRACE) { puts "iat::ant::makeIt: $ns $ptnum $pts" }
40
    variable kind
    variable dPTRs
        variable px1
    variable px2
45 variable px3
    variable px4

    set negpts [list]
    set pospts [list]
50
    calc_size $ns
    set px $px1

    set offset $px
    switch $dPTRs($ptnum) {
55     "line" { set offset $px3 }
        default { set offset $px1 }
    }

60
    set lstpt ""
    set pass 1
    foreach curpt $pts {
        if ($curpt == {}) { continue }
        if ($lstpt == "") { set lstpt $curpt; continue }
65 #puts " lstpt = $lstpt"
        #puts " curpt = $curpt"
        set len [lindex [x2pts_length $lstpt $curpt] 0]
        #puts " len = $len"
        set ang [x2pts_angle $lstpt $curpt]
        #puts " ang = $ang"
        set lstx [lindex $lstpt 0]
        set lsty [lindex $lstpt 1]
        set curx [lindex $curpt 0]
70
        set cury [lindex $curpt 1]
        # zero is the line offset from head
        set zero 0
        if ($pass == 1) { set zero $offset }
        # midline points
        set midtmp [list $zero 0 [expr 0+$len] 0 ]
        set midtmp [points_rotate $ang $midtmp]
80 set midtmp [points_translate_lst $lstx $lsty $midtmp]
    }
}

```

```

# negative X points
set negtmp [list $zero [expr 0-$px] [expr 0+$len] [expr 0-$px] ]
set negtmp [points_rotate $ang $negtmp]
set negtmp [points_translate_1st $lstx $lsty $negtmp]
# positive X points
set postmp [list $zero [expr 0+$px] [expr 0+$len] [expr 0+$px] ]
set postmp [points_rotate $ang $postmp]
set postmp [points_translate_1st $lstx $lsty $postmp]
if ($pass == 1) {
    set negpts [list [lindex $midtmp 0] [lindex $midtmp 1]]
    set negpts [concat $negpts $negtmp]
    set pospts [concat [list [lindex $postmp 2] [lindex $postmp 3] [lindex $postmp 0]
[lindex $postmp 1] ] $pospts]
} else {
    lappend negpts [lindex $negtmp 2] [lindex $negtmp 3]
    set pospts [concat [list [lindex $postmp 2] [lindex $postmp 3]] $pospts]
}
set lstpt $curpt
incr pass
}

# append midpoint to end
# reverse the pospts and append to negpts
set newpts [concat $negpts [lindex $midtmp 2] [lindex $midtmp 3] $pospts]
#puts " newpts = $newpts"

return $newpts
}

proc iat::ant::ant_draw_pointer_old () {
    #puts "pointerDraw"
    variable canvas
    variable imageX
    variable imageY
    variable offsetX
    variable offsetY
    variable roiKey
    variable points
    variable order
    variable symbol
    variable label
    variable center
    variable pointer
    variable size
    variable color
    variable sorl
    variable linecolor
    variable fillcolor
    variable pointerPoint
    variable angle
    variable symbolPoint
    variable symbolPoints
    variable orderToKey
    variable symbols

    variable styleFontSmall
    variable styleFontDefault
    variable styleFontLarge

    #set x1 [expr $x -5]
    #set x2 [expr $x +5]
    #set y1 [expr $y -5]
    #set y2 [expr $y +5]
    #$canvas create rect $x1 $y1 $x2 $y2 -fill "" -outline yellow -width 2 -tags [list handle $roiKey]

    #set fsz [expr round(ceil(((($imageX + $imageY)/2) * 0.001 * 48 )))
    set symbolFont fontDefault
    switch $size {
        "small" { set symbolFont fontSmall }
        "default" { set symbolFont fontDefault }
        "large" { set symbolFont fontLarge }
    }
    #set fsz [expr round(ceil(((($imageX + $imageY)/2) * 0.001 * $fptsz )))
    #puts "font size = $fsz"
    #font configure $symbolFont -size $fsz

    # Test code...
    #drawTestAngles
    #set pt [lindex $points $pointerPoint]
    #puts "pointerPoint = $pointerPoint"

    set sub 0

```

```

set ptrlen 0
set pattern {^(\\w\\:){1,4}$}
if {[regexp $pattern $symbol]} {
# subordinate
5   if {[info exists orderToKey($symbol)]} {
        set sub 1
        set symbolPoint $symbolPoints($orderToKey($symbol))
        # NOTE: symbolPoint stored as 10K relative...
        set symbolPoint [pointsFrom10K $imageX $imageY [list $symbolPoint]]
10    set symbolPoint [lindex [pointsTranslate $offsetX $offsetY $symbolPoint] 0]
        #set ptrlen [lindex [iat::pointer::2ptsLength $pointerPoint $symbolPoint] 0]
    }
    #puts "symbol = $symbol, key = $orderToKey($symbol), keySymbol = $symbols($orderToKey($symbol))"
    #puts "symbolPoint = $symbolPoint"
15 }
set ptrlen [lindex [iat::pointer::2ptsLength $pointerPoint $symbolPoint] 0]

set x [lindex $pointerPoint 0]
set y [lindex $pointerPoint 1]
set pinfo [iat::pointer::pointer $pointer $ptrlen]
if {$pinfo == -1} { return }
if {[length $pinfo] > 1} {
25    set ppts [lindex $pinfo 1]
        if {$sub == 1} {
            set tmpa [iat::pointer::2ptsAngle $pointerPoint $symbolPoint]
            #puts "tmp angle = $tmpa"
            set ppts [iat::pointer::pointsRotate $tmpa $ppts]
            set ppts [iat::pointer::pointsTranslate $x $y $ppts]
30    #Scanvas create line "$pointerPoint $symbolPoint" -width 2 -fill blue -tags [list adorne
key$roiKey]
        } else {
            set ppts [iat::pointer::pointsRotate $angle $ppts]
            set ppts [iat::pointer::pointsTranslate $x $y $ppts]
35    }
        $Scanvas create poly $ppts -outline $linecolor -width 1 -fill $fillcolor -tags [list adorne
key$roiKey $order]
    }
    if {"$center$pointer" == "centernone"} {
40        set ptt $pointerPoint
    } else {
        set ptt $symbolPoint
    }
}

45 set xt [lindex $ptt 0]
set yt [lindex $ptt 1]
set drawtext $symbol
if {$sorl == "label"} { set drawtext $label }
if {$sub == 0} {
50    $Scanvas create text $xt $yt -text $drawtext \
        -font $symbolFont \
        -anchor [iat::pointer::gravityLabel $angle] \
        -fill $fillcolor \
        -tags [list adorne key$roiKey $order]
55    #Scanvas create line [list [expr $xt-4] [expr $yt+4] [expr $xt+4] [expr $yt-4]] -fill red -width 2
    -tags [list adorne key$roiKey]
    #Scanvas create line [list [expr $xt+4] [expr $yt+4] [expr $xt-4] [expr $yt-4]] -fill red -width 2
    -tags [list adorne key$roiKey]
60 }
}

proc iat::ant::ant_select { ns key } {
    variable TRACE
65    if {$TRACE} { puts "iat::and::ant_select: $ns $key" }

    variable antkey

    upvar #0 [join [list [namespace current] $ns canvas] ::] canvas
70    upvar #0 [join [list [namespace current] $ns select_mode] ::] select_mode

    set key [string tolower $key]
    #if {$key == "active"} { set key $antkey }
    if {$key == ""} { return }
75    if {$key == "active"} { set key $antkey }
    ant_load $ns $key
    #if {[roiDraw] > 0} { return }

    set rv 0
80    #puts " select_mode = $select_mode"

```

Appendix 2

```

    $canvas addtag CURRENT withtag key$antkey
    ant_erase $ns $key
    ant_draw_segments $ns
    if ($select_mode == "edit") {
5       set rv [ant_draw_pointers $ns $select_mode]
        ant_draw_sectors $ns
        ant_draw_vertexs $ns
    } else {
10      ant_draw_vertexs $ns
        set rv [ant_draw_pointers $ns $select_mode]
    }
    #drawSymbolHandle
    return $rv
15 }

proc iat::ant::ant_deselect { ns } {
    variable TRACE
    if ($TRACE) { puts "iat::ant::ant_deselect: $ns" }
20
    variable antkey

    upvar #0 [join [list [namespace current] $ns canvas] ::] canvas

25    if ($antkey == "") { return }
    #puts " DESELECTING ANT: $antkey"
    ant_erase $ns $antkey
    ant_draw $ns $antkey
    ant_lower $ns $antkey
30
    return
}

proc iat::ant::ant_move_ant_delta { ns dpt } {
35    variable TRACE
    if ($TRACE) { puts "iat::ant::ant_move_ant_delta: $ns $dpt" }

    variable points
    variable verts
40    variable tails

    upvar #0 [join [list [namespace current] $ns canvas] ::] canvas
    upvar #0 [join [list [namespace current] $ns select_mode] ::] select_mode

45    set dx [lindex $dpt 0]
    set dy [lindex $dpt 1]

    #puts " before = $points"
    set points [points_translate $dx $dy $points]
50    #puts " after = $points"

    if ($select_mode == "annotation") {
        foreach {key value} [array get tails] {
            set newpt [points_translate $dx $dy [list $value]]
55            set tails($key) [lindex $newpt 0]
            set verts($key) [points_translate $dx $dy $verts($key)]
        }
    }

60    ant_save $ns
}

65 proc iat::ant::ant_lower { ns key } {
    variable TRACE
    if ($TRACE) { puts "iat::ant::ant_deselect: $ns" }

    variable antkey

70    upvar #0 [join [list [namespace current] $ns canvas] ::] canvas

    set key [string tolower $key]
    if ($key == "active") { set key $antkey }

75    $canvas lower key$key
    $canvas raise key$key image
}

80
# NOTE

```

Appendix 2

```

# doMakeSectors and drawVertices are called as a pair (and should be called from
# a single function doMakeHandles....
# Calling drawVertices after doMakeSectors solves the problem of not being able
# to delete a point because only the sector is clickable. This is because the
5 # vertices are drawn on top of the sectors.
#

proc iat::ant::ant_draw_sectors { ns } {

10     variable points
    variable kind

    upvar #0 [join [list [namespace current] $ns canvas] ::] canvas

15     $canvas delete sector

    set sectors [list]
    set lx 0 ; set ly 0
    set tmps $points
20     if ($kind == "area") {
        lappend tmps [lindex $points 0]
    }
    set tmps [join $tmps]
    #puts "sector tmps = $tmps"
25     foreach {x y} $tmps {
        if ($lx == 0 ) {
            set lx $x ; set ly $y
            continue
        } else {
30             set nx [expr {($x - $lx)/2} + $lx]
            set ny [expr {($y - $ly)/2} + $ly]
            lappend sectors [list $nx $ny]
            set lx $x ; set ly $y
        }
35     }

    #puts "sectors = $sectors"
    set n 1
40     foreach {pt} $sectors {
        set x [lindex $pt 0]
        set y [lindex $pt 1]
        set x1 [expr $x -3]
        set x2 [expr $x +3]
45         set y1 [expr $y -3]
        set y2 [expr $y +3]
        set midx [expr round( ($x2 + $x1) / 2 )]
        $canvas create poly $midx $y1 $x2 $y2 $x1 $y2 -fill yellow -outline black -width 1 -tags
50 [list handle sector num$n]
        incr n
    }
}

55 proc iat::ant::ant_draw_ptr_sectors { ns ptnum } {

    variable points
    variable heads
    variable verts
    variable tails
60     variable kind

    upvar #0 [join [list [namespace current] $ns canvas] ::] canvas

    set sectors [list]
    set lx 0 ; set ly 0
    set tmps [list]

65     if ($heads($ptnum) == "auto") {
        set idx [nearest_point $tails($ptnum) $points]
        set headpt [lindex $points $idx]
70     } else {
        set headpt [lindex $points $ptnum]
    }
    set tailpt $tails($ptnum)

75     set tmps [list]
    lappend tmps $headpt
    set tmps [concat $tmps $verts($ptnum)]
80     lappend tmps $tailpt

```

```

set tmps [join $tmps]
#puts " ptr sector tmps = $tmps"
foreach {x y} $tmps {
    if {$lx == 0} {
5       set lx $x ; set ly $y
        continue
    } else {
        set nx [expr (($x - $lx)/2) + $lx]
        set ny [expr (($y - $ly)/2) + $ly]
10      lappend sectors [list $nx $ny]
        set lx $x ; set ly $y
    }
}

15
#puts " ptr sectors = $sectors"
set n 0
foreach {pt} $sectors {
    set x [lindex $pt 0]
20    set y [lindex $pt 1]
    set x1 [expr $x -3]
    set x2 [expr $x +3]
    set y1 [expr $y -3]
    set y2 [expr $y +3]
25    set midx [expr round( ($x2 + $x1) / 2 )]
    $canvas create poly $midx $y1 $x2 $y2 $x1 $y2 -fill yellow -outline black -width 1 -tags
[list handle ptrsect num$ptnum sx$sn ]
    incr n
}
30 }

proc iat::ant::ant_draw_segments { ns } {
    #puts "iat::ant::ant_draw_segments: $ns"

35    variable points
    variable kind
    variable heads
    variable tails

40    upvar #0 [join [list [namespace current] $ns canvas] ::] canvas

    $canvas delete segment

    set tmps [join $points]
45    if {$kind == "edge"} {
        if {[llength $tmps] < 4} { return }
        $canvas create line $tmps -width 2 -fill red -tags [list segment]
    } elseif {$kind == "area"} {
        if {[llength $tmps] < 6} { return }
50    $canvas create poly $tmps -width 2 -fill "" -outline red -tags [list segment]
    }
}

55 proc iat::ant::ant_draw_vertexs { ns } {
    #puts "iat::ant::ant_draw_vertexs: $ns"

    variable points

60    upvar #0 [join [list [namespace current] $ns canvas] ::] canvas
    upvar #0 [join [list [namespace current] $ns select_mode] ::] select_mode

    $canvas delete vertex

65    set shape rect
    if {$select_mode == "edit"} { set shape oval }

    set n 0
    foreach pt $points {
70        set x [lindex $pt 0]
        set y [lindex $pt 1]
        set x1 [expr $x -3]
        set x2 [expr $x +3]
        set y1 [expr $y -3]
        set y2 [expr $y +3]
75        $canvas create $shape $x1 $y1 $x2 $y2 -fill yellow -outline black -width 1 -tags [list handle
vertex num$sn]
        incr n
    }
80    # $canvas itemconfigure HANDLE -fill red -outline black

```



```

}

proc iat::ant::ant_draw_ptr_vertexOLD { ns ptnum } {

5   variable verts

    foreach {key value} [array get verts] {
        if {$value == ""} { continue }
        ant_draw_ptr_vertex $ns $key
10  }
}

proc iat::ant::ant_draw_ptr_vertexs { ns ptnum } {
    variable TRACE
15   if {$TRACE} { puts "iat::ant::ant_draw_ptr_vertexs: $ns $ptnum" }

    variable verts

    upvar #0 [join [list [namespace current] $ns canvas] ::] canvas
20   upvar #0 [join [list [namespace current] $ns select_mode] ::] select_mode

    set shape rect
    if {$select_mode == "edit"} { set shape oval }

25   set n 0
    foreach {pt} $verts($ptnum) {
        set x [lindex $pt 0]
        set y [lindex $pt 1]
        set x1 [expr $x -3]
30        set x2 [expr $x +3]
        set y1 [expr $y -3]
        set y2 [expr $y +3]
        $canvas create $shape $x1 $y1 $x2 $y2 -fill yellow -outline black -width 1 -tags [list handle
ptrvert num$ptnum vx$n]
35        incr n
    }
}

40 proc iat::ant::drawSymbolHandle {} {
    variable TRACE
    if {$TRACE} { puts "iat::ant::ant_vertexs_draw: $ns" }

    variable points

45   set pt $symbolPoint
    set x [lindex $pt 0]
    set y [lindex $pt 1]
    set x1 [expr $x -3]
50    set x2 [expr $x +3]
    set y1 [expr $y -3]
    set y2 [expr $y +3]
    $canvas create rect $x1 $y1 $x2 $y2 -fill yellow -outline black -width 1 -tags [list handle symbol]
}

55 proc iat::ant::ant_vertexs_add { ns pts } {
    variable TRACE
    if {$TRACE} { puts "iat::ant::ant_vertexs_add: $pts" }

60    foreach pt $pts {
        ant_vertex_add $ns $pt
    }
}

65 proc iat::ant::ant_vertex_add { ns pt } {
    variable TRACE
    if {$TRACE} { puts "iat::ant::ant_vertex_add: $ns $pt" }

70    variable points

    lappend points $pt
    #puts "  points = $points"

75 }

proc iat::ant::ant_insert_vertex { ns idx newpt } {
    variable TRACE
    if {$TRACE} { puts "iat::ant::ant_insert_vertex: $ns $idx $newpt" }

80    variable kind

```

```

variable points
variable heads
variable verts
variable tails
5
    if ($idx > [llength $points]) {
        lappend points $newpt
    } else {
        set points [linsert $points $idx $newpt]
10    }
    #puts " points = $points"

    # pinned pointers must be readjusted...
    set hpts [array names heads]
    set hpts [lsort -integer $hpts]
15    for {set i [expr $idx+1]} {$i>=0} {incr i -1} {
        set hpt [lindex $hpts $i]
        if ($idx <= $hpt) {
            ant_move_ptr_head $ns $hpt [expr $hpt+1]
20        }
    }

    ant_save $ns

25 )

proc iat::ant::ant_move_vertex { ns idx newpt } {
    variable TRACE
    if ($TRACE) { puts "iat::ant::ant_move_vertex: $ns $idx $newpt" }
30
    variable points

    set points [lreplace $points $idx $idx $newpt]
    ant_save $ns
35
}

proc iat::ant::ant_delete_vertex { ns idx } {
    variable TRACE
    if ($TRACE) { puts "iat::ant::ant_delete_vertex: $ns $idx" }
40

    variable kind
    variable points
    variable heads
    variable verts
45    variable tails

    # Don't delete beyond minimum points...
    if ($kind == "area") {
        if ([llength $points] == 3) { return }
50    } elseif ($kind == "edge") {
        if ([llength $points] == 2) { return }
    } else {
        if ([llength $points] == 1) { return }
55    }

    set points [lreplace $points $idx $idx]

    # pinned pointers must be readjusted...
    set hpts [array names heads]
    set hpts [lsort -integer $hpts]
    foreach hpt $hpts {
        if ($hpt > $idx) {
            ant_move_ptr_head $ns $hpt [expr $hpt-1]
60        }
    }
65
    ant_save $ns

70 )

proc iat::ant::ant_delete_pointer { ns ptnum } {
    variable TRACE
    if ($TRACE) { puts "iat::ant::ant_delete_pointer: $ptnum" }
75

    variable points
    variable heads
    variable verts
    variable tails
    variable dPTRs
80    variable dSYMs

```

```

    set heads($ptnum) ""
    set verts($ptnum) ""
    set tails($ptnum) ""
    set dPTRs($ptnum) ""
5   set dSYMs($ptnum) ""

    ant_save $ns
}
10
proc iat::ant::ant_move_ptr_head { ns idx newidx } {
    variable TRACE
    if {$TRACE} { puts "iat::ant::ant_move_ptr_head: $ns $idx $newidx" }

15     variable points
        variable heads
        variable verts
        variable tails
    variable dSYMs
20    variable dPTRs

        if {$newidx == "auto"} {
            set heads($idx) "auto"
            ant_save $ns
25            return
        }

        if {[info exists heads($idx)]} { return -3 }
        if {$heads($idx) == ""} { return -3 }
30    if {$idx == $newidx} { return -1 }
        if {$heads($idx) == "auto"} { set heads($idx) $idx }

        #puts "heads($idx) = $heads($idx)"
        #puts "tails($idx) = $tails($idx)"
35
        set heads($newidx) $newidx
        set tails($newidx) $tails($idx)
        set verts($newidx) $verts($idx)
        set dSYMs($newidx) $dSYMs($idx)
40    set dPTRs($newidx) $dPTRs($idx)

        set heads($idx) ""
        set tails($idx) ""
        set dSYMs($idx) ""
45    set dPTRs($idx) ""
        array set verts [list]

        ant_save $ns

50    return $newidx
}

proc iat::ant::ant_move_ptr_vert { ns ptnum vertn newpt } {
    variable TRACE
55    if {$TRACE} { puts "iat::ant::ant_move_ptr_vert: $ns $ptnum $vertn $newpt" }

        variable verts

        set vs $verts($ptnum)
        set vs [lreplace $vs $vertn $vertn $newpt]
        set verts($ptnum) $vs

        ant_save $ns
}
65
proc iat::ant::ant_move_ptr_tail { ns idx newpt } {
    variable TRACE
    if {$TRACE} { puts "iat::ant::ant_move_ptr_tail: $ns $idx $newpt" }

70    variable verts
        variable tails

        set x [lindex $tails($idx) 0]
        set y [lindex $tails($idx) 1]
        set dx [expr [lindex $newpt 0] - $x]
75    set dy [expr [lindex $newpt 1] - $y]
        set verts($idx) [points_translate $dx $dy $verts($idx)]

        set tails($idx) $newpt

80    ant_save $ns

```

```

)

proc iat::ant::ant_insert_ptrvert { ns ptnum vertn newpt } {
    variable TRACE
5    if {$TRACE} { puts "iat::ant::ant_insert_ptrvert: $ns $ptnum $vertn $newpt" }

    variable verts

    set vs $verts($ptnum)
10    if {$vertn >= [llength $vs]} {
        lappend vs $newpt
    } else {
        set vs [linsert $vs $vertn $newpt]
15    }
    set verts($ptnum) $vs

    #puts "  points = $points"
    ant_save $ns
20 }

proc iat::ant::ant_delete_ptrvert { ns ptnum vertn } {
    variable TRACE
25    if {$TRACE} { puts "iat::ant::ant_delete_ptrvert: $ptnum $vertn" }

    variable verts

    set vs $verts($ptnum)
    set vs [lreplace $vs $vertn $vertn]
30    set verts($ptnum) $vs

    ant_save $ns

35 }

proc iat::ant::roiSymbolMove { fromPt toPt } {
    #puts "roiSymbolMove"
    variable canvas
    variable symbolDirty
    variable symbolPoint

    $canvas delete symbol
    set symbolPoint $toPt
45    set symbolDirty 1

    roiSave

    return 0
50 }

proc iat::ant::roiReadAllXML { raw } {
    variable channels
    if {$raw == ""} {
55        if {$channels != ""} {
            incr channels
            if {$channels > 90} { set channels 65 }
        }
        return
60    }
    if {$channels == ""} {
        roiDeleteAll
        iat::ant::xml::roiReadAll $raw
    } else {
65        set num $channels
        set char [format %c $num]
        set channels "$char:"
        iat::ant::xml::roiReadAll $raw
        set channels $num
70        incr channels
        if {$channels > 90} { set channels 65 }
    }
}

75 proc iat::ant::noop { args } {
    #puts "NOOP: $args"
}

80 proc iat::ant::roiViewSet { nv } {
    #variable view

```

```

switch --exact $nv {
    "none" {
        set view "none"
    }
    default {
        set view "all"
    }
}
}
10 proc iat::ant::ant_dump { ns lvl } {
    puts "iat::ant::ant_dump: $ns"

    set str [ant_make_all $ns $lvl]
15    puts $str
}

proc iat::ant::ant_dump_svg { ns lvl } {
20    puts "iat::ant::ant_dump_svg: $ns"

    set str [ant_make_svg_all $ns $lvl]
    puts $str
25 }

proc iat::ant::ant_dump_keys { ns } {
    puts "iat::ant::ant_dump_keys: $ns"

30    upvar #0 [join {list [namespace current] $ns orders} ::] orders

    set lst1 [list]
    set lst2 [list]
    foreach (key value) [array get orders] {
35        lappend lst1 $key
        lappend lst2 $value
        puts "key $key = $value"
    }
    #set lst [lsort -dictionary $lst]
40    #puts "keys = $lst"
}

45 if {0} {
}
iat.app.txt
50 package require BWidget
package require Img
package require base64
#package require tkdnd

55 namespace eval iat {
    font create fontSmall -family helvetica -size 16
    font create fontDefault -family helvetica -size 16
    font create fontLarge -family helvetica -size 16
60
    # for cut/copy/paste
    variable tmp_ant_copy ""
}

65 source iat.icons.tcl
source iat.canvas.tcl
source iat.thumbs.tcl
source iat.ant.tcl
70 source iat.tex.tcl

namespace eval iat::dialog {
    variable TRACE 0
    variable ref_list [list NONE]
75    variable ref_combo ""
    variable ref_name "NONE"
    variable ref_file ""
    variable ref_tree ""
    variable ref_code ""
80    variable ref_symbol ""
    variable ref_label ""

```

```

    variable grp_tree ""
}

source iat.dialog.groups.tcl
5 source iat.dialog.borders.tcl
source iat.dialog.dataref.tcl
source iat.dialog.doc.tcl
source iat.var.js4svg.tcl
source iat.var.todo.tcl
10 source iat.var.splash.tcl

namespace eval iat::app {
    variable TRACE 0
    variable DEMO1 0
15    variable BATIK 0 # must also turn menu off in js4svg.js
    variable SQRIMG 0
    variable SERVER 0
    variable SERVER_ONCE 0
    variable SERVER_STATE WAIT
20    variable id 0
    variable version "0.8.4"
    variable rsrc_url ""
    variable init_url "/"
    variable use_javascript_file 1
25 }

# This starts the tcl httpd server...
if {$::iat::app::SERVER} {
    set ::iat::app::SERVER_STATE WAIT
30    set ::iat::app::SERVER_URL ""
    source ./tclhttpd/bin/httpd.tcl
}

proc iat::app::proc { ns cmd args } {
35    variable TRACE
    if {$TRACE} { puts "iat::app::proc: $ns $cmd $args" }

    upvar #0 [join [list [namespace current] $ns window] ::] window

40    switch $cmd {
        "configure" {
            foreach {key value} $args {
                switch -- $key {
45                    "-url" { url_open_url $ns $value }
                    "-resources" { url_set_resources $ns $value }
                    "-init_url" { url_set_init_url $ns $value }
                    "-scale" { set_scale $ns $value }
                }
            }
        }
50        "cget" {
            switch -- [lindex $args 0] {
                "-window" { return $window }
            }
        }
55        "dump" {
            [namespace current]::dump $ns
        }
        default {
60        }
    }

    return {}
}

65
proc iat::app::create { path } {
    variable id
    variable DEMO1
    variable version
70    variable SERVER
    variable SERVER_STATE

    if {$path == "."} { set path "" }
    set wid [incr id]
75    set wid "iat$wid"

    # splash screen...
    wm iconify .
    if {$DEMO1} {
80        app_splash $wid
    }
}

```

```

toplevel $path.$wid -borderwidth 2
    wm minsize $path.$wid 400 400
    wm geometry $path.$wid 600x400
5    wm title $path.$wid "IAT v$version"
set path $path.$wid
#puts "path = $path"

10    set ns [namespace current]::$wid
namespace eval $ns {
    variable window ""
    variable splash 1
    variable svg_pkg 0
15    variable open_url "/"
    variable image_url ""
    variable ants_url ""
    variable image_frame ""
        variable image_canvas ""
20        variable image_scale 100
        variable toolbar_state_url 1
    variable toolbar_state_edit 1
    variable toolbar_state_view 1
        variable toolbar_state_symlbl 1
25    variable toolbar_state_cs 1
    variable toolbar_state_cap 1
    variable status_label ""
    variable entry_url ""
    variable entry_view ""
30    variable entry_inview ""
    variable entry_code ""
    variable entry_symbol ""
        variable entry_label ""
    variable entry_caption ""
35    variable entry_cs_class ""
    variable entry_cs_tumor ""
    variable entry_cs_node ""
    variable entry_cs_metastasis ""
    variable entry_cs_note ""
40 }
    set cmd "proc [namespace current]::$wid { cmd args } {eval [namespace current]::proc $wid \$cmd
\$args}"
    namespace eval :: $cmd

45    upvar #0 [join [list $ns window] ::] window
    set window $path

        upvar #0 [join [list $ns image_frame] ::] image_frame
        upvar #0 [join [list $ns image_canvas] ::] image_canvas
50    upvar #0 [join [list $ns status_label] ::] status_label
    upvar #0 [join [list $ns entry_url] ::] entry_url
    upvar #0 [join [list $ns entry_view] ::] entry_view
    upvar #0 [join [list $ns entry_inview] ::] entry_inview
    upvar #0 [join [list $ns entry_code] ::] entry_code
55    upvar #0 [join [list $ns entry_symbol] ::] entry_symbol
        upvar #0 [join [list $ns entry_label] ::] entry_label
    upvar #0 [join [list $ns entry_caption] ::] entry_caption

    upvar #0 [join [list $ns entry_cs_class] ::] entry_cs_class
60    upvar #0 [join [list $ns entry_cs_tumor] ::] entry_cs_tumor
    upvar #0 [join [list $ns entry_cs_node] ::] entry_cs_node
    upvar #0 [join [list $ns entry_cs_metastasis] ::] entry_cs_metastasis
    upvar #0 [join [list $ns entry_cs_note] ::] entry_cs_note

65    menu $path.menubar -type menubar
    $path.menubar add cascade -label File -menu $path.menubar.file -underline 0
    $path.menubar add cascade -label Edit -menu $path.menubar.edit -underline 0
    $path.menubar add cascade -label View -menu $path.menubar.view -underline 0
    $path.menubar add cascade -label Settings -menu $path.menubar.settings -underline 0
70    $path.menubar add cascade -label Help -menu $path.menubar.help -underline 0
    if (!$DEMO1) {
        $path.menubar add cascade -label Debug -menu $path.menubar.debug -underline 0
    }

75    #export menu
    menu $path.menubar.export -tearoff 0
    $path.menubar.export add command -label "SVG Package" -underline 0 \
        -command "iat::app::app_export_svgpkg $wid"
    $path.menubar.export add command -label "Image" -underline 0 \
80    -command "iat::app::app_export_image $wid"
    $path.menubar.export add command -label "Postscript" -underline 0 \

```

Appendix 2

```

-command "iat::app::app_export_ps $wid"
$spath.menubar.export add command -label "HTML: Default Wrapper" -underline 0 \
-command "iat::app::app_export_html_default $wid"
$spath.menubar.export add command -label "HTML: Quiz Wrapper" -underline 0 \
5 -command "iat::app::app_export_html_quiz $wid"
#end export menu

#file menu
menu $spath.menubar.file -tearoff 0
10 $spath.menubar.file add command -label "New" -underline 0 \
-command "iat::app::app_new"
$spath.menubar.file add command -label "Open Image" -underline 0 \
-command "iat::app::url_open $wid"
15 $spath.menubar.file add command -label "Open Folder" -underline 0 \
-command "iat::app::folder_open $wid"
$spath.menubar.file add command -label "Save" -underline 0 \
-command "iat::app::url_save $wid"
$spath.menubar.file add command -label "Save As..." -underline 5 \
-command "iat::app::url_save_as $wid"
20 $spath.menubar.file add separator
$spath.menubar.file add cascade -label "Export..." -menu $spath.menubar.export -underline 0
$spath.menubar.file add separator
$spath.menubar.file add command -label "Close Image" -underline 1 \
-command "iat::app::app_close_image $wid"
25 $spath.menubar.file add command -label "Close Window" -underline 1 \
-command "iat::app::app_close_window $wid"
$spath.menubar.file add separator
$spath.menubar.file add command -label "Quit" -underline 1 \
-command "exit"
30 #end file menu

# edit menu
menu $spath.menubar.edit -tearoff 1
$spath.menubar.edit add command -label "Create Area" -underline 0 \
35 -command "iat::app::edit_create $wid area"
$spath.menubar.edit add command -label "Create Edge" -underline 0 \
-command "iat::app::edit_create $wid edge"
$spath.menubar.edit add command -label "Create Point" -underline 0 \
-command "iat::app::edit_create $wid point"
40 $spath.menubar.edit add separator
$spath.menubar.edit add command -label "Groups" -underline 0 \
-command "iat::app::dialog_groups $wid"
$spath.menubar.edit add separator
$spath.menubar.edit add command -label "Edit Borders" -underline 0 \
45 -command "iat::app::dialog_borders $wid"
# end edit menu

# view menu
set image_scale_var [join [list iat::app $wid image_scale] ::]
50 menu $spath.menubar.view -tearoff 1
$spath.menubar.view add radio -label "25%" -underline 0 \
-variable $image_scale_var -value 25 \
-command "iat::app::scale_image $wid"
$spath.menubar.view add radio -label "50%" -underline 0 \
55 -variable $image_scale_var -value 50 \
-command "iat::app::scale_image $wid"
$spath.menubar.view add radio -label "100%" -underline 0 \
-variable $image_scale_var -value 100 \
-command "iat::app::scale_image $wid"
60 $spath.menubar.view add radio -label "200%" -underline 0 \
-variable $image_scale_var -value 200 \
-command "iat::app::scale_image $wid"
$spath.menubar.view add radio -label "400%" -underline 0 \
65 -variable $image_scale_var -value 400 \
-command "iat::app::scale_image $wid"
# end view menu

# settings menu
#puts "state_var = $state_var"
70 menu $spath.menubar.settings -tearoff 1
# url toolbar
set state_var [join [list iat::app $wid toolbar_state_url] ::]
$spath.menubar.settings add check -label "Show URL" -underline 0 \
-variable $state_var \
75 -command "iat::app::toggle_toolbar $wid $spath tb_url {urll urle} $state_var"

# edit toolbar
set state_var [join [list iat::app $wid toolbar_state_edit] ::]
$spath.menubar.settings add check -label "Show Edit" -underline 0 \
80 -variable $state_var \
-command "iat::app::toggle_toolbar $wid $spath tb_edit { select1 select2 blank1 new_point
new_edge new_area blank2 pointer1 pointer2 ptrsty ptrpin ptrsym blank3 color move delete blank4 }

```



```

5 $state_var"
    # view toolbar
    set state_var [join [list iat::app $wid toolbar_state_view] ::]
    $path.menubar.settings add check -label "Show View" -underline 0 \
    -variable $state_var \
    -command "iat::app::toggle_toolbar $wid $path tb_vw { vw1 vwe invw1 invwe} $state_var"
    # code & symbol & label toolbar
    set state_var [join [list iat::app $wid toolbar_state_symlbl] ::]
    $path.menubar.settings add check -label "Show FCAT" -underline 0 \
    -variable $state_var \
    -command "iat::app::toggle_toolbar $wid $path tb_sl { fcatl codl code syml syml lb1l lble codb}
10 $state_var"
    # TNM Cancer Staging shorthand
    set state_var [join [list iat::app $wid toolbar_state_cs] ::]
    $path.menubar.settings add check -label "Show TNM" -underline 0 \
    -variable $state_var \
    -command "iat::app::toggle_toolbar $wid $path tb_cs { tnm1 class1 classe t1 te n1 ne m1 me notel
notee} $state_var"
    # caption toolbar
    set state_var [join [list iat::app $wid toolbar_state_cap] ::]
    $path.menubar.settings add check -label "Show Caption" -underline 0 \
    -variable $state_var \
    -command "iat::app::toggle_toolbar $wid $path tb_cap {cap1 cape} $state_var "
25 # end settings menu

    # help menu
    menu $path.menubar.help -tearoff 0
    $path.menubar.help add command -label "About..." -underline 0 \
    -command "iat::app::help_about $wid"
    $path.menubar.help add command -label "To Do" -underline 0 \
    -command "iat::app::help_todo $wid"
    # end help menu

    # debug menu
35 if {!$DEMO1} {
    menu $path.menubar.debug -tearoff 1
    $path.menubar.debug add command -label "Console" -underline 0 \
    -command "iat::app::show_console $wid"
    $path.menubar.debug add command -label "Dump Ants" -underline 0 \
    -command "iat::app::dump_ants $wid"
    $path.menubar.debug add command -label "Dump SVG" -underline 0 \
    -command "iat::app::dump_svg $wid"
    $path.menubar.debug add command -label "Dump Keys" -underline 0 \
    -command "iat::app::dump_keys $wid"
45 }
    # end debug menu

    $path configure -menu $path.menubar

50
    # URL toolbar
    set url_tb [frame $path.tb_url -relief solid -bd 1]
    #puts "url_tb = $url_tb"
    label $url_tb.url1 -text "URL:"
55 pack $url_tb.url1 -side left
    Entry $url_tb.url2 -width 60
    pack $url_tb.url2 -side left -pady 2 -fill x -expand 1
    $url_tb.url2 configure -command "iat::app::url_enter $wid"
    set entry_url $url_tb.url2
    # linux
    #dnd bindtarget $url_tb.e text/plain <Drop> "iat::app::url_drop $wid %A %a %T %W %D" 1
    # windows
    # dnd bindtarget $url_tb.e Files <Drop> "iat::app::url_drop $wid %A %a %T %W %D" 1
    # dnd bindsources $url_tb.e CF_HDROP { return [pwd] }
65 pack $url_tb -side top -anchor nw -fill x -expand 0

    # edit toolbar
    set edit_tb [frame $path.tb_edit -relief solid -bd 1]
    set tmp [button $edit_tb.select1 \
    -image [image create photo -data $iat::icons::SelectSolid] \
    -command "iat::app::edit_select $wid annotation" ]
    pack $tmp -side left
    set tmp [button $edit_tb.select2 \
    -image [image create photo -data $iat::icons::SelectHollow] \
    -command "iat::app::edit_select $wid edit" ]
75 pack $tmp -side left
    set tmp [button $edit_tb.blank1 \
    -image [image create photo -data $iat::icons::Blank] \
    -relief flat \
    -command "" ]
80 pack $tmp -side left

```

Appendix 2

```

set tmp [button $edit_tb.new_point \
    -image [image create photo -data $iat::icons::Point] \
    -command "iat::app::edit_create $wid point" ]
pack $tmp -side left
5
set tmp [button $edit_tb.new_edge \
    -image [image create photo -data $iat::icons::Line] \
    -command "iat::app::edit_create $wid edge" ]
pack $tmp -side left
10
set tmp [button $edit_tb.new_area \
    -image [image create photo -data $iat::icons::Polygon] \
    -command "iat::app::edit_create $wid area" ]
pack $tmp -side left
#set tmp [button $edit_tb.new_rectangle \
#    -image [image create photo -data $iat::icons::FullScreen] \
#    -command "" ]
#    pack $tmp -side left
#set tmp [button $edit_tb.new_circle \
#    -image [image create photo -data $iat::icons::Circle] \
#    -command "" ]
#    pack $tmp -side left
20
set tmp [button $edit_tb.blank2 \
    -image [image create photo -data $iat::icons::Blank] \
    -relief flat \
    -command "" ]
25
pack $tmp -side left
set tmp [button $edit_tb.pointer1 \
    -image [image create photo -data $iat::icons::PointerSingle] \
    -command "iat::app::edit_create_pointer $wid single" ]
pack $tmp -side left
30
set tmp [button $edit_tb.pointer2 \
    -image [image create photo -data $iat::icons::PointerMultiple] \
    -command "iat::app::edit_create_pointer $wid multiple" ]
pack $tmp -side left
set tmp [button $edit_tb.ptrsty \
35
    -image [image create photo -data $iat::icons::PointerHead] \
    -command "iat::app::edit_ptr_style $wid" ]
pack $tmp -side left
set tmp [button $edit_tb.ptrpin \
40
    -image [image create photo -data $iat::icons::Pin] \
    -command "iat::app::edit_ptr_pin $wid" ]
pack $tmp -side left
set tmp [button $edit_tb.ptrsym \
    -image [image create photo -data $iat::icons::Symbol] \
    -command "iat::app::edit_ptr_symbol $wid" ]
45
pack $tmp -side left
set tmp [button $edit_tb.blank3 \
    -image [image create photo -data $iat::icons::Blank] \
    -relief flat \
    -command "" ]
50
pack $tmp -side left
set tmp [button $edit_tb.color \
    -image [image create photo -data $iat::icons::Color] \
    -command "iat::app::edit_ant_color $wid" ]
pack $tmp -side left
55
set tmp [button $edit_tb.move \
    -image [image create photo -data $iat::icons::Move] \
    -command "iat::app::edit_move $wid" ]
pack $tmp -side left
#set tmp [button $edit_tb.copy \
60
#    -image [image create photo -data $iat::icons::Copy] \
#    -command "iat::app::edit_ant_copy $wid" ]
#    pack $tmp -side left
#set tmp [button $edit_tb.paste \
#    -image [image create photo -data $iat::icons::Blank] \
#    -command "iat::app::edit_ant_paste $wid" ]
#    pack $tmp -side left
65
set tmp [button $edit_tb.delete \
    -image [image create photo -data $iat::icons::Cut] \
    -command "iat::app::edit_ant_cut $wid" ]
pack $tmp -side left
70
set tmp [button $edit_tb.blank4 \
    -image [image create photo -data $iat::icons::Blank] \
    -relief flat \
    -command "" ]
75
pack $tmp -side left
pack $edit_tb -side top -anchor nw -fill x -expand 0

# view toolbar
set vw_tb [frame $path.tb_vw -relief solid -bd 1]
#puts "sl_tb = $sl_tb"
80
label $vw_tb.vw1 -text "VIEW:"

```

```

pack $vw_tb.vwl -side left
ComboBox $vw_tb.vwe -width 12 -values [list ALL NONE] -modifycmd "iat::app::edit_set_view $wid"
set entry_view $vw_tb.vwe
$entry_view setvalue first
5 pack $vw_tb.vwe -side left -fill x -expand 0
  #set tmp [button $vw_tb.vwb \
  #   -image [image create photo -data $iat::icons::Code] \
  #   -command "iat::app::edit_update_view $wid" ]
  #pack $vw_tb.vwb -side left -padx 4
10 label $vw_tb.invw1 -text "  IN VIEWS:"
  pack $vw_tb.invw1 -side left
  Entry $vw_tb.invw2 -width 48 -command "iat::app::edit_set_inview $wid"
  set entry_inview $vw_tb.invw2
  pack $vw_tb.invw2 -side left -fill x -expand 0 -pady 4
15 pack $vw_tb -side top -anchor nw -fill x -expand 0

# code & symbol & label toolbar
set sl_tb [frame $path.tb_sl -relief solid -bd 1]
20 #puts "sl_tb = $sl_tb"
  label $sl_tb.fcat1 -text "FCAT"
  pack $sl_tb.fcat1 -side left
  label $sl_tb.cod1 -text "CODE:"
  pack $sl_tb.cod1 -side left
25 Entry $sl_tb.code -width 14 -command "iat::app::edit_set_code $wid"
  set entry_code $sl_tb.code
  pack $sl_tb.code -side left -fill x -expand 0
  label $sl_tb.sym1 -text "SYMBOL:"
  pack $sl_tb.sym1 -side left
30 Entry $sl_tb.syme -width 8 -command "iat::app::edit_set_symbol $wid"
  set entry_symbol $sl_tb.syme
    pack $sl_tb.syme -side left -fill x -expand 0
    label $sl_tb.lb11 -text "LABEL:"
    pack $sl_tb.lb11 -side left
35 Entry $sl_tb.lble -width 32 -command "iat::app::edit_set_label $wid"
  set entry_label $sl_tb.lble
  pack $sl_tb.lble -side left -pady 2 -fill x -expand 0
  set tmp [button $sl_tb.codb \
  -image [image create photo -data $iat::icons::Code] \
  -command "iat::app::edit_ant_data $wid" ]
40 pack $sl_tb.codb -side left -padx 4
  pack $sl_tb -side top -anchor nw -fill x -expand 0

45 # TNM Cancer Staging shorthand
set cs_tb [frame $path.tb_cs -relief solid -bd 1]
#puts "sl_tb = $sl_tb"
label $cs_tb.tnml -text "TNM"
pack $cs_tb.tnml -side left -pady 2
50 label $cs_tb.class1 -text "STAGE:"
  pack $cs_tb.class1 -side left
  Entry $cs_tb.classe -width 4 -command "iat::app::edit_set_cs_class $wid"
  set entry_cs_class $cs_tb.classe
  pack $cs_tb.classe -side left -fill x -expand 0
55 label $cs_tb.t1 -text "T"
  pack $cs_tb.t1 -side left
  Entry $cs_tb.te -width 4 -command "iat::app::edit_set_cs_tumor $wid"
  set entry_cs_tumor $cs_tb.te
  pack $cs_tb.te -side left -fill x -expand 0
60 label $cs_tb.n1 -text "N"
  pack $cs_tb.n1 -side left
  Entry $cs_tb.ne -width 4 -command "iat::app::edit_set_cs_node $wid"
  set entry_cs_node $cs_tb.ne
  pack $cs_tb.ne -side left -fill x -expand 0
65 label $cs_tb.m1 -text "M"
  pack $cs_tb.m1 -side left
  Entry $cs_tb.me -width 4 -command "iat::app::edit_set_cs_metastasis $wid"
  set entry_cs_metastasis $cs_tb.me
  pack $cs_tb.me -side left -fill x -expand 0
70 pack $cs_tb -side top -anchor nw -fill x -expand 0
  label $cs_tb.note1 -text "NOTE"
  pack $cs_tb.note1 -side left
  Entry $cs_tb.notee -width 42 -command "iat::app::edit_set_cs_note $wid"
  set entry_cs_note $cs_tb.notee
75 pack $cs_tb.notee -side left -fill x -expand 0
  pack $cs_tb -side top -anchor nw -fill x -expand 0

# caption toolbar
set cap_tb [frame $path.tb_cap -relief solid -bd 1]
80 #puts "sl_tb = $sl_tb"
  label $cap_tb.cap1 -text "CAPTION:"

```

Appendix 2

```

pack $cap_tb.cap1 -side left -padx 2 -pady 2
text $cap_tb.cape -width 72 -height 2
set entry_caption $cap_tb.cape
pack $cap_tb.cape -side left -pady 2 -fill x -expand 0
5 pack $cap_tb -side top -anchor nw -fill x -expand 0

set f [frame $path.f -relief solid -bd 1]
pack $f -side top -anchor nw -fill both -expand 1

10 set f [frame $path.f.f -relief solid -bd 1]
pack $f -side top -anchor nw -fill both -expand 1
set image_frame $f
#puts "image_frame = $image_frame"

15 set c [iat::canvas::create $f]
set image_canvas $c

# help bar
label $path.help -text "Ready."; pack $path.help -side left
20 set status_label $path.help

$image_canvas configure -callbackselect "[namespace current]::handle_ant_select $wid"
$image_canvas configure -callbackdeselect "[namespace current]::handle_ant_deselect $wid"
$image_canvas configure -status $status_label

25 # $image_canvas configure -callbackserver "[namespace current]::url_save_server $wid"
if {$SERVER} {
    $image_canvas configure -callbackserver "[namespace current]::url_save_server $wid"

30 set fh [open "./tclhttpd/htdocs/index.htm" w]
puts $fh "<html>\n"
puts $fh "<head>\n"
puts $fh "<title>IAT SERVER</title>\n"
puts $fh "<meta http-equiv='REFRESH' content='5;URL=index.htm'>\n"
35 puts $fh "</head>\n"
puts $fh "<body>\n"
puts $fh "IAT server waiting for session..."
puts $fh "</body>\n"
puts $fh "</html>\n"
40 close $fh
}

return [join [list [namespace current] $wid] ::]
}

45 proc iat::app::app_new {} {
    return [create .]
}

50 proc iat::app::app_close_image { ns } {
    variable TRACE
    if ($TRACE) { puts "iat::app::app_close_image: $ns" }

    variable SERVER
55 variable SERVER_STATE
    upvar #0 [join [list [namespace current] $ns image_canvas] ::] image_canvas
    upvar #0 [join [list [namespace current] $ns image_url] ::] image_url
    upvar #0 [join [list [namespace current] $ns ants_url] ::] ants_url
    upvar #0 [join [list [namespace current] $ns entry_url] ::] entry_url

60 set SERVER_STATE WAIT
if {$SERVER} {
    set fh [open "./tclhttpd/htdocs/index.htm" w]
    puts $fh "<html>\n"
65 puts $fh "<head>\n"
puts $fh "<title>IAT SERVER</title>\n"
puts $fh "</head>\n"
puts $fh "<body>\n"
puts $fh "IAT server session closed..."
70 puts $fh "</body>\n"
puts $fh "</html>\n"
close $fh
}

75 $image_canvas close

set image_url ""
set ants_url ""
$entry_url delete 0 end

80 )

```

```

proc iat::app::app_close_window { ns } {
    variable TRACE
    if ($TRACE) { puts "iat::app::app_close_window: $ns" }
    app_close_image $ns
    destroy . $ns
}

proc iat::app::url_set_resources { ns url } {
    variable TRACE
    if ($TRACE) { puts "iat::app::url_set_resources: $ns $url" }

    variable rsrc_url
    set rsrc_url $url
}

proc iat::app::url_set_init_url { ns url } {
    variable TRACE
    if ($TRACE) { puts "iat::app::url_set_init_url: $ns $url" }

    variable init_url
    set init_url $url
}

proc iat::app::url_enter { ns } {
    variable TRACE
    if ($TRACE) { puts "iat::app::url_enter: $ns" }

    upvar #0 [join [list [namespace current] $ns entry_url] ::] entry_url

    set url [$entry_url get]
    url_open_url $ns $url
}

proc iat::app::url_drop { ns action actions type widget data } {
    puts "iat::app::drop_url: $ns $action $actions $type \"$data\""

    if {[string match text/* $type]} {
        set url [string trim $data]
        $widget delete 0 end
        $widget insert 0 $url
        url_open_url $ns $url
    } else {
    }
}

proc iat::app::url_open { ns } {
    variable TRACE
    if ($TRACE) { puts "iat::app::url_open: $ns" }

    variable SERVER
    variable init_url
    upvar #0 [join [list [namespace current] $ns open_url] ::] open_url

    if ($SERVER) {
        set init_url ./tclhttpd/htdocs
    }

    set new_url [tk_getOpenFile -title "Open image/iat file." \
        -initialdir $init_url \
        -defaultextension ".svg" \
        -filetypes { {IMG { .png .PNG .tif .TIF .jpg .JPG }} {SVG { .svg .SVG }} } ]

    if ($new_url == "") { return }
    puts " new_url = $new_url"

    set new_url "file:$new_url"
    url_open_url $ns $new_url
}

proc iat::app::url_open_url { ns {url ""} } {
    variable TRACE
    if ($TRACE) { puts "iat::app::url_open_url: $ns $url" }

    variable SERVER
    variable SERVER_STATE
    upvar #0 [join [list [namespace current] $ns image_canvas] ::] image_canvas
    upvar #0 [join [list [namespace current] $ns image_url] ::] image_url
    upvar #0 [join [list [namespace current] $ns ants_url] ::] ants_url
}

```

Appendix 2

```
upvar #0 [join [list [namespace current] $ns entry_url] ::] entry_url
upvar #0 [join [list [namespace current] $ns open_url] ::] open_url
```

```
app_close_image $ns
```

```
5  if {[regexp (^file:) $url]} {
        $entry_url delete 0 end
        $entry_url insert 0 $url
        regexp (^file:(.*)) $url m path
        #puts "    path = $path"
        regexp (.*)\.(\S+)$ $path m ext
        #puts "    ext = $ext"
        set ext [string tolower $ext]
        switch -regexp $ext {
15      "png|jpg|tif" {
                set tmp ""
                set image_url $url
                url_load_image $ns $image_url
                set tmp [url_for_ants $ns $image_url]
20      if ($tmp != "") {
                set ants_url $tmp
                url_load_ants $ns $ants_url
            }
            set open_url [file dirname $path]
        }
        "svg" {
                set tmp ""
                set ants_url $url
                set tmp [url_for_image $ns $ants_url]
30      puts "    url_for_image = $tmp"
            if ($tmp != "") {
                set image_url $tmp
                url_load_image $ns $image_url
            }
            url_load_ants $ns $ants_url
            set open_url [file dirname $path]
        }
        default {
            if ([file isdirectory $path]) {
40      folder_open_url $ns "file:$path"
            }
        }
    } else {
45      puts "ERROR, non-file url: $url"
    }
}
```

```
$image_canvas redraw
```

```
50  if ($SERVER) {
        set SERVER_STATE GO
        url_save_server $ns

        #set fh [open "./tclhttpd/htdocs/index.htm" w]
55      #puts $fh "<html>\n"
        #puts $fh "<head>\n"
        #puts $fh "<title>IAT SERVER</title>\n"
        #puts $fh "<meta http-equiv='REFRESH' content='5;URL=index.htm'>\n"
        #puts $fh "</head>\n"
60      #puts $fh "<body>\n"
        #puts $fh "IAT server session started..."
        #puts $fh "</body>\n"
        #puts $fh "</html>\n"
        #close $fh
65    }
}
```

```
70  proc iat::app::url_for_ants { ns url } {
        variable TRACE
        if ($TRACE) { puts "iat::app::url_for_ants: $ns $url" }
```

```
        regexp (^file:(.*)"\.(\S+)$ $url m base
```

```
75      set tmp "$base.svg"
        if ([file exists $tmp]) { return "file:$tmp" }
        set tmp "$base.SVG"
        if ([file exists $tmp]) { return "file:$tmp" }
```

```
80      return ""
    }
```

```

proc iat::app::url_for_image { ns url } {
    variable TRACE
    if ($TRACE) { puts "iat::app::url_for_image: $ns $url" }

5       regexp (^file:(.*)\.\S+$) $url m base

    set tmp "$base.png"
    if ([file exists $tmp]) { return "file:$tmp" }
    set tmp "$base.PNG"
10     if ([file exists $tmp]) { return "file:$tmp" }

    set tmp "$base.tif"
    if ([file exists $tmp]) { return "file:$tmp" }
    set tmp "$base.TIF"
15     if ([file exists $tmp]) { return "file:$tmp" }

    set tmp "$base.jpg"
    if ([file exists $tmp]) { return "file:$tmp" }
    set tmp "$base.JPG"
20     if ([file exists $tmp]) { return "file:$tmp" }

    return ""
}

25 proc iat::app::url_load_image { ns {url ""} } {
    variable TRACE
    if ($TRACE) { puts "iat::app::url_load_image: $ns $url" }

    upvar #0 [join [list [namespace current] $ns image_url] ::] image_url
    upvar #0 [join [list [namespace current] $ns image_canvas] ::] image_canvas

    if {$url == ""} { set url $image_url }

    if ([string match file:* $url]) {
35         regexp (^file:(.*)) $url m path
            $image_canvas configure -file $path
    } else {
    }
40 }

proc iat::app::url_load_ants { ns {url ""} } {
    variable TRACE
    if ($TRACE) { puts "iat::app::url_load_ants: $ns $url" }

45     upvar #0 [join [list [namespace current] $ns image_canvas] ::] image_canvas

    if ([regexp (^file:) $url]) {
50         regexp (^file:(.*)) $url m path

            if ([file exists $path]) {
                set svg ""
                set fh [open $path r]
                set svg [read $fh]
55                 close $fh
                # regexp out the <IAT>...</IAT> data.
                set ants ""
                regexp (<IAT>.*</IAT>) $svg ants
                # parse here... pass reference...
                set doc [tex::create -xml $ants]
                $doc parse
                $doc dump; exit
                $image_canvas annotations read_cmds $doc
60                 $image_canvas annotations parse $ants
                edit_update_view $ns
            }
    }
70 }

proc iat::app::url_save_server { ns } {
    variable TRACE
    if ($TRACE) { puts "iat::app::url_save: $ns" }

75     variable SERVER_ONCE
    variable SERVER_STATE
    upvar #0 [join [list [namespace current] $ns image_url] ::] image_url
    upvar #0 [join [list [namespace current] $ns image_canvas] ::] image_canvas

80     if ($SERVER_STATE != "GO") { return }

```

```

set svgfile [file rootname [file tail $image_url]].svg

set fh [open "./tclhttpd/htdocs/index.htm" w]
5 puts $fh "<html>\n"
  puts $fh "<head>\n"
    puts $fh "<title>IAT: $svgfile</title>\n"
    puts $fh "<!-- <meta http-equiv=\"REFRESH\" content=\"5;URL=index.htm\"> -->\n"
    puts $fh "</head>\n"
10 puts $fh "<body>\n"
  puts $fh "<embed name=\"SVG0\" type=\"image/svg+xml\" width=\"100%\" height=\"100%\"
src=\"$svgfile\"></embed>\n"
  puts $fh "<noembed>No SVG embed...</noembed>\n"
  puts $fh "</body>\n"
15 puts $fh "</html>\n"
  close $fh

set rvs [$image_canvas svg]
#puts $rvs
20 set menu [lindex $rvs 7]
  set ants [lindex $rvs 8]

set uPath "./tclhttpd/htdocs/update.xml"
set fhx [open $uPath w]
25 puts $fhx "<g id='NEWANTS'>\n"
  puts $fhx "$menu\n$sants"
  puts $fhx "</g>\n"
  close $fhx

30 #if {$SERVER_ONCE == 0} {
  # url_save $ns
  # incr SERVER_ONCE
  #}

35 }

proc iat::app::url_save { ns } {
  variable TRACE
  if {$TRACE} { puts "iat::app::url_save: $ns" }
40
  variable SERVER
  variable SERVER_STATE
    upvar #0 [join [list [namespace current] $ns image_canvas] ::] image_canvas
    upvar #0 [join [list [namespace current] $ns image_url] ::] image_url
45    upvar #0 [join [list [namespace current] $ns ants_url] ::] ants_url

  set SERVER_STATE WAIT

    if {$ants_url == ""} {
50      url_save_as $ns
      return
    }

    if {[file exists $ants_url]} {
55      set choice [tk_messageBox \
        -title "Overwrite file?" \
        -message "Overwrite existing annotation (.iat) file?" \
        -icon question \
        -type yesno \
60        -default yes ]
      if {$choice != "yes"} { return }
    }

    #set ants [$image_canvas annotations make all 0]
65 set ants [app_make_svg $ns]
  url_save_ants $ns $ants_url $sants

  set SERVER_STATE GO
}

70
proc iat::app::url_save_as { ns } {
  variable TRACE
  if {$TRACE} { puts "iat::app::url_save_as: $ns" }

75    upvar #0 [join [list [namespace current] $ns image_canvas] ::] image_canvas
    upvar #0 [join [list [namespace current] $ns image_url] ::] image_url
    upvar #0 [join [list [namespace current] $ns ants_url] ::] ants_url

  regexp (^file:(.)) $image_url m image_path
80 set init_path [file dirname $image_path]
  set init_file [lindex [file split [file rootname $image_path]] end]

```



```

set new_url [tk_getSaveFile -title "Save SVG file:" \
    -initialdir $init_path \
    -initialfile $init_file \
    -defaultextension ".svg" \
    -filetypes {"SVG" {svg SVG}} ]

if {$new_url == ""} { return }

if {[file exists $new_url]} {
    set choice [tk_messageBox \
        -title "Overwrite file?" \
        -message "Overwrite existing SVG file?" \
        -icon question \
        -type yesno \
        -default yes ]
    if {$choice != "yes"} { return }
}

set ants_url "file:$new_url"
#set ants [image_canvas annotations make all 2]
set ants [app_make_svg $ns]
url_save_ants $ns $ants_url $ants
}

proc iat::app::url_save_ants { ns url ants } {
    variable TRACE
    if {$TRACE} { puts "iat::app::url_save_ants: $ns $url \n $ants" }

    if {[regexp {^file:} $url]} {
        regexp {^file:(.*)} $url m path

        if {[file exists "$path.old"]} {
            file delete "$path.old"
        }
        if {[file exists $path]} {
            file rename $path "$path.old"
        }
    }

    set fh [open $path w]
    #puts $fh "<?xml version=\"1.0\" ?>"
    #puts $fh "<image>"
    puts $fh $ants
    #puts $fh "</image>\n"
    close $fh
}

proc iat::app::folder_open { ns } {
    variable TRACE
    if {$TRACE} { puts "iat::app::folder_open: $ns" }

    upvar #0 [join [list [namespace current] $ns open_url] ::] open_url

    set new_url [tk_chooseDirectory -title "Open image folder..." \
        -initialdir $open_url ]

    if {$new_url == ""} { return }
    #puts " new_url = $new_url"

    set new_url "file:$new_url"
    #url_open_url $ns $new_url
    folder_make_contact_sheet $ns $new_url
}

proc iat::app::folder_open_url { ns new_url } {
    variable TRACE
    if {$TRACE} { puts "iat::app::folder_open_url: $ns $new_url" }

    upvar #0 [join [list [namespace current] $ns open_url] ::] open_url

    if {$new_url == ""} { return }

    folder_make_contact_sheet $ns $new_url
}

proc iat::app::folder_make_contact_sheet { ns url } {

```

```

variable TRACE
if {$TRACE} { puts "iat::app::folder_make_contact_sheet: $ns" }

upvar #0 [join [list [namespace current] $ns image_frame] ::] image_frame
5 upvar #0 [join [list [namespace current] $ns image_canvas] ::] image_canvas
upvar #0 [join [list [namespace current] $ns open_url] ::] open_url

app_close_image $ns

10 #folder_make_thumbnails $ns $url

#puts "image canvas = $image_canvas"
$image_canvas destroy
set c [iat::thumbs::create $image_frame]
15 set image_canvas $c
$image_canvas configure -callbackselect "iat::app::contact_sheet_select"
$image_canvas configure -url $url

return

20 regexp {^file:(.*)} $url m srcPath
set tmpPath [file join $srcPath 00_TMP]
set tmbPath [file join $tmpPath T]

25 set files [glob [file join $tmbPath *.JPG]]

pack forget $image_frame
set wpath $image_frame
destroy $image_frame

30 set image_frame [frame $image_frame]
set csf $image_frame

canvas $csf.canvas -width 10 -height 10 \
35 -yscrollcommand [list $csf.yscroll set]
scrollbar $csf.yscroll -orient vertical \
-command [list $csf.canvas yview]
pack $csf.yscroll -side right -fill y
pack $csf.canvas -side left -fill both -expand true
40 #grid $stop.c.canvas $stop.c.yscroll -sticky news
pack $csf -side top -fill both -expand true

set f [frame $csf.canvas.f -bd 0]
$csf.canvas create window 10 10 -anchor nw -window $f

45 set n 1
foreach {f1 f2 f3} $files {

    if {[file exists $f1]} {
50         set tmb1 [image create photo -file $f1]
        set btn1 [button $f.tmb$n -image $tmb1 -command "iat::app::contact_sheet_select $ns $f1"]
    } else {
        set btn1 [button $f.tmb$n -text X]
    }
55     incr n

    if {[file exists $f2]} {
        set tmb2 [image create photo -file $f2]
        set btn2 [button $f.tmb$n -image $tmb2 -command "iat::app::contact_sheet_select $ns $f2"]
60     } else {
        set btn2 [button $f.tmb$n -text X]
    }
    incr n

65     if {[file exists $f3]} {
        set tmb3 [image create photo -file $f3]
        set btn3 [button $f.tmb$n -image $tmb3 -command "iat::app::contact_sheet_select $ns $f3"]
    } else {
        set btn3 [button $f.tmb$n -text X]
70     }
    incr n

    grid $btn1 $btn2 $btn3 -padx 4 -pady 4
    #pack $btn

75 }

tkwait visibility $csf.canvas
set bbox [grid bbox $f 0 0]
set incr [lindex $bbox 3]
set width [winfo reqwidth $f]
80 set height [winfo reqheight $f]

```

Appendix 2

```

$csf.canvas config -scrollregion "0 0 $width [expr $height+50]"
$csf.canvas config -yscrollincrement 20
$csf.canvas config -width $width -height [expr $height+50]

5 )

proc iat::app::contact_sheet_select { ns tfile } {
    variable TRACE
    if ($TRACE) { puts "iat::app::contact_sheet_select: $ns $tfile" }

10     set tparts [file split [file rootname $tfile]]
    set iparts [lrange $tparts 0 [expr [llength $tparts]-4] ]
    #set ifile [file join $iparts]
    lappend iparts [lindex $tparts end].PNG
15     set path [eval "file join $iparts"]
    #puts "image file = $path"

    set app [app_new]
    $app configure -url "file:$path"

20 }

proc iat::app::app_make_svg { ns } {
25     variable TRACE
    if ($TRACE) { puts "iat::app::app_make_svg: $ns" }

    variable DEMO1
    variable SQRIMG
30     variable SERVER
    variable BATIK

    upvar #0 [join [list [namespace current] $ns image_canvas] ::] image_canvas
    upvar #0 [join [list [namespace current] $ns image_url] ::] image_url
35     upvar #0 [join [list [namespace current] $ns svg_pkg] ::] svg_pkg

    # current view...
    upvar #0 [join [list [namespace current] $ns entry_view] ::] entry_view
    set view_vals [$entry_view cget -values]
40     set view_text [lindex $view_vals [$entry_view getvalue]]

    set dtd "<!DOCTYPE svg PUBLIC "-//W3C//DTD SVG 20010904//EN"
    \"http://www.w3.org/TR/2001/REC-SVG-20010904/DTD/svg10.dtd\" \"[ <!ATTLIST svg xmlns:a3 CDATA #IMPLIED
a3:scriptImplementation CDATA #IMPLIED> <!ATTLIST script a3:scriptImplementation CDATA #IMPLIED> \]>\n"
45     set rvs [$image_canvas svg]
    #puts $rvs
    set bL [lindex $rvs 0]
    set bT [lindex $rvs 1]
50     set bR [lindex $rvs 2]
    set bB [lindex $rvs 3]
    set bColor [lindex $rvs 4]
    set imgx [lindex $rvs 5]
    set imgy [lindex $rvs 6]
55     set menu [lindex $rvs 7]
    set ants [lindex $rvs 8]

    if (![regexp (^file:) $image_url]) {
        regexp (^file:(. *)) $image_url m path
        set parts [file split $path]
    } else {
        return "ERROR in image_url"
    }

65     # Use to generate square output (for KA scale drag-and-drop)
    set recx $imgx
    set recy $imgy
    set handles ""
    if ($SQRIMG) {
70         if ($recx > $recy) {
            set recy $recx
        } else {
            set recx $recy
        }
    }

75     set bL 0; set bT 0; set bR 0; set bB 0
    set handles "onload=\"handleOnLoadScale(evt)\" onzoom=\"handleUpdateScale(evt)\"
onscroll=\"handleUpdateScale(evt)\" onresize=\"handleUpdateScale(evt)\"
    }
    if ($SERVER) {
80         set handles "onload=\"handleOnLoad(evt)\"
    }

```

Appendix 2

```

append handles " xmlns=\"http://www.w3.org/2000/svg\" xmlns:xlink=\"http://www.w3.org/1999/xlink\"
xmlns:a3=\"http://ns.adobe.com/AdobeSVGViewerExtensions/3.0/\" a3:scriptImplementation=\"Adobe\"

5   set svg ""

    set bL [expr round($imgx * $bL)]
    set bT [expr round($imgy * $bT)]
    set bR [expr round($imgx * $bR)]
    set bB [expr round($imgy * $bB)]

10   set alone "no"
    if {$svg_pkg} { set alone "yes" }
    append svg "<?xml version='1.0' standalone='$alone' ?>\n"
    append svg "$dtd"
15   #append svg "<svg width='[expr $imgx+$bL+$bR]' height='[expr $imgy+$bT+$bB]'\>\n"
    # previous lines didn't allow dynamic port changes...
    append svg "<svg viewBox='0 0 [expr $recx+$bL+$bR] [expr $recy+$bT+$bB]' preserveAspectRatio='xMinYMin'
$handles"
    #append svg "xmlns:xlink='http://www.w3c.org/1999/xlink' "
20   append svg ">\n"
    # metadata
    append svg "<metadata><![CDATA\[\n"
    append svg " <IAT>\n"
    append svg [$image_canvas annotations make all 3]
25   append svg " </IAT>\n"
    append svg "\\]\]></metadata>\n"

    if {$DEMO1} {
        append svg "<rect width='[expr $recx+$bL+$bR]' height='[expr $recy+$bT+$bB]' style='fill:white;
30   stroke:red; stroke-width:2px' />\n"
        append svg "<text x='$bL' y='$bT' style='font-size:32; text-anchor:start; fill:red'>N/A in IAT
Technology Evaluation</text>\n"
        append svg "</svg>\n"
        return $svg
35   }
    # javascript
    variable use_javascript_file
    if {$use_javascript_file} {
        set jsfile [file join . js4svg.js]
        if {[file exists $jsfile]} {
40           set fh [open $jsfile r]
            set js [read $fh]
            close $fh
            append svg $js
45         }
    } elseif {$DEMO1} {
        # don't include javascript...
    } else {
        append svg [iat::var_str_js4svg]
50   }
    append svg "<!-- END_JAVA -->\n"

    append svg "<rect width='[expr $recx+$bL+$bR]' height='[expr $recy+$bT+$bB]' style='fill:$bColor;
55   stroke:red; stroke-width:2px' />\n"
    #puts "exportImageAsSVG: annotationSource = $annotationSource"
    if {0} {
        set iatfile [lindex $parts end]
        set chnames [array names channelFileMap]
        set chnames [lsort -dictionary $chnames]
60       foreach chname $chnames {
            set endchfile [lindex [file split $channelFileMap($chname)] end]
            set display "none"
            if {$endchfile == $iatfile} { set display "inline" }
65       #puts "exportImageAsSVG add channel: $endchfile"
            append svg "<image id='$endchfile-channel' style='display:$display' x='$bL' y='$bT' width='[expr
$imgx]' height='[expr $imgy]' xlink:href='./$endchfile'\>\n"
            append svg "</image>\n"
        }
70   } elseif {$svg_pkg} {
        #puts "image: $path = [file size $path]"
        set input [open $path r]
        fconfigure $input -translation binary -encoding binary
        set img_str [base64::encode [read $input]]
75       close $input
        #puts $img_str

        append svg "<image id='default-channel' style='display:inline' x='$bL' y='$bT' width='[expr $imgx]'
height='[expr $imgy]'\n"
80       append svg "xlink:href=\"data:;base64,\n$img_str\">\n"
        append svg "</image>\n"

```

```

    } else {
        append svg "<image id='default-channel' style='display:inline' x='$bL' y='$bT' width='[expr $imgx]'
height='[expr $imgy]' xlink:href='../[lindex $parts end]'>\n"
        append svg "</image>\n"
5    }

    # stop and go buttons for server delivery...
    if ($SERVER) {
        set u [expr $recx/25]
        set v [expr $recx/50]
        set z [expr $recx/100]
        append svg "<rect x='[expr $bL+$v]' y='[expr $recy-$bB-$u]' width='[expr $u*6]' height='[expr $u]'
style='fill:white; stroke:white; stroke-width:$z' />\n"
        append svg "<rect id='updateStopButton' x='[expr $bL+$v]' y='[expr $recy-$bB-$u]' width='[expr $u]'
15 height='[expr $u]' style='fill:red; stroke:black; stroke-width:2px; visibility:inherit;'
onclick='antRefreshStop()' />\n"
        append svg "<polygon id='updateStartButton' points='[expr $bL+$v],[expr $recy-$bB] [expr
$bL+$v],[expr $recy-$bB-$u] [expr $bL+$v+$u],[expr $recy-$bB-$v]' style='fill:green; stroke:black;
stroke-width:2px; visibility:hidden;' onclick='antRefreshStart()' />\n"
        append svg "<text id='currentViewText' x='[expr $bL+$u+$u]' y='[expr $recy-$bB-$z]'
20 style='font-size:24;'> $view_text </text>\n"
    }

    append svg "<g id='SVGANTS'><!-- START_ANTS --->\n"
25    # context menu
    if ($BATIK) {
        # do not insert menu...
        append svg $ants
    } else {
        append svg $menu
        if (!$SERVER) {
            append svg $ants
        }
    }
35    append svg "</g><!-- END_ANTS --->\n"
    #append svg "<!-- END_ANTS --->\n"
    append svg "</svg>\n"
    #puts $svg
    #set fh [open $fileNameSVG w]
    #puts $fh $svg
    #close $fh

    #set antpath [file dirname $path]
    #append antpath "/update.xml"
    #puts "antpath = $antpath"
    #set fh [open $antpath w]
    #puts $fh "<g id='NEWSVGANTS'>\n"
    #puts $fh "$menu\n$ants"
    #puts $fh "</g>\n"
45    #close $fh

    # Generate sample html file from svg...
    #exportSVGDefaultHTMLPage [file root $fileNameImage].HTM [lindex [file split $fileNameSVG] end] $svg

55    return $svg
}

proc iat::app::app_export_ps { ns } {
    variable TRACE
60    if ($TRACE) { puts "iat::app::app_export_ps: $ns" }

    upvar #0 [join [list [namespace current] $ns image_canvas] ::] image_canvas
    upvar #0 [join [list [namespace current] $ns image_url] ::] image_url

65    if ([regexp {^file:} $image_url]) {
        regexp {^file:(.*)} $image_url m path
        set img_file [file rootname $path]
        append img_file "_x.ps"
        #puts "img_file = $img_file"
    } else {
70        return "ERROR in app_export_ps"
    }

    if ([file exists $img_file]) {
75        set choice [tk_messageBox \
            -title "Overwrite file?" \
            -message "Overwrite existing Postscript (.ps) file?" \
            -icon question \
            -type yesno \
            -default yes ]
80        if ($choice != "yes") { return }
    }

```

```

    }

    $image_canvas postscript $img_file
5 )

proc iat::app::app_export_image { ns } {
    variable TRACE
    if {$TRACE} { puts "iat::app::app_export_image: $ns" }
10
    upvar #0 [join [list [namespace current] $ns image_canvas] ::] image_canvas
    upvar #0 [join [list [namespace current] $ns image_url] ::] image_url

    if {[regexp (^file:) $image_url]} {
15
        regexp (^file:(.*)) $image_url m path
        set img_file [file rootname $path]
        append img_file "_CANVAS.jpg"
        #puts "img_file = $img_file"
    } else {
20
        return "ERROR in image_url"
    }

    if {[file exists $img_file]} {
        set choice [tk_messageBox \
25
            -title "Overwrite file?" \
            -message "Overwrite existing image (.jpg) file?" \
            -icon question \
            -type yesno \
            -default yes ]
30
        if {$choice != "yes"} { return }
    }

    set img [$image_canvas image]

35
    $img write $img_file -format JPEG
}

proc iat::app::app_export_svg { ns } {
40
    variable TRACE
    if {$TRACE} { puts "iat::app::app_export_svg: $ns" }

    variable DEMO1
    if {$DEMO1} {
45
        tk_messageBox -type ok -message "This option is not available in the IAT Technology Evaluation."
        return
    }

    upvar #0 [join [list [namespace current] $ns image_canvas] ::] image_canvas
50
    upvar #0 [join [list [namespace current] $ns image_url] ::] image_url

    if {[regexp (^file:) $image_url]} {
        regexp (^file:(.*)) $image_url m path
        set svg_file [file rootname $path]
        append svg_file ".svg"
55
        puts "svg_file = $svg_file"
    } else {
        return "ERROR in image_url"
    }

60
    if {[file exists $svg_file]} {
        set choice [tk_messageBox \
            -title "Overwrite file?" \
            -message "Overwrite existing SVG (.svg) file?" \
65
            -icon question \
            -type yesno \
            -default yes ]
        if {$choice != "yes"} { return }
    }

70
    set svg [app_make_svg $ns]
    puts $svg

    set fh [open $svg_file w]
75
    puts $fh $svg
    close $fh
}

80 proc iat::app::app_export_svgpkg { ns } {
    variable TRACE

```

Appendix 2

```

if ($TRACE) { puts "iat::app::app_export_svgpkg: $ns" }

variable DEMO1
if ($DEMO1) {
5   tk_messageBox -type ok -message "This option is not available in the IAT Technology Evaluation."
    return
}

upvar #0 [join [list [namespace current] $ns image_canvas] ::] image_canvas
10 upvar #0 [join [list [namespace current] $ns image_url] ::] image_url
upvar #0 [join [list [namespace current] $ns svg_pkg] ::] svg_pkg

if ([regexp (^file:) $image_url]) {
    regexp (^file:(. *)) $image_url m path
15   set svg_file [file rootname $path]
    append svg_file "_pkg.svg"
    #puts "  svg_file = $svg_file"
} else {
20   return "ERROR in image_url"
}

if ([file exists $svg_file]) {
    set choice [tk_messageBox \
25       -title "Overwrite file?" \
        -message "Overwrite existing SVG package (_pkg.svg) file?" \
        -icon question \
        -type yesno \
        -default yes ]
    if ($choice != "yes") { return }
30 }

set svg_pkg 1
set svg [app_make_svg $ns]
set svg_pkg 0
35 #puts $svg

set fh [open $svg_file w]
puts $fh $svg
close $fh
40 }

proc iat::app::app_export_html_default { ns } {
    variable TRACE
45   if (1) { puts "iat::app::app_export_html_default: $ns" }

    variable DEMO1
    if ($DEMO1) {
50       tk_messageBox -type ok -message "This option is not available in the IAT Technology Evaluation."
        return
    }

    upvar #0 [join [list [namespace current] $ns image_canvas] ::] image_canvas
    upvar #0 [join [list [namespace current] $ns image_url] ::] image_url
55   upvar #0 [join [list [namespace current] $ns svg_pkg] ::] svg_pkg

    if ([regexp (^file:) $image_url]) {
        regexp (^file:(. *)) $image_url m path
        # read only...
        set svg_file [file rootname $path]
        append svg_file ".svg"
        puts "  svg_file = $svg_file"
        # write only...
        set html_file [file rootname $path]
65       append html_file "_default.htm"
        puts "  html_file = $html_file"
    } else {
        return "ERROR in image_url"
    }
70 }

if ([file exists $html_file]) {
    set choice [tk_messageBox \
75       -title "Overwrite file?" \
        -message "Overwrite existing HTML file (_default.htm) file?" \
        -icon question \
        -type yesno \
        -default yes ]
    if ($choice != "yes") { return }
80 }

set svg [$image_canvas annotations make all 3]

```

```

#puts $svg
set orders [list]
set state "NONE"
set lines [split $svg "\n"]
5  foreach line $lines {
    if {[regexp {^\\s*</roi>} $line]} {
        set state NONE
    }
    if {[regexp {^\\s*<roi } $line]} {
10      regexp {^\\s*<roi\\s+.*order=\\s*(\\S+)\\s*} $line match order
        lappend orders $order
        #puts " order = $order"
        set state ROI
    }
15  }

set orders [lsort -dictionary $orders]
set tmps [list]
foreach order $orders {
20   lappend tmps "\\$order\\"
}
set arr "\\[[join $tmps ","]\\]"
puts " arr = $arr"

25  set html "<html>\\n"

# javascript
variable use_javascript_file
if {$use_javascript_file} {
30   set jsfile [file join . js4html.js]
    if {[file exists $jsfile]} {
        set fh [open $jsfile r]
        set js [read $fh]
        close $fh
35   append html $js
    }
} elseif {$DEMO1} {
    # don't include javascript...
} else {
40   append html [iat::var_str_js4html]
}

set ants_html ""

45  append html "<head>"
    append html "</head>"
    append html "<body>"
    append html "<table width='100%' height='100%' border='1'>\\n"
    append html "<tr width='100%'>\\n"
50   append html "<td width='70%'><embed width='100%' height='100%' src='$svg_file' name='image'
        puginpage='http://www.adobe.com/svg/'></td>\\n"
    append html "<td width='30%'>\\n"
    append html "<form name='hilite_form'>\\n <table width='100%' height='100%' valign='TOP' border='1'>\\n"
    append html " <tr><td><input type='button' value='Toggle MouseOvers'
55  onclick='\\window.antToggleMouseOverAll($arr,1);\\'></td></tr>\\n"
    append html " <tr><td><input type='button' value='Hide All'
        onclick='\\window.antSetShowAll($arr,false,1);\\'></td></tr>\\n"
    append html " <tr><td><input type='button' value='Show All'
        onclick='\\window.antSetShowAll($arr,true,1);\\'></td></tr>\\n"
60   append html " <tr><td><br>ANNOTATIONS</td></tr>\\n"
    append html $ants_html
    #append html "</td>\\n</tr>\\n"
    append html " <tr><td><br>CAPTION</td></tr>\\n"
    append html " <tr width='100%'><td width='100%' height='100%' align='LEFT' valign='TOP'><p
65  id='caption'>no caption</p></td></tr>\\n"

    append html " </table>\\n</form>\\n"
    append html "</td></tr></table>\\n"
    append html "</body>\\n"
70   append html "</html>"
    #puts $html

    set fh [open $html_file w]
    puts $fh $html
75   close $fh

    return
}

80 proc iat::app::app_export_html_old_old_old {} {

```



```

set lines [split $svg "\n"]
set iatimage ""
set iatchannels [list]
set iatviews [list]
5 set order ""
set symbol ""
set label ""
set caption ""
set IMG 0
10 set SYM 0
set ALL 0
set OK 0
foreach line $lines {
    #puts "line: $line"
    15 if {[regexp (^s*<image\s+id='(\S*)-channel') $line match xxx ]} {
        lappend iatchannels $xxx
    }
    if {[regexp (^s*<image\s+id='(\S*)-channel'..'display:inline') $line match xxx ]} {
        lappend iatimage $xxx
    }
    20 # svg symbol contains iat symbol label and captioin for each order
    # note: the dangers of a polluted namespace...
    if {[regexp (^s*</symbol>) $line ]} {
        #puts "save symbol: $order, $symbol, $label, $caption"
        25 set txtdatas($order) [list symbol $symbol label $label caption $caption]
        set order ""
        set symbol ""
        set label ""
        set caption ""
        30 set SYM 0
    }
    if ($SYM) {
        if {[regexp (<symbol>\s*(\S*)\s*</symbol>) $line match xxx ]} {
            set symbol $xxx
            #puts "html found symbol: $symbol"
        }
        if {[regexp (<label>\s*(.*)\s*</label>) $line match xxx ]} {
            set label $xxx
            #puts "html found label: $label"
        }
        40 if {[regexp (<caption>\s*(.*)\s*</caption>) $line match xxx ]} {
            set caption $xxx
            #puts "html found caption: $caption"
        }
    }
    45 if {[regexp (^s*<symbol\s+id='(\S+)') $line match xxx ]} { set order $xxx; set SYM 1 }
    # Annotation data taken from All view
    if {[regexp (<!--\s*end\s+All-view) $line ]} { set ALL 0 }
    if ($ALL) {
        50 if {[regexp (<g\s+id='ALL-(\S+)') $line match xxx ]} {
            set order $xxx
            #puts "html order = $order"
            set OK 1
        }
    }
    55 if ($OK) {
        if ([info exists txtdata]) { unset txtdata }
        regexp (^(\S+;)) $order match okey
        if ([info exists txtdatas($okey)]) {
            60 set lst $txtdatas($okey)
            array set txtdata $txtdatas($okey)
        } else {
            set lst [list symbol none label none caption none]
            array set txtdata $lst
        }
        65 #puts "load symbol = $lst"
        set str " <tr width='100%'><td width='100%' align='LEFT'><input type='checkbox' value=''
onclick=\"setAnnotationVisibility(this,'$order')\" checked > <a
href=\"javascript:showCaption('$txtdata(caption)')\">$okey $txtdata(label) </a> </td></tr>\n"
        70 append ants_html $str
        #puts "html ant: $str"
        set OK 0
    }
    if {[regexp (<g\s+id='ALL-view') $line ]} { set ALL 1 }
    75 # All miat view plus other views
    if {[regexp (<g\s+id='(\S+)-view') $line match xxx ]} { lappend iatviews $xxx }
}

80 set html "<html>\n"
# file that contains javascript...

```

```

set jsfile [file join $iatPath js4html.js]
set fh [open $jsfile r]
append html "<script language='JavaScript1.2'>\n"
append html "<!--\n"
5 append html [read $fh]
append html "\ncurrent_channel = '$iatimage'\n"
append html "// -->\n"
append html "</script>\n"
close $fh

10
append html "<head>"
append html "</head>"
append html "<body>"
append html "<table width='100%' height='100%' border='1'>\n"
15 append html "<tr width='100%'>\n"
append html "<td width='70%'><embed width='100%' height='100%' src='$fileNameSVG' name='image'
puginpage='http://www.adobe.com/svg/viewer/install/'></td>\n"
append html "<td width='30%'>\n"
append html "<form name='hilite_form'>\n <table width='100%' height='100%' valign='TOP' border='1'>\n"
20 append html " <tr><td><input type='checkbox' value=''
onclick='toggleMouseOvers(this)'>ROLLOVERS</td></tr>\n"

append html " <tr><td><br>CHANNELS</td></tr>\n"
foreach iatchannel $iatchannels {
25   set checked ""
   if {$iatchannel == $iatimage} { set checked "checked" }
   append html " <tr width='100%'><td width='100%' align='LEFT'><input type='radio'
name='channel-group' value='$iatchannel' onclick='\"setChannel(this,\"$iatchannel')\" $checked > $iatchannel
</td></tr>\n"
30 }

append html " <tr><td><br>VIEWS</td></tr>\n"
foreach iatview $iatviews {
   set checked ""
35   if {$iatview == "ALL"} { set checked "checked" }
   append html " <tr width='100%'><td width='100%' align='LEFT'><input type='radio' name='view-group'
value='$iatview' onclick='\"setViewVisibility(this,\"$iatview')\" $checked > $iatview </td></tr>\n"
}

40 append html " <tr><td><br>ANNOTATIONS</td></tr>\n"
append html $ants_html
#append html "</td>\n</tr>\n"
append html " <tr><td><br>CAPTION</td></tr>\n"
append html " <tr width='100%'><td width='100%' height='100%' align='LEFT' valign='TOP'><p
45 id='caption'>no caption</p></td></tr>\n"

append html " </table>\n</form>\n"
append html "</td></tr></table>\n"
append html "</body>\n"
50 append html "</html>"
#puts $html

set fh [open $fileNameHTML w]
puts $fh $html
55 close $fh
}

proc iat::app::scale_image { ns } {
60   upvar #0 [join [list [namespace current] $ns image_canvas] ::] image_canvas
   upvar #0 [join [list [namespace current] $ns image_scale] ::] image_scale

   $image_canvas configure -scale $image_scale

65   return 1
}

proc iat::app::toggle_toolbar { ns p tb tbs var } {
70   variable TRACE
   if ($TRACE) { puts "iat::app::toggle_toolbar: $ns $p $tb { $tbs } $var" }

   set r [set $var]
   #puts "$var = $r"

75   if ($r == 0) {
     foreach s $tbs {
       #puts "forget: $p.$tb.$s"
       pack forget $p.$tb.$s
80     }
     frame $p.$tb.xox

```

```

    pack $p.$tb.xxx
  ) else {
    destroy $p.$tb.xxx
    foreach s $tbs {
5      #puts "    packing: $p.$tb.$s"
      pack $p.$tb.$s -side left -pady 2 -expand 0
    }
  }
10 }

proc iat::app::edit_create { ns kind } {

  variable SERVER_STATE

15   upvar #0 [join [list [namespace current] $ns image_url] ::] image_url
   upvar #0 [join [list [namespace current] $ns image_canvas] ::] image_canvas
   upvar #0 [join [list [namespace current] $ns status_label] ::] status_label

   set SERVER_STATE WAIT
20   $image_canvas create roi $kind
   set SERVER_STATE GO

}

25 proc iat::app::edit_select { ns mode } {

   upvar #0 [join [list [namespace current] $ns image_canvas] ::] image_canvas

   $image_canvas configure -select $mode
30 }

proc iat::app::edit_create_pointer { ns num } {

35   upvar #0 [join [list [namespace current] $ns image_url] ::] image_url
   upvar #0 [join [list [namespace current] $ns image_canvas] ::] image_canvas
   upvar #0 [join [list [namespace current] $ns status_label] ::] status_label

   $image_canvas create pointer $num
40 }

proc iat::app::edit_ptr_style { ns } {
   upvar #0 [join [list [namespace current] $ns image_canvas] ::] image_canvas
45   $image_canvas pointer style
}

proc iat::app::edit_ptr_pin { ns } {
   upvar #0 [join [list [namespace current] $ns image_canvas] ::] image_canvas
50   $image_canvas pointer pin
}

proc iat::app::edit_ptr_symbol { ns } {
   upvar #0 [join [list [namespace current] $ns image_canvas] ::] image_canvas
55   $image_canvas pointer symbol
}

proc iat::app::edit_ant_color { ns } {
60   upvar #0 [join [list [namespace current] $ns image_canvas] ::] image_canvas
   set color [$image_canvas active get color]
   set color [tk_chooseColor -initialcolor $color]
   $image_canvas active set color $color
}

65 proc iat::app::edit_ant_data { ns } {
  variable DEMO1

   upvar #0 [join [list [namespace current] $ns image_canvas] ::] image_canvas
70   upvar #0 [join [list [namespace current] $ns status_label] ::] status_label
   upvar #0 [join [list [namespace current] $ns entry_code] ::] entry_code
   upvar #0 [join [list [namespace current] $ns entry_symbol] ::] entry_symbol
   upvar #0 [join [list [namespace current] $ns entry_label] ::] entry_label

75   variable DEMO1
   if ($DEMO1) {
     tk_messageBox -type ok -message "This option is not available in the IAT Technology Evaluation."
     return
   }

80   set lst [iat::dialog::dialog_edit_data]

```

```

#puts " lst = $lst"
if {$lst == {}} { return }

$entry_code delete 0 end
$entry_symbol delete 0 end
$entry_label delete 0 end

$entry_code insert 0 [lindex $lst 0]
$entry_symbol insert 0 [lindex $lst 1]
10 $entry_label insert 0 [lindex $lst 2]
}

proc iat::app::edit_move { ns } {
15     upvar #0 [join [list [namespace current] $ns image_canvas] ::] image_canvas

    $image_canvas move active

20 }

proc iat::app::edit_ant_copy { ns } {
    variable tmp_ant_copy
25     upvar #0 [join [list [namespace current] $ns image_canvas] ::] image_canvas

    set tmp_ant_copy [$image_canvas annotations make active 0]
    #puts " tmp_ant_copy\n$tmp_ant_copy"
30 }

proc iat::app::edit_ant_paste { ns } {
35     variable tmp_ant_copy

    upvar #0 [join [list [namespace current] $ns image_canvas] ::] image_canvas

    $image_canvas annotations paste $tmp_ant_copy
40 }

proc iat::app::edit_ant_cut { ns } {
45     variable SERVER
    variable SERVER_STATE
    upvar #0 [join [list [namespace current] $ns image_canvas] ::] image_canvas

    set SERVER_STATE WAIT
    edit_ant_copy $ns
    $image_canvas delete active
    set SERVER_STATE GO

50     if {$SERVER} {
        url_save_server $ns
55     }
}

proc iat::app::edit_set_view { ns } {
60     #puts "iat::app::edit_set_view: $ns"

    upvar #0 [join [list [namespace current] $ns image_canvas] ::] image_canvas
    upvar #0 [join [list [namespace current] $ns entry_view] ::] entry_view

65     set vals [$entry_view cget -values]
    $image_canvas active set view [lindex $vals [$entry_view getvalue]]
}

proc iat::app::edit_update_view { ns {ivwIN ""} } {
70     #puts "iat::app::edit_update_view: $ns"

    upvar #0 [join [list [namespace current] $ns image_canvas] ::] image_canvas
    upvar #0 [join [list [namespace current] $ns entry_view] ::] entry_view

75     set vals [$entry_view cget -values]
    set val [lindex $vals [$entry_view getvalue]]

    if {$ivwIN == ""} {
    } else {
80         set ret 1
        set ivws [split $ivwIN]

```

```

    foreach ivw $ivws {
        if {[lsearch $vals $iw] < 0} {
            set ret 0
            break
        }
    }
    if ($ret) { return }
}

10 #puts "VIEW VALUE = $val"
    set newvals [split [$image_canvas active update view]]
    if {$newvals == [list]} { return }
    set vals [concat [list ALL NONE] $newvals]
    $entry_view configure -values $vals
15 set idx [lsearch -exact $vals $val]
    if {$idx < 0} {
        $entry_view setvalue first
    } else {
        $entry_view setvalue @$idx
20 }

    #edit_set_view $ns
}

25 proc iat::app::edit_set_inview { ns } {

    upvar #0 [join [list [namespace current] $ns image_canvas] ::] image_canvas
    upvar #0 [join [list [namespace current] $ns entry_inview] ::] entry_inview
30 $image_canvas active set inview [$entry_inview get]
}

proc iat::app::edit_set_symbol { ns } {
35 upvar #0 [join [list [namespace current] $ns image_canvas] ::] image_canvas
    upvar #0 [join [list [namespace current] $ns entry_symbol] ::] entry_symbol

    $image_canvas active set symbol [$entry_symbol get]
40 }

proc iat::app::edit_set_label { ns } {
45 upvar #0 [join [list [namespace current] $ns image_canvas] ::] image_canvas
    upvar #0 [join [list [namespace current] $ns entry_label] ::] entry_label

    $image_canvas active set label [$entry_label get]
50 }

proc iat::app::edit_set_cs_class { ns } {
55 upvar #0 [join [list [namespace current] $ns image_canvas] ::] image_canvas
    upvar #0 [join [list [namespace current] $ns entry_cs_class] ::] entry_cs_class

    $image_canvas active set cs_class [$entry_cs_class get]
60 }

proc iat::app::edit_set_cs_tumor { ns } {
65 upvar #0 [join [list [namespace current] $ns image_canvas] ::] image_canvas
    upvar #0 [join [list [namespace current] $ns entry_cs_tumor] ::] entry_cs_tumor

    $image_canvas active set cs_tumor [$entry_cs_tumor get]
70 }

proc iat::app::edit_set_cs_node { ns } {
75 upvar #0 [join [list [namespace current] $ns image_canvas] ::] image_canvas
    upvar #0 [join [list [namespace current] $ns entry_cs_node] ::] entry_cs_node

    $image_canvas active set cs_node [$entry_cs_node get]
80 }

proc iat::app::edit_set_cs_metastasis { ns } {
    upvar #0 [join [list [namespace current] $ns image_canvas] ::] image_canvas

```

```

upvar #0 [join [list [namespace current] $ns entry_cs_metastasis] ::] entry_cs_metastasis

$image_canvas active set cs_metastasis [$entry_cs_metastasis get]

5 )

proc iat::app::edit_set_cs_note { ns } {

    upvar #0 [join [list [namespace current] $ns image_canvas] ::] image_canvas
10    upvar #0 [join [list [namespace current] $ns entry_cs_note] ::] entry_cs_note

    $image_canvas active set cs_note [$entry_cs_note get]

    )
15
proc iat::app::handle_ant_select { ns } {
    variable TRACE
    if {$TRACE} { puts "iat::app::handle_ant_select: $ns" }

20    upvar #0 [join [list [namespace current] $ns image_canvas] ::] image_canvas
    upvar #0 [join [list [namespace current] $ns entry_inview] ::] entry_inview
    upvar #0 [join [list [namespace current] $ns entry_code] ::] entry_code
    upvar #0 [join [list [namespace current] $ns entry_symbol] ::] entry_symbol
    upvar #0 [join [list [namespace current] $ns entry_label] ::] entry_label
25    upvar #0 [join [list [namespace current] $ns entry_caption] ::] entry_caption

    upvar #0 [join [list [namespace current] $ns entry_cs_class] ::] entry_cs_class
    upvar #0 [join [list [namespace current] $ns entry_cs_tumor] ::] entry_cs_tumor
    upvar #0 [join [list [namespace current] $ns entry_cs_node] ::] entry_cs_node
30    upvar #0 [join [list [namespace current] $ns entry_cs_metastasis] ::] entry_cs_metastasis
    upvar #0 [join [list [namespace current] $ns entry_cs_note] ::] entry_cs_note

    $entry_inview delete 0 end
    $entry_code delete 0 end
35    $entry_symbol delete 0 end
    $entry_label delete 0 end
    $entry_caption delete 0.1 end

    $entry_cs_class delete 0 end
    $entry_cs_tumor delete 0 end
40    $entry_cs_node delete 0 end
    $entry_cs_metastasis delete 0 end
    $entry_cs_note delete 0 end

45    set ivw [$image_canvas active get inview]
    set cod [$image_canvas active get code]
    set sym [$image_canvas active get symbol]
    set lbl [$image_canvas active get label]
    set cap [$image_canvas active get caption]
50

    #puts "    symbol = $sym"
    #puts "    label = $lbl"
    #puts "    caption = $cap"

55    set cs_class [$image_canvas active get cs_class]
    set cs_tumor [$image_canvas active get cs_tumor]
    set cs_node [$image_canvas active get cs_node]
    set cs_metastasis [$image_canvas active get cs_metastasis]
    set cs_note [$image_canvas active get cs_note]
60

    $entry_inview insert 0 $ivw
    $entry_code insert 0 $cod
    $entry_symbol insert 0 $sym
    $entry_label insert 0 $lbl
65    $entry_caption insert 0.1 $cap

    $entry_cs_class insert 0 $cs_class
    $entry_cs_tumor insert 0 $cs_tumor
    $entry_cs_node insert 0 $cs_node
70    $entry_cs_metastasis insert 0 $cs_metastasis
    $entry_cs_note insert 0 $cs_note

    )

75 proc iat::app::handle_ant_deselect { ns } {
    variable TRACE
    if {$TRACE} { puts "iat::app::handle_ant_deselect: $ns" }

    upvar #0 [join [list [namespace current] $ns image_canvas] ::] image_canvas
80    upvar #0 [join [list [namespace current] $ns entry_inview] ::] entry_inview
    upvar #0 [join [list [namespace current] $ns entry_code] ::] entry_code

```

Appendix 2

```

upvar #0 [join [list [namespace current] $ns entry_symbol] ::] entry_symbol
upvar #0 [join [list [namespace current] $ns entry_label] ::] entry_label
upvar #0 [join [list [namespace current] $ns entry_caption] ::] entry_caption

5 upvar #0 [join [list [namespace current] $ns entry_cs_class] ::] entry_cs_class
upvar #0 [join [list [namespace current] $ns entry_cs_tumor] ::] entry_cs_tumor
upvar #0 [join [list [namespace current] $ns entry_cs_node] ::] entry_cs_node
upvar #0 [join [list [namespace current] $ns entry_cs_metastasis] ::] entry_cs_metastasis
10 upvar #0 [join [list [namespace current] $ns entry_cs_note] ::] entry_cs_note

set ivw [string trim [$entry_inview get]]
set cod [string trim [$entry_code get]]
set sym [string trim [$entry_symbol get]]
set lbl [string trim [$entry_label get]]
15 set cap [string trim [$entry_caption get 0.1 end]]

#puts " symbol = $sym"
#puts " label = $lbl"
#puts " caption = $cap"

20 set cs_class [string trim [$entry_cs_class get]]
set cs_tumor [string trim [$entry_cs_tumor get]]
set cs_node [string trim [$entry_cs_node get]]
set cs_metastasis [string trim [$entry_cs_metastasis get]]
25 set cs_note [string trim [$entry_cs_note get]]

if {$iwv != ""} { $image_canvas active set inview $iwv }
if {$cod != ""} { $image_canvas active set code $cod }
if {$sym != ""} { $image_canvas active set symbol $sym }
30 if {$lbl != ""} { $image_canvas active set label $lbl }
if {$cap != ""} { $image_canvas active set caption $cap }

if {$cs_class != ""} { $image_canvas active set cs_class $cs_class }
if {$cs_tumor != ""} { $image_canvas active set cs_tumor $cs_tumor }
35 if {$cs_node != ""} { $image_canvas active set cs_node $cs_node }
if {$cs_metastasis != ""} { $image_canvas active set cs_metastasis $cs_metastasis }
if {$cs_note != ""} { $image_canvas active set cs_note $cs_note }

$entry_inview delete 0 end
40 $entry_code delete 0 end
$entry_symbol delete 0 end
$entry_label delete 0 end
$entry_caption delete 0.1 end

45 $entry_cs_class delete 0 end
$entry_cs_tumor delete 0 end
$entry_cs_node delete 0 end
$entry_cs_metastasis delete 0 end
$entry_cs_note delete 0 end
50

edit_update_view $ns $iwv
)

55 proc iat::app::dialog_groups { ns } {
variable DEMO1

upvar #0 [join [list [namespace current] $ns image_url] ::] image_url
upvar #0 [join [list [namespace current] $ns image_canvas] ::] image_canvas
60

variable DEMO1
if {$DEMO1} {
tk_messageBox -type ok -message "This option is not available in the IAT Technology Evaluation."
return
65 }

set ants [$image_canvas cget -annotations]
set rv [iat::dialog::dialog_edit_groups $ants]
)
70

proc iat::app::dialog_borders { ns } {

upvar #0 [join [list [namespace current] $ns image_url] ::] image_url
upvar #0 [join [list [namespace current] $ns image_canvas] ::] image_canvas
75

set borders [$image_canvas cget -borders]
#puts "borders = $borders"
set newborders [iat::dialog::dialog_edit_borders $borders]
if {$newborders == {}} { return }
80 $image_canvas configure -borders $newborders
)

```

Appendix :

```

proc iat::app::app_splash { ns } {
    variable TRACE
    if ($TRACE) { puts "iat::app::app_splash: $ns" }
    iat::dialog::dialog_doc "MIAT Technology Evaluation" [iat::var_str_splash]
5 }

proc iat::app::help_about { ns } {
    variable TRACE
    if ($TRACE) { puts "iat::app::help_about: $ns" }
10
    variable version

    set str ""
    append str "Electronic Medical Education Resource Group (EMERG)\n"
15 append str "Medical Image Annotation Tool (MIAT or IAT v$version)\n"
    append str "(c) 2001, 2002 University of Utah, SLC UT\n\n"
    append str "Contacts\n"
    append str "Director: patricia.goede@hsc.utah.edu\n"
    append str "Software: jason.lauman@hsc.utah.edu\n"
20
    tk_messageBox -title "About IAT v$version" -message $str
}

25 proc iat::app::help_todo { ns } {
    variable TRACE
    if ($TRACE) { puts "iat::app::help_todo: $ns" }
    iat::dialog::dialog_doc "IAT Documentation: To Do" [iat::var_str_todo]
}
30

proc iat::app::show_console { ns } {
    variable TRACE
    if ($TRACE) { puts "iat::app::show_console: $ns" }
    console show
35 }

proc iat::app::dump_ants { ns } {
    variable TRACE
    if ($TRACE) { puts "iat::app::dump_ants: $ns" }
40 upvar #0 [join [list [namespace current] $ns image_canvas] ::] image_canvas
    $image_canvas dump annotations 0
}

proc iat::app::dump_svg { ns } {
45 variable TRACE
    if ($TRACE) { puts "iat::app::dump_svg: $ns" }
    upvar #0 [join [list [namespace current] $ns image_canvas] ::] image_canvas
    $image_canvas dump svg
}
50

proc iat::app::dump_keys { ns } {
    variable TRACE
    if ($TRACE) { puts "iat::app::dump_keys: $ns" }
    upvar #0 [join [list [namespace current] $ns image_canvas] ::] image_canvas
55 $image_canvas dump keys
}

proc iat::app::debug_canvas {} {
    variable imageCanvas
60 $imageCanvas dump
}

iat.canvas.txt
# Copyright (c) 2001, University of Utah
# All rights reserved.
65 #
# iat.canvas.tcl

#package provide iat.canvas 0.2

70 namespace eval iat::canvas {

    variable TRACE 0
    variable id 0
    variable sizes [list 25 50 100 200 400]
75 variable point [list 0 0]
    variable ptnum ""
    variable vertn ""
    variable ptrmode "single"

80 }

```



```

proc iat::canvas::proc { cname cmd args } {
    variable TRACE
    if ($TRACE) { puts "iat::canvas::proc: $cname $cmd $args" }

5   upvar #0 [join [list [namespace current] $cname state] ::] state
    upvar #0 [join [list [namespace current] $cname status_label] ::] status_label
    upvar #0 [join [list [namespace current] $cname callback_select] ::] callback_select
    upvar #0 [join [list [namespace current] $cname callback_deselect] ::] callback_deselect
    upvar #0 [join [list [namespace current] $cname callback_deselect_server] ::] callback_deselect_server
10   upvar #0 [join [list [namespace current] $cname annotations] ::] annotations

    # end create if call from app...
    if {$state == "CREATE"} {
15     ant_create_end $cname 0 0
    }

    switch $cmd {
        "configure" {
20         foreach {key value} $args {
            switch -- $key {
                "-file" { set_file $cname $value }
                "-image" { set_image $cname $value }
                "-scale" { set_scale $cname $value }
25         "-borders" { set_borders $cname $value }
                    "-status" { set status_label $value }
                    "-select" { set_select_mode $cname $value }
                    "-callbackselect" { set callback_select $value }
                    "-callbackdeselect" { set callback_deselect $value }
30         "-callbackserver" { set callback_deselect_server $value }
            }
        }
    }

    "cget" {
35     #puts "proc = cget: $args"
        switch -- [lindex $args 0] {
            "-borders" { return [get_borders $cname] }
            "-annotations" { return $annotations }
        }
    }

40   "begin" {
        $annotations begin [lindex $args 0]
    }

    "end" {
45     # do nothing for now
    }

    "active" {
        set rv [$annotations $args]
        return $rv
50     }

    "annotations" {
        switch -- [lindex $args 0] {
            "make" {
55         # arg 2 is indent level
            ant_deselect $cname
            set str [make_cmds $cname [lindex $args 2]]
            append str [$annotations make [lindex $args 1] [expr [lindex $args 2]]]
            return $str
        }

            "parse" {
60         $annotations parse [lindex $args 1]
        }

            "read_cmds" {
            return [ant_read_cmds $cname [lindex $args 1]]
65         }

            "paste" {
                click_reset $cname
                $annotations parse [lindex $args 1]
                $annotations draw all
70         }
        }
    }

    if {$state == "THUMB"} {
        click_reset_thumbnail $cname
    } else {
75     click_reset $cname
    }
}

"borders" {
    set_borders $cname $args
80 }

"close" {

```

Appendix 2

```

        return [close $cname]
    }
    "create" {
        foreach {key value} $args {
5         switch -- [lindex $args 0] {
            "roi" { return [tool_create_start $cname $value] }
            "pointer" { return [ant_create_pointer_start $cname $value] }
            "symbol" { return [ant_create_symbol $cname] }
        }
10    }
    "delete" {
        switch -- [lindex $args 0] {
15         "symbol" { return [ant_delete_symbol $cname] }
            "active" { return [ant_delete $cname] }
        }
    }
    "destroy" {
        return [widget_destroy $cname]
20    }
    "image" {
        return [ant_make_image $cname]
    }
    "make_cmds" {
        return [ant_make_cmds $cname]
25    }
    "move" {
        switch -- [lindex $args 0] {
30         "active" { return [ant_move $cname] }
        }
    }
    "redraw" {
        return [redraw_image $cname]
    }
35    "postscript" {
        return [ant_make_ps $cname [lindex $args 0]]
    }
    "pointer" {
        switch -- [lindex $args 0] {
40         "style" { return [ant_ptr_style $cname] }
            "pin" { return [ant_ptr_pin $cname] }
            "symbol" { return [ant_ptr_symbol $cname] }
        }
    }
45    "svg" {
        return [ant_make_svg $cname]
    }
    "dump" {
        switch -- [lindex $args 0] {
50         "annotations" { return [dump_annotations $cname] }
            "keys" { return [dump_keys $cname] }
            "svg" { return [dump_svg $cname] }
        }
    }
55    default {
    }

    )
60    return ""
}

65 proc iat::canvas::create { path } {
    variable TRACE
    if ($TRACE) { puts "iat::canvas::create: $path" }
    variable id
    variable sizes
70
    if ($path == ".") { set path "" }
    set wid [incr id]
    set w [ScrolledWindow $path.w$wid -relief sunken -borderwidth 2]
    pack $w -side top -anchor nw -fill both -expand yes
75    set path $w

    set f [ScrollableFrame [$path getframe].f -areawidth 0 -areaheight 0]
    pack $f -side top -anchor nw -fill both -expand yes
    set path $f
80

    set c [canvas [$path getframe].c -width 2 -height 2 -borderwidth 2 -background gray]

```

```

$w setwidget $f

pack $c -anchor nw -fill both -expand yes

5   set ns [namespace current]::canvas$wid
   namespace eval $ns {
       variable widget
       variable canvas
       variable state NONE
10   variable select_mode annotation
       variable filename
       variable images
       variable image ""
       variable annotations
15   variable percent 100
       variable borderL 0.005
       variable borderT 0.005
       variable borderR 0.005
       variable borderB 0.005
20   variable borderColor black

       variable status_label ""
       variable callback_select "noop"
       variable callback_deselect "noop"
25   variable callback_deselect_server "noop"

       foreach size $iat::canvas::sizes { set images($size) "" }

   )

30   upvar #0 [join [list $ns widget] ::] widget
   upvar #0 [join [list $ns canvas] ::] canvas
   upvar #0 [join [list $ns annotations] ::] annotations

   set widget $w
   set canvas $c
35   set annotations [iat::ant::create -canvas $c -cmdcanvas [namespace current]::canvas$wid ]
   #puts " annotations = $annotations"

   set wcmd "proc [namespace current]::canvas$wid { cmd args } {eval [namespace current]::proc
40 canvas$wid \$cmd \$args}"
   namespace eval :: $wcmd

   # default behavior it to pan it...
   #bind $c <ButtonPress-1> "[namespace current]::toolStartPan $f $W %x %y"
45   #bind $c <Button1-Motion> "[namespace current]::toolDoPan $f $W %x %y"

   return [namespace current]::canvas$wid
}

50 proc iat::canvas::thumbnail { path } {
   variable TRACE
   if ($TRACE) { puts "iat::canvas::thumbnail: $path" }
   variable id
   variable sizes

55   if ($path == ".") { set path "" }
   set wid [incr id]

   set w [frame $path.w$wid]
60   pack $w -side top -anchor nw -fill both -expand yes
   set path $w

   set c [canvas $path.c -width 2 -height 2 -borderwidth 2 -background gray]
   pack $c -anchor nw -fill both -expand yes

65   set l [label $path.l -text ""]
   pack $l -anchor nw -fill x -expand yes

   set ns [namespace current]::canvas$wid
70   namespace eval $ns {
       variable widget
       variable canvas
       variable state NONE
       variable select_mode annotation
75   variable filename
       variable images
       variable image ""
       variable annotations
       variable percent 100
       variable borderL 0.10
80   variable borderT 0.10

```

```

variable borderR 0.10
variable borderB 0.10
variable borderColor red

5   variable status_label ""
    variable callback_select "noop"
    variable callback_deselect "noop"
    variable callback_deselect_server "noop"

10  foreach size $iat::canvas::sizes { set images($size) "" }

    }
    upvar #0 [join [list $ns widget] ::] widget
    upvar #0 [join [list $ns canvas] ::] canvas
15  upvar #0 [join [list $ns state] ::] state
    upvar #0 [join [list $ns status_label] ::] status_label
    upvar #0 [join [list $ns annotations] ::] annotations

    set widget $w
20  set canvas $c
    set status_label $l
    set annotations [iat::ant::create -canvas $c -cmdcanvas [namespace current]::canvas$wid ]
    #puts " annotations = $annotations"

25  set wcmd "proc [namespace current]::canvas$wid { cmd args } {eval [namespace current]::proc canvas$wid
    \ $cmd \ $args}"
    namespace eval :: $wcmd

    # default behavior it to pan it...
30  #bind $c <ButtonPress-1> "[namespace current]::toolStartPan $f %W %x %y"
    #bind $c <Button1-Motion> "[namespace current]::toolDoPan $f %W %x %y"

    #click_reset_thumbnail canvas$wid
    set state THUMB

35  return [namespace current]::canvas$wid
    }

proc iat::canvas::widget_destroy { ns } {
40  variable TRACE
    if {$TRACE} { puts "iat::canvas::widget_destroy: $ns" }
    variable id
    variable sizes

45  upvar #0 [join [list [namespace current] $ns widget] ::] widget

    pack forget $widget
    ::destroy $widget
}

50  proc iat::canvas::close { ns } {
    variable TRACE
    if {$TRACE} { puts "iat::canvas::close: $ns" }

55  variable sizes

    upvar #0 [join [list [namespace current] $ns canvas] ::] canvas
    upvar #0 [join [list [namespace current] $ns image] ::] image
    upvar #0 [join [list [namespace current] $ns images] ::] images
60  upvar #0 [join [list [namespace current] $ns annotations] ::] annotations

    $annotations close

    foreach size $sizes {
65  if ($images($size) != "") {
        image delete $images($size)
    }
    set images($size) ""
    }

70  $canvas configure -background black
    $canvas configure -width 2
    $canvas configure -height 2

75 }

proc iat::canvas::dump { cname } {
    upvar #0 [join [list [namespace current] $cname canvas] ::] canvas
    upvar #0 [join [list [namespace current] $cname image] ::] image
80  upvar #0 [join [list [namespace current] $cname images] ::] images
    upvar #0 [join [list [namespace current] $cname percent] ::] percent

```

Appendix 2

```

    puts "canvas = $canvas"
    puts "image = $image"
    puts "images = {array get images}"
    puts "percent = $percent"
5 }

proc iat::canvas::noop { args } {
    variable TRACE
    if {$TRACE} { puts "NOOP: $args" }
10 }

proc iat::canvas::set_file { cname file } {
    upvar #0 [join [list [namespace current] $cname filename] ::] filename

15     set filename $file
        set img [image create photo -file $file]
        set_image $cname $img
    }

20 proc iat::canvas::set_select_mode { ns mode } {
    variable TRACE
    if {$TRACE} { puts "iat::canvas::set_select_mode: $ns $mode" }

    upvar #0 [join [list [namespace current] $ns annotations] ::] annotations
25     upvar #0 [join [list [namespace current] $ns select_mode] ::] select_mode
        upvar #0 [join [list [namespace current] $ns state] ::] state

    set reselect 0
    set key active
30     if {$state == "ANT"} {
        set key [$annotations get key]
        set reselect 1
    }

35     click_reset $ns

    if {$mode == "edit"} {
        set select_mode edit
    } else {
40         set select_mode annotation
    }
    $annotations configure -select $mode

    if {$reselect} {
45         ant_select $ns key$key
    }

}

50 proc iat::canvas::redraw_image { ns } {
    variable TRACE
    if {$TRACE} { puts "iat::canvas::redraw_image: $ns" }

    upvar #0 [join [list [namespace current] $ns state] ::] state
55     upvar #0 [join [list [namespace current] $ns canvas] ::] canvas
        upvar #0 [join [list [namespace current] $ns image] ::] image
        upvar #0 [join [list [namespace current] $ns images] ::] images
        upvar #0 [join [list [namespace current] $ns annotations] ::] annotations
        upvar #0 [join [list [namespace current] $ns borderL] ::] borderL
60         upvar #0 [join [list [namespace current] $ns borderT] ::] borderT
            upvar #0 [join [list [namespace current] $ns borderR] ::] borderR
            upvar #0 [join [list [namespace current] $ns borderB] ::] borderB
            upvar #0 [join [list [namespace current] $ns borderColor] ::] borderColor

65         set ix [image width $image]
            set iy [image height $image]

            # b = border
            set bL [expr round($ix * $borderL)]
70             set bT [expr round($iy * $borderT)]
                set bR [expr round($ix * $borderR)]
                set bB [expr round($iy * $borderB)]

            click_reset $ns
75             $annotations erase all

            $canvas delete image
            #$canvas delete border

80             $canvas configure -background $borderColor
                $canvas configure -width [expr $ix + ($bL + $bR)]

```

Appendix 2

```

$canvas configure -height [expr $iy + ($bt + $bb)]

$canvas create image 0 0 -anchor nw -image $image -tags [list image]
$canvas coords image $bL $bT
5
$annotations configure -offset [list $bL $bT] -size [list $ix $iy]

$annotations draw all

10  #if {$state == "THUMB"} { click_reset_thumbnail $cname }
    }

proc iat::canvas::get_borders { ns } {
15  variable TRACE
    if ($TRACE) { puts "iat::canvas::get_borders: $ns" }

    upvar #0 [join [list [namespace current] $ns borderL] ::] borderL
    upvar #0 [join [list [namespace current] $ns borderT] ::] borderT
20  upvar #0 [join [list [namespace current] $ns borderR] ::] borderR
    upvar #0 [join [list [namespace current] $ns borderB] ::] borderB
    upvar #0 [join [list [namespace current] $ns borderColor] ::] borderColor

    #set x ::canvas
    #set x [namespace current]::$cname$x
    #set c [set $x]

    return [list $borderL $borderT $borderR $borderB $borderColor]
}
30
proc iat::canvas::set_borders { cname lst } {
    variable TRACE
    if ($TRACE) { puts "iat::canvas::set_borders: $cname $lst" }

35  upvar #0 [join [list [namespace current] $cname borderL] ::] borderL
    upvar #0 [join [list [namespace current] $cname borderT] ::] borderT
    upvar #0 [join [list [namespace current] $cname borderR] ::] borderR
    upvar #0 [join [list [namespace current] $cname borderB] ::] borderB
    upvar #0 [join [list [namespace current] $cname borderColor] ::] borderColor
40

    set x ::canvas
    set x [namespace current]::$cname$x
    set c [set $x]

45  set borderL [lindex $lst 0]
    set borderT [lindex $lst 1]
    set borderR [lindex $lst 2]
    set borderB [lindex $lst 3]
    set borderColor [lindex $lst 4]
50

    redraw_image $cname
}

proc iat::canvas::set_image { cname img } {
55  variable TRACE
    if ($TRACE) { puts "iat::canvas::set_image: $cname $img" }
    variable sizes

    upvar #0 [join [list [namespace current] $cname canvas] ::] canvas
    upvar #0 [join [list [namespace current] $cname state] ::] state
60  upvar #0 [join [list [namespace current] $cname image] ::] image
    upvar #0 [join [list [namespace current] $cname images] ::] images
    upvar #0 [join [list [namespace current] $cname percent] ::] percent

65  foreach size $sizes {
        if ($images($size) != "") {
            image delete $images($size)
        }
        set images($size) ""
70  }

    set image $img
    set images(100) $img

75  # new image set to current scale...
    set_scale $cname $percent

    click_reset $cname
}
80
proc iat::canvas::set_scale { cname newp } {

```

```

variable TRACE
if ($TRACE) { puts "iat::canvas::set_scale: $cname $newp" }

    upvar #0 [join [list [namespace current] $cname canvas] ::] canvas
5   upvar #0 [join [list [namespace current] $cname image] ::] image
    upvar #0 [join [list [namespace current] $cname images] ::] images
    upvar #0 [join [list [namespace current] $cname percent] ::] percent

    set percent $newp
10   if {$images($percent) == ""} {
        set srcImg $images(100)
        set newImg [image create photo]
        if {$percent == 100} {
15           # copy
            $newImg copy $srcImg
        } elseif {$percent > 100} {
            # zoom
            set n [expr round($percent/100)]
            $newImg copy $srcImg -zoom $n
20        } else {
            # subsample
            set n [expr round(100/$percent)]
            $newImg copy $srcImg -subsample $n -shrink
25        }
        set images($percent) $newImg
    }

    set image $images($percent)
    redraw_image $cname
30 }

proc iat::canvas::ant_deselect { cname } {
    variable TRACE
    if ($TRACE) { puts "iat::canvas::ant_deselect: $cname" }
35
    upvar #0 [join [list [namespace current] $cname canvas] ::] canvas
    upvar #0 [join [list [namespace current] $cname image] ::] image
    upvar #0 [join [list [namespace current] $cname annotations] ::] annotations
    upvar #0 [join [list [namespace current] $cname state] ::] state
40   upvar #0 [join [list [namespace current] $cname callback_deselect] ::] callback_deselect

    $canvas dtag SELECTED

    eval $callback_deselect
45   $annotations save

    $annotations deselect

}
50

proc iat::canvas::click_reset_thumbnail { cname } {
    variable TRACE
    if ($TRACE) { puts "iat::canvas::click_reset_thumbnail: $cname" }
55
    upvar #0 [join [list [namespace current] $cname canvas] ::] canvas
    upvar #0 [join [list [namespace current] $cname image] ::] image
    upvar #0 [join [list [namespace current] $cname state] ::] state
    upvar #0 [join [list [namespace current] $cname status_label] ::] status_label
    upvar #0 [join [list [namespace current] $cname filename] ::] filename
60   upvar #0 [join [list [namespace current] $cname callback_select] ::] callback_select

    #ant_deselect $cname

    bind $canvas <Button-1> $callback_select
65   bind $canvas <Button1-Motion> {iat::canvas::noop_thumbnail %x %y}
    bind $canvas <Double-Button-1> "iat::canvas::noop_thumbnail %x %y"
    bind $canvas <ButtonRelease-1> "iat::canvas::noop_thumbnail %x %y"
    $canvas bind image <Double-Button-1> $callback_select
    $canvas bind ant <Button-1> $callback_select
70   # will need pointer and label here as well...

    if ($status_label != "") { $status_label configure -text [file tail [file rootname $filename]] }

    set state THUMB
75 }

proc iat::canvas::click_reset_server { cname } {
    variable TRACE
    if ($TRACE) { puts "iat::canvas::click_reset_server: $cname" }
80
    upvar #0 [join [list [namespace current] $cname callback_deselect_server] ::] callback_deselect_server

```

```

click_reset $cname
eval $callback_deselect_server
}
5
proc iat::canvas::click_reset { cname } {
    variable TRACE
    if ($TRACE) { puts "iat::canvas::click_reset: $cname" }

10    upvar #0 [join [list [namespace current] $cname canvas] ::] canvas
        upvar #0 [join [list [namespace current] $cname image] ::] image
        upvar #0 [join [list [namespace current] $cname state] ::] state
        upvar #0 [join [list [namespace current] $cname status_label] ::] status_label

15    if ($state == "THUMB") { click_reset_thumbnail $cname; return }

    ant_deselect $cname

    bind $canvas <Button-1> {iat::canvas::noop click_reset %x %y}
20    bind $canvas <Button1-Motion> {iat::canvas::noop click_reset %x %y}
    bind $canvas <Double-Button-1> "iat::canvas::click_reset_server $cname"
    bind $canvas <ButtonRelease-1> "iat::canvas::noop click_reset B1-Release $cname %x %y"
    $canvas bind image <Double-Button-1> "iat::canvas::click_reset_server $cname"
    $canvas bind ant <Button-1> "iat::canvas::click_ant $cname %x %y"
25    # will need pointer and label here as well...

    if ($status_label != "") { $status_label configure -text "Ready." }

    set state READY
30 }

proc iat::canvas::click_ant { ns x y } {
    variable TRACE
    if ($TRACE) { puts "iat::canvas::click_ant: $ns $x $y" }

35    variable point
        upvar #0 [join [list [namespace current] $ns canvas] ::] canvas
        upvar #0 [join [list [namespace current] $ns state] ::] state

40    #bind $canvas <Button-1> {}
    #bind $canvas <Double-Button-1> "iat::canvas::click_reset $ns"
    #bind $canvas <Button-1> "iat::canvas::click_handle $ns %x %y"

    set point [list $x $y]

45    if ($state == "CREATE") {
        ant_create_vertex $ns $x $y
    } elseif ($state == "MOVE") {
        # don't deselect...
50    } else {
        ant_deselect $ns
        ant_select_at $ns $x $y
        #puts "    HERE!!!"
        #bind $canvas <Double-Button-1> "iat::canvas::noop ant_click_reset $cname"
55    #bind $canvas bind image <Double-Button-1> "iat::canvas::noop ant_click_reset $cname"
    }

    #bind $canvas <Button1-Motion> "iat::canvas::ant_drag_ant $ns %x %y"

60 }

proc iat::canvas::click_handle { ns x y } {
    variable TRACE
    if ($TRACE) { puts "iat::canvas::click_handle: $ns $x $y" }

65    variable point
    variable ptnum
    variable vertn

70    upvar #0 [join [list [namespace current] $ns canvas] ::] canvas
        upvar #0 [join [list [namespace current] $ns annotations] ::] annotations
        upvar #0 [join [list [namespace current] $ns state] ::] state

    switch $state {
75        "READY" {
            #puts "ClickHandle: do nothing (no polygon selected)"
        }
        "ANT" {
            #puts "ClickHandle: select handle"
80            # vertex is in a different polygon

```


Appendix 2

```

#set point [isPointInPoints $x $y $points]
# if ($point < 0) {
#   sector is in a different polygon
#   #set point [isPointInPoints $x $y $sectors]
#   # if ($point < 0) { return }
# }

set point [list $x $y]
$canvas addtag HANDLE closest $x $y 3
$canvas itemconfigure HANDLE -fill red -outline black

set tags [$canvas gettags HANDLE]
set type "none"
if {[lsearch $tags vertex] > -1} { set type vertex }
if {[lsearch $tags sector] > -1} { set type sector }
if {[lsearch $tags symbol] > -1} { set type symbol }
if {[lsearch $tags tail] > -1} { set type tail }
if {[lsearch $tags head] > -1} { set type head }
if {[lsearch $tags ptrvert] > -1} {
    set type ptrvert
    set vidx [lsearch -regexp $tags {vx(\d+)})
    set tag [lindex $tags $vidx]
    regexp {vx(\d+)} $tag m vertn
}
if {[lsearch $tags ptrsect] > -1} {
    set type ptrsect
    set vidx [lsearch -regexp $tags {sx(\d+)})
    set tag [lindex $tags $vidx]
    regexp {sx(\d+)} $tag m vertn
}
if {$type == "none"} { error "Handle is not a head, tail, vertex, sector or symbol!" }

set nidx [lsearch -regexp $tags {num(\d+)})
set tag [lindex $tags $nidx]
regexp {num(\d+)} $tag m ptnum
#puts " ptnum = $ptnum"

set state NONE

# have to bind things that are _not_ the handle...
$canvas bind border <Button-1> "iat::canvas::ant_move_$type $ns $x $y"
$canvas bind image <Button-1> "iat::canvas::ant_move_$type $ns $x $y"
$canvas bind ant <Button-1> "iat::canvas::ant_move_$type $ns $x $y"
$canvas bind segment <Button-1> "iat::canvas::ant_move_$type $ns $x $y"
bind $canvas <Button1-Motion> "iat::canvas::ant_drag_$type $ns $x $y"
#puts " HERE!!"
bind $canvas <Double-Button-1> "iat::canvas::noop click_reset $ns"

set state [string toupper $type]
}
"VERTEX" {
    $canvas addtag DELHANDLE closest $x $y 3
    set tags [$canvas gettags DELHANDLE]
    $canvas dtag DELHANDLE
    set nidx [lsearch -regexp $tags {num(\d+)})
    set tag [lindex $tags $nidx]
    regexp {num(\d+)} $tag m tmpnum
    #puts " ptnum = $ptnum"
    #puts " tmpnum = $tmpnum"
    if {$tmpnum == $ptnum} {
        ant_delete_vertex $ns $x $y
    }
}
"SECTOR" {
    ant_insert_vertex $ns $x $y
}
"HEAD_old" {
    # moving the head is handled through the pointer tail now...
    $canvas addtag DELHANDLE closest $x $y 3
    set tags [$canvas gettags DELHANDLE]
    $canvas dtag DELHANDLE
    set nidx [lsearch -regexp $tags {num(\d+)})
    set tag [lindex $tags $nidx]
    regexp {num(\d+)} $tag m tmpnum

    $annotations move head $tmpnum auto
    ant_select $ns active
}
"TAIL" {
    $canvas addtag DELHANDLE closest $x $y 3

```

Appendix 2

```

    set tags [$canvas gettags DELHANDLE]
    $canvas dtag DELHANDLE
    set nidx [lsearch -regexp $tags {num(\d+)})
    set tag [lindex $tags $nidx]
    regexp {num(\d+)} $tag m tmpnum

    $annotations delete pointer $tmpnum
    ant_select $ns active

}

"PTRVERT" {
    $canvas addtag DELHANDLE closest $x $y 3
    set tags [$canvas gettags DELHANDLE]
    $canvas dtag DELHANDLE
    set nidx [lsearch -regexp $tags {vx(\d+)})
    set tag [lindex $tags $nidx]
    regexp {vx(\d+)} $tag m tmpn
    if {$tmpn == $vertn} {
        ant_delete_ptrvert $ns $ptnum $vertn
        ant_select $ns active
    }
}

"PTRSECT" {
    ant_insert_ptrvert $ns $x $y
}

"SYMBOL" {
    #roiSymbolMove $x $y
}

default {
    iat::canvas::noop click_handle $x $y
}
}

35 proc iat::canvas::toolStartPan { w c x y } {
    variable TRACE
    if {$TRACE} { puts "iat::canvas::toolStartPan: $w $c $x $y" }
    variable panX
    variable panY
    variable panSX
    variable panSY

    set panX $x
    set panY $y

    set xv [$w xview]
    set xd [expr [lindex $xv 1] - [lindex $xv 0]]
    set panSX [expr $xd / 10]

    set yv [$w yview]
    set yd [expr [lindex $yv 1] - [lindex $yv 0]]
    set panSY [expr $yd / 10]
}

55 proc iat::canvas::toolDoPan { w c x y } {
    variable TRACE
    if {$TRACE} { puts "iat::canvas::toolDoPan: $w $c $x $y" }
    variable panX
    variable panY
    variable panSX
    variable panSY

    set dx [expr $panX - $x]
    set dy [expr $panY - $y]

    if {$dx > 10} {$w xview moveto [expr [lindex [$w xview] 0] + $panSX]}
    elseif {$dx < -10} {$w xview moveto [expr [lindex [$w xview] 0] - $panSX]}

    if {$dy > 10} {$w yview moveto [expr [lindex [$w yview] 0] + $panSY]}
    elseif {$dy < -10} {$w yview moveto [expr [lindex [$w yview] 0] - $panSY]}
}

proc iat::canvas::tool_create_start { cname kind } {
    variable TRACE
    if {$TRACE} { puts "iat::canvas::tool_start_create_ant: $kind" }

    upvar #0 [join [list [namespace current] $cname canvas] ::] canvas
    upvar #0 [join [list [namespace current] $cname image] ::] image
    upvar #0 [join [list [namespace current] $cname annotations] ::] annotations
    upvar #0 [join [list [namespace current] $cname state] ::] state

```

```

upvar #0 [join [list [namespace current] $cname status_label] ::] status_label

if {$state == "CREATE"} {
5   ant_create_end $cname 0 0
}

click_reset $cname

10  bind $canvas <Button-1> "iat::canvas::ant_create_vertex $cname %x %y"
    bind $canvas <Double-1> "iat::canvas::ant_create_end $cname %x %y"
    $canvas bind ant <Button-1> "iat::canvas::noop tool_create_start Button-1 $cname %x %y"

    $annotations create roi $kind
    set state CREATE

15  switch $kind {
        "point" { $status_label configure -text "Click 1 or more points. Double-click for last point
and end create." }
        "edge" { $status_label configure -text "Click 2 or more points to create edge. Double-click
20 for last point and end create." }
        "area" { $status_label configure -text "Click 3 or more points to create area. Double-click
for last point and end create." }
        "circle" { }
        "rectangle" { }
25     default { $status_label configure -text "Unknown create kind..." }
    }

    #if {$kind == "group"} {
30     #   roiCreateEnd 0 0
    #} else {
    #   set inCreate 1
    #}
}

35  proc iat::canvas::ant_create_end { cname x y } {
    variable TRACE
    if {$TRACE} { puts "iat::canvas::ant_create_end: $x $y" }

40     upvar #0 [join [list [namespace current] $cname canvas] ::] canvas
        upvar #0 [join [list [namespace current] $cname image] ::] image
        upvar #0 [join [list [namespace current] $cname annotations] ::] annotations
        upvar #0 [join [list [namespace current] $cname state] ::] state
        upvar #0 [join [list [namespace current] $cname status_label] ::] status_label

45     bind $canvas <Button-1> {}
        bind $canvas <Double-Button-1> {}
        $canvas bind ant <Button-1> {}

50     # NOTE: Don't use click_reset because is deselects which saves annotation...

    # don't allow polygons with less than 3 points...
    set npts 0
    switch [$annotations kind active] {
55         "group" { set npts 0 }
        "point" { set npts 1 }
        "edge" { set npts 2 }
        "area" { set npts 3 }
        "rectangle" { set npts 2 }
60         "circle" { set npts 2 }
    }

    if {[llength [$annotations points active]] < $npts} {
        $canvas delete handle
        $annotations delete active
65         set state NONE
        return
    }

    # post-process points if creating rectangle or circle...
    if {[llength [$annotations kind] == "rectangle"]} {
70         if {[llength [$annotations points active]] != 2} {
            $canvas delete handle
            $annotations delete active
            set choice [tk_messageBox \
                -title "Rectangle Problem" \
75             -message "Rectangle must be specified with top-left and bottom-right points." \
                -icon warning \
                -type ok ]

            return
        }
        roiCreateEndRectangle
80     } elseif {[llength [$annotations kind] == "circle"]} {

```

```

        if ([length [$annotations points active]] != 2) {
            $canvas delete handle
            $annotations delete active
            iat::roi::roiDelete
5         set choice [tk_messageBox \
                -title "Circle Problem" \
                -message "Circle must be specified with center and radius points." \
                -icon warning \
                -type ok ]
10        return
        }
        roiCreateEndCircle
    )

15    # without state reset infinite loop occurs...
    set state "ANT"
        $annotations save
        # $annotations draw active
        # click_reset $cname
20    ant_select $cname active
    )

proc iat::canvas::ant_create_vertex { cname x y } {
25    variable TRACE
    if ($TRACE) { puts "iat::canvas::ant_create_vertex: $x $y" }

        upvar #0 [join [list [namespace current] $cname canvas] ::] canvas
        upvar #0 [join [list [namespace current] $cname image] ::] image
30        upvar #0 [join [list [namespace current] $cname annotations] ::] annotations
        upvar #0 [join [list [namespace current] $cname state] ::] state

        $annotations create vertex [list $x $y]
        $annotations erase active
35        $annotations draw segments
        $annotations draw vertexs
    )

40 proc iat::canvas::ant_create_pointer_start { ns num } {
    variable TRACE
    if ($TRACE) { puts "iat::canvas::ant_create_pointer: $ns $num" }

45        variable head
        variable ptrmode

        upvar #0 [join [list [namespace current] $ns canvas] ::] canvas
        upvar #0 [join [list [namespace current] $ns annotations] ::] annotations
        upvar #0 [join [list [namespace current] $ns state] ::] state
50        if ($state != "ANT") { return }

        set ptrmode single
        if ($num == "multiple") { set ptrmode multiple }
55        set head auto

        bind $canvas <Double-1> "iat::canvas::click_reset $ns $x $y"
        bind $canvas <Button-1> "iat::canvas::ant_create_pointer_tail $ns $x $y"
        $canvas bind handle <Button-1> "iat::canvas::ant_create_pointer_head $ns $x $y"
60    }

    proc iat::canvas::ant_create_pointer_tail { ns x y } {
        variable TRACE
65        if ($TRACE) { puts "iat::canvas::ant_create_pointer_tail: $ns $x $y" }

        variable head
        variable ptrmode

70        upvar #0 [join [list [namespace current] $ns canvas] ::] canvas
        upvar #0 [join [list [namespace current] $ns annotations] ::] annotations
        upvar #0 [join [list [namespace current] $ns state] ::] state

        # fix... if head and x,y are same then handle was clicked...
75        if ([lindex $head 0] == "head") { set head [lindex $head 1]; return }

        $annotations create pointer $head [list $x $y] {}

        if ($ptrmode == "multiple") {
80            bind $canvas <Double-1> "iat::canvas::click_reset $ns $x $y"
            bind $canvas <Button-1> "iat::canvas::ant_create_pointer_tail $ns $x $y"
        }
    }

```

Appendix 2

```

    $canvas bind handle <Button-1> "iat::canvas::ant_create_pointer_head $ns %x %y"
  ) else {
    bind $canvas <Double-1> "iat::canvas::click_reset $ns %x %y"
    bind $canvas <Button-1> "iat::canvas::noop_pointer_tail $ns %x %y"
5
  }

  ant_select $ns active

10 )

proc iat::canvas::ant_create_pointer_head { ns x y } {
  variable TRACE
  if ($TRACE) { puts "iat::canvas::ant_create_pointer_head: $ns $x $y" }
15
  variable head

  upvar #0 [join [list [namespace current] $ns canvas] ::] canvas
  upvar #0 [join [list [namespace current] $ns annotations] ::] annotations
20
  upvar #0 [join [list [namespace current] $ns state] ::] state

  $canvas addtag DELHANDLE closest $x $y 3
  set tags [$canvas gettags DELHANDLE]
  $canvas dtag DELHANDLE
25
  set nidx [lsearch -regexp $tags {num(\d+)}]
  set tag [lindex $tags $nidx]
  regexp {num(\d+)} $tag m tmpnum

  set head [list head $tmpnum]
30
}

proc iat::canvas::ant_ptr_symbol { ns } {
  variable TRACE
35
  if ($TRACE) { puts "iat::canvas::ant_ptr_symbol: $ns" }

  variable head
  variable ptnum

40
  upvar #0 [join [list [namespace current] $ns canvas] ::] canvas
  upvar #0 [join [list [namespace current] $ns annotations] ::] annotations
  upvar #0 [join [list [namespace current] $ns state] ::] state

45
  if ($state == "TAIL") {
    #puts " state == TAIL"
    $annotations pointer symbol $ptnum toggle
  } else {
    # do nothing... click_reset!
50
  }

  click_reset $ns
  ant_select $ns active

55 )

proc iat::canvas::ant_ptr_style { ns } {
  variable TRACE
60
  if ($TRACE) { puts "iat::canvas::ant_ptr_style: $ns" }

  variable head
  variable ptnum

  upvar #0 [join [list [namespace current] $ns canvas] ::] canvas
65
  upvar #0 [join [list [namespace current] $ns annotations] ::] annotations
  upvar #0 [join [list [namespace current] $ns state] ::] state

  if ($state == "TAIL") {
70
    #puts " state == TAIL"
    $annotations pointer style $ptnum toggle
  } else {
    # do nothing... click_reset!
75
  }

  click_reset $ns
  ant_select $ns active

80
}

proc iat::canvas::ant_ptr_pin { ns } {

```

```

variable TRACE
if ($TRACE) { puts "iat::canvas::ant_ptr_pin: $ns" }

variable head
5 variable ptnum

upvar #0 [join [list [namespace current] $ns canvas] ::] canvas
upvar #0 [join [list [namespace current] $ns annotations] ::] annotations
upvar #0 [join [list [namespace current] $ns state] ::] state
10

if ($state == "TAIL") {
    #puts " state == TAIL"
    $annotations pointer pin $ptnum toggle
15 } else {
    # do nothing... click_reset!
}

click_reset $ns
20 ant_select $ns active
}

proc iat::canvas::ant_select { ns tag } {
25 variable TRACE
    if ($TRACE) { puts "iat::canvas::ant_select: $ns $tag" }

    upvar #0 [join [list [namespace current] $ns canvas] ::] canvas
    upvar #0 [join [list [namespace current] $ns annotations] ::] annotations
30 upvar #0 [join [list [namespace current] $ns select_mode] ::] select_mode
    upvar #0 [join [list [namespace current] $ns state] ::] state
    upvar #0 [join [list [namespace current] $ns callback_select] ::] callback_select

    set key active
    if ($tag == "active") {
        set key [$annotations get key]
    } else {
        set tags [$canvas gettags $tag]
        #puts "tags of $tag = $tags"
        set keyidx [lsearch -regexp $tags {key(\d+)}]
40 if {$keyidx < 0} { puts "ERROR: ant_select: $tags"; return }
        set tag [lindex $tags $keyidx]
        regexp {key(\d+)} $tag m key
        $canvas addtag SELECTED withtag $tag
45 }

    # If there are no canvas tags then it is a non-visual annotation (group)

    $canvas bind border <Button-1> "iat::canvas::noop ant_select border $ns %x %y"
50 $canvas bind image <Button-1> "iat::canvas::noop ant_select image $ns %x %y"
    $canvas bind ant <Button-1> "iat::canvas::noop ant_select ant $ns %x %y"
    $canvas bind segment <Button-1> "iat::canvas::click_ant $ns %x %y"
    if ($select_mode == "edit") {
        $canvas bind handle <Button-1> "iat::canvas::click_handle $ns %x %y"
55 #bind $canvas <Button1-Motion> "iat::canvas::noop ant_select B1-Motions $ns %x %y"
        #bind $canvas <ButtonRelease-1> "iat::canvas::noop ant_select B1-Release $ns %x %y"
    } else {
        $canvas bind handle <Button-1> "iat::canvas::noop ant_select B1"
        $canvas bind head <Button-1> "iat::canvas::click_handle $ns %x %y"
60 $canvas bind tail <Button-1> "iat::canvas::click_handle $ns %x %y"
        $canvas bind segment <Button1-Motion> "iat::canvas::ant_drag_ant $ns %x %y"
        #bind $canvas <Button1-Motion> "iat::canvas::ant_drag_ant $ns %x %y"
    }
}

# Test not binding double click here...
65 #bind $canvas <Double-Button-1> "iat::canvas::click_reset $ns"

$annotations select $key
#puts " SELECTED: $key"

70 # callback
eval $callback_select

    set state "ANT"
}
75

proc iat::canvas::ant_select_at { ns x y } {
    variable TRACE
    if ($TRACE) { puts "iat::canvas::ant_select_at: $ns $x $y" }

80 variable point

```

Appendix 1

```

upvar #0 [join [list [namespace current] $ns canvas] ::] canvas
upvar #0 [join [list [namespace current] $ns annotations] ::] annotations

set point [list $x $y]
$canvas delete SELECTED
$canvas addtag SELECTED closest $x $y
ant_select $ns SELECTED
)

10 proc iat::canvas::ant_delete { ns } {
    variable TRACE
    if {$TRACE} { puts "iat::canvas::ant_delete: $ns" }

    upvar #0 [join [list [namespace current] $ns canvas] ::] canvas
15    upvar #0 [join [list [namespace current] $ns annotations] ::] annotations
    upvar #0 [join [list [namespace current] $ns state] ::] state

    if {$state != "ANT"} { return }
    set key [$annotations get key]
    #puts " DELETING: $key"
    ant_deselect $ns
    $annotations erase $key
    $annotations delete annotation $key
    click_reset $ns
25 }

proc iat::canvas::ant_delete_vertex { ns x y } {
    variable TRACE
    if {$TRACE} { puts "iat::canvas::ant_delete_vertex: $ns $x $y" }

    variable point
    variable ptnum

    upvar #0 [join [list [namespace current] $ns canvas] ::] canvas
35    upvar #0 [join [list [namespace current] $ns annotations] ::] annotations

    $annotations delete vertex $ptnum
    ant_select $ns active

40 }

proc iat::canvas::ant_move { ns } {
    variable TRACE
    if {$TRACE} { puts "iat::canvas::ant_move: $ns" }

    upvar #0 [join [list [namespace current] $ns canvas] ::] canvas
    upvar #0 [join [list [namespace current] $ns state] ::] state

    if {$state != "ANT"} { return }
50    set state MOVE
    bind $canvas <Button1-Motion> "iat::canvas::ant_drag_ant $ns %x %y"
}

55 proc iat::canvas::ant_drag_ant { ns x y } {
    variable TRACE
    if {$TRACE} { puts "iat::canvas::ant_drag_ant: $ns $x $y" }

    variable point

    upvar #0 [join [list [namespace current] $ns canvas] ::] canvas
    upvar #0 [join [list [namespace current] $ns annotations] ::] annotations
    upvar #0 [join [list [namespace current] $ns state] ::] state

65    if {$state == "MOVE"} {
        set state DRAG
        bind $canvas <ButtonRelease-1> "iat::canvas::ant_drag_ant_end $ns %x %y"
    }
    if {$state != "DRAG"} { return }

    set dx [expr $x - [lindex $point 0]]
    set dy [expr $y - [lindex $point 1]]
    $annotations move delta [list $dx $dy]
75    set point [list $x $y]
    # This does not change canvas bindings...
    $annotations select active

    }

80 proc iat::canvas::ant_drag_ant_end { ns x y } {

```

```

variable TRACE
if ($TRACE) { puts "iat::canvas::ant_drag_ant_end: $ns $x $y" }

    upvar #0 [join [list [namespace current] $ns canvas] ::] canvas
    upvar #0 [join [list [namespace current] $ns annotations] ::] annotations
5    upvar #0 [join [list [namespace current] $ns state] ::] state
    bind $canvas <Button1-Motion> "iat::canvas::noop ant_drag_ant_end $ns %x %y"
    $annotations select active
    set state "ANT"
10    #ant_move_vertex $ns $x $y
}

proc iat::canvas::ant_drag_vertex { ns x y } {
    variable TRACE
15    if ($TRACE) { puts "iat::canvas::ant_drag_vertex: $ns $x $y" }

    variable point
    variable ptnum

20    upvar #0 [join [list [namespace current] $ns canvas] ::] canvas
    upvar #0 [join [list [namespace current] $ns annotations] ::] annotations
    upvar #0 [join [list [namespace current] $ns state] ::] state

    if ($state == "VERTEX") {
25        set state DRAG
        bind $canvas <ButtonRelease-1> "iat::canvas::ant_drag_vertex_end $ns %x %y"
    }
    if ($state != "DRAG") { return }

30    $annotations move vertex $ptnum [list $x $y]
    # This does not change canvas bindings...
    $annotations select active
}

35    proc iat::canvas::ant_drag_vertex_end { ns x y } {
        variable TRACE
        if ($TRACE) { puts "iat::canvas::ant_drag_vertex_end: $ns $x $y" }
        upvar #0 [join [list [namespace current] $ns state] ::] state
40        set state "VERTEX"
        ant_move_vertex $ns $x $y
    }

    proc iat::canvas::ant_move_vertex { ns x y } {
45        variable TRACE
        if ($TRACE) { puts "iat::canvas::ant_move_vertex: $ns $x $y" }

        variable point
        variable ptnum

50        upvar #0 [join [list [namespace current] $ns canvas] ::] canvas
        upvar #0 [join [list [namespace current] $ns annotations] ::] annotations
        upvar #0 [join [list [namespace current] $ns state] ::] state

55        if ($state != "VERTEX") { return }

        click_reset $ns
        $annotations move vertex $ptnum [list $x $y]
        ant_select $ns active
60    }

    proc iat::canvas::ant_drag_sector { ns x y } {
        ant_insert_vertex $ns $x $y
65        click_handle $ns $x $y
    }

    proc iat::canvas::ant_move_sector { ns x y } {
        ant_insert_vertex $ns $x $y
70    }

    proc iat::canvas::ant_insert_vertex { ns x y } {
        variable TRACE
        if ($TRACE) { puts "iat::canvas::ant_insert_vertex: $ns $x $y" }
75        variable point
        variable ptnum

        upvar #0 [join [list [namespace current] $ns canvas] ::] canvas
80        upvar #0 [join [list [namespace current] $ns annotations] ::] annotations
        upvar #0 [join [list [namespace current] $ns state] ::] state
    }

```



```

    if ($state != "SECTOR") { return }

    $annotations insert vertex $ptnum [list $x $y]
    ant_select $ns active
5
}

proc iat::canvas::ant_drag_tail { ns x y } {
    variable TRACE
10    if ($TRACE) { puts "iat::canvas::ant_drag_tail: $ns $x $y" }

    variable point
    variable ptnum

15    upvar #0 [join [list [namespace current] $ns canvas] ::] canvas
    upvar #0 [join [list [namespace current] $ns annotations] ::] annotations
    upvar #0 [join [list [namespace current] $ns state] ::] state

    if ($state == "TAIL") {
20        set state DRAG
        bind $canvas <ButtonRelease-1> "iat::canvas::ant_drag_tail_end $ns %x %y"
    }
    if ($state != "DRAG") { return }

25    $annotations move tail $ptnum [list $x $y]
    # This does not change canvas bindings...
    set rv [$annotations select active]
    #puts " ptnum = $ptnum, rv = $rv"
    if ($rv >= 0) { set ptnum $rv }
30
}

proc iat::canvas::ant_drag_tail_end { ns x y } {
    variable TRACE
35    if ($TRACE) { puts "iat::canvas::ant_drag_tail_end: $ns $x $y" }
    upvar #0 [join [list [namespace current] $ns state] ::] state
    set state "TAIL"
    ant_move_tail $ns $x $y
}

40
proc iat::canvas::ant_move_tail { ns x y } {
    variable TRACE
    if ($TRACE) { puts "iat::canvas::ant_move_tail: $ns $x $y" }

45    variable point
    variable ptnum

    upvar #0 [join [list [namespace current] $ns canvas] ::] canvas
    upvar #0 [join [list [namespace current] $ns annotations] ::] annotations
50    upvar #0 [join [list [namespace current] $ns state] ::] state

    if ($state != "TAIL") { return }

    click_reset $ns
55    $annotations move tail $ptnum [list $x $y]
    ant_select $ns active
}

60 proc iat::canvas::ant_drag_head { ns x y } {
    variable TRACE
    if ($TRACE) { puts "iat::canvas::ant_drag_head: $ns $x $y" }

    variable point
65    variable ptnum

    upvar #0 [join [list [namespace current] $ns canvas] ::] canvas
    upvar #0 [join [list [namespace current] $ns annotations] ::] annotations
    upvar #0 [join [list [namespace current] $ns state] ::] state
70

    if ($state == "HEAD") {
        set state DRAG
        bind $canvas <ButtonRelease-1> "iat::canvas::ant_drag_head_end $ns %x %y"
    }
75    if ($state != "DRAG") { return }

    set rv [$annotations move head $ptnum [list $x $y]]
    # This does not change canvas bindings...
    $annotations select active
    # puts " ptnum = $ptnum, rv = $rv"
80    if ($rv >= 0) { set ptnum $rv }

```

```

}
proc iat::canvas::ant_drag_head_end { ns x y } {
    variable TRACE
    if ($TRACE) { puts "iat::canvas::ant_drag_head_end: $ns $x $y" }
5    upvar #0 [join [list [namespace current] $ns state] ::] state
    set state "HEAD"
    ant_move_head $ns $x $y
}

10 proc iat::canvas::ant_move_head { ns x y } {
    variable TRACE
    if ($TRACE) { puts "iat::canvas::ant_move_head: $ns $x $y" }

    variable point
15    variable ptnum

    upvar #0 [join [list [namespace current] $ns canvas] ::] canvas
    upvar #0 [join [list [namespace current] $ns annotations] ::] annotations
    upvar #0 [join [list [namespace current] $ns state] ::] state
20    if ($state != "HEAD") { return }

    click_reset $ns
    $annotations move head $ptnum [list $x $y]
25    ant_select $ns active
}

30 proc iat::canvas::ant_drag_ptrvert { ns x y } {
    variable TRACE
    if ($TRACE) { puts "iat::canvas::ant_drag_ptrvert: $ns $x $y" }

    variable point
35    variable ptnum
    variable vertn

    upvar #0 [join [list [namespace current] $ns canvas] ::] canvas
    upvar #0 [join [list [namespace current] $ns annotations] ::] annotations
40    upvar #0 [join [list [namespace current] $ns state] ::] state

    if ($state == "PTRVERT") {
        set state DRAG
        bind $canvas <ButtonRelease-1> "iat::canvas::ant_drag_ptrvert_end $ns %x %y"
45    }
    if ($state != "DRAG") { return }

    $annotations move ptrvert $ptnum $vertn [list $x $y]
    # This does not change canvas bindings...
50    $annotations select active
}

55 proc iat::canvas::ant_drag_ptrvert_end { ns x y } {
    variable TRACE
    if ($TRACE) { puts "iat::canvas::ant_drag_ptrvert_end: $ns $x $y" }

    upvar #0 [join [list [namespace current] $ns state] ::] state
    set state "PTRVERT"
60    ant_move_ptrvert $ns $x $y
}

proc iat::canvas::ant_move_ptrvert { ns x y } {
    variable TRACE
65    if ($TRACE) { puts "iat::canvas::ant_move_ptrvert: $ns $x $y" }

    variable point
    variable ptnum
    variable vertn
70

    upvar #0 [join [list [namespace current] $ns canvas] ::] canvas
    upvar #0 [join [list [namespace current] $ns annotations] ::] annotations
    upvar #0 [join [list [namespace current] $ns state] ::] state

75    if ($state != "PTRVERT") { return }

    click_reset $ns
    $annotations move ptrvert $ptnum $vertn [list $x $y]
    ant_select $ns active
80
}

```

```

proc iat::canvas::ant_drag_ptrsect { ns x y } {
    variable TRACE
    if ($TRACE) { puts "iat::canvas::ant_drag_ptrvert: $ns $x $y" }

5      ant_insert_ptrvert $ns $x $y
      click_handle $ns $x $y
}

10 proc iat::canvas::ant_move_ptrsect { ns x y } {
    variable TRACE
    if ($TRACE) { puts "iat::canvas::ant_move_ptrvert: $ns $x $y" }
    ant_insert_ptrvert $ns $x $y
}

15 proc iat::canvas::ant_insert_ptrvert { ns x y } {
    variable TRACE
    if ($TRACE) { puts "iat::canvas::ant_insert_ptrvert: $ns $x $y" }

20      variable point
      variable ptnum
      variable vertn

      upvar #0 [join [list [namespace current] $ns canvas] ::] canvas
      upvar #0 [join [list [namespace current] $ns annotations] ::] annotations
25      upvar #0 [join [list [namespace current] $ns state] ::] state

      if ($state != "PTRSECT") { return }

      $annotations insert ptrvert $ptnum $vertn [list $x $y]
30      ant_select $ns active
}

35 proc iat::canvas::ant_delete_ptrvert { ns ptnum vertn } {
    variable TRACE
    if ($TRACE) { puts "iat::canvas::ant_delete_ptrvert: $ns $ptnum $vertn" }

      upvar #0 [join [list [namespace current] $ns canvas] ::] canvas
      upvar #0 [join [list [namespace current] $ns annotations] ::] annotations
40      $annotations delete ptrvert $ptnum $vertn
      ant_select $ns active
}

45 }

proc iat::canvas::ant_lower { ns } {
    variable TRACE
    if ($TRACE) { puts "iat::canvas::ant_lower: $ns" }

50      upvar #0 [join [list [namespace current] $ns canvas] ::] canvas
      upvar #0 [join [list [namespace current] $ns state] ::] state

      if ($state != "ANT") { return }

55      $canvas lower SELECTED
      $canvas raise SELECTED image

      ant_deselect $ns
      click_reset $ns
60 }

proc iat::canvas::make_cmds { ns lvl } {
    variable TRACE
65      if ($TRACE) { puts "iat::canvas::make_cmds: $ns $lvl" }

      set str ""
      #append str "\nbegin canvas\n"

70      set lst [get_borders $ns]
      #append str "borders"
      # border percent widths
      #append str " [lindex $lst 0] [lindex $lst 1] [lindex $lst 2] [lindex $lst 3]"
      # border color
75      #append str " [lindex $lst 4]\n"
      set pre [string repeat " " $lvl]
      append str "$pre<canvas>\n"
      append str "$pre <border color=\"[lindex $lst 4]\" > [lrange $lst 0 3] </border>\n"
      append str "$pre</canvas>\n"
80      #append str "end canvas\n\n"

```

Appendix 2

```

    return $str
}

proc iat::canvas::ant_make_image { ns } {
5   variable TRACE
    if ($TRACE) { puts "iat::canvas::ant_make_image: $ns" }

    upvar #0 [join [list [namespace current] $ns canvas] ::] canvas
    upvar #0 [join [list [namespace current] $ns image] ::] image
10   upvar #0 [join [list [namespace current] $ns annotations] ::] annotations
    upvar #0 [join [list [namespace current] $ns state] ::] state

    $annotations erase
    click_reset $ns
15   $annotations draw all

    set img [image create photo -format window -data $canvas]

    return $img
20 }

proc iat::canvas::ant_make_svg { ns } {
    variable TRACE
    if ($TRACE) { puts "iat::canvas::ant_make_svg: $ns" }
25
    upvar #0 [join [list [namespace current] $ns image] ::] image
    upvar #0 [join [list [namespace current] $ns annotations] ::] annotations
    upvar #0 [join [list [namespace current] $ns borderL] ::] borderL
    upvar #0 [join [list [namespace current] $ns borderT] ::] borderT
30   upvar #0 [join [list [namespace current] $ns borderR] ::] borderR
    upvar #0 [join [list [namespace current] $ns borderB] ::] borderB
    upvar #0 [join [list [namespace current] $ns borderColor] ::] borderColor

    set ix [image width $image]
35   set iy [image height $image]

    $annotations erase
    set rvs [$annotations make svg]
    set menu [lindex $rvs 0]
    set ants [lindex $rvs 1]
40   #click_reset $ns
    $annotations select
    $annotations draw all

    return [list $borderL $borderT $borderR $borderB $borderColor $ix $iy $menu $ants]
45 }

proc iat::canvas::ant_read_cmds { ns doc } {
    variable TRACE
50   if ($TRACE) { puts "iat::canvas::ant_read_cmds: $ns $doc" }

    upvar #0 [join [list [namespace current] $ns image] ::] image
    upvar #0 [join [list [namespace current] $ns annotations] ::] annotations
    upvar #0 [join [list [namespace current] $ns borderL] ::] borderL
55   upvar #0 [join [list [namespace current] $ns borderT] ::] borderT
    upvar #0 [join [list [namespace current] $ns borderR] ::] borderR
    upvar #0 [join [list [namespace current] $ns borderB] ::] borderB
    upvar #0 [join [list [namespace current] $ns borderColor] ::] borderColor

60   upvar #0 [join [list $doc doc_by_eid] ::] doc_by_eid
    upvar #0 [join [list $doc doc_by_elt] ::] doc_by_elt

    if {[info exists doc_by_elt(border)]} {
        set eids $doc_by_elt(border)
65         #puts " eids = $eids"
        set eid [lindex $eids end]

        #puts " $doc_by_eid($eid)"
        array set A $doc_by_eid($eid)
70         array set O $A(opt)

        if {[info exists O(color)]} {
            set borderColor $O(color)
            #puts " color = $borderColor"
75         }
        if {[info exists A(dat)]} {
            set B $A(dat)
            #puts " B = $B"
            set borderL [lindex $B 0]
80             set borderT [lindex $B 1]
            set borderR [lindex $B 2]

```

```

    set borderB [lindex $B 3]
  )
}
5   $annotations read_cmds $doc
    return 0
}
10  proc iat::canvas::dump_annotations { ns } {
    upvar #0 [join [list [namespace current] $ns annotations] ::] annotations
    $annotations dump
15  }
    proc iat::canvas::dump_keys { ns } {
20  upvar #0 [join [list [namespace current] $ns annotations] ::] annotations
    $annotations dump_keys
    click_reset $ns
25  $annotations draw all
    }
    proc iat::canvas::dump_svg { ns } {
30  upvar #0 [join [list [namespace current] $ns annotations] ::] annotations
    $annotations dump_svg
    click_reset $ns
35  $annotations draw all
    }
    proc iat::canvas::ant_make_ps { ns filename {height 5i} } {
40  variable TRACE
    if {$TRACE} { puts "iat::canvas::ant_make_ps: $ns $filename" }
    upvar #0 [join [list [namespace current] $ns canvas] ::] canvas
45  #set fontMap(*-Arial-bold-*-*--24-*) [list Arial 24]
    #set fontMap(*-Helvetica-*-*--24-*) [list Arial 24]
    $canvas create rect 0 0 [$canvas cget -width] [$canvas cget -height] -fill #222 -tags forPS
    $canvas lower forPS
    #return [$canvas postscript -pageheight $height -colormode gray]
50  #set PS [$canvas postscript -pageheight $height]
    set PS [$canvas postscript -file $filename]
    $canvas delete forPS
    return $PS
    }
55  iat.icons.txt
    # iat.icons.tcl

    namespace eval iat::icons {
60  set SelectSolid {\
R01G0DlhFAAUAPCAAAAAAAAAQAAAgAAA/wAgAAAgQAAggAAg/wBAAABAQABA\
gABA/wBgAABgQABggABg/wCAAACAQACAgACA/wCgAACgQACggACg/wDAAADA\
QADAgADA/wD/AAD/QAD/gAD//yAAACAAQCAAgCAA/yAgACAgQACggACg/yBA\
65  ACBAQCBAgCBA/yBgACBgQCBggCBg/yCAACCAQCCAgCCA/yCgACCgQCCggCCg\
/yDAACDAQCDagCDA/yD/ACD/QCD/gCD//0AAAEAAQEAAgEAA/0AgAEAgQEAg\
gEAg/0BAAEBAQEBAgEBA/0BgAEBgQEBggEBg/0CAAECAQECAgECA/0CgAECg\
QECggECg/0DAAEDAQEDAgEDA/0D/AED/QED/gED//2AAAGAAQGAAGGAA/2Ag\
AGAgQGAAGGAg/2BAAGBAQGBAgGBA/2BgAGBgQGBggGBg/2CAAGCAQGCAGGCA\
70  /2CgAGCgQGCGgGCg/2DAAGDAQGDAGGDA/2D/AGD/QGD/gGD//4AAAIQAQIAA\
gIAA/4AgAIAgQIAggIAG/4BAATBAQIBAgIBA/4BgAIBgQIBggIBg/4CAAICA\
QICAgICA/4CgAICgQICggICg/4DAAIDAQIDAgIDA/4D/AID/QID/gID//6AA\
AKAAQKAAGKAA/6AgAKAgQKAggKAg/6BAAKBAQKBAGKBA/6BgAKBgQKBggKBg\
75  /6CAAKCAQKCAGKCA/6CgAKCgQKCggKCg/6DAAKDAQKDAGKDA/6D/AKD/QKD/\
gKD//8AAAMAAQMAAGMAA/8AgAMAgQMAGgMAG/8BAAMBAAQMBAGMBA/8BgAMBg\
QMBggMBg/8CAAMCAQMCAGMCA/8CgAMCgQMCggMCg/8DAAMDAQMDAGMDA/8D/\
AMD/QMD/gMD///9AAP8AQFP8AgP8A//8gAP8gQFP8ggP8g//9AAP9AQFP9AgP9A\
//9gAP9gQFP9ggP9g//+AAP+AQF+AgP+A//+gAP+gQP+ggP+g//AAP/AQF/A\
80  gP/A////AP//QP//gP///yH5BAEAP8ALAAAAAUABQAAAhLAP8JHEiwMGD\
AhIqXCjgoECGEB3+g8hQ4kSKCS1epKhxY0WLGBtKDCKs4UKPJQt+9GhSocqM\
L112RDmT5syVGnHm1FmTZ82fBAMCADs=\

```

```
set Polygon {\n
R01G0DlhFAAUAPCAAAAAAAAAQAAAgAAA/wAgAAAgQAAggAAg/wBAAABAQABA\
5   gABA/wBgAABgQABggABg/wCAAACAQACAgACA/wCgAACgQACggACg/wDAAADA\
   QADAgADA/wD/AAD/QAD/gAD//yAAACAAQCAAgCAA/yAgACAgQCAggCag/yBA\
   ACBAQCBAgCBA/yBgACBgQCBggCBg/yCAACCAQCCAgCCA/yCgACCgQCCggCCg\
   /yDAACDAQCDagCDA/yD/ACD/QCD/gCD//0AAAEAAQEAAgEAA/0AgAEAgQEAg\
   gEAg/0BAAEBAQEBAgEBA/0BgAEBgQEBggEBg/0CAAECAQECAgECA/0CgAECg\
10  QECggECg/0DAAEDAQEDAgEDA/0D/AED/QED/gED//2AAAGAAQGAAGGAA/2Ag\
   AGAgQGAggGAg/2BAAGBAQGBAgGBA/2BgAGBgQGBggGBg/2CAAGCAQGCAGGCA\
   /2CgAGCgQGCggGCg/2DAAGDAQGDAGGDA/2D/AGD/QGD/gGD//4AAATAAQIAA\
   gIAA/4AgAIAgQIAGgIAG/4BAATBAQIBAgIBA/4BgAIBgQIBggIBg/4CAATICA\
   QICAgICA/4CgAICgQICggICg/4DAAIDAQIDAgIDA/4D/AID/QID/gID//6AA\
15  AKAAQKAAGKAA/6AgAKAgQKAggKAg/6BAAKBAQKBAGKBA/6BgAKBgQKBggKBg\
   /6CAAKCAQKCAgKCA/6CgAKCgQKCggKCg/6DAAKDAQKDAgKDA/6D/AKD/QKD/\
   gKD//8AAAMAAQMAAGMAA/8AgAMAgQMAggMAg/8BAAMBAQMBAGMBA/8BgAMBg\
   QMBggMBg/8CAAMCAQMCAGMCA/8CgAMCgQMCggMCg/8DAAMDAQMDAGMDA/8D/\
20  AMD/QMD/gMD///8AAP8AQF8AgP8A//8gAP8gQP8ggP8g//9AAP9AQP9AgP9A\
   //9gAP9gQP9ggP9g//+AAP+AQF+AgP+A//+gAP+gQP+ggP+g///AAP/AQP/A\
   gP/A////AP//QP//gP///yH5BAEAAP8ALAAAAAUABQAAAhPAP8JHEIwoMGD\
   CA8KWJhQ4cKHAhoOhEhxKOCFSlWxHhRoMaOHIma1Fjw4UiIDkuCPCnynOmJ\
   F1/CjChZs2GGyWgVikTpU6LLX8KHxowIAA7\
}\n
25  set Point {\n
R01G0DlhFAAUAPCAAAAAAAAAQAAAgAAA/wAgAAAgQAAggAAg/wBAAABAQABA\
   gABA/wBgAABgQABggABg/wCAAACAQACAgACA/wCgAACgQACggACg/wDAAADA\
30  QADAgADA/wD/AAD/QAD/gAD//yAAACAAQCAAgCAA/yAgACAgQCAggCag/yBA\
   ACBAQCBAgCBA/yBgACBgQCBggCBg/yCAACCAQCCAgCCA/yCgACCgQCCggCCg\
   /yDAACDAQCDagCDA/yD/ACD/QCD/gCD//0AAAEAAQEAAgEAA/0AgAEAgQEAg\
   gEAg/0BAAEBAQEBAgEBA/0BgAEBgQEBggEBg/0CAAECAQECAgECA/0CgAECg\
35  QECggECg/0DAAEDAQEDAgEDA/0D/AED/QED/gED//2AAAGAAQGAAGGAA/2Ag\
   AGAgQGAggGAg/2BAAGBAQGBAgGBA/2BgAGBgQGBggGBg/2CAAGCAQGCAGGCA\
   /2CgAGCgQGCggGCg/2DAAGDAQGDAGGDA/2D/AGD/QGD/gGD//4AAATAAQIAA\
   gIAA/4AgAIAgQIAGgIAG/4BAATBAQIBAgIBA/4BgAIBgQIBggIBg/4CAATICA\
   QICAgICA/4CgAICgQICggICg/4DAAIDAQIDAgIDA/4D/AID/QID/gID//6AA\
40  AKAAQKAAGKAA/6AgAKAgQKAggKAg/6BAAKBAQKBAGKBA/6BgAKBgQKBggKBg\
   /6CAAKCAQKCAgKCA/6CgAKCgQKCggKCg/6DAAKDAQKDAgKDA/6D/AKD/QKD/\
   gKD//8AAAMAAQMAAGMAA/8AgAMAgQMAggMAg/8BAAMBAQMBAGMBA/8BgAMBg\
   QMBggMBg/8CAAMCAQMCAGMCA/8CgAMCgQMCggMCg/8DAAMDAQMDAGMDA/8D/\
45  AMD/QMD/gMD///8AAP8AQF8AgP8A//8gAP8gQP8ggP8g//9AAP9AQP9AgP9A\
   //9gAP9gQP9ggP9g//+AAP+AQF+AgP+A//+gAP+gQP+ggP+g///AAP/AQP/A\
   gP/A////AP//QP//gP///yH5BAEAAP8ALAAAAAUABQAAAgVAP8JHEIwoMGD\
   CBMqXMiwoCOHEBkKmAhhxosWHFik6zCigosaIEOKHEmYpMmBAQEAOw==\
}\n
set Color {\n
R01G0DlhFAAUAPCAAAAAAAAAQAAAgAAA/wAgAAAgQAAggAAg/wBAAABAQABA\
50  gABA/wBgAABgQABggABg/wCAAACAQACAgACA/wCgAACgQACggACg/wDAAADA\
   QADAgADA/wD/AAD/QAD/gAD//yAAACAAQCAAgCAA/yAgACAgQCAggCag/yBA\
   ACBAQCBAgCBA/yBgACBgQCBggCBg/yCAACCAQCCAgCCA/yCgACCgQCCggCCg\
   /yDAACDAQCDagCDA/yD/ACD/QCD/gCD//0AAAEAAQEAAgEAA/0AgAEAgQEAg\
55  gEAg/0BAAEBAQEBAgEBA/0BgAEBgQEBggEBg/0CAAECAQECAgECA/0CgAECg\
   QECggECg/0DAAEDAQEDAgEDA/0D/AED/QED/gED//2AAAGAAQGAAGGAA/2Ag\
   AGAgQGAggGAg/2BAAGBAQGBAgGBA/2BgAGBgQGBggGBg/2CAAGCAQGCAGGCA\
   /2CgAGCgQGCggGCg/2DAAGDAQGDAGGDA/2D/AGD/QGD/gGD//4AAATAAQIAA\
   gIAA/4AgAIAgQIAGgIAG/4BAATBAQIBAgIBA/4BgAIBgQIBggIBg/4CAATICA\
60  QICAgICA/4CgAICgQICggICg/4DAAIDAQIDAgIDA/4D/AID/QID/gID//6AA\
   AKAAQKAAGKAA/6AgAKAgQKAggKAg/6BAAKBAQKBAGKBA/6BgAKBgQKBggKBg\
   /6CAAKCAQKCAgKCA/6CgAKCgQKCggKCg/6DAAKDAQKDAgKDA/6D/AKD/QKD/\
   gKD//8AAAMAAQMAAGMAA/8AgAMAgQMAggMAg/8BAAMBAQMBAGMBA/8BgAMBg\
   QMBggMBg/8CAAMCAQMCAGMCA/8CgAMCgQMCggMCg/8DAAMDAQMDAGMDA/8D/\
65  AMD/QMD/gMD///8AAP8AQF8AgP8A//8gAP8gQP8ggP8g//9AAP9AQP9AgP9A\
   //9gAP9gQP9ggP9g//+AAP+AQF+AgP+A//+gAP+gQP+ggP+g///AAP/AQP/A\
   gP/A////AP//QP//gP///yH5BAEAAP8ALAAAAAUABQAAAhPAP8JHEIwoEEB\
   CBMqXJhQoACD/xBCfBhx4sOLFSLCjxoEOLGUNWPLiRoEaQDGO5FPhyoEaG\
   MBU6jEnzI8mUEU/1lLjTpsqGKXWG5DnU50igGYUGLXry5tCKNGFCnGowIAA7\
}\n
70  set Line {\n
R01G0DlhFAAUAPCAAAAAAAAAQAAAgAAA/wAgAAAgQAAggAAg/wBAAABAQABA\
   gABA/wBgAABgQABggABg/wCAAACAQACAgACA/wCgAACgQACggACg/wDAAADA\
75  QADAgADA/wD/AAD/QAD/gAD//yAAACAAQCAAgCAA/yAgACAgQCAggCag/yBA\
   ACBAQCBAgCBA/yBgACBgQCBggCBg/yCAACCAQCCAgCCA/yCgACCgQCCggCCg\
   /yDAACDAQCDagCDA/yD/ACD/QCD/gCD//0AAAEAAQEAAgEAA/0AgAEAgQEAg\
   gEAg/0BAAEBAQEBAgEBA/0BgAEBgQEBggEBg/0CAAECAQECAgECA/0CgAECg\
80  QECggECg/0DAAEDAQEDAgEDA/0D/AED/QED/gED//2AAAGAAQGAAGGAA/2Ag\
   AGAgQGAggGAg/2BAAGBAQGBAgGBA/2BgAGBgQGBggGBg/2CAAGCAQGCAGGCA\
   /2CgAGCgQGCggGCg/2DAAGDAQGDAGGDA/2D/AGD/QGD/gGD//4AAATAAQIAA\
   gIAA/4AgAIAgQIAGgIAG/4BAATBAQIBAgIBA/4BgAIBgQIBggIBg/4CAATICA\
}
```

Appendix 2

```
QICAgICA/4CgAICgQICggICg/4DAAIDAQIDAgIDA/4D/AID/QID/gID//6AA\
AKAAQKAAGKAA/6AgAKAgQKAggKAg/6BAAKBAQKBAGKBA/6BgAKBgQKBggKBg\
/6CAAKCAQKCAgKCA/6CgAKCgQKAggKAg/6DAAKDAQKDAgKDA/6D/AKD/QKD/\
gKD//8AAAMAAQMAAgMAA/8AgAMAgQMAggMAg/8BAAMBAQMBAGMBA/8BgAMBg\
5 QMBggMBg/8CAAMCAQMCAGMCA/8CgAMCgQMCggMCg/8DAAMDAQMDAGMDA/8D/\
AMD/QMD/gMD///8AAP8AQF8AgP8A//8gAP8gQP8ggP8g//9AAP9AQF9AgP9A\
//9gAP9gQP9ggP9g//+AAP+AQF+AgP+A//+gAP+gQP+ggP+g///AAP/AQP/A\
gP/A///AP//QP//gP///yH5BAEAP8ALAAAAAUABQAAAg/AP8JHEIwoMGD\
10 CEMmFMBQoUGGEB0ShNhQokCKAiz+w6gxosaNFTuGtOhRZMaPJrlyJEKRZUuT\
IyWm/EizpsCAADs=\
)
```

```
set Cut (\
```

```
15 R01GODlhFAAUAPCAAAAAAAQAAAgAAA/wAgAAAgQAAGgAAg/wBAAABAQABA\
gABA/wBgAABgQABggABg/wCAACAQACAgACA/wCgAACgQACggACg/wDAAADA\
QADAgADA/wD/AAD/QAD/gAD//yAAACAAQCAAgCAA/yAgACAgQCAggCAG/yBA\
ACBAQCBAGCBA/yBgACBgQCBggCBg/yCAACCAQCCAgCCA/yCgACCgQCCggCCg\
/yDAACDAQCDAGCDA/yD/ACD/QCD/gCD//0AAAEAAQEAAGAAA/0AgAEAgQEAg\
gEAg/0BAAEBAQEBAgEBA/0BgAEBgQEBggEBg/0CAAECAQECAgECA/0CgAECg\
20 QECggECg/0DAAEDAQEDAgEDA/0D/AED/QED/gED//2AAAGAAQGAAGGAA/2Ag\
AGAgQGAggGAg/2BAAGBAQGBAgGBA/2BgAGBgQGBggGBg/2CAAGCAQGCAGGCA\
/2CgAGCgQGCggGCg/2DAAGDAQGDAGGDA/2D/AGD/QGD/gGD//4AAIAAQIAA\
gIAA/4AgAIAgQIAggIAG/4BAAIBAQIBAgIBA/4BgAIBgQIBggIBg/4CAATCA\
QICAgICA/4CgAICgQICggICg/4DAAIDAQIDAgIDA/4D/AID/QID/gID//6AA\
25 AKAAQKAAGKAA/6AgAKAgQKAggKAg/6BAAKBAQKBAGKBA/6BgAKBgQKBggKBg\
/6CAAKCAQKCAgKCA/6CgAKCgQKAggKAg/6DAAKDAQKDAgKDA/6D/AKD/QKD/\
gKD//8AAAMAAQMAAgMAA/8AgAMAgQMAggMAg/8BAAMBAQMBAGMBA/8BgAMBg\
QMBggMBg/8CAAMCAQMCAGMCA/8CgAMCgQMCggMCg/8DAAMDAQMDAGMDA/8D/\
AMD/QMD/gMD///8AAP8AQF8AgP8A//8gAP8gQP8ggP8g//9AAP9AQF9AgP9A\
30 //9gAP9gQP9ggP9g//+AAP+AQF+AgP+A//+gAP+gQP+ggP+g///AAP/AQP/A\
gP/A///AP//QP//gP///yH5BAEAP8ALAAAAAUABQAAAg/AP8JHEIwoMGD\
CA0ETPhPADIGChs6FCAQ4UOKC1C1I1RIMECHweGBDKr48iFF09mLHxcIk1w\
LV16dBHtpssLSNSNyVDkzJs+bEIF2rFgS5caiK33mNEp0qM6Ng0GBAA7\
)
```

```
35 set PointerSingle (\
```

```
R01GODlhFAAUAPCAAAAAAAQAAAgAAA/wAgAAAgQAAGgAAg/wBAAABAQABA\
gABA/wBgAABgQABggABg/wCAACAQACAgACA/wCgAACgQACggACg/wDAAADA\
40 QADAgADA/wD/AAD/QAD/gAD//yAAACAAQCAAgCAA/yAgACAgQCAggCAG/yBA\
ACBAQCBAGCBA/yBgACBgQCBggCBg/yCAACCAQCCAgCCA/yCgACCgQCCggCCg\
/yDAACDAQCDAGCDA/yD/ACD/QCD/gCD//0AAAEAAQEAAGAAA/0AgAEAgQEAg\
gEAg/0BAAEBAQEBAgEBA/0BgAEBgQEBggEBg/0CAAECAQECAgECA/0CgAECg\
QECggECg/0DAAEDAQEDAgEDA/0D/AED/QED/gED//2AAAGAAQGAAGGAA/2Ag\
AGAgQGAggGAg/2BAAGBAQGBAgGBA/2BgAGBgQGBggGBg/2CAAGCAQGCAGGCA\
45 /2CgAGCgQGCggGCg/2DAAGDAQGDAGGDA/2D/AGD/QGD/gGD//4AAIAAQIAA\
gIAA/4AgAIAgQIAggIAG/4BAAIBAQIBAgIBA/4BgAIBgQIBggIBg/4CAATCA\
QICAgICA/4CgAICgQICggICg/4DAAIDAQIDAgIDA/4D/AID/QID/gID//6AA\
AKAAQKAAGKAA/6AgAKAgQKAggKAg/6BAAKBAQKBAGKBA/6BgAKBgQKBggKBg\
/6CAAKCAQKCAgKCA/6CgAKCgQKAggKAg/6DAAKDAQKDAgKDA/6D/AKD/QKD/\
50 gKD//8AAAMAAQMAAgMAA/8AgAMAgQMAggMAg/8BAAMBAQMBAGMBA/8BgAMBg\
QMBggMBg/8CAAMCAQMCAGMCA/8CgAMCgQMCggMCg/8DAAMDAQMDAGMDA/8D/\
AMD/QMD/gMD///8AAP8AQF8AgP8A//8gAP8gQP8ggP8g//9AAP9AQF9AgP9A\
//9gAP9gQP9ggP9g//+AAP+AQF+AgP+A//+gAP+gQP+ggP+g///AAP/AQP/A\
55 gP/A///AP//QP//gP///yH5BAEAP8ALAAAAAUABQAAAg/AP8JHEIwoMGD\
AhIKOMhQcUKGBh0mhFhQ4kKBBliJHxY8aOHgVODDlWJm1/JkmmDLnSY8uN\
LyFadGkrPeyJKh+ejPkVIAA7\
)
```

```
set SelectHollow (\
```

```
60 R01GODlhFAAUAPCAAAAAAAQAAAgAAA/wAgAAAgQAAGgAAg/wBAAABAQABA\
gABA/wBgAABgQABggABg/wCAACAQACAgACA/wCgAACgQACggACg/wDAAADA\
QADAgADA/wD/AAD/QAD/gAD//yAAACAAQCAAgCAA/yAgACAgQCAggCAG/yBA\
ACBAQCBAGCBA/yBgACBgQCBggCBg/yCAACCAQCCAgCCA/yCgACCgQCCggCCg\
65 /yDAACDAQCDAGCDA/yD/ACD/QCD/gCD//0AAAEAAQEAAGAAA/0AgAEAgQEAg\
gEAg/0BAAEBAQEBAgEBA/0BgAEBgQEBggEBg/0CAAECAQECAgECA/0CgAECg\
QECggECg/0DAAEDAQEDAgEDA/0D/AED/QED/gED//2AAAGAAQGAAGGAA/2Ag\
AGAgQGAggGAg/2BAAGBAQGBAgGBA/2BgAGBgQGBggGBg/2CAAGCAQGCAGGCA\
/2CgAGCgQGCggGCg/2DAAGDAQGDAGGDA/2D/AGD/QGD/gGD//4AAIAAQIAA\
gIAA/4AgAIAgQIAggIAG/4BAAIBAQIBAgIBA/4BgAIBgQIBggIBg/4CAATCA\
70 QICAgICA/4CgAICgQICggICg/4DAAIDAQIDAgIDA/4D/AID/QID/gID//6AA\
AKAAQKAAGKAA/6AgAKAgQKAggKAg/6BAAKBAQKBAGKBA/6BgAKBgQKBggKBg\
/6CAAKCAQKCAgKCA/6CgAKCgQKAggKAg/6DAAKDAQKDAgKDA/6D/AKD/QKD/\
gKD//8AAAMAAQMAAgMAA/8AgAMAgQMAggMAg/8BAAMBAQMBAGMBA/8BgAMBg\
QMBggMBg/8CAAMCAQMCAGMCA/8CgAMCgQMCggMCg/8DAAMDAQMDAGMDA/8D/\
75 AMD/QMD/gMD///8AAP8AQF8AgP8A//8gAP8gQP8ggP8g//9AAP9AQF9AgP9A\
//9gAP9gQP9ggP9g//+AAP+AQF+AgP+A//+gAP+gQP+ggP+g///AAP/AQP/A\
gP/A///AP//QP//gP///yH5BAEAP8ALAAAAAUABQAAAhUAP8JHEIwoMGD\
AhIqXCjgoECGB3+S4iwoUSFBSlKnKjxocWNHTluFKKcxEGKCOU6RnmQ5cqW\
H1OehJnRJmPi1209Khy06fNHc+7CkUo9CjDgMCADs=\
80 )
```

[illegible]


```
R01G0D1hFAAUAPcAAAAAAAAQAAgAAA/wAgAAAgQAAGgAAg/wBAAABAQABA\
gABA/wBgAABgQABggABg/wCAACAQACAgACA/wCgAACgQACggACg/wDAAADA\
QADAgADA/wD/AAD/QAD/gAD//yAAACAAQCAAgCAA/yAgACAgQCAGgCAG/yBA\
ACBAQCBAGCBA/yBgACBgQCBggCBg/yCAACCAQCCAgCCA/yCgACCGQCCggCCg\
/yDAACDAQCDAGCDA/yD/ACD/QCD/gCD//0AAAEAAQEAAGAAA/0AgAEAgQEAg\
gEAg/0BAAEBAQEBAgEBA/0BgAEBgQEBggEBg/0CAAECAQECAGECA/0CgAECg\
QECggECg/0DAAEDAQEDAgEDA/0D/AED/QED/gED//2AAAGAAQGAAGGAA/2Ag\
AGAgQGAggGAg/2BAAGBAQGBAgGBA/2BgAGBgQGBggGBg/2CAAGCAQGCAGGCA\
/2CgAGCGQGCggGCg/2DAAGDAQGDAGGDA/2D/AGD/QGD/gGD//4AAATIAAQIAA\
gIAA/4AgAIAgQIAggIAG/4BAATIBAQIBAgIBA/4BgAIBgQIBggIBg/4CAATICA\
QICAgICA/4CgAICgQICggICg/4DAAIDAQIDAgIDA/4D/AID/QID/gID//6AA\
AKAAQKAAGKAA/6AgAKAgQKAggKAg/6BAAKBAQKBAGKBA/6BgAKBgQKBggKBg\
/6CAAKCAQKCAgKCA/6CgAKCgQKCggKCg/6DAAKDAQKDAGKDA/6D/AKD/QKD/\
gKD//8AAAMAAQMAAGMAA/8AgAMAgQMAggMAG/8BAAMBAQMBAGMBA/8BgAMBg\
QMBggMBg/8CAAMCAQMCAGMCA/8CgAMCgQMCggMCg/8DAAMDAQMDAGMDA/8D/\
AMD/QMD/gMD///8AAP8AQ8AgP8A//8gAP8gQP8ggP8g//9AAP9AQ9AgP9A\
//9gAP9gQP9ggP9g//+AAP+AQp+AgP+A//+gAP+gQP+ggP+g///AAP/AQP/A\
gP/A////AP//QP//gP///yH5BAEAP8ALAAAAAAUABQAAAhPAP8JFChgoEGC\
BxmQKDiw4EKHDCM+ZAIroICLGC8axdHgwI8eGGTuGB0lRpmOTHISiNDlyosWP\
EknGVKJyYcmYLzXiFlITZs+VF//VDKowIAA7\
)

set Move {\
R01G0D1hFAAUAPcAAAAAAAAQAAgAAA/wAgAAAgQAAGgAAg/wBAAABAQABA\
gABA/wBgAABgQABggABg/wCAACAQACAgACA/wCgAACgQACggACg/wDAAADA\
QADAgADA/wD/AAD/QAD/gAD//yAAACAAQCAAgCAA/yAgACAgQCAGgCAG/yBA\
ACBAQCBAGCBA/yBgACBgQCBggCBg/yCAACCAQCCAgCCA/yCgACCGQCCggCCg\
/yDAACDAQCDAGCDA/yD/ACD/QCD/gCD//0AAAEAAQEAAGAAA/0AgAEAgQEAg\
gEAg/0BAAEBAQEBAgEBA/0BgAEBgQEBggEBg/0CAAECAQECAGECA/0CgAECg\
QECggECg/0DAAEDAQEDAgEDA/0D/AED/QED/gED//2AAAGAAQGAAGGAA/2Ag\
AGAgQGAggGAg/2BAAGBAQGBAgGBA/2BgAGBgQGBggGBg/2CAAGCAQGCAGGCA\
/2CgAGCGQGCggGCg/2DAAGDAQGDAGGDA/2D/AGD/QGD/gGD//4AAATIAAQIAA\
gIAA/4AgAIAgQIAggIAG/4BAATIBAQIBAgIBA/4BgAIBgQIBggIBg/4CAATICA\
QICAgICA/4CgAICgQICggICg/4DAAIDAQIDAgIDA/4D/AID/QID/gID//6AA\
AKAAQKAAGKAA/6AgAKAgQKAggKAg/6BAAKBAQKBAGKBA/6BgAKBgQKBggKBg\
/6CAAKCAQKCAgKCA/6CgAKCgQKCggKCg/6DAAKDAQKDAGKDA/6D/AKD/QKD/\
gKD//8AAAMAAQMAAGMAA/8AgAMAgQMAggMAG/8BAAMBAQMBAGMBA/8BgAMBg\
QMBggMBg/8CAAMCAQMCAGMCA/8CgAMCgQMCggMCg/8DAAMDAQMDAGMDA/8D/\
AMD/QMD/gMD///8AAP8AQ8AgP8A//8gAP8gQP8ggP8g//9AAP9AQ9AgP9A\
//9gAP9gQP9ggP9g//+AAP+AQp+AgP+A//+gAP+gQP+ggP+g///AAP/AQP/A\
gP/A////AP//QP//gP///yH5BAEAP8ALAAAAAAUABQAAAhVAP8JHDhQgACC\
CBMKNghQoUOGDB0ihahrIKGKBy1OzGiR40KF/0BGLOhxZEiTy9GxdiypcuX\
JxuSVCKzpkqazEfm1Fht48eKPlv6jImSZ9GgIAKGBAA7\
)

set Code {\
R01G0D1hFAAUAPcAAAAAAAAQAAgAAA/wAgAAAgQAAGgAAg/wBAAABAQABA\
gABA/wBgAABgQABggABg/wCAACAQACAgACA/wCgAACgQACggACg/wDAAADA\
QADAgADA/wD/AAD/QAD/gAD//yAAACAAQCAAgCAA/yAgACAgQCAGgCAG/yBA\
ACBAQCBAGCBA/yBgACBgQCBggCBg/yCAACCAQCCAgCCA/yCgACCGQCCggCCg\
/yDAACDAQCDAGCDA/yD/ACD/QCD/gCD//0AAAEAAQEAAGAAA/0AgAEAgQEAg\
gEAg/0BAAEBAQEBAgEBA/0BgAEBgQEBggEBg/0CAAECAQECAGECA/0CgAECg\
QECggECg/0DAAEDAQEDAgEDA/0D/AED/QED/gED//2AAAGAAQGAAGGAA/2Ag\
AGAgQGAggGAg/2BAAGBAQGBAgGBA/2BgAGBgQGBggGBg/2CAAGCAQGCAGGCA\
/2CgAGCGQGCggGCg/2DAAGDAQGDAGGDA/2D/AGD/QGD/gGD//4AAATIAAQIAA\
gIAA/4AgAIAgQIAggIAG/4BAATIBAQIBAgIBA/4BgAIBgQIBggIBg/4CAATICA\
QICAgICA/4CgAICgQICggICg/4DAAIDAQIDAgIDA/4D/AID/QID/gID//6AA\
AKAAQKAAGKAA/6AgAKAgQKAggKAg/6BAAKBAQKBAGKBA/6BgAKBgQKBggKBg\
/6CAAKCAQKCAgKCA/6CgAKCgQKCggKCg/6DAAKDAQKDAGKDA/6D/AKD/QKD/\
gKD//8AAAMAAQMAAGMAA/8AgAMAgQMAggMAG/8BAAMBAQMBAGMBA/8BgAMBg\
QMBggMBg/8CAAMCAQMCAGMCA/8CgAMCgQMCggMCg/8DAAMDAQMDAGMDA/8D/\
AMD/QMD/gMD///8AAP8AQ8AgP8A//8gAP8gQP8ggP8g//9AAP9AQ9AgP9A\
//9gAP9gQP9ggP9g//+AAP+AQp+AgP+A//+gAP+gQP+ggP+g///AAP/AQP/A\
gP/A////AP//QP//gP///yH5BAEAP8ALAAAAAAUABQAAAhTAP8JHEIwMGD\
CBMqRChAwMCGBCEDWPiPySWHAILm3MjxokeMHY1S10hrJREiSFUVKTLmwpCuF\
K1l1mRN1xJEiDJKMyPHLzIs+OEVCkjfmyqNGXAKQEAOW==\
)

set PointerMultiple {\
R01G0D1hFAAUAPcAAAAAAAAQAAgAAA/wAgAAAgQAAGgAAg/wBAAABAQABA\
gABA/wBgAABgQABggABg/wCAACAQACAgACA/wCgAACgQACggACg/wDAAADA\
QADAgADA/wD/AAD/QAD/gAD//yAAACAAQCAAgCAA/yAgACAgQCAGgCAG/yBA\
ACBAQCBAGCBA/yBgACBgQCBggCBg/yCAACCAQCCAgCCA/yCgACCGQCCggCCg\
/yDAACDAQCDAGCDA/yD/ACD/QCD/gCD//0AAAEAAQEAAGAAA/0AgAEAgQEAg\
gEAg/0BAAEBAQEBAgEBA/0BgAEBgQEBggEBg/0CAAECAQECAGECA/0CgAECg\
QECggECg/0DAAEDAQEDAgEDA/0D/AED/QED/gED//2AAAGAAQGAAGGAA/2Ag\
AGAgQGAggGAg/2BAAGBAQGBAgGBA/2BgAGBgQGBggGBg/2CAAGCAQGCAGGCA\
/2CgAGCGQGCggGCg/2DAAGDAQGDAGGDA/2D/AGD/QGD/gGD//4AAATIAAQIAA\
gIAA/4AgAIAgQIAggIAG/4BAATIBAQIBAgIBA/4BgAIBgQIBggIBg/4CAATICA\
QICAgICA/4CgAICgQICggICg/4DAAIDAQIDAgIDA/4D/AID/QID/gID//6AA\
AKAAQKAAGKAA/6AgAKAgQKAggKAg/6BAAKBAQKBAGKBA/6BgAKBgQKBggKBg\
/6CAAKCAQKCAgKCA/6CgAKCgQKCggKCg/6DAAKDAQKDAGKDA/6D/AKD/QKD/\
gKD//8AAAMAAQMAAGMAA/8AgAMAgQMAggMAG/8BAAMBAQMBAGMBA/8BgAMBg\
QMBggMBg/8CAAMCAQMCAGMCA/8CgAMCgQMCggMCg/8DAAMDAQMDAGMDA/8D/\
AMD/QMD/gMD///8AAP8AQ8AgP8A//8gAP8gQP8ggP8g//9AAP9AQ9AgP9A\
//9gAP9gQP9ggP9g//+AAP+AQp+AgP+A//+gAP+gQP+ggP+g///AAP/AQP/A\
gP/A////AP//QP//gP///yH5BAEAP8ALAAAAAAUABQAAAhTAP8JHEIwMGD\
CBMqRChAwMCGBCEDWPiPySWHAILm3MjxokeMHY1S10hrJREiSFUVKTLmwpCuF\
K1l1mRN1xJEiDJKMyPHLzIs+OEVCkjfmyqNGXAKQEAOW==\
}
```

```

/6CAAKCAQKCAgKCA/6CgAKCgQKCgKCg/6DAAKDAQKDAgKDA/6D/AKD/QKD/\
gKD//8AAAMAAQMAAgMAA/8AgAMAgQMAggMAg/8BAAMBAQMBAgMBA/8BgAMBg\
QMBggMBg/8CAAMCAQMCAGMCA/8CgAMCgQMCggMCg/8DAAMDAQMDAgMDA/8D/\
AMD/QMD/gMD//8AAP8AQF8AgP8A//8gAP8gQP8ggP8g//9AAP9AQF9AgP9A\
5 //9gAP9gQP9ggP9g//+AAP+AQF+AgP+A//+gAP+gQP+ggP+g///AAP/AQF/A\
gP/A///AP//QP//gP///yH5BAEAAP8ALAAAAAUABQAAAhYAP8JHEiwoEGB\
AhIKMKhwIcGGCR9C1NiQokKLEQdCdKjxYsGKDD1+FCnx4L+MTU2iHKmSZMeW\
MA+uLCnTJUKbJ3HOEdkS5E2fGzMG5bgRI0mfHXfmjCkwIAA7\
}
10 set iconList [list SelectSolid Polygon Point Color Line Cut PointerSingle SelectHollow Symbol Circle
Rectangle Blank Copy Pin PointerHead Move Code PointerMultiple ]
}
iat.antsvg.txt
15 # Copyright (c) 2001, University of Utah
# All rights reserved.
#
# iat.antsvg.tcl

20 namespace eval iat::ant {
}

# NOTE!!!
# Modelled after the iat::roi::roiDraw* functions
25 proc iat::ant::midpoint { pt1 pt2 } {
    set x1 [lindex $pt1 0]
    set y1 [lindex $pt1 1]
    set x2 [lindex $pt2 0]
    30 set y2 [lindex $pt2 1]
    set x3 [expr round( ($x1+$x2)/2 )]
    set y3 [expr round( ($y1+$y2)/2 )]
    return [list $x3 $y3]
}
35 proc iat::ant::smoothpoly { type pts } {
    set lstpt [lindex $pts end]
    set flip 0
    40 foreach pt $pts {
        set mid [midpoint $lstpt $pt]
        set q1 [midpoint $lstpt $mid]
        set q2 [midpoint $mid $pt]
        lappend tmps [join $q1 ","]
        45 lappend tmps [join $mid ","]
        lappend tmps [join $q2 ","]
        #lappend tmps [join $pt ","]
        set lstpt $pt
    }
    50 set s [lindex $tmps 0]
    set tmps [lreplace $tmps 0 0]
    lappend tmps $s
    set s [lindex $tmps 0]
    lappend tmps $s
    55 set s "M[lindex $tmps 0]"
    set tmps [lreplace $tmps 0 0 $s]
    set s "C[lindex $tmps 1]"
    set tmps [lreplace $tmps 1 1 $s]

    60 # doctor for edge...
    if {$type == "edge"} {
        set s "M[lindex $tmps 3]"
        set tmps [lreplace $tmps 0 3 $s]
        set tmps [lreplace $tmps end end]
        65 set tmps [lreplace $tmps end end]
    }

    return $tmps
}
70 proc iat::ant::ant_make_svg_pointer { ns ptnum lvl } {
    variable TRACE
    if {$TRACE} { puts "iat::ant::ant_make_svg_pointer: $ns $ptnum $lvl" }

    75 variable antkey
    variable order
    variable points
    variable heads
    variable verts
    80 variable tails
    variable dSYMS

```

```

variable dPTRs
variable kind
variable code
variable symbol
5 variable label

variable color
variable linecolor
variable fillcolor
10 variable symbolFont
variable px1

#variable styleFontSmall
#variable styleFontDefault
15 #variable styleFontLarge

upvar #0 [join [list [namespace current] $ns canvas] ::] canvas
upvar #0 [join [list [namespace current] $ns imageX] ::] imageX
upvar #0 [join [list [namespace current] $ns imageY] ::] imageY
20 upvar #0 [join [list [namespace current] $ns offsetX] ::] offsetX
upvar #0 [join [list [namespace current] $ns offsetY] ::] offsetY

#set x1 [expr $x -5]
#set x2 [expr $x +5]
25 #set y1 [expr $y -5]
#set y2 [expr $y +5]
#$canvas create rect $x1 $y1 $x2 $y2 -fill "" -outline yellow -width 2 -tags [list handle $roiKey]

#set bfsz $styleFontDefault
#switch $size {
#   "small" { set bfsz $styleFontSmall}
#   "default" { set bfsz $styleFontDefault }
#   "large" { set bfsz $styleFontLarge }
#}
30 #set bfsz symbolFont
#set fsz [expr round(ceil(((imageX + imageY)/2) * 0.001 * $bfsz ))]
#puts "font size = $fsz"
#font configure symbol -size $fsz

40 set headpt [lindex $points $ptnum]
set tailpt $tails($ptnum)
if {$tailpt == ""} { return }
set draw_symbol $dSYMs($ptnum)
set draw_style $dPTRs($ptnum)
45

set ptrlen [lindex [x2pts_length $headpt $tailpt] 0]
if {[llength $verts($ptnum)] > 0} {
    set angle [x2pts_angle $headpt [lindex $verts($ptnum) 0]]
} else {
50     set angle [x2pts_angle $headpt $tailpt]
}

set svgorder iat-$order; append svgorder -pointer$ptnum
set p "p"; set h "h"
55 #set svgorder2 $order; append svgorder2 head-$ptnum

set x [lindex $headpt 0]
set y [lindex $headpt 1]
set pinfo [create_pointer $ns $draw_style $ptrlen]
60 if {$pinfo == -1} { return }
if {[llength $pinfo] > 1} {
    set hppts $pinfo
    set sub 0
    if {$sub == 1} {
65         set tmpa [x2pts_angle $headpt $tailpt]
        #puts "tmp angle = $tmpa"
        set ppts [points_rotate $tmpa $ppts]
        set ppts [points_translate_lst $x $y $ppts]
        #$canvas create line "$pointerPoint $symbolPoint" -width 2 -fill blue -tags [list adorer
70 key$roiKey]
    } else {
        set hppts [points_rotate $angle $hppts]
        set hppts [points_translate_lst $x $y $hppts]
    }
75     set tmps [list]
    lappend tmps $headpt
    set tmps [concat $tmps $verts($ptnum)]
    lappend tmps $tailpt
    # makeIt breaks down points...
80     set ppts [makeIt $ns $ptnum $tmps]
    foreach {x y} $ppts { lappend tmps1 [list $x $y] }

```

Appendix 2

```

set tmps1 [smoothpoly area $tmps1]
#puts "tmps1 = $tmps1"

set tmps2 $ppts
lappend tmps2 [lindex $tmps2 0] [lindex $tmps2 1]
set tmps2 [join $tmps2]

set tmps3 $hppts
#lappend tmps3 [lindex $tmps3 0] [lindex $tmps3 1]
set tmps3 [join $tmps3]

#$canvas create poly $ppts -smooth true -outline $linecolor -width 1 -fill $fillcolor -tags [list
ant pointer key$antkey]
#append str "<polyline id='test1' style='fill:black; fill-opacity:0; stroke:black; stroke-width:3' "
#append str "points='$tmps2' />\n"
if {$draw_style != "none"} {
    append str "<g id='$svgorder'>\n"
    append str "    <path id='$svgorder$p' style='fill:$fillcolor; fill-opacity:1; stroke:$fillcolor;
stroke-width:3' "
    append str "d='$tmps1' />\n"
    #$canvas create poly $hppts -outline $linecolor -width 1 -fill $fillcolor -tags [list ant
pointer key$antkey]
    append str "    <polygon id='$svgorder$h' style='fill:$fillcolor; fill-opacity:1;
stroke:$fillcolor; stroke-width:3' "
    append str "points='$tmps3' />\n"
    append str "</g>\n"
}, else {
    append str "<g id='$svgorder'>\n"
    append str "</g>\n"
}
}

set xt [lindex $tailpt 0]
set yt [lindex $tailpt 1]
# returns e or w
set gl [iat::ant::gravity_label $angle]
#puts "$angle = $gl"
set dx 0
set dy 0
set ta "middle"
switch $gl {
    "w" { set ta "start"; set dx $pxl }
    "e" { set ta "end"; set dx -$pxl }
    default { set ta "middle" }
}

# interactive visual note "spot"
set svgorder iat-$order; append svgorder -inote$ptnum
#set iszr [expr round(ceil(($imageX + $imageY)/2) * 0.001 * 5)]
append str "<circle id='$svgorder' cx='[expr $xt]' cy='[expr $yt]' r='[expr $pxl]' style='fill:blue;
stroke:white; stroke-width:2px' />\n"

# if {[regexp -nocase {e} $gl]} {
#     set dx [expr round($fsz*([string length $drawtext])/2)]
#     set xt [expr $xt-$dx]
# }
# if {[regexp -nocase {w} $gl]} {
#     set dx [expr round($fsz*([string length $drawtext])/2)]
#     set xt [expr $xt+$dx]
# }

set bfsz $symbolFont
set fsz [expr round(ceil((($imageX + $imageY)/2) * 0.001 * [font configure $bfsz -size] ))]
# temporary fix for minimum font size...
if ($fsz < 12) { set fsz 12 }
append fsz pt
#puts "font size = $fsz"

set svgorder iat-$order; append svgorder -symbol$ptnum

switch $draw_symbol {
    "code" { set txt $code }
    "symbol" { set txt $symbol }
    "label" { set txt $label }
    "none" { set txt "" }
    default { set txt "?" }
}

append str "<text id='$svgorder' x='[expr $xt+$dx]' y='$yt' style='font-size:$fsz; baseline-shift:-25%;
text-anchor:$ta; fill:$fillcolor'>"
append str $txt

```

```

    append str "</text>\n"

    return $str
}
5
proc iat::ant::ant_make_svg_pointers { ns lvl } {
    variable TRACE
    if {$TRACE} { puts "iat::ant::ant_make_svg_pointers: $ns $lvl" }

10    variable heads

    set str ""
    foreach {key value} [array get heads] {
        if {$value == ""} { continue }
15        append str [ant_make_svg_pointer $ns $key $lvl]
    }

    return $str
}
20

proc iat::ant::ant_make_svg_ant { ns {key ""} lvl } {
    variable TRACE
    if {$TRACE} { puts "iat::ant::ant_make_svg_ant: $ns $key $lvl" }

25    variable antkey
    variable order
    variable points
    variable kind
30    variable symbol
    variable label
    variable caption

    variable color
35    variable fillcolor
    variable linecolor

    upvar #0 [join [list [namespace current] $ns canvas] ::] canvas
    upvar #0 [join [list [namespace current] $ns offsetX] ::] offsetX
40    upvar #0 [join [list [namespace current] $ns offsetY] ::] offsetY

    set key [string tolower $key]
    if {$key == ""} { set key $antkey }
    if {$key == "active"} {set key $antkey }
45    if {$key == ""} { return "" }

    #ant_erase $ns $key
    #if {$key != $antkey} { ant_load $ns $key }
    ant_load $ns $key

50    ant_draw_precalc $ns

    set str ""

55    if {$kind == "none"} { return "" }
    if {$kind == "group"} {
        set gtag "<symbol id='$order'>\n"
        append gtag "<title> [STRXML "group label"] </title>\n"
        append gtag "<desc>\n"
60        #append gtag " <symbol> [STRXML "group symbol"] </symbol>\n"
        #append gtag " <label> [STRXML "group label"] </label>\n"
        #append gtag " <caption> [STRXML "group caption"] </caption>\n"
        append gtag "</desc>\n"
        append gtag "</symbol>\n"
65        return $gtag
    }

    set part "all"

70    #onmouseover='target_visible(evt)' onmouseout='target_hidden(evt)'
    switch $part {
        "none" {}
        "pointer" {}
        # all or region
75        default {
            set tmps [smoothpoly $kind $points]

            set tmps2 $points
            lappend tmps2 [lindex $tmps2 0]
80            set tmps2 [join $tmps2]

```

```

set svgorder iat-$order; append svgorder -region
switch $kind {
    "area" {
        append str "<path id='$svgorder' style='fill:$fillcolor; fill-opacity:0;
5 stroke:$fillcolor; stroke-width:3' "
        append str "d='$tmps' />\n"
        #append str "<polyline id='$svgorder-test' style='fill:black; fill-opacity:0;
stroke:black; stroke-width:3' "
        #append str "points='$tmps2' />\n"
10    # $canvas create poly $tmps -outline $fillcolor -width 2 -fill "" -tags [list roi
key$roiKey $order]
    }
    "edge" {
        #set tmps [join $points]
        append str "<path id='$svgorder' style='fill:$fillcolor; fill-opacity:0;
15 stroke:$fillcolor; stroke-width:3' "
        append str "d='$tmps' />\n"
        # $canvas create line $tmps -width 2 -fill $fillcolor -tags [list roi key$roiKey $order]
    }
    # point is default!
    default {
        foreach {x y} $tmps {
            # $canvas create oval [expr $x-6] [expr $y-6] [expr $x+6] [expr $y+6] -outline
25 $fillcolor -width 3 -fill "" -tags [list roi key$roiKey $order]
        }
    }
}
}

set svgorder iat-$order; append svgorder -inote
append str "<g id='$svgorder'></g>\n"

switch $part {
35    "none" {}
    "region" {}
    # all or pointer
    default {
        append str [ant_make_svg_pointers $ns $lvl]
40    }
}

# add 'g' tag for group
set gtag "<symbol>\n"
append gtag "<title> [STRXML $label] </title>\n"
#append gtag "<desc>\n"
set symid iat-$order; append symid -symbol
#append gtag " <symbol id='$symid'> [STRXML $symbol] </symbol>\n"
append gtag " <text id='$symid'> [STRXML $symbol] </text>\n"
50 set lblid iat-$order; append lblid -label
#append gtag " <label id='$lblid'> [STRXML $label] </label>\n"
append gtag " <text id='$lblid'> [STRXML $label] </text>\n"
set capid iat-$order; append capid -caption
#append gtag " <caption id='$capid'> [STRXML $caption] </caption>\n"
55 append gtag " <text id='$capid'> [STRXML $caption] </text>\n"
#append gtag "</desc>\n"
append gtag $str
append gtag "\n</symbol>\n"

60 return $gtag
}

proc iat::ant::ant_make_svg_menu { ns lvl } {
    variable TRACE
65    if {$TRACE} { puts "iat::ant::ant_make_svg_menu: $ns $lvl" }

    variable view

    upvar #0 [join [list [namespace current] $ns orders] ::] orders
    upvar #0 [join [list [namespace current] $ns polys] ::] polys
    upvar #0 [join [list [namespace current] $ns inviews] ::] inviews
    upvar #0 [join [list [namespace current] $ns symbols] ::] symbols
    upvar #0 [join [list [namespace current] $ns labels] ::] labels

75    array set viewArray [list]

    set str ""
    append str "<defs>\n"
    append str " <menu id='NewMenu' xmlns='http://foo' onload='GetPosition( evt )'>\n"
80    #append str " <header>Annotation Menu</header>\n"
    #append str " <separator />\n"

```

Appendix 2

```

append str " <menu>\n"
append str " <header> Annotations </header>\n"
#append str " <separator />\n"
# create by order
5  foreach {key val} [array get orders] { set ord2key($val) $key }
   set ords [array names ord2key]
   set ords [lsort -dictionary $ords]
   set arr [list]
   foreach ord $ords {
10      #append symbols [ant_make_svg_ant $ns $key $lvl]
      set key $ord2key($ord)
      if {[info exists polys($key)]} { continue }
      if { $polys($key) == [list]} { continue }
      lappend arr '\$ord\'
15      set ord $orders($key)
      if {[info exists symbols($key)]} { set sym $symbols($key)
      } else { set sym "?" }
      if {[info exists labels($key)]} { set lbl $labels($key)
      } else { set lbl "?" }
20      set item "menu-$ord"; append item "-annotation"
      append str " <item id='$item' onactivate='antToggleShowAnt($ord,true,true)' checked='yes' >
      $ord&#58; $lbl </item>\n"
      # setup view data too...
      if {[info exists invs($key)]} { set ivs $invs($key)
25      } else { set ivs "" }
      foreach v [split $ivs] {
          if {[info exist viewArray($v)]} {
              set tmp $viewArray($v)
              append tmp ", '\$ord\' "
              set viewArray($v) $tmp
30          } else {
              set tmp '\$ord\' "
              set viewArray($v) $tmp
          }
      }
35      }
      set arr "\[[join $arr ",,"]]"
      append str " </menu>\n"
      append str " <separator />\n"
40      append str " <menu>\n"
      append str " <header>Views</header>\n"
      set iid ""
      if {$view == "ALL"} { set iid "id=\"currentIATView\"" }
      append str " <item $iid onactivate=\"antSetViewText('ALL');antSetShowAll($arr,true,true)\"> ALL
45 </item>\n"
      set iid ""
      if {$view == "NONE"} { set iid "id=\"currentIATView\"" }
      append str " <item $iid onactivate=\"antSetViewText('NONE');antSetShowAll($arr,false,true)\"> NONE
</item>\n"
50      set vws [array names viewArray]
      set vws [lsort -dictionary $vws]
      foreach vw $vws {
          set iid ""
          if {$view == $vw} {
55              set iid "id=\"currentIATView\""
          }
          set varr $viewArray($vw)
          append str " <item $iid
          onactivate=\"antSetViewText('$vw');antSetShowAll($arr,false,false);antSetShowAll(\[$varr\],true,true)\"> $vw
60 </item>\n"
      }
      append str " </menu>\n"
      append str " <separator />\n"
      #append str " <item onactivate=\"antToggleShowAll($arr,true)\"> Toggle </item>\n"
65      #append str " <item onactivate=\"antSetShowAll($arr,true,true)\"> Show </item>\n"
      #append str " <item onactivate=\"antSetShowAll($arr,false,true)\"> Hide </item>\n"
      #append str " <separator />\n"
      append str " <menu>\n"
      append str " <header>Interactivity</header>\n"
70      append str " <item id='menu-mouseovers' onactivate=\"antToggleMouseOverAll($arr,true)\" checked='no' >
      Mouseovers </item>\n"
      append str " </menu>\n"
      append str " <separator />\n"
      append str " <menu>\n"
75      append str " <header>Window</header>\n"
      append str " <item action='ZoomIn'>Zoom &In</item>\n"
      append str " <item action='ZoomOut'>Zoom &Out</item>\n"
      append str " <item action='OriginalView'>&Original View</item>\n"
      append str " <item action='Quality'>Higher &Quality</item>\n"
80      append str " </menu>\n"
      append str " <separator />\n"

```



```

5   append str " <menu>\n"
    append str " <header>About</header>\n"
    append str " <item onactivate='antAbout()'>About Annotations</item>\n"
    append str " <item action='About'>About SVG Viewer</item>\n"
    append str " <item action='ViewSVG'>&View SVG</item>\n"
    append str " <item action='ViewSource'>View Sourc&e</item>\n"
    append str " </menu>\n"
    append str " </defs>\n"
10  return $str
}

proc iat::ant::ant_make_svg_views { ns lvl } {
15  variable TRACE
    if {$TRACE} { puts "iat::ant::ant_make_svg_views: $ns $lvl" }

    #
    # append views in svg <g> tags
    #
20  upvar #0 [join [list [namespace current] $ns orders] ::] orders
    upvar #0 [join [list [namespace current] $ns polys] ::] polys
    upvar #0 [join [list [namespace current] $ns aheads] ::] aheads
    upvar #0 [join [list [namespace current] $ns kinds] ::] kinds
25  upvar #0 [join [list [namespace current] $ns symbols] ::] symbols
    upvar #0 [join [list [namespace current] $ns labels] ::] labels

    #set allords [list]
    #foreach key [array names iat::roi::orders] {
30  #   set ord $iat::roi::orders($key)
    #   set lbl $iat::roi::symbols($key)
    #   set txts($ord) "$ord $lbl"
    #   set kinds($ord) $iat::roi::kinds($key)
    #   set views($ord) $iat::roi::views($key)
35  #   lappend allords $ord
    #}
    #set allords [lsort -dictionary $allords]

    set allords [list]
    foreach {key value} [array get polys] {
40  set ord $orders($key)
    set lbl $symbols($key)
    set txts($ord) "$ord $lbl"
    set aheads($ord) $aheads($key)
45  set kinds($ord) $kinds($key)
    set viws($ord) all
    lappend allords $ord
    }
    set allords [lsort -dictionary $allords]
50  #puts " allords = $allords"

    #set viewNames [array names viewData]
    #set viewNames [lsort -dictionary $viewNames]
    set viewNames [list]
    set viewNames [concat [list NONE ALL] $viewNames]
55  #puts "viewNames = $viewNames"
    foreach viewName $viewNames {
    set spc ""
    set ordStack [list]
    set visibility hidden
60  if {[info exists vdata]} { unset vdata }
    if {$viewName == "NONE"} {
    # no annotations...
    } elseif {$viewName == "ALL"} {
65  foreach ord $allords { set vdata($ord) "all" }
    set visibility visible
    } else {
    #array set vdata $viewData($viewName)
    }
70  set svg_notes ""
    set ords [array names vdata]
    set ords [lsort -dictionary $ords]
    append svg "<g id='$viewName-view' style='visibility:$visibility'>\n"
    foreach {ord} $ords {
75  set see $vdata($ord)
    #puts "$viewName: $ord = $see\n"
    # don't write groups - no visual annotation
    set orderAnt iat-$ord; append orderAnt -annotation
    set orderRegion iat-$ord; append orderRegion -region
    set orderPointer iat-$ord; append orderPointer -pointer
80  set orderINote iat-$ord; append orderINote -inote
    }
    }

```

```

set orderSymbol iat-$ord; append orderSymbol -symbol

#puts "[lindex $ordStack end] == $viewName-$ord"
5 while {[expr {[length $ordStack] > 0} && ![regexp [lindex $ordStack end] $viewName-$ord]]} {
    set spc [string repeat " " [length $ordStack]]
    append svg "$spc</g><!-- end [lindex $ordStack end]-annotation -->\n"
    set ordStack [lreplace $ordStack end end]
10 }

set spc [string repeat " " [expr [length $ordStack] +1]]

set svg_pointers ""
foreach (key value) $aheds($ord) {
15   if {$value == ""} { continue }
   #puts "  ahead = $key\n"
   append svg_pointers "$spc <use id='$viewName-$orderPointer$key'
xlink:href='#$orderPointer$key' />\n"
   append svg_pointers "$spc <use id='$viewName-$orderINote$key' xlink:href='#$orderINote$key'
20 onmouseover='antSetMouseOverINote(\"$ord\", \"$key\", true)'
onmouseout='antSetMouseOverINote(\"$ord\", \"$key\", false)' />\n"
   append svg_pointers "$spc <use id='$viewName-$orderSymbol$key'
xlink:href='#$orderSymbol$key' />\n"
   append svg_notes "$spc <use id='$viewName-$orderINote' xlink:href='#$orderINote' />\n"
25 }

lappend ordStack $viewName-$ord
append svg "$spc<g id='$viewName-$orderAnt'
onmouseover='antSetMouseOverAnt(\"$ord\", true, false)' onmouseout='antSetMouseOverAnt(\"$ord\", false, false)'
30 onclick='antShowCaption(\"$ord\")'>\n"
  switch $see {
    "pointer" {
      #append svg "$spc <use id='$viewName-$orderPointer' xlink:href='#$orderPointer'
onmouseover='onAntMouseOver(evt)' onmouseout='onAntMouseOff(evt)' />\n"
35      append svg "$spc <use id='$viewName-$orderPointer' xlink:href='#$orderPointer' />\n"
      append svg "$spc <use id='$viewName-$orderSymbol' xlink:href='#$orderSymbol' />\n"
    }
    "region" {
      #append svg "$spc <use id='$viewName-$orderRegion' xlink:href='#$orderRegion'
40 onmouseover='onAntMouseOver(evt)' onmouseout='onAntMouseOff(evt)' />\n"
      append svg "$spc <use id='$viewName-$orderRegion' xlink:href='#$orderRegion' />\n"
    }
    "none" {
      append svg "$spc <!-- none -->\n"
45 }
    default {
      #append svg "$spc <use id='$viewName-$orderRegion' xlink:href='#$orderRegion'
onmouseover='onAntMouseOver(evt)' onmouseout='onAntMouseOff(evt)' />\n"
      #append svg "$spc <use id='$viewName-$orderRegion-test' xlink:href='#$orderRegion-test'
50 />\n"
      append svg "$spc <use id='$viewName-$orderRegion' xlink:href='#$orderRegion' />\n"
      append svg "$svg_pointers\n"
      #append svg "$spc <use id='$viewName-$orderPointer' xlink:href='#$orderPointer' />\n"
      #append svg "$spc <use id='$viewName-$orderSymbol' xlink:href='#$orderSymbol' />\n"
55      #append svg "$spc <use id='$viewName-test1' xlink:href='#test1' />\n"
      #append svg "$spc <use id='$viewName-test2' xlink:href='#test2' />\n"
    }
  }
}

60 while {[length $ordStack] > 0} {
  set spc [string repeat " " [length $ordStack]]
  append svg "$spc</g><!-- end [lindex $ordStack end]annotation -->\n"
  set ordStack [lreplace $ordStack end end]
65 }
append svg "$svg_notes\n"
append svg "</g><!-- end $viewName-view -->\n"
}

return $svg
70 }

proc iat::ant::ant_make_svg_all { ns lvl } {
  variable TRACE
  if ($TRACE) { puts "iat::ant::ant_make_svg_all: $ns $lvl" }
75   upvar #0 [join [list [namespace current] $ns polys] ::] polys

  set menu ""
  set symbols ""
80   set views ""

```

```

foreach {key value} [array get polys] {
    append symbols [ant_make_svg_ant $ns $key $lvl]
}
append views [ant_make_svg_views $ns $lvl]
5   append menu [ant_make_svg_menu $ns $lvl]

    return [list "$menu" "$symbols\n$views"]
}
iat.tex.txt
10 # Copyright (c) 2001, 2002, University of Utah
    # All rights reserved.
    #
    # iat.tex.tcl

15 package require uri

namespace eval tex {
    variable TRACE 0
    variable next_nsid 1
20 }

proc tex::next_nsid { } {

25     variable next_nsid

    return [incr next_nsid]
}

30 namespace eval tex::doc { }

proc tex::proc { ns cmd args } {
    variable TRACE
    if {$TRACE} { puts "tex::proc: $ns $cmd $args" }
35     upvar #0 [join [list [namespace current] doc $ns xml_str] ::] xml_str

    switch $cmd {
        "configure" {
40             #puts "cmd = configure: $args"
            foreach {key value} $args {
                #puts "key = $key & value = $value"
                switch -- $key {
45                     "-xml" { doc_set_xml $ns $value }
                     "-url" { doc_set_url $ns $value }
                     "-file" { doc_set_file $ns $value }
                }
            }
        }
50         "cget" {
            #puts "cmd = cget: $args"
            switch -- [lindex $args 0] {
                "-url" { return [doc_get_url $ns] }
            }
        }
55         "read" {
            return [doc_read $ns]
        }
        "parse" {
60             return [doc_parse $ns $xml_str]
        }
        "dump" {
            doc_dump $ns
        }
65         default {
            puts "ERROR unknown command = $cmd"
        }
    }

70     return {}
}

proc tex::create { args } {
    variable TRACE
75     if {$TRACE} { puts "tex::create: $args" }

    set nsid [next_nsid]

    set ns [namespace current]::doc::id$nsid

80     namespace eval $ns {

```

```

variable xml
array set xml {list}

5   variable ID 999
    variable ns ""
    variable xml_str ""

    variable url ""

10  variable eids
    variable tags
    variable opts
    variable dats
15  variable nods

    variable eid 0
    variable tag "TAG"
    variable opt {list}
20  variable dat ""
    variable nod {list}

    variable doc_by_eid
    variable doc_by_elt

25  array set doc_by_eid {list}
    array set doc_by_elt {list}

    variable elt_to_widget
30  variable elt_eid
}

set cmd "proc [namespace current]::doc::id$nsid { cmd args } {eval [namespace current]::proc id$nsid
\${cmd} \${args}}"
35 namespace eval :: $cmd
    eval "[namespace current]::doc::id$nsid configure $args"

    return [namespace current]::doc::id$nsid
}

40 #proc unknown { args } {
#   puts "unknown: $args"
#}

45 proc tex::clear_state { ns } {

    upvar #0 [join {list [namespace current] doc $ns eids} ::] eids
    upvar #0 [join {list [namespace current] doc $ns tags} ::] tags
    upvar #0 [join {list [namespace current] doc $ns opts} ::] opts
50  upvar #0 [join {list [namespace current] doc $ns dats} ::] dats
    upvar #0 [join {list [namespace current] doc $ns nods} ::] nods

    set eid 0
    set tag "TAG"
55  set opt {list}
    set dat ""
    set nod {list}

}

60 proc tex::stack_push { ns } {

    upvar #0 [join {list [namespace current] doc $ns eids} ::] eids
    upvar #0 [join {list [namespace current] doc $ns tags} ::] tags
65  upvar #0 [join {list [namespace current] doc $ns opts} ::] opts
    upvar #0 [join {list [namespace current] doc $ns dats} ::] dats
    upvar #0 [join {list [namespace current] doc $ns nods} ::] nods

    upvar #0 [join {list [namespace current] doc $ns eid} ::] eid
70  upvar #0 [join {list [namespace current] doc $ns tag} ::] tag
    upvar #0 [join {list [namespace current] doc $ns opt} ::] opt
    upvar #0 [join {list [namespace current] doc $ns dat} ::] dat
    upvar #0 [join {list [namespace current] doc $ns nod} ::] nod

75  if (![info exists eids(_TOS_)]) { set eids(_TOS_) 0 }

    incr eids(_TOS_)
    set TOS $eids(_TOS_)
    set eids($TOS) $eid
80  set tags($TOS) $tag
    set opts($TOS) $opt

```

```

set dats($TOS) $dat
set nods($TOS) $nod

clear_state $ns

5 )

proc tex::stack_pop { ns } {

10   upvar #0 [join [list [namespace current] doc $ns eids] ::] eids
   upvar #0 [join [list [namespace current] doc $ns tags] ::] tags
   upvar #0 [join [list [namespace current] doc $ns opts] ::] opts
   upvar #0 [join [list [namespace current] doc $ns dats] ::] dats
   upvar #0 [join [list [namespace current] doc $ns nods] ::] nods

15   upvar #0 [join [list [namespace current] doc $ns eid] ::] eid
   upvar #0 [join [list [namespace current] doc $ns tag] ::] tag
   upvar #0 [join [list [namespace current] doc $ns opt] ::] opt
   upvar #0 [join [list [namespace current] doc $ns dat] ::] dat
   upvar #0 [join [list [namespace current] doc $ns nod] ::] nod

20   if {[info exists eids(_TOS_)]} { return 0 }
   if {$eids(_TOS_) == 0} { return 0 }

   set TOS $eids(_TOS_)
25   set eid $eids($TOS)
   set tag $tags($TOS)
   set opt $opts($TOS)
   set dat $dats($TOS)
   set nod $nods($TOS)
30   incr eids(_TOS_) -1

   #puts "nodes: $nod"

   unset eids($TOS)
35   unset tags($TOS)
   unset opts($TOS)
   unset dats($TOS)
   unset nods($TOS)

40   return 1
}

proc tex::tos_add_node { ns n } {
   variable TRACE
45   if ($TRACE) { puts "tex::stack_add_node: $n" }

   upvar #0 [join [list [namespace current] doc $ns eids] ::] eids
   upvar #0 [join [list [namespace current] doc $ns tags] ::] tags
   upvar #0 [join [list [namespace current] doc $ns opts] ::] opts
50   upvar #0 [join [list [namespace current] doc $ns dats] ::] dats
   upvar #0 [join [list [namespace current] doc $ns nods] ::] nods

   if {[info exists eids(_TOS_)]} { return 0 }

55   lappend nods($eids(_TOS_)) $n
   #puts "  tos nodes: $nods($eids(_TOS_))"

   return 1
}

60 proc tex::set_node { ns eid tag opt dat nod } {
   variable TRACE
   if ($TRACE) { puts "tex::set_node: $ns $eid $tag ..." }

65   upvar #0 [join [list [namespace current] doc $ns doc_by_eid] ::] doc_by_eid
   upvar #0 [join [list [namespace current] doc $ns doc_by_elt] ::] doc_by_elt

   set doc_by_eid($eid) [list eid $eid tag $tag opt $opt dat $dat nod $nod]
   lappend doc_by_elt($tag) $eid

70 }

proc tex::doc_dump { ns } {
   variable TRACE
   if ($TRACE) { puts "tex::doc_dump: $ns" }

75   upvar #0 [join [list [namespace current] doc $ns xml] ::] xml
   upvar #0 [join [list [namespace current] doc $ns doc_by_eid] ::] doc_by_eid
   upvar #0 [join [list [namespace current] doc $ns doc_by_elt] ::] doc_by_elt

80   puts "_____ "
   set keys [array names xml]

```

```

foreach key $keys {
    puts "xml $key = $xml($key)"
}

5  set eids [array names doc_by_eid]
    set eids [lsort -integer $eids]
    foreach eid $eids {
        #puts "  eid $eid = $doc_by_eid($eid)"
        array set A $doc_by_eid($eid)
10     puts "    _____"
        puts "      eid: $A(eid)"
        puts "      tag: $A(tag)"
        puts "      opts: $A(opt)"
        puts "      data: \"$A(dat)\""
15     puts "      nodes: $A(nod)"
    }
}

proc tex::slave_unknown { ns cmd args } {
20  variable TRACE
    if ($TRACE) { puts "tex::slave_unknown: $ns $cmd $args" }

    upvar #0 [join [list [namespace current] doc $ns xml] ::] xml
    upvar #0 [join [list [namespace current] doc $ns ID] ::] ID
25  upvar #0 [join [list [namespace current] doc $ns eid] ::] eid
    upvar #0 [join [list [namespace current] doc $ns tag] ::] tag
    upvar #0 [join [list [namespace current] doc $ns opt] ::] opt
    upvar #0 [join [list [namespace current] doc $ns dat] ::] dat
    upvar #0 [join [list [namespace current] doc $ns nod] ::] nod
30  upvar #0 [join [list [namespace current] doc $ns tns] ::] tns

    #set tag [lindex $args 0]
    #set data $args

35  #puts "length: [llength $data]"
    if {[regexp {^<\?xml} $cmd mat]} {
        # xml document...
        foreach token $args {
40             if {$token == ">"} {
                break
            } elseif {[regexp {(\\w+)=\\'|\\")(\\S+)(\\'|\\")}$token mat key a val b]} {
                #puts "option: $key = \"$val\""
                set xml($key) $val
45             }
        }

        clear_state $ns
    } elseif {[regexp {^<!--} $cmd mat]} {
50     # comment
    } elseif {[regexp {^</\\S+>} $cmd mat tag]} {
        # close tag

        stack_pop $ns
        set dat [string trim $dat]
        tos_add_node $ns $eid
        set_node $ns $eid $tag $opt [XMLSTR $dat] $nod

60     #puts "  eid: $eid"
        #puts "  tag: $tag"
        #puts "  opts: [array get opt]"
        #puts "  data: \"$dat\""
        #puts "  nodes: $nod"

65     clear_state $ns

    } elseif {[regexp {^<(\\S+)>} $cmd mat tag]} {
        # start tag
        #puts "  tag start = $tag"
70     set eid [incr ID]

        set_end_tag 0
        set_is_data 1
        set_opt [list]
75     set_dat ""
        set_nod [list]
        foreach token $args {
            if {$is_data} {
                if {[regexp "</$tag>" $token]} {
80                 set_end_tag 1
                    continue
                }
            }
        }
    }
}

```

```

    ) else {
        append dat "$token "
    }
}

5   )

    if (!$end_tag) {
        stack_push $ns
    } else {
10      set dat [string trim $dat]
        tos_add_node $ns $eid
        set_node $ns $eid $tag $opt [XMLSTR $dat] $nod

        #puts "    eid: $eid"
15      #puts "    tag: $tag"
        #puts "    opts: [array get opt]"
        #puts "    data: \"$dat\""
        #puts "    nods: $nod"

20      clear_state $ns
    }

} elseif {[regexp {^<(\S+)} $cmd mat tag]} {
25      # start tag with arguments
        set eid [incr ID]

        set end_tag 0
        set is_data 0
        set opt [list]
30      set dat ""
        set nod [list]
        foreach token $args {
            if {$is_data} {
                if {[regexp "</$tag>" $token]} {
35                  set end_tag 1
                    continue
                } else {
                    append dat "$token "
                }
            } else {
40              if {$token == ">"} {
                    set is_data 1
                    continue
                } elseif {$token == "/>"} {
45                  set end_tag 1
                    continue
                } elseif {[regexp {(\w+)=('|")(\S+)('|"))} $token mat key a val b]} {
                    #puts "option: $key = \"$val\""
                    #set opt($key) $val
50                  lappend opt $key $val
                }
            }
        }
    }

55      if (!$end_tag) {
        stack_push $ns
    } else {
        set dat [string trim $dat]
        tos_add_node $ns $eid
60      set_node $ns $eid $tag $opt [XMLSTR $dat] $nod

        #puts "    eid: $eid"
        #puts "    tag: $tag"
        #puts "    opts: [array get opt]"
65      #puts "    data: \"$dat\""
        #puts "    nods: $nod"

        clear_state $ns
    }

70      ) else {
        # unknown command
        error "invalid command name \"$cmd\""
    }

75      #puts "tag: $tag"
        #puts "data: $data"
        #puts "long: [llength $data]"
        #set cmd "set doc $data"
        #puts "cmd = $cmd"
80      #set rv [eval $cmd]

```

```

#puts "doc = $doc"
#if ([length $doc] == 1) { return [lindex $doc 0] }
#set rv [list tex::tag $tag [eval $doc]]
return ""
5)

proc tex::doc_set_xml { ns str } {
    variable TRACE
    if ($TRACE) { puts "tex::doc_set_xml: $ns $str" }
10    upvar #0 [join [list [namespace current] doc $ns xml_str] ::] xml_str
    set xml_str $str
}

15 proc tex::doc_set_url { ns u } {
    variable TRACE
    if ($TRACE) { puts "tex::doc_set_url: $ns $u" }
20    upvar #0 [join [list [namespace current] doc $ns url] ::] url
    set url $u
}

25 proc tex::doc_get_url { ns } {
    variable TRACE
    if ($TRACE) { puts "tex::doc_get_url: $ns" }
30    upvar #0 [join [list [namespace current] doc $ns url] ::] url
    return $url
}

proc tex::doc_read { ns } {
35    variable TRACE
    if ($TRACE) { puts "tex::doc_read: $ns" }
    upvar #0 [join [list [namespace current] doc $ns url] ::] url
40    puts "url = $url"
    array set A [uri::split $url]
    #foreach {key val} [array get A] {
        # puts "$key = $val"
    }
45    switch $A(scheme) {
        "file" {
            set fh [open $A(path) r]
            set str [read $fh]
50            close $fh
            doc_parse $ns $str
        }
        "http" {
55        }
        default {
        }
    }
60 }

proc tex::doc_parse { ns args } {
    variable TRACE
65    if ($TRACE) { puts "tex::doc_parse: $ns ..." }
    set i [interp create -safe A]
    interp alias $i unknown {} [namespace current]::slave_unknown $ns
    #puts "aliases = [interp aliases $i]"
70    regsub -all (;) [lindex $args 0] {\;} str
    #puts $str; exit
    if ([catch {interp eval $i $str} err]) {
        #puts "error = $err"
        error $err
75        interp delete A
    }
    interp delete A
}

80 # regsubs < > & ' ' for xml...
proc tex::XMLSTR {str} {

```



```

regsub -all {\;} $str {;} str1
regsub -all {\&lt;} $str1 (<) str2
regsub -all {\&gt;} $str2 (>) str3
regsub -all {\&quot;} $str3 (") str4
5  regsub -all {\&apos;} $str4 (') str5
regsub -all {\&amp;} $str5 (\&) str6
return $str6
}

10 if {0} {
    set doc [tex::create -url file:./Back01.xml]
    $doc read
    $doc dump
    exit
15 }
iat.antptr.txt
# Copyright (c) 2001, University of Utah
# All rights reserved.
#
20 # iat.antptr.tcl

namespace eval iat::ant {
    variable px1
25    variable px2
    variable px3
    variable px4
    variable px5
    variable px6
30    variable len
    variable siz

    set px1 10
    set px2 10
35    set px3 10
    set px4 10
    set px5 10
    set px6 10

40    variable styleSizeSmall 0.002
    variable styleSizeDefault 0.005
    variable styleSizeLarge 0.010

    variable pointerNames [list none line wedge arrow]
45 }

proc iat::ant::calc_size { ns } {
    variable px1
50    variable px2
    variable px3
    variable px4
    variable px5
    variable px6
55    variable styleSizeSmall
    variable styleSizeDefault
    variable styleSizeLarge

60    upvar #0 [join [list [namespace current] $ns imageX] ::] imageX
    upvar #0 [join [list [namespace current] $ns imageY] ::] imageY

    set percent 0.005
    #puts "calcOther: $iat::roi::size"
65    set size default
    switch $size {
        "small" { set percent $styleSizeSmall }
        "default" { set percent $styleSizeDefault }
        "large" { set percent $styleSizeLarge }
70    }

    # ave of image x & y
    if {$imageX == 0} { return }
    if {$imageY == 0} { return }
75    set ave [expr ($imageX + $imageY)/2 ]
    set px1 [expr round(ceil($ave * $percent)) ]
    set px2 [expr $px1 * 2]
    set px3 [expr $px1 * 3]
    set px4 [expr $px1 * 4]
80    set px5 [expr $px1 * 5]
    set px6 [expr $px1 * 6]

```

```

    )

proc iat::ant::points_translate { dx dy pts } {
5   #puts "iat::ant::points_translate: $dx $dy"
   #puts "  points = $pts"
   set newpts [list]
   foreach pt $pts {
       set x [expr [lindex $pt 0] + $dx]
10      set y [expr [lindex $pt 1] + $dy]
       lappend newpts [list $x $y]
   }
   return $newpts
}

15 proc iat::ant::points_translate_lst { dx dy pts } {
   set ptsn [list]
   foreach {x y} $pts {
       set xm [expr $x + $dx]
20      set ym [expr $y + $dy]
       lappend ptsn $xm $ym
   }
   return $ptsn
}

25 proc iat::ant::point_rotate { angle x y } {
   #puts "iat::ant::point_rotate: $angle $x $y"
   # rotate point around origin...
   set radius [expr sqrt(($x*$x)+($y*$y))]
   set radians [expr atan2($y,$x)]
30  set radians [expr $radians + (-1*$angle*3.1416)/180];
   set xm [expr round(ceil($radius*cos($radians)))]
   set ym [expr round(ceil($radius*sin($radians)))]
   return [list $xm $ym]
35 }

proc iat::ant::points_rotate { angle pts } {
   set ptsn [list]
   foreach {x y} $pts {
40      set ptn [point_rotate $angle $x $y]
       set xm [lindex $ptn 0]
       set ym [lindex $ptn 1]
       lappend ptsn $xm $ym
   }
45  return $ptsn
}

proc iat::ant::x2pts_length {pt1 pt2} {
   #puts "2ptsLength: $pt1 $pt2"
50  set x1 [lindex $pt1 0]
   set y1 [lindex $pt1 1]
   set x2 [lindex $pt2 0]
   set y2 [lindex $pt2 1]
   if {$x1 > $x2} {
55      set x [expr $x1 - $x2]
   } else {
       set x [expr $x2 - $x1]
   }
   if {$y1 > $y2} {
60      set y [expr $y1 - $y2]
   } else {
       set y [expr $y2 - $y1]
   }
   set len [expr sqrt(($x*$x)+($y*$y))]
65  return [list [expr round($len)] $x $y]
}

proc iat::ant::x2pts_angle {pt1 pt2} {
   #puts "2ptsAngle: $pt1 $pt2"
70  set rv [x2pts_length $pt1 $pt2]
   #set len [lindex $rv 0]
   set rvx [lindex $rv 1]
   set rvy [lindex $rv 2]
   set radians [expr atan2($rvy,$rvx)]
75  set angle [expr (($radians*180)/(3.1416))]
   set x [expr [lindex $pt2 0]-[lindex $pt1 0]]
   set y [expr [lindex $pt2 1]-[lindex $pt1 1]]

   #puts "pt1 = $pt1"
   #puts "pt2 = $pt2"
80  #puts "x = $x , y = $y"

```

```

    if ($x == 0) {
        if ($y >= 0) {
            set angle [expr $angle + 0]
        } else {
5           set angle [expr $angle + 180]
        }
    } elseif ($x > 0) {
        if ($y == 0) {
            set angle [expr $angle + 0]
10        } elseif ($y > 0) {
            set angle [expr $angle + 0]
        } else {
            set angle [expr 360 - $angle]
        }
15    } else {
        if ($y == 0) {
            set angle [expr $angle + 180]
        } elseif ($y > 0) {
            set angle [expr 180 - $angle]
20        } else {
            set angle [expr $angle + 180]
        }
    }
    return [expr -1*ceil($angle)]
25 }

proc iat::ant::pointer_line {tlen} {
    variable px1
    variable px2
30    variable px3
    variable px4
    variable px5
    variable siz
    set xo 0
    set yo 0
35    set sss [expr round(ceil($px1/4))]
    # line head
    set pts [list]
    lappend pts $xo $yo
40    lappend pts [expr $xo + $px4] [expr $yo - $px1]
    lappend pts [expr $xo + $px4] [expr $yo + $px1]

    return $pts
    #return [list $lbl $pts]
45 }

proc iat::ant::pointer_arrow {tlen} {
    variable px1
    variable px2
50    variable px3
    variable px4
    variable px5
    variable siz
    set xo 0
    set yo 0
55    # arrow head
    set pts [list]
    lappend pts $xo $yo
    lappend pts [expr $xo + $px3] [expr $yo - $px3]
60    lappend pts [expr $xo + $px3] [expr $yo - $px1]
    lappend pts [expr $xo + $px3] [expr $yo + $px1]
    lappend pts [expr $xo + $px3] [expr $yo + $px3]

    return $pts
65    #return [list $lbl $pts]
}

proc iat::ant::pointer_diamond {tlen} {
    variable px1
    variable px2
70    variable px3
    variable px4
    variable px5
    variable siz
75    set xo 0
    set yo 0
    # diamond head
    set pts [list]
    lappend pts $xo $yo
80    lappend pts [expr $xo + $px3] [expr $yo - $px2]
    lappend pts [expr $xo + $px5] [expr $yo - $px1]

```

Appendix 2

```

lappend pts [expr $xo + $px5] [expr $yo + $px1]
lappend pts [expr $xo + $px3] [expr $yo + $px2]

return $pts
5  #return [list $lbl $pts]
}

proc iat::ant::create_pointer { ns type {size 0} } {
10  calc_size $ns

  switch $type {
    "none" {
15      return [pointer_line $size]
    }
    "line" {
      return [pointer_line $size]
    }
    "arrow" {
20      return [pointer_arrow $size]
    }
    "diamond" {
      return [pointer_diamond $size]
    }
25    default {
      return -1
    }
  }
}

30
proc iat::ant::nearest_point {point points} {
  set mind 10000
  set idx 0
  set minidx 0
35  foreach p $points {
    set rv [x2pts_length $point $p]
    set d [lindex $rv 0]
    if {$d < $mind} { set mind $d; set minidx $idx }
    incr idx
40  }
  return $minidx
}

proc iat::ant::gravity_angle { grav } {
45  switch $grav {
    "N" {
      return 90
    }
    "E" {
50      return 0
    }
    "S" {
      return 270
    }
    "W" {
55      return 180
    }
    "NE" {
      return 45
60      }
    "SE" {
      return 315
    }
    "SW" {
65      return 225
    }
    "NW" {
      return 135
    }
70    default {
      # C (center)
      return 0
    }
  }
}

75
proc iat::ant::gravity_label {angle} {
  set angle [expr $angle * -1]
  #puts "iat::ant::gravityLabel: $angle"
80  # note: drawing begins at 0 degrees and rotates clockwise
  if {$angle > 0} {

```

```

    if ($angle < 90) {
        return w
    } elseif ($angle < 180) {
        return e
5    } elseif ($angle < 270) {
        return e
    } elseif ($angle < 360) {
        return w
10    } else {
        return c
    }
} else {
    return c
}
15 }

proc iat::ant::gravityLabelOld { grav } {
    switch $grav {
        "N" {
20            return "s"
        }
        "E" {
            return "w"
        }
25        "S" {
            return "n"
        }
        "W" {
            return "e"
30        }
        "NE" {
            return "sw"
        }
        "SE" {
35            return "nw"
        }
        "SW" {
            return "ne"
        }
40        "NW" {
            return "se"
        }
        default {
45            # C (center)
            return "c"
        }
    }
}

50 proc iat::ant::gravity_point { grav pts } {
    set wxi 0 ; set wxp 10000 ; set exi 0 ; set exp 0
    set nyi 0 ; set nyp 10000 ; set syi 0 ; set syp 0
    # find extremes...
    set idx 0
55    foreach {x y} $pts {
        if {$x < $wxp} {
            set wxp $x ; set wxi $idx
        }
        if {$x > $exp} {
60            set exp $x ; set exi $idx
        }
        if {$y < $nyp} {
            set nyp $y ; set nyi $idx
        }
65        if {$y > $syp} {
            set syp $y ; set syi $idx
        }
        incr idx
    }
70    # return index of pt for gravity...
    switch $grav {
        "N" {
            return $nyi
        }
75        "E" {
            return $exi
        }
        "S" {
            return $syi
80        }
        "W" {

```

```

    return $wxi
}
"NE" {
5   if {$nyi == $exi} {
        return $nyi
    }

    if {$exi == 0} {
10      set exi [expr [llength $pts]/2]
    }

    if {$nyi == [expr $exi-1]} {
        return $nyi
    } else {
15      return [expr round($nyi+(($exi-$nyi)/2))]
    }
}
"NW" {
20   if {$nyi == $wxi} {
        return $nyi
    }

    if {$nyi == 0} {
25      set nyi [expr [llength $pts]/2]
    }

    if {$nyi == [expr $wxi+1]} {
        return $nyi
    } else {
30      return [expr round($nyi-(($nyi-$wxi)/2))]
    }
}
"SE" {
35   if {$syi == $exi} {
        return $syi
    }

    if {$syi == 0} {
40      set syi [expr [llength $pts]/2]
    }

    if {$syi == [expr $exi+1]} {
        return $syi
    } else {
45      return [expr round($syi-(($syi-$exi)/2))]
    }
}
"SW" {
50   if {$syi == $wxi} {
        return $syi
    }

    if {$wxi == 0} {
55      set wxi [expr [llength $pts]/2]
    }

    if {$syi == [expr $wxi-1]} {
        return $syi
    } else {
60      return [expr round($syi+(($wxi-$syi)/2))]
    }
}
default {
65   return -1
}
}

if {0} {
70   puts "testing..."
    set p1 [list 1 0]
    set p2 [list 0 1]
    puts "Length [join $p1 ,] [join $p2 ,]: [join [iat::ant::2ptsLength $p1 $p2] :]"

75   set p1 [list 1 0]
    set p2 [list -1 0]
    puts "Length [join $p1 ,] [join $p2 ,]: [join [iat::ant::2ptsLength $p1 $p2] :]"

80   set p1 [list 1 1]
    set p2 [list -1 -1]
    puts "Length [join $p1 ,] [join $p2 ,]: [join [iat::ant::2ptsLength $p1 $p2] :]"
}

```

```

set p1 [list 0 0]
set p2 [list 1 0]
puts "0 Angle [join $p1 ,] [join $p2 ,]: [iat::ant::2ptsAngle $p1 $p2]"

5   set p1 [list 0 0]
    set p2 [list 1 1]
    puts "45 Angle [join $p1 ,] [join $p2 ,]: [iat::ant::2ptsAngle $p1 $p2]"

10  set p1 [list 0 0]
    set p2 [list 0 1]
    puts "90 Angle [join $p1 ,] [join $p2 ,]: [iat::ant::2ptsAngle $p1 $p2]"

    set p1 [list 0 0]
    set p2 [list -1 1]
15  puts "135 Angle [join $p1 ,] [join $p2 ,]: [iat::ant::2ptsAngle $p1 $p2]"

    set p1 [list 0 0]
    set p2 [list -1 0]
20  puts "180 Angle [join $p1 ,] [join $p2 ,]: [iat::ant::2ptsAngle $p1 $p2]"

    set p1 [list 0 0]
    set p2 [list -1 -1]
    puts "135 Angle [join $p1 ,] [join $p2 ,]: [iat::ant::2ptsAngle $p1 $p2]"

25  set p1 [list 0 0]
    set p2 [list 0 -1]
    puts "270 Angle [join $p1 ,] [join $p2 ,]: [iat::ant::2ptsAngle $p1 $p2]"

    set p1 [list 0 0]
    set p2 [list 1 -1]
30  puts "315 Angle [join $p1 ,] [join $p2 ,]: [iat::ant::2ptsAngle $p1 $p2]"

    set p1 [list 1 1]
    set p2 [list 1 -1]
35  puts "270 Angle [join $p1 ,] [join $p2 ,]: [iat::ant::2ptsAngle $p1 $p2]"

    set p1 [list 0 1]
    set p2 [list 0 -1]
40  puts "270 Angle [join $p1 ,] [join $p2 ,]: [iat::ant::2ptsAngle $p1 $p2]"

    set p1 [list -1 -1]
    set p2 [list 1 -1]
    puts "0 Angle [join $p1 ,] [join $p2 ,]: [iat::ant::2ptsAngle $p1 $p2]"

45  set p1 [list 2 2]
    set p2 [list -3 -3]
    puts "135 Angle [join $p1 ,] [join $p2 ,]: [iat::ant::2ptsAngle $p1 $p2]"

    exit
50 }
    iat.antio.txt
    # Copyright (c) 2001, University of Utah
    # All rights reserved.
    #
55 # iat.antio.tcl

    namespace eval iat::ant {

    }

60  proc iat::ant::read_ants { ns url } {
        puts "iat::ant::read_ants: $ns $url"
    }

65  proc iat::ant::write_ants { ns url } {
        puts "iat::ant::write_ants: $ns $url"
    }

70  proc iat::ant::ants_read_cmds { ns doc } {
        variable TRACE
        if ($TRACE) { puts "iat::ant::ants_read_cmds: $ns $doc" }

75  variable antkey
        variable rawsave
        variable precmd

        upvar #0 [join [list $doc doc_by_eid] ::] doc_by_eid
80  upvar #0 [join [list $doc doc_by_elt] ::] doc_by_elt

```

Appendix 2

```

set rawsave 1

if {[info exists doc_by_elt(annotations)]} {
  set eids $doc_by_elt(annotations)
  #puts " eids = $eids"
  set eid [lindex $eids end]
  if {$eid > 0} {
    #puts " ants = $doc_by_eid($eid)"
    array set A $doc_by_eid($eid)
    set ants $A(nod)
    foreach roi $ants {
      ants_read_cmds_ant $ns $doc $roi
    }
  }
}

set rawsave 0

return 0
}

proc iat::ant::ants_read_cmds_ant { ns doc roi } {
  variable TRACE
  if ($TRACE) { puts "iat::ant::ants_read_cmds_ant: $ns $roi" }

  variable thisptr
  variable order

  upvar #0 [join [list $doc doc_by_eid] ::] doc_by_eid
  upvar #0 [join [list $doc doc_by_elt] ::] doc_by_elt

  set precmd "[namespace current]::$ns"

  if {[info exists doc_by_eid($roi)]} {
    #puts " roi = $doc_by_eid($roi)"
    array set A $doc_by_eid($roi)
    array set Ao $A(opt)

    # create roi with type
    set cmd "create roi $Ao(type)"
    set cmd "$precmd $cmd"
    #puts " cmd = $cmd"
    eval $cmd

    if {[info exists Ao(order)]} {
      set cmd "set order $Ao(order)"
      set cmd "$precmd $cmd"
      #puts " cmd = $cmd"
      eval $cmd
    }

    set nods $A(nod)
    foreach nod $nods {
      set cmds [list]
      set cmd ""
      #puts " nod = $doc_by_eid($nod)"
      array set B $doc_by_eid($nod)
      array set Bo $B(opt)
      set tag $B(tag)
      switch $tag {
        "views" {
          set cmd "set inview \{$B(dat)\}"
          lappend cmds $cmd
        }
        "code" {
          set cmd "set code \{$B(dat)\}"
          lappend cmds $cmd
        }
        "symbol" {
          set cmd "set symbol \{$B(dat)\}"
          lappend cmds $cmd
        }
        "label" {
          set cmd "set label \{$B(dat)\}"
          lappend cmds $cmd
        }
        "cs_class" {
          set cmd "set cs_class \{$B(dat)\}"
          lappend cmds $cmd
        }
      }
    }
  }
}

```



```

"cs_tumor" {
  set cmd "set cs_tumor \{$B(dat)\}"
  lappend cmds $cmd
}
5 "cs_node" {
  set cmd "set cs_node \{$B(dat)\}"
  lappend cmds $cmd
}
10 "cs_metastasis" {
  set cmd "set cs_metastasis \{$B(dat)\}"
  lappend cmds $cmd
}
"cs_note" {
  set cmd "set cs_note \{$B(dat)\}"
  lappend cmds $cmd
}
15 "caption" {
  set cmd "set caption \{$B(dat)\}"
  lappend cmds $cmd
}
20 "vertexs" {
  set pts [list]
  foreach pair $B(dat) { lappend pts [split $pair (,)] }
  set cmd "create vertexs [list $pts]"
  lappend cmds $cmd
25 }
"pointer" {
  set pts [list]
  set shp $Bo(shape)
  set txt $Bo(text)
  set tail [split $Bo(tail) (,)]
  foreach pair $B(dat) { lappend pts [split $pair (,)] }
  set cmd "create pointer $Bo(head) [list $tail] [list $pts]"
  lappend cmds $cmd
  set cmd "pointer style active $shp"
  lappend cmds $cmd
  set cmd "pointer symbol active $txt"
  lappend cmds $cmd
}
40 "color" {
  set cmd "set color $B(dat)"
  lappend cmds $cmd
}
}
45 foreach cmd $cmds {
  if {$cmd != ""} {
    #set cmd "[namespace current]::$ns $line"
    set cmd "$precmd $cmd"
    #puts "cmd = $cmd"
    eval $cmd
50 }
  }
}
55 ant_save $ns
return 0
}
60
proc iat::ant::ants_parse { ns ants } {
  variable TRACE
  if {$TRACE} { puts "iat::ant::ants_parse: $ns $ants" }
65
  variable antkey
  variable rawsave
  variable precmd

  set rawsave 1

70
  set lines [split $ants "\n"]
  foreach line $lines {
    if {$line == ""} { continue }
    if {[regexp {^\s*#} $line]} { continue }
75    #set cmd "[namespace current]::$ns $line"
    set cmd "$precmd $line"
    puts "cmd = $cmd"
    eval $cmd
  }
80
  set rawsave 0

```

```

    return 0
}

5 proc iat::ant::ant_make_all { ns lvl } {
    variable TRACE
    if {$TRACE} { puts "iat::ant::ant_make_all: $ns $lvl" }

    upvar #0 [join [list [namespace current] $ns canvas] ::] canvas
10    upvar #0 [join [list [namespace current] $ns polys] ::] polys

    set str ""

    #append str "begin annotations\n"
    set pre [string repeat " " $lvl]
    append str "$pre<annotations>\n"
    foreach (key value) [array get polys] {
        append str [ant_make $ns $key [expr $lvl+2]]
    }
20    #append str "end annotations\n"
    append str "$pre</annotations>\n"

    return $str
}

25 proc iat::ant::ant_make { ns key lvl } {
    variable TRACE
    if {$TRACE} { puts "iat::ant::ant_make: $ns $key $lvl" }

30    variable antkey
    variable order
    variable points
    variable heads
    variable verts
35    variable tails
    variable dSYMs
    variable dPTRs
    variable kind
    variable color
40    variable invview
    variable code
    variable symbol
    variable label
    variable caption
45    variable cs_class
    variable cs_tumor
    variable cs_node
    variable cs_metastasis
    variable cs_note

50    upvar #0 [join [list [namespace current] $ns offsetX] ::] offsetX
    upvar #0 [join [list [namespace current] $ns offsetY] ::] offsetY
    upvar #0 [join [list [namespace current] $ns imageX] ::] imageX
    upvar #0 [join [list [namespace current] $ns imageY] ::] imageY
55    upvar #0 [join [list [namespace current] $ns polys] ::] polys

    if {$key == ""} { set key $antkey }
    if {$key == "active"} { set key $antkey }
    ant_load $ns $key

60    set str ""

    set roipts $points
    set roipts [points_translate -$offsetX -$offsetY $roipts]
65    set roipts [pointsTo10K $imageX $imageY $roipts]

    #append str "# key $antkey\n"
    set pre [string repeat " " $lvl]
    #append str "$pre<!-- key $antkey -->\n"
70    #append str "create roi $kind\n"
    append str "$pre<roi type=\"$kind\" order=\"$order\" >\n"
    append str "$pre <views> [STRXML $invview] </views>\n"
    append str "$pre <code> [STRXML $code] </code>\n"
    #append str "set symbol \"$symbol\"\n"
75    append str "$pre <symbol> [STRXML $symbol] </symbol>\n"
    #append str "set label \"$label\"\n"
    append str "$pre <label> [STRXML $label] </label>\n"
    append str "$pre <caption> [STRXML $caption] </caption>\n"
    # TNM Cancer Staging...
80    append str "$pre <cs_class> [STRXML $cs_class] </cs_class>\n"
    append str "$pre <cs_tumor> [STRXML $cs_tumor] </cs_tumor>\n"

```

```

append str "$pre <cs_node> [STRXML $cs_node] </cs_node>\n"
append str "$pre <cs_metastasis> [STRXML $cs_metastasis] </cs_metastasis>\n"
append str "$pre <cs_note> [STRXML $cs_note] </cs_note>\n"
#append str "create vertexs ( $roipts )\n"
5  set vlst [list]
  foreach pt $roipts { lappend vlst [join $pt ","] }
  append str "$pre <vertexs> [join $vlst { }] </vertexs>\n"
  foreach {key value} [array get heads] {
10    if ($value == "") { continue }
    # added as extra data in output for processing...
    if ($value == "auto") {
      set headpt [nearest_point $tails($key) $points]
    } else {
15      set headpt $value
    }

    set tailpt [points_translate -offsetX -offsetY [list $tails($key)]]
    set tailpt [pointsTo10K $imageX $imageY $tailpt]
    set tailpt [lindex $tailpt 0]

20    set vertpts $verts($key)
    set vertpts [points_translate -offsetX -offsetY $vertpts]
    set vertpts [pointsTo10K $imageX $imageY $vertpts]

25    #append str "create pointer $value \{$tailpt\} \{$vertpts \}\n"
    set vlst [list]
    foreach pt $vertpts { lappend vlst [join $pt ","] }
    append str "$pre <pointer head=\"$value\" point=\"$headpt\" tail=\"[join $tailpt { }]\",
shape=\"$dPTRs($key)\" text=\"$dSYMs($key)\" > [join $vlst { }] </pointer>\n"
30  }
  #append str "set color \"$color\"\n"
  append str "$pre <color> $color </color>\n"
  #append str "save\n"
  append str "$pre</roi>\n"
35

  return $str
}

40 # regsubs < > & " ' for xml...
proc iat::ant::STRXML {str} {
  regsub -all (&) $str {\&} str1
  regsub -all (<) $str1 {\&lt;} str2
  regsub -all (>) $str2 {\&gt;} str3
45  regsub -all (\") $str3 {\&quot;} str4
  regsub -all (\') $str4 {\&apos;} str5
  regsub -all (\n) $str5 { } str6
  return $str6
}
50 iat.thumbs.txt
# iat.thumbs.tcl

namespace eval iat::thumbs {
55   variable TRACE 0
   variable id 0
}

60
proc iat::thumbs::proc { cname cmd args } {
  variable TRACE
  if {$TRACE} { puts "iat::thumbs::proc: $cname $cmd $args" }

65  upvar #0 [join [list [namespace current] $cname callback_select] :] callback_select
  upvar #0 [join [list [namespace current] $cname callback_deselect] :] callback_deselect

  switch $cmd {
    "configure" {
70      foreach {key value} $args {
        switch -- $key {
          "-url" { make_contact_sheet $cname $value }
          "-callbackselect" { set callback_select $value }
          "-callbackdeselect" { set callback_deselect $value }
75        }
      }
    }
    "cget" {
80      #puts "proc = cget: $args"
      switch -- [lindex $args 0] {
        "-borders" { return [get_borders $cname] }
      }
    }
  }
}

```

```

    }
    "destroy" {
        return [widget_destroy $cname]
5      }
    default {
    }

10  }

    return ""
}

15  proc iat::thumbs::create { path } {
    variable TRACE
    if {$TRACE} { puts "iat::thumbs::create: $path" }
    variable id
20    variable sizes

    if {$path == "."} { set path "" }
    set wid [incr id]
    set w [ScrolledWindow $path.w$wid -relief sunken -borderwidth 2]
25    pack $w -side top -anchor nw -fill both -expand yes
    set path $w

    set f [ScrollableFrame [$path getframe].f -areawidth 0 -areaheight 0]
30    pack $f -side top -anchor nw -fill both -expand yes
    set path $f

    #set c [canvas [$path getframe].c -width 2 -height 2 -borderwidth 2 -background gray]
    $w setwidget $f

35    #pack $c -anchor nw -fill both -expand yes

    set ns [namespace current]::thumb$wid
    namespace eval $ns {
        variable widget
        variable frame
40        variable url

        variable callback_select "noop"
        variable callback_deselect "noop"
45    }

    upvar #0 [join [list $ns widget] ::] widget
    upvar #0 [join [list $ns frame] ::] frame

50    set widget $w
    set frame $f
    #set canvas $c
    #set annotations [iat::ant::create -canvas $c -cmdcanvas [namespace current]::canvas$wid ]
    #puts " annotations = $annotations"
55    set wcmd "proc [namespace current]::thumb$wid { cmd args } {eval [namespace current]::proc thumb$wid
    \ $cmd \ $args}"
    namespace eval :: $wcmd

60    # default behavior it to pan it...
    #bind $c <ButtonPress-1> "[namespace current]::toolStartPan $f %W %x %y"
    #bind $c <Button1-Motion> "[namespace current]::toolDoPan $f %W %x %y"

    return [namespace current]::thumb$wid
65 }

    proc iat::thumbs::widget_destroy { ns } {
        variable TRACE
        if {$TRACE} { puts "iat::thumbs::widget_destroy: $ns" }
70        variable id
        variable sizes

        upvar #0 [join [list [namespace current] $ns widget] ::] widget

75        pack forget $widget
        ::destroy $widget
    }

    proc iat::thumbs::make_contact_sheet { ns new_url } {
80        variable TRACE
        if {$TRACE} { puts "iat::thumbs::make_contact_sheet: $ns $new_url" }

```

```

upvar #0 [join [list [namespace current] $ns frame] ::] frame
#upvar #0 [join [list [namespace current] $ns image_canvas] ::] image_canvas
upvar #0 [join [list [namespace current] $ns url] ::] url
5 upvar #0 [join [list [namespace current] $ns callback_select] ::] callback_select

make_thumbnails $ns $new_url

10 set url $new_url

regexp {^file:(.*)} $url m srcPath
set tmpPath [file join $srcPath 00_TMP]
set tmbPath [file join $tmpPath T]

15 set files [glob [file join $tmbPath *.JPG]]

#pack forget $image_frame
#set wpath $image_frame
#destroy $image_frame

20 #set image_frame [frame $image_frame]
#set csf $image_frame

set f [$frame getframe]

25 #canvas $csf.canvas -width 10 -height 10 \
# -yscrollcommand [list $csf.yscroll set]
#scrollbar $csf.yscroll -orient vertical \
# -command [list $csf.canvas yview]
30 #pack $csf.yscroll -side right -fill y
#pack $csf.canvas -side left -fill both -expand true
#grid $top.c.canvas $top.c.yscroll -sticky news
#pack $csf -side top -fill both -expand true

35 #set f [frame $csf.canvas.f -bd 0]
#$csf.canvas create window 10 10 -anchor nw -window $f

set btns [list]
set colmax 3
40 set col 0
set n 0

foreach {img_file} $files {

45 if {[file exists $img_file]} {

set tmb [image create photo -file $img_file]
set ant_file [file_for_ants $ns $img_file]
set btn [frame $f.tmb$n]

50 if {$ant_file == ""} {
set c [iat::canvas::thumbnail $btn]
$c configure -callbackselect "$callback_select $ns \"$img_file\""
$c configure -file $img_file
55 $c redraw
} else {
set c [iat::canvas::thumbnail $btn]
$c configure -callbackselect "$callback_select $ns \"$img_file\""
$c configure -file $img_file
60 set fh [open $ant_file r]
set svg [read $fh]
close $fh
set ants ""
regexp {(<IAT>.*</IAT>)} $svg ants
# parse here... pass reference...
set doc [tex::create -xml $ants]
$doc parse
#$doc dump; exit
65 $c annotations read_cmds $doc
#$c annotations read_cmds $ants
70 $c redraw
}

} else {
75 set btn [button $f.tmb$n -text X]
}

lappend btns $btn
incr n
80 incr col

```

Appendix :

```

1   if {$col >= $colmax} {
2       set cmd "grid [join $btns] -padx 4 -pady 4"
3       eval $cmd
4       set btns [list]
5       set col 0
6   }
7
8   #grid $btn1 $btn2 $btn3 -padx 4 -pady 4
9   #pack $btn
10
11   #tkwait visibility $csf.canvas
12   #set bbox [grid bbox $f 0 0]
13   #set incr [lindex $bbox 3]
14   #set width [winfo reqwidth $f]
15   #set height [winfo reqheight $f]
16   #${csf}.canvas config -scrollregion "0 0 $width [expr $height+50]"
17   #${csf}.canvas config -yscrollincrement 20
18   #${csf}.canvas config -width $width -height [expr $height+50]
19
20 }
21
22 proc iat::thumbs::make_thumbnails { ns url } {
23     variable TRACE
24     if {$TRACE} { puts "iat::thumbs::make_thumbnails: $ns $url" }
25
26     set old [focus]
27
28     toplevel .d -borderwidth 10
29     wm title .d "Contact Sheet"
30     wm protocol .d WM_DELETE_WINDOW {set ::OK 1}
31
32     regexp {^file:(.*)} $url m srcPath
33     set tmpPath [file join $srcPath 00_TMP]
34     set tmbPath [file join $tmpPath T]
35
36     if {[file exists $tmpPath]} { file mkdir $tmpPath }
37     if {[file exists $tmbPath]} { file mkdir $tmbPath }
38
39     set files [glob [file join $srcPath *.TIF,PNG,JPG]]
40
41     set lb [label .d.lb -text "Creating thumbnails, please wait..."]
42     pack $lb -side top -expand y -fill x
43
44     set ::progress 0
45     set pb [ProgressBar .d.pb -variable ::progress -maximum [llength $files]]
46     pack $pb -expand y -fill x
47
48     foreach file $files {
49         #puts "file: $file"
50         set newfile [lindex [file split [file rootname $file]] end]
51         set newfile [file join $tmbPath $newfile.JPG]
52         #append newfile .JPG
53         #puts "new file: $newfile"
54         if {[file exists $newfile]} {
55             set srcImg [image create photo -file $file]
56             set tmbImg [image create photo]
57             $tmbImg copy $srcImg -subsample 8 -shrink
58             $tmbImg write $newfile -format JPEG
59         }
60         incr ::progress
61     }
62
63     grab release .d
64     focus $old
65     destroy .d
66 }
67
68 proc iat::thumbs::file_for_ants { ns tmb } {
69     variable TRACE
70     if {$TRACE} { puts "iat::thumbs::url_for_ants: $ns $tmb" }
71
72     #regexp {^file:(.*)\.S+$} $url m base
73
74     set tparts [file split [file rootname $tmb]]
75     set iparts [lrange $tparts 0 [expr [llength $tparts]-4] ]
76     #set ifile [file join $iparts]
77     lappend iparts [lindex $tparts end]
78     set base [eval "file join $iparts"]
79
80 }

```

```

#puts "base = $base"
set tmp "$base.svg"
if {[file exists $tmp]} { return "$tmp" }
set tmp "$base.SVG"
5   if {[file exists $tmp]} { return "$tmp" }

    return ""
}
iat.var.js4svg.txt
10

proc iat::var_str_js4svg () {
    set str ""
15   append str "<!-- ECMAScript --> \n"
    append str "<script type='text/ecmascript'><![CDATA\[ \n"
    append str " \n"
    append str "function antAbout () \n"
    append str "{ \n"
20   append str "    var msg = \"Generated by IAT version 0.8.3\"; \n"
    append str "    alert(msg); \n"
    append str "} \n"
    append str " \n"
    append str "function antMakeMenu () \n"
25   append str "{ \n"
    append str "    var tmpMenuRoot = parseXML( printNode( document.getElementById( 'NewMenu' ) ),
contextMenu ); \n"
    append str "    contextMenu.replaceChild( tmpMenuRoot, contextMenu.firstChild ); \n"
    append str "} \n"
30   append str " \n"
    append str "function antShowCaption (key) \n"
    append str "{ \n"
    append str "    //alert(\"caption key: \"+key); \n"
    append str "    var lblt = document.getElementById(key+'-label'); \n"
35   append str "    var caplt = document.getElementById(key+'-caption'); \n"
    append str "    if( caplt.firstChild == null ) { return; } \n"
    append str "    var lblstr = lblt.firstChild.data; \n"
    append str "    var capstr = caplt.firstChild.data; \n"
    append str "    \n"
40   append str "    var new_str = lblstr+\"\\n\\n\"; \n"
    append str "    var s = 0 \n"
    append str "    var e = 50; \n"
    append str "    //alert(\"length: \"+capstr.length); \n"
    append str "    while( e < capstr.length ) \n"
45   append str "    { \n"
    append str "        if( capstr.charAt(e).match(/s/) ) \n"
    append str "        { \n"
    append str "            new_str = new_str+\"\\n\"+capstr.substring(s,e); \n"
    append str "            s = e+1; \n"
50   append str "            e = e + 49; \n"
    append str "        } \n"
    append str "        e++; \n"
    append str "    } \n"
    append str "    new_str = new_str+\"\\n\\n\"+capstr.substring(s,capstr.length); \n"
55   append str "    alert(new_str); \n"
    append str "} \n"
    append str " \n"
    append str "function antToggleShowAll (arr, menu) \n"
    append str "{ \n"
60   append str "    //alert('keys: '+arr); \n"
    append str "    for( var i in arr ) \n"
    append str "    { \n"
    append str "        //alert('key: '+arr\[i\]); \n"
    append str "        antToggleShowAnt(arr\[i\],false); \n"
65   append str "    } \n"
    append str " \n"
    append str "    if( menu ) antMakeMenu(); \n"
    append str "} \n"
    append str " \n"
70   append str "function antToggleShowAnt (key, menu) \n"
    append str "{ \n"
    append str "    //alert('key: '+key); \n"
    append str "    var item = document.getElementById('menu-'+key+'-annotation'); \n"
    append str "    \n"
75   append str "    if( item.getAttribute('checked') == 'yes') \n"
    append str "    { \n"
    append str "        antSetShowAnt(key,false); \n"
    append str "    } else { \n"
    append str "        antSetShowAnt(key,true); \n"
80   append str "    } \n"
    append str " \n"

```

Appendix 2

```

append str "    if( menu ) antMakeMenu(); \n"
append str "}" \n"
append str "\n"
append str "function antSetShowAll (arr, show, menu) \n"
5 append str "{ \n"
append str "    //alert('keys: '+arr); \n"
append str "    for( var i in arr) \n"
append str "    { \n"
append str "        //alert('key: '+arr\[i\]); \n"
10 append str "        antSetShowAnt(arr\[i\], show, false); \n"
append str "    } \n"
append str "\n"
append str "    if( menu ) antMakeMenu(); \n"
append str "}" \n"
15 append str "\n"
append str "function antSetShowAnt (key, show, menu) \n"
append str "{ \n"
append str "    //alert('annotation: '+ant); \n"
append str "    var item = document.getElementById('menu-'+key+'-annotation'); \n"
20 append str "    var elt = document.getElementById('ALL-'+key+'-annotation'); \n"
append str "    var style = elt.getStyle(); \n"
append str "    //alert('element: '+elt); \n"
append str "    \n"
append str "    if( show == false ) \n"
25 append str "    { \n"
append str "        item.setAttribute('checked', 'no'); \n"
append str "        style.setProperty('visibility','hidden'); \n"
append str "    } else { \n"
append str "        item.setAttribute('checked','yes'); \n"
30 append str "        style.setProperty('visibility','inherit'); \n"
append str "    } \n"
append str "\n"
append str "    if( menu ) antMakeMenu(); \n"
append str "}" \n"
35 append str "\n"
append str "function antToggleMouseOverAll (arr, menu) \n"
append str "{ \n"
append str "    \n"
append str "    var item = document.getElementById('menu-mouseovers'); \n"
40 append str "\n"
append str "    if( item.getAttribute('checked') == 'yes') \n"
append str "    { \n"
append str "        item.setAttribute('checked', 'no'); \n"
append str "        antSetMouseOverAll(arr,true,false); \n"
45 append str "        antMouseOver = false; \n"
append str "    } else { \n"
append str "        antMouseOver = true; \n"
append str "        item.setAttribute('checked', 'yes'); \n"
append str "        antSetMouseOverAll(arr,false,false); \n"
50 append str "    } \n"
append str "    \n"
append str "    if( menu ) antMakeMenu(); \n"
append str "}" \n"
append str "\n"
55 append str "function antSetMouseOverAll(arr, over, menu) \n"
append str "{ \n"
append str "    //alert('keys: '+arr); \n"
append str "    for( var i in arr) \n"
append str "    { \n"
60 append str "        //alert('key: '+arr\[i\]); \n"
append str "        antSetMouseOverAnt(arr\[i\], over, false); \n"
append str "    } \n"
append str "    \n"
append str "    if( menu ) antMakeMenu(); \n"
65 append str "}" \n"
append str "\n"
append str "function antSetMouseOverAnt (key, over, menu) \n"
append str "{ \n"
append str "    \n"
70 append str "    var elt = document.getElementById('ALL-'+key+'-annotation'); \n"
append str "    var style = elt.getStyle(); \n"
append str "    \n"
append str "    if( antMouseOver == true) \n"
append str "    { \n"
75 append str "        if( over == false ) \n"
append str "        { \n"
append str "            style.setProperty('opacity',0); \n"
append str "        } else { \n"
append str "            style.setProperty('opacity',1); \n"
80 append str "        } \n"
append str "    } \n"

```



```

    append str " \n"
    append str " \n"
    append str "var antMouseOver = false; \n"
    append str "current_view = 'ALL'; \n"
5   append str " \n"
    append str "var newMenuRoot = parseXML( printNode( document.getElementById( 'NewMenu' ) ), contextMenu
); \n"
    append str "contextMenu.replaceChild( newMenuRoot, contextMenu.firstChild ); \n"
    append str " \n"
10  append str "\\\]></script> \n"
    append str " \n"
    return $str
}
iat.dialog.dataref.txt
15 # Copyright (c) 2001, University of Utah
    # All rights reserved.
    #
    # iat.dialog.dataref.tcl

20 proc iat::dialog::dialog_edit_data_test () {
    return [list code symbol label]
}

proc iat::dialog::tree_click_node { id } {
25  variable TRACE
    if ($TRACE) { puts "iat::dialog::tree_click_node: $id" }

    variable ref_tree
    variable ref_id_to_lst
30  variable ref_code
    variable ref_symbol
    variable ref_label

    if (![info exists ref_id_to_lst($id)]) { return }
35  $ref_tree selection clear
    $ref_tree selection add $id
    set lst $ref_id_to_lst($id)
    set ref_code [lindex $lst 1]
    set ref_symbol [lindex $lst 2]
40  set ref_label [lindex $lst 3]
}

proc iat::dialog::combo_select_ref {} {
45  variable TRACE
    if ($TRACE) { puts "iat::dialog::combo_select_ref:" }

    variable ref_list
    variable ref_combo

50  set idx [$ref_combo getvalue]
    if ($idx == 0) {
        # NONE list item
        return
55  }
    set name [lindex $ref_list $idx]
    #puts " name = $name"
    set url "$iat::app::rsrc_url/references/$name.TXT"
    #puts " url = $url"
60  load_ref_file $name $url
}

proc iat::dialog::load_ref_leaf { branch leaf lvl } {
65  variable TRACE
    if ($TRACE) { puts "iat::dialog::load_ref_leaf: $branch $leaf $lvl" }

    variable ref_tree
    variable ref_id_to_lst
70  if (![info exists ref_id_to_lst($branch)]) { return }
    set new_branch $branch
    set next_leaf $leaf
    while ([info exists ref_id_to_lst($next_leaf)]) {
75  set line $ref_id_to_lst($next_leaf)
    set next_lvl [lindex $line 0]
    if ($next_lvl == $lvl) {
        #incr ref_id
        set new_branch [$ref_tree insert end $branch $next_leaf -text "[lindex $line 1]: [lindex $line
80 3]"]
        set next_leaf [expr $next_leaf+1]
    }
}

```

```

    ) elseif ($next_lvl > $lvl) {
        set next_leaf [load_ref_leaf $new_branch $next_leaf $next_lvl]
    } else {
        return $next_leaf
5    }
}

return $next_leaf
}
10
proc iat::dialog::load_ref_file { name url } {
    variable TRACE
    if {$TRACE} { puts "iat::dialog::load_ref_file: $name $url" }

15    variable ref_name
    variable ref_file
    variable ref_tree
    variable ref_id_to_lst

20    if {$name == "NONE"} { return }
    if {$ref_name != $name} {

        if {[regexp (^file:) $url]} { return }
        set ref_file $url
25        regexp (^file:(.*)) $url m path

        set fh [open $path r]
        set lines [split [read $fh] "\n"]
        close $fh

30        set ref_id 0
        array unset ref_id_to_lst
        array set ref_id_to_lst [list]

35        set ref_name $name
        set ref_id_to_lst($ref_id) "$name"

        foreach line $lines {
            if {[regexp (^s*$) $line]} { continue }
            incr ref_id
            set ref_id_to_lst($ref_id) $line
            #puts " $ref_id = $line"
40        }
    }

45    # branch, leaf, level
    $ref_tree delete [$ref_tree nodes root]
    set root [$ref_tree insert end root 0 -text "$name"]
    load_ref_leaf 0 1 0

50 }

proc iat::dialog::load_ref_list { url } {
    variable TRACE
55    if {$TRACE} { puts "iat::dialog::load_ref_list: $url" }

    variable ref_list

    if {[regexp (^file:) $url]} { return }
    regexp (^file:(.*)) $url m path
60    set files [glob $path/*.txt]
    #puts " reflst = $reflst"
    set ref_list [list NONE]
    foreach file $files {
65        set name [file tail [file rootname $file]]
        lappend ref_list $name
    }

70 }

proc iat::dialog::dialog_edit_data {} {

    variable ref_list
    variable ref_combo
75    variable ref_name
    variable ref_file
    variable ref_tree

    variable ref_code
    variable ref_symbol
80    variable ref_label

```

```

set path $iat::app::rsrc_url/references
regexp (^file:(.*)) $path m path
if {[file exists $path]} {
5   tk_messageBox -type ok -icon warning -title "Resources" -message "Unable to access: $path"
   return
}

10  if {[length $ref_list] == 1} {
    set ref_name "NONE"
    set ref_file ""
    load_ref_list $iat::app::rsrc_url/references
  }

15  set old [focus]

    toplevel .d -borderwidth 10
    wm title .d "References"
    wm protocol .d WM_DELETE_WINDOW {set ::OK 1}

20  set f [frame .d.f]
    pack $f -fill both -expand yes

    set dl [label .d.f.dl -text "Current Reference:"]
25  set dc [ComboBox .d.f.dc -values $ref_list -modifycmd "iat::dialog::combo_select_ref"]
    grid $dl $dc x x -pady 4
    set ref_combo $dc
    $ref_combo setvalue @[lindex [lsearch $ref_list $ref_name] 0]

30  set tf [frame .d.f.tf]
    grid $tf - - -sticky news
    set tree [Tree $tf.t -width 40 -height 20 -padx 22 -deltay 22\
               -yscrollcommand [list $tf.yscroll set] \
               -opencmd "" ]
35  set sbar [scrollbar $tf.yscroll -orient vertical \
               -command [list $tf.t yview] ]
    grid $tree $sbar -sticky news
    set ref_tree $tree
    load_ref_file $ref_name $ref_file

40  $tree bindText <Button-1> "iat::dialog::tree_click_node"

    set ::OK 0
    button .d.f.ok -text OK -command {set ::OK 2}
45  button .d.f.cancel -text Cancel -command {set ::OK 1}
    grid x x .d.f.ok .d.f.cancel -pady 4

    focus .d
    grab .d
50  tkwait variable ::OK

    grab release .d
    focus $old
    destroy .d

55  if ($::OK != "2") {return [list]}

    return [list $ref_code $ref_symbol $ref_label]
  }
}
60 iat.dialog.groups.txt
   # Copyright (c) 2001, University of Utah
   # All rights reserved.
   #
   # iat.dialog.border.tcl
65
   proc iat::dialog::dialog_edit_groups_test {} {
     return [list .20 .20 .20 .20]
   }

70 proc iat::ant::grp_dlg_drop_ant { ns tree xxx where cmd type data } {
   variable TRACE
   if ($TRACE) { puts "iat::ant::grp_dlg_drop_ant: $ns $tree $where $cmd $type $data" }

   set rel [lindex $where 0]
75  if {$rel == "bad"} {
     set parent [$tree parent $data]
     set nodes [$tree nodes $parent]
     #puts "old nodes = $nodes"
     set oldidx [lsearch -exact $nodes $data]
80  set nodes [lreplace $nodes $oldidx $oldidx]
     set newidx [lsearch -exact $nodes [lindex $where 1]]

```

```

    set nodes [linsert $nodes $newidx $data]
    #puts "new nodes = $nodes"
    $tree reorder $parent $nodes
5   ) elseif ($rel == "node") {
    set newparent [lindex $where 1]
    $tree move $newparent $data 0
    ) elseif ($rel == "position") {
    set newparent [lindex $where 1]
    set newpos [lindex $where 2]
10   $tree move $newparent $data $newpos
    ) else {
        # do nothing...
    }
}
15
proc iat::ant::grp_dlg_make_leaf { ns tree branch order } {
    variable TRACE
    if {$TRACE} { puts "iat::ant::grp_dlg_build_leaf: $ns $tree $branch $order" }

20   variable ord2key
    variable leaf_id
    variable symbol ""
    variable label ""

25   set key $ord2key($order)
    ant_load $ns $key

    set new_leaf [$tree insert end $branch [incr leaf_id] -text "$symbol: $label" -data $key]

30   set idx 1
    while {$idx < 20} {
        if {[info exists ord2key($order.$idx)]} {
            grp_dlg_make_leaf $ns $tree $new_leaf $order.$idx
        }
35   incr idx
    }
}

40 proc iat::ant::grp_dlg_make_tree { ns tree } {
    variable TRACE
    if {$TRACE} { puts "iat::ant::grp_dlg_build_tree: $ns $tree" }

    variable ord2key
45   variable leaf_id

    upvar #0 [join [list [namespace current] $ns orders] ::] orders

    array unset ord2key
    array set ord2key [list]
50   set leaf_id 0

    foreach (key val) [array get orders] {
        #puts "key: $key = $val"
        set ord2key($val) $key
55   }

    set new_leaf [$tree insert end root 0 -text "IMAGE"]

60   set idx 1
    while {$idx < 20} {
        if {[info exists ord2key($idx)]} {
            grp_dlg_make_leaf $ns $tree 0 $idx
        }
65   incr idx
    }

    ant_create_defaults

70 }

proc iat::ant::grp_dlg_read_leaf { ns tree branch (order "") } {
    variable TRACE
    if {$TRACE} { puts "iat::ant::grp_dlg_read_leaf: $ns $tree $branch $order" }

75   upvar #0 [join [list [namespace current] $ns orders] ::] orders

    if {$branch == 0} {
        set order ""
    } else {
80   set key [$tree itemcget $branch -data]

```

```

    set orders($key) $order
    #puts "key: $key = $order"
    append order "."
}
5
set idx 1
set nodes [$tree nodes $branch]
foreach node $nodes {
    grp_dlg_read_leaf $ns $tree $node $order$idx
10    incr idx
}

proc iat::ant::grp_dlg_read_tree { ns tree } {
15    variable TRACE
    if ($TRACE) { puts "iat::ant::grp_dlg_read_tree: $ns $tree" }

    grp_dlg_read_leaf $ns $tree 0
20 }

proc iat::dialog::dialog_edit_groups {ants} {
    variable TRACE
    if ($TRACE) { puts "iat::dialog::dialog_edit_groups: $ants" }
25
    variable grp_tree
    set ns [lindex [split $ants "::"] end]

    set old [focus]
30
    toplevel .d -borderwidth 10
    wm title .d "Annotation Groups"
    wm protocol .d WM_DELETE_WINDOW {set ::OK 1}

    set f [frame .d.f]
    pack $f -fill both -expand yes

    set tf [frame .d.f.tf]
    pack $tf -fill both -expand yes
40    #grid $tf - - - -sticky news

    set tb [frame .d.f.tb]
    pack $tb -fill x -expand no

45    Tree $tf.t -width 40 -height 10 -padx 22 -deltay 22\
        -yscrollcommand [list $tf.yscroll set] \
        -dragenabled true \
        -dropenabled true \
        -opencmd "" \
50        -dropcmd "iat::ant::grp_dlg_drop_ant $ns"
    set grp_tree $tf.t
    scrollbar $tf.yscroll -orient vertical \
        -command [list $tf.t yview]
    pack $tf.yscroll -side right -fill y
55    pack $tf.t -side left -fill both -expand true

    set ::OK 0
    button $tb.ok -text OK -command {set ::OK 2}
    button $tb.cancel -text Cancel -command {set ::OK 1}
60    grid $tb.ok $tb.cancel -sticky e -pady 4

    # Build the annotation tree...
    iat::ant::grp_dlg_make_tree $ns $grp_tree

65    focus .d
    grab .d
    tkwait variable ::OK

    # Save the new grouping orders...
70    if ($::OK == "2") {
        iat::ant::grp_dlg_read_tree $ns $grp_tree
    }

    grab release .d
75    focus $old
    destroy .d

    return 0
}
80 iat.var.splash.txt

```

```

proc iat::var_str_splash {} {
    set str ""
    append str "Electronic Medical Education Resource Group (EMERG) \n"
5    append str "Medical Image Annotation Tool (MIAT or IAT v0.8.4) \n"
    append str "(c) 2001, 2002 University of Utah, SLC UT \n"
    append str "\n"
    append str "TECHNOLOGY EVALUATION - 2002.04.08 \n"
    append str "\n"
10    append str "This software is property of the of the University of Utah and has been licensed through
the University of Utah Technology Transfer Office for software evaluation purposes only. This software
application (iat.exe) may not be copied, distributed or presented outside of the licensing organization. \n"
    append str "\n"
    append str "This software may only be used to test and evaluate included software functionality for use
15 in an academic or commercial environment. This version of the MIAT/IAT software application represents the
core annotation mechanisms, and does not include many of the available presentation, organization and
translation methods that make the MIAT/IAT an end-user suitable software application. \n"
    append str "\n"
    append str "Direct questions, comments and problems regarding the MIAT to one of the following EMERG
20 personnel. \n"
    append str "\n"
    append str "    Technical Contact \n"
    append str "        Jason Lauman \n"
    append str "        jason.lauman@hsc.utah.edu \n"
25    append str "        801-641-2944 \n"
    append str "\n"
    append str "    Licensing Contact \n"
    append str "        Patricia Goede \n"
    append str "        patricia.goede@hsc.utah.edu \n"
30    append str "        801-585-1737 \n"
    append str "\n"
    append str "\n"
    append str "NO WARRANTY \n"
    append str "\n"
35    append str "EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE
THE SOFTWARE \"AS IS\" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED
TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. \n"
    append str "\n"
    append str "IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT
40 HOLDER BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES
ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA
BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER
PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. \n"
    append str "\n"
45    return $str
}
iat.dialog.borders.txt
# Copyright (c) 2001, University of Utah
# All rights reserved.
50 #
# iat.dialog.border.tcl

proc iat::dialog::dialog_edit_borders_test {} {
    return [list .20 .20 .20 .20]
55 }

proc iat::dialog::dialog_edit_borders {lst} {

    set old [focus]

60    toplevel .d -borderwidth 10
    wm title .d "Edit Borders"
    wm protocol .d WM_DELETE_WINDOW {set ::OK 1}

65    set vL "0"; set vT "0"; set vR "0"; set vB "0"
    regexp (\.(\\d+)) [lindex $lst 0] match vL; append vL "%s"
    regexp (\.(\\d+)) [lindex $lst 1] match vT; append vT "%s"
    regexp (\.(\\d+)) [lindex $lst 2] match vR; append vR "%s"
    regexp (\.(\\d+)) [lindex $lst 3] match vB; append vB "%s"
70    set ::iat::dialog::color [lindex $lst 4]

    set f [frame .d.f]
    pack $f -fill both -expand yes

75    set eL [entry .d.f.el -width 4]
    set eT [entry .d.f.et -width 4]
    set eR [entry .d.f.er -width 4]
    set eB [entry .d.f.eb -width 4]
    set t1 [label .d.f.t1]; set t2 [label .d.f.t2]
80    set m1 [canvas .d.f.c -width 64 -height 64]
    set b1 [label .d.f.b1]; set b2 [label .d.f.b2]

```

```

$ml create rect 2 2 62 62 -width 2 -outline black

grid $t1 $eT $t2
grid $eL $m1 $eR
5  grid $b1 $eB $b2

    $eL insert end $vL
    $eT insert end $vT
    $eR insert end $vR
10  $eB insert end $vB

    label .d.f.cl -background $iat::dialog::color -width 4
    button .d.f.cb -text "border color" \
        -command {set ::iat::dialog::color [tk_chooseColor -parent .d -initialcolor $::iat::dialog::color];
15  .d.f.cl configure -background $::iat::dialog::color}

        grid .d.f.cl .d.f.cb -pady 4

    set ::OK 0
    button .d.f.ok -text OK -command {set ::OK 2}
    button .d.f.cancel -text Cancel -command {set ::OK 1}
    grid .d.f.ok .d.f.cancel

20  focus .d
    grab .d
    tkwait variable ::OK

    set vL [$eL get]
    set vT [$eT get]
30  set vR [$eR get]
    set vB [$eB get]

    regexp ((\d+)) $vL match x; set vL ".$x"
    regexp ((\d+)) $vT match x; set vT ".$x"
35  regexp ((\d+)) $vR match x; set vR ".$x"
    regexp ((\d+)) $vB match x; set vB ".$x"

    grab release .d
    focus $old
40  destroy .d

    if {$::OK != "2"} {return [list]}

    return [list $vL $vT $vR $vB $::iat::dialog::color]
45 )
iat.dialog.doc.txt
# Copyright (c) 2001, University of Utah
# All rights reserved.
#
50 # iat.dialog.border.tcl

proc iat::dialog::dialog_doc_test {} {
    return [list]
}

55 proc iat::dialog::dialog_doc { title txt } {

    set old [focus]

60  toplevel .d -borderwidth 10
    wm title .d $title
    wm protocol .d WM_DELETE_WINDOW {set ::OK 1}
    wm minsize .d 400 400
    wm geometry .d 450x650

65  set f [frame .d.f]
    pack $f -fill both -expand yes

70  set f [text .d.f.txt -width 60 -height 40 -wrap word -yscrollcommand [list .d.f.sb set]]
    $f insert 1.0 $txt
    #pack $f -side left -fill both -expand yes

    set f [scrollbar .d.f.sb -command [list .d.f.txt yview]]
75  #pack $f -side right -expand y

    grid .d.f.txt .d.f.sb -sticky news

    set ::OK 0
    button .d.ok -text OK -command {set ::OK 2}
80  pack .d.ok -anchor c -pady 4

```

```
focus .d
grab .d
tkwait variable ::OK

5   grab release .d
    focus $old
    destroy .d

    return [list]
10 }
    iat.var.todo.txt

15 proc iat::var_str_todo () {
    set str ""
    append str "MIAT v0.8.4 \n"
    append str "To Do List \n"
    append str "2002.04.08 \n"
20   append str " \n"
    append str "Contact sheet does not update to reflect changes in the image directory. \n"
    append str " \n"
    append str "Contact sheet shows annotations, but symbols drawn on images resize when \n"
    append str "an image is opened. Each canvas will have to maintain instance font \n"
25   append str "preferences instead of using global preferences. \n"
    append str " \n"
    append str "Reorganize load/save code so that it is more consistant for collaborative \n"
    append str "annotations and other advanced used of annotations. \n"
    append str " \n"
30   append str " \n"
    return $str
}
iat.txt
# iat.tcl

35   source iat.app.tcl

    set app [iat::app::create .]
    wm iconify .

40   $app configure -resources "file:/WORK_STATIC/iat-0.6/IAT"

    #$app configure -init_url "/"
    #$app configure -init_url "/WORK/NIHSL12/NIHSLV/00_DB/images/tissue"
45   #$app configure -url "file:/windows/desktop/images/BackImages/Back01.PNG"
    #$app configure -url "file:/images/HeadAndNeck/01_CT_2_25.PNG"

    #$app configure -url "file:/work/iat-0.6/src/tclhttpd/htdocs/APC_1_1_10x.jpg"
50   #$app configure -url "file:/WORK_STATIC/iat-0.6/src/tclhttpd/htdocs/01_CT_2_25.PNG"
```


CLAIMS

What is claimed is:

1. A method for visually annotating a digital image, said digital image being raster based, said method comprising the steps of:
 - 5 providing a digital image;
 - annotating said digital image;
 - storing electronically said annotations as vector based information linked to said digital image such that the digital image remains in a substantially unaltered condition; and
 - rendering said digital image with the annotations for display such that the annotations
 - 10 can be perceived by a user.
2. The method of claim 1, wherein the digital image is an image of at least a portion of a human body.
3. The method of claim 2, wherein the step of annotating the digital image includes the step of defining a region of interest and adding textual information.
- 15 4. The method of claim 1, wherein the step of storing comprises storing said annotations in a second file and said digital image is stored in a first file.
5. The method of claim 1, wherein the step of storing comprises storing said annotations in the same file which contains the digital image.
6. The method of claim 1, wherein step of storing comprises storing said annotations as
- 20 text information.
7. The method of claim 6, wherein the annotations are stored in an XML compatible format.
8. The method of claim 1, wherein said annotations comprise at least one member selected from the group consisting of a region of interest, a pointer, a symbol, a caption, a label and
- 25 an abbreviation.
9. The method of claim 8, further comprising the step of hierarchically organizing the annotations into logical groupings pursuant to a user defined structure.
10. The method of claim 8, wherein at least part of the annotation utilizes user defined lexicons.
- 30 11. The method of claim 1, wherein metadata is also stored along with the annotations.
12. The method of claim 1, wherein the annotation comprises a region of interest, said region of interest being defined by one selected from the group consisting of: a set of points, a polygon, and a polyline.
13. The method of claim 1 wherein the step of rendering the image with the annotations
- 35 comprises the step of displaying the annotations in a context appropriate display.
14. The method of claim 1 wherein each of the annotations can be selectively chosen for display on the digital image during the rendering step.
15. The method of claim 1 wherein each of the annotations can be displayed according to a predefined user grouping.
- 40 16. The method of claim 1 wherein the annotations are uniquely identified.
17. The method of claim 1 wherein the digital image comprises a sequence of digital images.
18. A method for interactively displaying annotations linked to a digital image, the annotations stored as vector information, said method comprising the steps of:
 - 45 selecting and displaying the digital image on a display; and
 - generating a graphical user interface on the display to accept user preferences, said graphical user interface allowing a user to toggle on and off any grouping of the annotations through the graphical user interface, the annotations being visible when toggled on and hidden from view when toggled off.
- 50 19. The method of claim 18 wherein the digital image is a raster based image.
20. The method of claim 18 wherein the graphical user interface further allows a user to activate and deactivate spatial contextual labels.
21. The method of claim 18 wherein the graphical user interface allows a user to pan the digital image and zoom in and out.
- 55 22. The method of claim 18 wherein the graphical user interface allows a user to toggle on and off annotations from a particular author.
23. The method of claim 18 wherein the graphical user interface allows a user to toggle on and off annotations from a particular specialty.
24. The method of claim 18 wherein the groupings are predefined by the user.
- 60 25. The method of claim 18 wherein the digital image remains in a substantially unaltered format.
26. The method of claim 18 wherein said annotations comprise at least one member selected from the group consisting of a region of interest, a pointer, a symbol, a caption, a label and an abbreviation.
- 65 27. The method of claim 26 wherein the annotations comprise entries from a previously defined lexicon.
28. A method for annotating a digital image, said method comprising the steps of:
 - displaying a digital image on a computer display;
 - annotating said digital image;
 - 70 grouping the annotations hierarchically pursuant to a user defined structure; and
 - storing said annotations as vector based information linked to said digital image such that the digital image remains in a substantially unaltered condition.
29. The method of claim 28 wherein the step of grouping the annotations hierarchically allows the annotation to be displayed in context appropriately.
- 75 30. The method of claim 28, wherein the annotations are saved in a format that can be electronically queried.
31. The method of claim 30, wherein the annotations are capable of being retrieved for interactive display.

32. The method of claim 28 wherein metadata is stored along with the annotations.
33. The method of claim 32 wherein the metadata uniquely identifies the annotations.
34. The method of claim 32 wherein the metadata comprises at least one selected from the group consisting of: the name of the author or creator of each of the annotations, a date indicating when annotation was added to the digital image, a title, a subject, a description, and an area of specialty of the author or creator.
35. A method for managing digital images, said method comprising:
inputting annotations for each of the digital images;
saving each of the annotations in a textual format linked to the digital image such that the digital image remains substantially unaltered;
generating a query, said query querying the annotations;
retrieving the appropriate annotations and their linked digital images, if any, in response to the query; and
displaying the retrieved digital images and their associated annotations.
36. The method of claim 35 wherein the step of inputting annotations comprises defining a region of interest on each of the associated digital images.
37. The method of claim 35 further comprising the step of hierarchically grouping the annotations pursuant to a user defined structure and the step of generating a query utilizing said user defined structure.
38. The method of claim 35 wherein the step of displaying the retrieved digital images comprises the step of interactively displaying the annotations associated with the retrieved digital images.
39. The method of claim 38 wherein the annotations can be toggled on and off, said annotations being visible when toggled on and hidden from view when toggled off.
40. The method of claim 39 wherein annotations can be displayed pursuant to a hierarchical grouping.
41. A system for visually annotating digital data stored in an electronic file, the system comprising:
an extraction means for extracting data from the electronic file to create a visual representation of the digital data;
an organizing means for assembling the extracted data into a visual representation that reflects the digital data;
a constructing means for permitting a human user to manually create dimensionally appropriate annotations;
a storing means for electronically storing the annotations as vector information such that the digital data stored in the electronic file is substantially unaltered; and
a presenting means for displaying the visual representation of the digital data along with the annotations.
42. The system of claim 41, wherein the extraction means identifies the format of the electronic file based upon the electronic file extension, MIME type as embedded into the electronic file or provided externally as metadata, or user input.
43. The system of claim 41, wherein the visual representation of the digital data is a single visual data element that has the dimensions of the original data.
44. The system of claim 41, wherein the visual representation of the digital data is a sequence of visual data elements that each has the dimension of the original digital data, but has an additional dimension that defines a sequence axis.
45. The system of claim 41, wherein the visual representation of the digital data is a set of visual data elements that each has the dimension of the original digital data, but has an additional channel dimension where each visual data element represents the same conceptual space.
46. The system of claim 41, wherein the visual representation of the digital data is a group of visual data elements that each has the dimension of the original digital data, but each visual data element is unique in the conceptual space that merits a grouping to visualize the similarities or differences of the visual elements.
47. The system of claim 41 further comprising an identifier means for marking each annotation with user identifying information to track authorship of the respective annotation.
48. The system of claim 41 wherein the presenting means is capable of restricting the display of at least a portion of the annotations based upon previously defined viewing rights assigned to each user.
49. The system of claim 41 wherein the presenting means is capable of restricting the display of at least a portion of the annotations based upon user input.
50. A system for annotating an image, said system comprising:
means for storing a raster based digital image in a file;
means for displaying said raster based digital image;
means for creating vector based annotations related to said image; and
means for linking said vector based annotations to said digital image such that said annotations are related to said digital image and said digital image is preserved in its original condition.
51. The system of claim 50, further comprising a presenting means for displaying said digital image and associated annotations.
52. The system of claim 51 wherein the presenting means further allows a user to selectively display the annotations.
53. The system of claim 52 wherein the annotations can be selectively displayed pursuant to a predefined hierarchical relationship.
54. The system of claim 52 wherein the annotations can be selectively displayed pursuant to by specialty.
55. The system of claim 52 wherein the annotations can be selectively displayed pursuant to user input received through a graphical user interface.

56. The system of claim 51 wherein the presenting means is an embedded self-contained user interface.

THIS PAGE BLANK (USPTO)




FIG. 1

DT05 Rec'd PCT/PTO 30 NOV 2004

THIS PAGE BLANK (USPTO)




FIG. 2

THIS PAGE BLANK (USPTO)




FIG 3A




FIG 3B

THIS PAGE BLANK (USPTO)




FIG. 4

THIS PAGE BLANK (USPTO)




FIG. 5A




FIG. 5B

THIS PAGE BLANK (USPTO)




FIG. 6

THIS PAGE BLANK (USPTO)




FIG. 7

THIS PAGE BLANK (USPTO)

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)